

























+ BALL BEARING UNITS



## Dimension

## Table

HOUSING			Page Nos.		Page Nos.		Page Nos.		Page Nos.		Page Nos.		Page Nos.		
Set screw type		UC2	B312	UCP2	B4	UCHP2	B26			UCF2	B42	UCFC2	B66	UCFL2	B78
		UC3	B318	UCPL2	B22	UCUP2	B30			UCF3	B48			UCFL3	B84
		UCX	B324	UCP3	B10					UCFS3	B60				
		AS2	B328	UCPX	B16					UCFX	B54	UCFCX	B72	UCFLX	B90
Eccentric locking collar type		UEL2	B336	ASPL2	B34			ASPP2	B38				ASFB2	B100	
		UEL3	B340					ASRPP2	B40				ASFD2	B102	
		AEL2	B346	UEL2	B148	UELHP2	B162			UELF2	B174			UELFL2	B198
		JEL2	B348	UELPL2	B158	UELUP2	B164			UELFU2	B184	UELFC2	B194	UELFLU2	B208
Adapter type		UK2	B354	UEL3	B152					UELF3	B178			UELFL3	B202
		UK3	B358	AELPL2	B166			AELPP2	B170				AELFB2	B212	
		UKX	B362	JELPL2	B168			AELRPP2	B172				AELFD2	B214	
Other bearings															
				AR2	B332	REL2	B350	UCS2	B366	UCS3	B370	ASS2	B374		

	Page Nos.		Page Nos.		Page Nos.		Page Nos.		Page Nos.		Page Nos.
UCFA2	B92			UCHB2	B110	UCT2	B114	UCT2- UCL2- UCM2-	B130 B132 B134	UCC2	B140
UCFH2	B96					UCT3	B120	UCM3-	B136	UCC3	B142
						UCTX	B126			UCCX	B146
		ASPF2	B104					ASPT2-	B138		
		ASRPF2	B106								
		ASPFL2	B108								
						UELT2	B228			UELC2	B242
						UELT3	B232			UELC3	B244
		AELPF2	B218					AELPT2-	B238		
		JELPF2	B220					JELPT2-	B240		
		AELRPF2	B222								
		AELPFL2	B224								
		JELPFL2	B226								
						UKT2	B294			UKC2	B306
						UKT3	B298			UKC3	B308
						UKTX	B302			UKCX	B310
UELS2	B376	UELS3	B380	AELS2	B384	JELS2	B386			CS2	B388

Technical Data

Set screw type

Eccentric locking collar type

Adapter type

Ball bearings

---

# Ball Bearing Units

---

CAT. No. E1154e

## TECHNICAL DATA INDEX

	Page
<b>1. Construction</b> .....	A3
<b>2. Design Features and Advantages</b> .....	A4
2.1 Maintenance free type .....	A4
2.2 Relubricatable type .....	A4
2.3 Special sealing feature .....	A4
2.4 Secure fitting .....	A5
2.5 Self-aligning .....	A5
2.6 Higher rated load capacity .....	A5
2.7 Light weight yet strong housing .....	A5
2.8 Easy mounting .....	A5
2.9 Accurate fitting of the housing .....	A5
2.10 Bearing replaceability .....	A5
<b>3. Tolerance</b> .....	A6
3.1 Tolerances of ball bearings for the unit .....	A6
3.2 Tolerances of housings .....	A9
<b>4. Basic Load Rating and Life</b> .....	A13
4.1 Bearing life .....	A13
4.2 Basic rated life and basic dynamic load rating .....	A13
4.3 Basic static load rating .....	A15
4.4 Allowable static equivalent load .....	A15
<b>5. Bearing Internal Clearance</b> .....	A16
5.1 Bearing internal clearance .....	A16
5.2 Internal clearance selection .....	A16
5.3 Bearing internal clearance selection standards .....	A17
<b>6. Lubrication</b> .....	A19
6.1 Maximum permissible speed of rotation .....	A19
6.2 Replenishment of grease .....	A19
6.3 Grease fitting .....	A21
6.4 Standard location of the grease fitting .....	A22
<b>7. Recommended Torques for Tightening Set Screws</b> .....	A23

## 1. Construction

The **NSK** bearing unit is a combination of a radial ball bearing, seal, and a housing of high-grade cast iron or pressed steel, which comes in various shapes.

The outer surface of the bearing and the internal surface of the housing are spherical, so that the unit is self-aligning.

The inside construction of the ball bearing for the unit is such that steel balls and retainers of the same type as in series 62 and 63 of the deep groove ball bearing are used. A duplex seal consisting of a combination of an oil-proof synthetic rubber seal and a slinger is

provided on both sides.

Depending on the type, the following methods of fitting to the shaft are employed:

- (1) The inner ring is fastened onto the shaft in two places by set screws.
- (2) The inner ring has a tapered bore and is fitted to the shaft by means of an adapter.
- (3) In the eccentric locking collar system the inner ring is fastened to the shaft by means of eccentric grooves provided at the side of the inner ring and on the collar.




Fig. 1.1

## 2. Design Features and Advantages

### 2.1 Maintenance free type

The **NSK** Maintenance free bearing unit contains a high-grade lithium-based grease, good for use over a long period, which is ideally suited to sealed-type bearings. Also provided is an excellent sealing device, which prevents any leakage of grease or penetration of dust and water from outside.

It is designed so that the rotation of the shaft causes the sealed-in grease to circulate through the inside space, effectively providing maximum lubrication. The lubrication effect is maintained over a long period with no need for replenishment of grease.

To summarize the advantages of the **NSK** maintenance free bearing unit:

- (1) As an adequate amount of good quality grease is sealed in at the time of manufacture, there is no need for replenishment. This means savings in terms of time and maintenance costs.
- (2) Since there is no need for any regreasing facilities, such as piping, a more compact design is possible.
- (3) The sealed-in design eliminates the possibility of grease leakage, which could lead to stained products.

### 2.2 Relubricatable type

The **NSK** relubricatable type bearing unit has an advantage over other similar units being so designed as to permit regreasing even in the case of misalignment of 2° to the right or left. The hole through which the grease fitting is mounted usually causes structural weakening of the housing.

However, as a result of extensive testing, in the **NSK** bearing unit the hole is positioned so as to minimize this adverse effect. In addition, the regreasing groove has been designed to minimize weakening of the housing.

While the **NSK** maintenance free type bearing unit is satisfactory for use under normal operating conditions in-doors, in the following circumstances it is necessary to use the relubricatable type bearing unit:

- (1) Cases where the temperature of the bearing rises above 100°C, 212°F:  
\*Normal temperature of up to 130°C, 266°F heat-resistant bearing units.
- (2) Cases where there is excessive dust, but space does not permit using a bearing unit with a cover.
- (3) Cases where the bearing unit is constantly exposed to splashes of water or any other liquid, but space does not permit using a bearing unit with a cover.
- (4) Cases in which the humidity is very high, and the machine in which the bearing unit is used is run

only intermittently.

- (5) Cases involving a heavy load of which the  $C_r/P_r$  value is about 10 or below, and the speed is 10 min<sup>-1</sup> or below, or the movement is oscillatory.
- (6) Cases where the number of revolutions is relatively high and the noise problem has to be considered; for example, when the bearing is used with the fan of an air conditioner.

### 2.3 Special sealing feature

#### 2.3.1 Standard bearing units

The sealing device of the ball bearing for the **NSK** bearing unit is a combination of a heat-resistant and oil-proof synthetic rubber seal and a slinger of an exclusive design.

The seal, which is fixed in the outer ring, is steel-reinforced, and its lip, in contact with the inner ring, is designed to minimize frictional torque.

The slinger is fixed to the inner ring of the bearing with which it rotates. There is a small clearance between its periphery and the outer ring.

These two types of seals on both sides of the bearing prevent grease leakage, and foreign matter is prevented from entering the bearing from outside.




Fig. 2.1

#### 2.3.2 Bearing units with covers

The **NSK** bearing unit with a cover consists of a standard bearing unit and an outside covering for extra protection against dust. Special consideration has been given to its design with respect to dust-proofing.

Sealing devices are provided in both the bearing and the housing, so that units of this type operate satisfactorily even in such adverse environments as flour mills, steel mills, foundries, galvanizing plants and chemical plants, where excessive dust is produced and/or liquids are used. They are also eminently suitable for outdoor environments where dust and rain are inevitable, and in heavy industrial machinery such as construction and transportation equipment.

The rubber seal of the cover contacts with the shaft by its two lips, as shown in Fig. 2.2 and 2.3. By filling the groove between the two lips with grease, an excellent sealing effect is obtained and, at the same time, the contacting portions of the lips are lubricated. Furthermore, the groove is so designed that when the shaft is inclined the rubber seal can move in the radial direction.

When bearing units are exposed to splashes of water rather than to dust, a drain hole (5 to 8 mm, 0.2 to 0.3 inches in diameter) is provided at the bottom of the cover, and grease should be applied to the side of the bearing itself instead of into the cover.




Fig. 2.2 Pressed steel cover




Fig. 2.3 Cast iron cover

### 2.4 Secure fitting

Fastening the bearing to the shaft is effected by tightening the ball-end set screw, situated on the inner ring. This is a unique feature which prevents loosening, even if the bearing is subjected to intense vibrations and shocks.

### 2.5 Self-aligning

With the **NSK** bearing unit, the outer surface of the ball bearing and the inner surface of the housing are spherical, thus this bearing unit has self-aligning characteristic. Any misalignment of axis that may arise from poor workmanship on the shaft or errors in fitting will be properly adjusted.

### 2.6 Higher rated load capacity

The bearing used in the unit is of the same internal construction as those in bearing series 62 and 63, and is capable of accommodating axial load as well as radial load, or composite load. The rated load capacity of this bearing is considerably higher than that of the corresponding self-aligning ball bearings used for standard plummer blocks.

### 2.7 Light weight yet strong housing

Housings for **NSK** bearing units come in various shapes. They consist of either high-grade cast iron, one-piece casting, or of precision finished pressed steel, the latter being lighter in weight. In either case, they are practically designed to combine lightness with maximum strength.

### 2.8 Easy mounting

The **NSK** bearing unit is an integrated unit consisting of a bearing and a housing.

As the bearing is prelubricated at manufacture with the correct amount of high-grade lithium base, it can be mounted on the shaft just as it is. It is sufficient to carry out a short test run after mounting.

### 2.9 Accurate fitting of the housing

In order to simplify the fitting of the pillow block and flange type bearing units, the housings are provided with a seat for a dowel pin, which may be utilized as needed.

### 2.10 Bearing replaceability

The bearing used in the **NSK** bearing unit is replaceable. In the event of bearing failure, a new bearing can be fitted to the existing housing.

## 3. Tolerance

The tolerances of the **NSK** bearing units are in accordance with the following JIS specifications:

### 3.1 Tolerances of ball bearings for the unit

The tolerances of ball bearings used in the unit are shown in the following tables, 3.1 to 3.4.



Set screw type

**Table 3.1 (1) Cylindrical bore (UC, UCS, AS, ASS, UEL, UELS, AEL, AELS)** Unit:  $\mu\text{m}/0.0001$  inch

Nominal bore diameter $d$				Cylindrical bore						Radial runout $K_{ia}$ (reference)
over		incl.		Bore diameter			Width			
mm	inch	mm	inch	$\Delta d_{amp}$ Deviations		$V_{dp}$ Variations	$\Delta B_{in}, \Delta C_{in}$ Deviations(reference)			
high	low	high	low	high	low	max.	high	low	max.	
10	0.3937	18	0.7087	+15	0	10	0	-120	15	
				+ 6	0	4	0	- 47	6	
18	0.7087	31.75	1.2500	+18	0	12	0	-120	18	
				+ 7	0	5	0	- 47	7	
31.75	1.2500	50.8	2.0000	+21	0	14	0	-120	20	
				+ 8	0	6	0	- 47	8	
50.8	2.0000	80	3.1496	+24	0	16	0	-150	25	
				+ 9	0	6	0	- 59	10	
80	3.1496	120	4.7244	+28	0	19	0	-200	30	
				+11	0	7	0	- 79	12	
120	4.7244	180	7.0866	+33	0	22	0	-250	35	
				+13	0	9	0	- 98	14	

**Remarks** Symbols

$\Delta d_{amp}$ : Mean bore diameter deviation  $V_{dp}$ : Bore diameter variation  $\Delta B_{in}$ : Inner ring width deviation  $\Delta C_{in}$ : Outer ring width deviation

**Table 3.1 (2) Cylindrical bore (AR, JEL, JELS, REL)** Unit:  $\mu\text{m}/0.0001$  inch

Nominal bore diameter $d$				Cylindrical bore diameter		
over		incl.		$\Delta d_{amp}$ Deviations		$V_{dp}$ Variations
mm	inch	mm	inch	high	low	max.
10	0.3937	18	0.7087	+13	0	6
				+ 5	0	2
18	0.7087	31.75	1.2500	+13	0	6
				+ 5	0	2
31.75	1.2500	50.8	2.0000	+13	0	6
				+ 5	0	2
50.8	2.0000	80	3.1496	+15	0	8
				+ 6	0	3

**Table 3.1 (3) Cylindrical bore (CS)** Unit:  $\mu\text{m}/0.0001$  inch


Nominal bore diameter $d$				Cylindrical bore						Radial runout $K_{ia}$ (reference)
over		incl.		Bore diameter			Width			
mm	inch	mm	inch	$\Delta d_{amp}$ Deviations		$V_{dp}$ Variations	$\Delta B_{in}, \Delta C_{in}$ Deviations(reference)			
high	low	high	low	high	low	max.	high	low	max.	
10	0.3937	18	0.7087	0	- 8	10	0	-120	15	
				0	- 3	4	0	- 47	6	
18	0.7087	31.75	1.2500	0	-10	12	0	-120	18	
				0	- 4	5	0	- 47	7	
31.75	1.2500	50.8	2.0000	0	-12	14	0	-120	20	
				0	- 5	6	0	- 47	8	

**Table 3.2 Tapered bore (UK, UKS)** Unit:  $\mu\text{m}/0.0001$  inch

Nominal bore diameter $d$				$\Delta d_{amp}$ Deviations		$\Delta d_{imp} - \Delta d_{amp}$		$V_{dp}^{(1)}$
over		incl.		high	low	max.	min.	max.
mm	inch	mm	inch	high	low	max.	min.	max.
18	0.7087	30	1.1811	+21	0	+21	0	13
				+ 8	0	+ 8	0	5
30	1.1811	50	1.9685	+25	0	+25	0	15
				+10	0	+10	0	6
50	1.9685	80	3.1496	+30	0	+30	0	19
				+12	0	+12	0	7
80	3.1496	120	4.7244	+35	0	+35	0	25
				+14	0	+14	0	10
120	4.7244	180	7.0866	+40	0	+40	0	31
				+16	0	+16	0	12

**Note** (1) To be applied for all radial flat surfaces of tapered hole.

**Remarks** 1. To be applied for tapered holes of 1/12.  
2. Symbols of quantity or values



**Table 3.3 Outer ring**

Unit:  $\mu\text{m}/0.0001$  inch

Nominal outside diameter $D$				Mean outside diameter deviation $\Delta_{Dm}$		Radial runout $K_{ra}$ (reference)
over		incl.		high	low	
mm	inch	mm	inch			max.
18	0.7087	30	1.1811	0	-9	15
				0	-4	6
30	1.1811	50	1.9685	0	-11	20
				0	-4	8
50	1.9685	80	3.1496	0	-13	25
				0	-5	10
80	3.1496	120	4.7244	0	-15	35
				0	-6	14
120	4.7244	150	5.9055	0	-18	40
				0	-7	16
150	5.9055	180	7.0866	0	-25	45
				0	-10	18
180	7.0866	250	9.8425	0	-30	50
				0	-12	20
250	9.8425	315	12.4016	0	-35	60
				0	-14	24

**Remarks** The low deviation of outside diameter  $D_m$  does not apply within the distance of 1/4 the width of the outer ring from the side.



Eccentric locking collar



Eccentric locking collar type

**Table 3.4 Eccentric locking collar**

Unit: mm/inch

Nominal bore diameter $d$				Bore diameter deviation $\Delta_{ds}$		Small bore diameter of eccentric surface deviation $\Delta_{d2s}$		Eccentricity deviation $\Delta_{fs}$		Collar width deviation $\Delta_{B2s}$		Collar eccentric surface width deviation $\Delta_{A1s}$	
over		incl.		high	low	high	low	high	low	high	low	high	low
mm	inch	mm	inch										
10	0.3937	36.512	1.4375	+0.250	+0.025	+0.3	0	+0.1	-0.1	+0.270	-0.270	0	-0.180
				+0.010	+0.001	+0.012	0	+0.004	-0.004	+0.011	-0.011	0	-0.007
36.512	1.4375	55.562	2.1875	+0.300	+0.025	+0.4	0	+0.1	-0.1	+0.330	-0.330	0	-0.180
				+0.012	+0.001	+0.016	0	+0.004	-0.004	+0.013	-0.013	0	-0.007
55.562	2.1875	61.912	2.4375	+0.300	+0.025	+0.4	0	+0.1	-0.1	+0.330	-0.330	0	-0.220
				+0.012	+0.001	+0.016	0	+0.004	-0.004	+0.013	-0.013	0	-0.009

## 3.2 Tolerances of housings

**Table 3.5 Spherical bore diameter of housings**

Unit:  $\mu\text{m}/0.0001$  inch

Nominal spherical bore diameter $D_a$				$D_a$ Deviations $\Delta_{Damp}$					
over		incl.		Tolerance class H7		Tolerance class J7		Tolerance class K7	
mm	inch	mm	inch	high	low	high	low	high	low
30	1.1811	50	1.9685	+25	0	+14	-11	+7	-18
				+10	0	+6	-4	+3	-7
50	1.9685	80	3.1496	+30	0	+18	-12	+9	-21
				+12	0	+7	-5	+4	-8
80	3.1496	120	4.7244	+35	0	+22	-13	+10	-25
				+14	0	+9	-5	+4	-10
120	4.7244	180	7.0866	+40	0	+26	-14	+12	-28
				+16	0	+10	-6	+5	-11
180	7.0866	250	9.8425	+46	0	+30	-16	+13	-33
				+18	0	+12	-6	+5	-13
250	9.8425	315	12.4016	+52	0	+36	-16	+16	-36
				+20	0	+14	-6	+6	-14

**Remarks** 1. Symbols

$\Delta_{Damp}$ : Mean spherical bore diameter deviation

2. Dimensional tolerances for spherical bore diameter of housing are classified as H7 for clearance fit, and J7 for intermediate fit.

3. Spherical bore diameter of housings are finished by following tolerance classes such as 52mm or less : K7, over 52mm and 180mm or less : J7, and over 180mm : H7 respectively.

**Table 3.6 Pillow block housings (P, PL, HP, UP)**


Unit: mm/inch

Housing numbers						$H$ Deviations $\Delta_{Hs}$
P203	—	—	—	—	—	$\pm 0.15$ $\pm 0.006$
P204	—	—	HP204	UP204	PL204	
P205	P305	PX05	HP205	UP205	PL205	
P206	P306	PX06	HP206	UP206	PL206	
P207	P307	PX07	HP207	UP207	PL207	
P208	P308	PX08	HP208	UP208	—	
P209	P309	PX09	HP209	UP209	PL209	
P210	P310	PX10	HP210	UP210	PL210	
P211	P311	PX11	—	—	—	
P212	P312	PX12	—	—	—	
P213	P313	PX13	—	—	—	$\pm 0.2$ $\pm 0.008$
P214	P314	PX14	—	—	—	
P215	P315	PX15	—	—	—	
P216	P316	PX16	—	—	—	
P217	P317	PX17	—	—	—	
P218	P318	PX18	—	—	—	
—	P319	—	—	—	—	
—	P320	PX20	—	—	—	
—	P321	—	—	—	—	$\pm 0.3$ $\pm 0.012$
—	P322	—	—	—	—	
—	P324	—	—	—	—	
—	P326	—	—	—	—	
—	P328	—	—	—	—	

**Remarks** 1.  $H$  is height of the shaft center line.

2. This table can be applied for bearing units with dust covers.

# Technical Data



**Table 3.7 (1) Flange unit housings (F, FU, FC, FS, FL, FLU, FB, FD)**


Unit: mm/inch

Housing numbers		location tolerance of bolt hole X	A <sub>2</sub> Deviations ΔA <sub>2s</sub>	H <sub>3</sub> Deviations ΔH <sub>3s</sub>						Radial runout of spigot joint Y
				FC2		FS3		FCX		
				high	low	high	low	high	low	
—	—	—	—	—	—	—	—	—	—	—
F204	—	—	FC204	—	FL204	—	—	—	—	—
F205	F305	FX05	FC205	FS305	FL205	FL305	FD205	—	—	—
F206	F306	FX06	FC206	FS306	FL206	FL306	FD206	—	—	—
F207	F307	FX07	FC207	FS307	FL207	FL307	FD207	—	—	—
F208	F308	FX08	FC208	FS308	FL208	FL308	—	—	—	—
F209	F309	FX09	FC209	FS309	FL209	FL309	—	—	—	—
F210	F310	FX10	FC210	FS310	FL210	FL310	—	—	—	—
F211	F311	FX11	FC211	FS311	FL211	FL311	—	—	—	—
F212	F312	FX12	FC212	FS312	FL212	FL312	—	—	—	—
F213	F313	FX13	FC213	FS313	FL213	FL313	—	—	—	—
F214	F314	FX14	FC214	FS314	FL214	FL314	—	—	—	—
F215	F315	FX15	FC215	FS315	FL215	FL315	—	—	—	—
F216	F316	FX16	FC216	FS316	FL216	FL316	—	—	—	—
F217	F317	FX17	FC217	FS317	FL217	FL317	—	—	—	—
F218	F318	FX18	FC218	FS318	FL218	FL318	—	—	—	—
—	F319	—	—	FS319	—	FL319	—	—	—	—
—	F320	FX20	—	—	FS320	—	FL320	—	—	—
—	F321	—	—	—	FS321	—	FL321	—	—	—
—	F322	—	—	—	FS322	—	FL322	—	—	—
—	F324	—	—	—	FS324	—	FL324	—	—	—
—	F326	—	—	—	FS326	—	FL326	—	—	—
—	F328	—	—	—	FS328	—	FL328	—	—	—

- Remarks**
1. J is the bolt hole's center line dimension, and P.C.D. A<sub>2</sub> is distance between the center line of spherical bore diameter of the housing and mounting surfaces, and H<sub>3</sub> is outside diameter of the spigot joint.
  2. Radial runout of spigot joint is applied for flange units with spigot joints.
  3. For FU2 and FLU2 types, tolerances for F2 shall be applied.
  4. For FCX and FLX types, tolerances for FX shall be applied.
  5. This table can be applied for bearing units with dust covers.

**Table 3.7 (2) Flange unit housings (diameter of bolt hole)**

Housing type	Nominal bore diameter N				N Deviations ΔN <sub>s</sub>	
	over		incl.		mm	inch
	mm	inch	mm	inch		
F, FU, FC, FS FA, FH, FLU	—	—	30	1.1811	±0.2	±0.008
	30	1.1811	41	1.6142	±0.3	±0.012



**Table 3.8 Flange unit housings (FH, FA, PF, PFL)**

Unit: mm/inch

Housing numbers	A <sub>2</sub> Deviations ΔA <sub>2s</sub>	Housing numbers	J Deviations ΔJ <sub>s</sub>	N Deviations ΔN <sub>s</sub>
—	±0.5 ±0.020	PF203	±0.4 ±0.016	±0.25 ±0.010
FH, FA204		PF204		
FH, FA205		PF205		
FH, FA206		PF206		
FH, FA207		PF207		
FH, FA208		PF208		
FH, FA209		PFL203		
FH, FA210		PFL204		
		PFL205		
		PFL206		
FA211	±0.8 ±0.032	PFL207		

- Remarks**
1. A<sub>2</sub> is distance between the center line of spherical bore diameter of housings.
  2. J is the bolt hole's center line dimension.



**Table 3.9 Take-up unit housings (T)** Unit: mm/inch

Housing numbers	$A_1$ Deviations $\Delta A_{1s}$		$H_1$ Deviations $\Delta H_{1s}$		Parallelism of guide $X$
			high	low	
			T204 — —		
T205 T305 TX05					
T206 T306 TX06	+0.2				
T207 T307 TX07	0	0	-0.5	0.5	
T208 T308 TX08	+0.008	0	-0.020	0.020	
T209 T309 TX09	0				
T210 T310 TX10					
T211 T311 TX11					
T212 T312 TX12					
T213 T313 TX13					
T214 T314 TX14				0.6	
T215 T315 TX15				0.024	
T216 T316 TX16					
T217 T317 TX17	+0.3				
— T318 —	0	0	-0.8		
— T319 —	+0.012	0	-0.032		
— T320 —	0				
— T321 —				0.7	
— T322 —				0.028	
— T324 —					
— T326 —				0.8	
— T328 —				0.032	

**Remarks** 1.  $A_1$  is the width of guide rail grooves.  
 2.  $H_1$  is the maximum span of guide rail grooves.  
 3. This table can be applied for bearing units with dust covers.

**Table 3.10 Cartridge unit housings (C)** Unit: mm/inch

Housing numbers	$H$ Deviations $\Delta H_s$						Radial runout of outside surface $\gamma$	$A$ Deviations $\Delta A_s$
	C2 Series		C3 Series		CX Series			
	high	low	high	low	high	low		
C204 — —	0	-0.030	—	—	—	—		
C205 C305 CX05	0	-0.0012						
C206 C306 CX06			0	-0.035	0	-0.035	0.2	
C207 C307 CX07	0	-0.035	0	-0.0014	0	-0.0014	±0.008	
C208 C308 CX08	0	-0.0014						
C209 C309 CX09								
C210 C310 CX10					0	-0.040		
C211 C311 CX11	0	-0.040	0	-0.040	0	-0.0016		
C212 C312 CX12	0	-0.0016						
C213 C313 —								
— C314 —							0.3	
— C315 —							0.012	
— C316 —			0	-0.046				
— C317 —			0	-0.0018				
— C318 —								
— C319 —								
— C320 —								
— C321 —			0	-0.052				
— C322 —			0	-0.0020				
— C324 —								
— C326 —			0	-0.057				
— C328 —			0	-0.0022				

**Remarks** 1.  $H$  is the outside diameter of cartridge housings.  
 2.  $A$  is width of cartridge housings.

## 4. Basic Load Rating and Life

### 4.1 Bearing life

Even in bearings operating under normal conditions, the surfaces of the raceway and rolling elements are constantly being subjected to repeated compressive stresses which cause flaking of these surfaces to occur. This flaking is due to material fatigue and will eventually cause the bearings to fail. The effective life of a bearing is usually defined in terms of the total number of revolutions a bearing can undergo before flaking of either the raceway surface or the rolling element surfaces occurs.

Other causes of bearing failure are often attributed to problems such as seizing, abrasions, cracking, chipping, gnawing, rust, etc. However, these so called "causes" of bearing failure are usually themselves caused by improper installation, insufficient or improper lubrication, faulty sealing or inaccurate bearing selection. Since the above mentioned "cause" of bearing failure can be avoided by taking the proper precautions, and are not simply caused by material fatigue, they are considered separately from the flaking aspect.

### 4.2 Basic rated life and basic dynamic load rating

A group of seemingly identical bearings when subjected to identical load and operating conditions will exhibit a wide diversity in their durability.

This "life" disparity can be accounted for by the difference in the fatigue of the bearing material itself. This disparity is considered statistically when calculating bearing life, and the basic rated life is defined as follows.

The basic rated life is based on a 90% statistical model which is expressed as the total number of revolutions 90% of the bearings, in an identical group of bearings subjected to identical operating conditions, will attain or surpass before flaking due to material fatigue occurs. For bearings operating at fixed constant speeds, the basic rated life (90% reliability) is expressed in the total number of hours of operation.

The basic dynamic load rating is an expression of the load capacity of a bearing based on a constant load which the bearing can sustain for one million revolutions (the basic life rating). For radial bearings this rating applies to pure radial loads, and for thrust bearings it refers to pure axial loads. The basic dynamic load ratings given in the bearing tables of this catalog are for bearings constructed of standard bearing materials, using standard manufacturing techniques. Please consult **NSK** for basic load ratings of bearings constructed of special materials or using special

manufacturing techniques.

The relationship between the basic rated life, the basic dynamic load rating and the bearing load is given in formula (4.1).

$$L_{10} = \left( \frac{C_r}{P_r} \right)^3 \dots \dots \dots (4.1)$$

where,

- $L_{10}$ : Basic rated life  $10^6$  revolutions
- $C_r$ : Basic dynamic rated load, N, lbf
- $P_r$ : Equivalent dynamic load, N, lbf

The basic rated life can also be expressed in terms of hours of operation (revolution), and is calculated as shown in formula (4.2).

$$L_{10h} = 500 f_n^3 \dots \dots \dots (4.2)$$

$$f_n = f_n \frac{C_r}{P_r} \dots \dots \dots (4.3)$$

$$f_n = \left( \frac{33.3}{n} \right)^{1/3} \dots \dots \dots (4.4)$$

where,

- $L_{10h}$ : Basic rated life, h
- $f_n$ : Life factor
- $f_n$ : Speed factor
- $n$ : Rotational speed, min<sup>-1</sup>

Formula (4.2) can also be expressed as shown in formula (4.5).

$$L_{10h} = \frac{10^6}{60n} \left( \frac{C_r}{P_r} \right)^3 \dots \dots \dots (4.5)$$

The relation between rotational speed  $n$  and speed factor  $f_n$  as well as the relation between the basic rated life  $L_{10h}$  and the life factor  $f_n$  is shown in Fig. 4.1.

When several bearings are incorporated in machines or equipment as complete units, all the bearings in the unit are considered as a whole when computing bearing life (see formula 4.6). The total bearing life of the unit is a life rating based on the viable lifetime of the unit before even one of the bearings fails due to rolling contact fatigue.

$$L = \frac{1}{\left(\frac{1}{L_1^{1.1}} + \frac{1}{L_2^{1.1}} + \dots + \frac{1}{L_n^{1.1}}\right)^{1/1.1}} \dots\dots(4.6)$$

where,  
*L* :Total life of the whole bearing assembly,h  
*L*<sub>1</sub>, *L*<sub>2</sub>, ... *L*<sub>*n*</sub>: Rated life of bearings 1, 2, ... *n*, h

In the case where load and the number of revolutions change at regulated intervals, after finding the rated life *L*<sub>1</sub>, *L*<sub>2</sub>, ... , *L*<sub>*n*</sub> under conditions of *n*<sub>1</sub>, *P*<sub>1</sub>; *n*<sub>2</sub>, *P*<sub>2</sub>; ... *n*<sub>*n*</sub>, *P*<sub>*n*</sub>: the built-in life *L*<sub>*m*</sub> can be given by the formula (4.7).

$$L_1 = \frac{10^6}{60n_1} \left(\frac{C_r}{P_1}\right)^3$$


$$L_2 = \frac{10^6}{60n_2} \left(\frac{C_r}{P_2}\right)^3$$

$$\vdots$$

$$L_n = \frac{10^6}{60n_n} \left(\frac{C_r}{P_n}\right)^3$$

$$L_m = \left(\frac{\phi_1}{L_1} + \frac{\phi_2}{L_2} + \dots + \frac{\phi_n}{L_n}\right)^{-1} \dots\dots\dots(4.7)$$

where,  
*L*<sub>1</sub>, *L*<sub>2</sub>, ... *L*<sub>*n*</sub>: Rated life under condition 1, 2, ... *n*, h  
*n*<sub>1</sub>, *n*<sub>2</sub>, ... *n*<sub>*n*</sub>: Number of revolutions under condition 1, 2, ... *n*, min<sup>-1</sup>  
*P*<sub>1</sub>, *P*<sub>2</sub>, ... *P*<sub>*n*</sub>: Equivalent load under condition 1, 2, ... *n*, N, lbf  
 $\phi_1, \phi_2, \dots, \phi_n$ : Ratio of condition 1, 2, ... *n* accounting for the total operating time  
*L*<sub>*m*</sub>: Built-in life, h



**Fig. 4.1 Bearing life rating scale**

**Table 4.1 Rating life for applications**

Service classification	Machine application	Life time <i>L</i> <sub><i>n</i></sub>
Machines used occasionally	Door mechanisms,Garage shutter	500
Equipment for short period or intermittent service-interruption permissible	Household appliances,Electric hand tools, Agricultural machines,Lifting tackles in shops	4 000 to 8 000
Intermittent service machines-high reliability	Power-Station auxiliary equipment,Elevators, Conveyors,Deck cranes	8 000 to 14 000
Machines used for 8 hours a day,but not always in full operation	Ore wagon axles,important gear units	14 000 to 20 000
Machines fully used for 8 hours	Blowers,General machinery in shops,Continuous operation cranes	20 000 to 30 000
Machines continuously used for 24 hours a day	Compressors,Pumps	50 000 to 60 000
Machines continuously used for 24 hours a day with maximum reliability	Power-station equipment,Water-supply equipment for urban areas,Mine ventilators	100 000 to 200 000

### 4.3 Basic static load rating

When stationary rolling bearings are subjected to static loads, they suffer from partial permanent deformation of the contact surfaces at the contact point between the rolling elements and the raceway. The amount of deformity increases as the load increases, and if this increase in load exceeds certain limits, the subsequent smooth operation of the bearing is impaired.

It has been found through experience that a permanent deformity of 0.0001 times the diameter of the rolling element, occurring at the most heavily stressed contact point between the raceway and the rolling elements, can be tolerated without any impairment in running efficiency.

The basic rated static load refers to a fixed static load limit at which a specified amount of permanent deformation occurs. It applies to pure radial loads for radial bearings. The maximum applied load values for contact stress occurring at the rolling element and raceway contact points are given below.

For ball bearings (for bearing unit): 4 200 MPa.

### 4.4 Allowable static equivalent load

Generally the static equivalent load which can be permitted is limited by the basic static rated load as stated in Section 4.3. However, depending on requirements regarding friction and smooth operation, these limits may be greater or lesser than the basic static rated load.

In the following formula (4.8) and Table 4.2 the safety factor *S*<sub>0</sub> can be determined considering the maximum static equivalent load.

$$S_0 = \frac{C_0}{P_0 \max} \dots\dots\dots(4.8)$$

where,

*S*<sub>0</sub>: Safety factor

*C*<sub>0</sub>: Basic static rated load, N, lbf

*P*<sub>0 max</sub>: Maximum static equivalent load, N, lbf

**Table 4.2 Minimum safety factor values *S*<sub>0</sub>**

Operating conditions	Ball bearings
High rotational accuracy demand	2
Normal rotating accuracy demand (Universal application)	1
Slight rotational accuracy deterioration permitted (Lcw speed,heavy loading,etc.)	0.5

**Remarks** When vibration and/or shock loads are present, a load factor based on the shock load needs to be included in the *P*<sub>0 max</sub> value.

## 5. Bearing Internal Clearance


### 5.1 Bearing internal clearance

Bearing internal clearance (initial clearance) is the amount of internal clearance a bearing has before being installed on a shaft or in a housing.

As shown in Fig. 5.1, when either the inner ring or the outer ring is fixed and the other ring is free to move, displacement can take place in either an axial or radial direction. This amount of displacement (radially or axially) is termed the internal clearance and, depending on the direction, is called the radial internal clearance or the axial internal clearance.

When the internal clearance of a bearing is measured, a slight measurement load is applied to the raceway so the internal clearance may be measured accurately. However, at this time, a slight amount of elastic deformation of the bearing occurs under the measurement load, and the clearance measurement value (measured clearance) is slightly larger than the true clearance. This discrepancy between the true bearing clearance and the increased amount due to the elastic deformation must be compensated for. These compensation values are given in Table 5.1.

The internal clearance values for each bearing class are shown in Tables 5.3.



**Table 5.1 Adjustment of radial internal clearance based on measured load** Unit:  $\mu\text{m}$

Nominal Bore Diameter $d$ (mm)	Measuring Load (N)	Radial Clearance Increase				
		C2	CN	C3	C4	C5
10	18	24.5	3 to 4	4	4	4
18	50	49	4 to 5	5	6	6
50	200	147	6 to 8	8	9	9

### 5.2 Internal clearance selection

The internal clearance of a bearing under operating conditions (effective clearance) is usually smaller than the same bearing's initial clearance before being installed and operated. This is due to several factors including bearing fit, the difference in temperature between the inner and outer rings, etc. As a bearing's operating clearance has an effect on bearing life, heat generation, vibration, noise, etc.; care must be taken in selecting the most suitable operating clearance.

Effective internal clearance:

The internal clearance differential between the initial clearance and the operating (effective) clearance (the amount of clearance reduction caused by interference fits, or clearance variation due to the temperature difference between the inner and outer rings) can be calculated by the following formula:

$$\delta_{\text{eff}} = \delta_o - (\delta_i + \delta_t) \quad (5.1)$$

where,

$\delta_{\text{eff}}$  : Effective internal clearance, mm

$\delta_o$  : Bearing internal clearance, mm

$\delta_i$  : Reduced amount of clearance due to interference, mm

$\delta_t$  : Reduced amount of clearance due to temperature differential of inner and outer rings, mm

Reduced clearance due to interference:

When bearings are installed with interference fits on shafts and in housings, the inner ring will expand and the outer ring will contract; thus reducing the bearings' internal clearance. The amount of expansion or contraction varies depending on the shape of the bearing, the shape of the shaft or housing, dimensions of the respective parts, and the type of materials used. The clearance can range from approximately 70% to 90% of the effective interference.

$$\delta_i = (0.70 \text{ to } 0.90) \cdot \Delta d_{\text{eff}} \quad (5.2)$$

where,

$\delta_i$  : Reduced amount of clearance due to interference, mm

$\Delta d_{\text{eff}}$  : Effective interference, mm

Reduced internal clearance due to inner/outer ring temperature difference:

During operation, normally the outer ring will be from 5° to 10°C cooler than the inner ring or rotating parts. However, if the cooling effect of the housing is large,

the shaft is connected to a heat source, or a heated substance is conducted through the hollow shaft; the temperature difference between the two rings can be ever greater. The amount of internal clearance is thus further reduced by the differential expansion of the two rings.

$$\delta_t = \alpha \cdot \Delta T \cdot D_o \quad (5.3)$$

where,

$\delta_t$  : Amount of reduced clearance due to heat differential, mm

$\alpha$  : Bearing steel linear expansion coefficient  $12.5 \times 10^{-6}/^\circ\text{C}$

$\Delta T$  : Inner/outer ring temperature differential, °C

$D_o$  : Outer ring raceway diameter, mm

Outer ring raceway diameter,  $D_o$ , values can be approximated by using formula 5.4.

For ball bearings,

$$D_o = 0.20(d + 4.0D) \quad (5.4)$$

where,

$d$  : Bearing bore diameter, mm

$D$  : Bearing outside diameter, mm

### 5.3 Bearing internal clearance selection standards

Theoretically, in regard to bearing life, the optimum operating internal clearance for any bearing would be a slight negative clearance after the bearing had reached normal operating temperature.

Unfortunately, under actual operating conditions, maintaining such optimum tolerances is often difficult at best. Due to various fluctuating operating conditions this slight minus clearance can quickly become a large minus, greatly lowering the life of the bearing and causing excessive heat to be generated. Therefore, an initial internal clearance which will result in a slightly greater than negative internal operating clearance should be selected.

Under normal operating conditions (e.g. normal load, fit, speed, temperature, etc.), a standard internal clearance will give a very satisfactory operating clearance.

Table 5.2 lists non-standard clearance recommendations for various applications and operating conditions.

**Table 5.2 Examples of applications where bearing clearances other than normal clearance are used**

Operating conditions	Applications	Selected clearance
Shaft is heated and housing is cooled.	Conveyor of casting machine	C5
Shaft or inner ring is heated.	Annealing pit, Drying pit, Curing pit	C4
Allows for shaft deflection and fitting errors.	Disc harrows	C4
	Combines	C3
Tight-fitted for both inner and outer rings.	Large blowers	C3
To reduce noise and vibration when rotating.	Multi-wing fan of air conditioners	C2

**Table 5.3(1)Cylindrical bore bearings**

Unit:  $\mu\text{m}/0.0001 \text{ inch}$

Nominal bore diameter $d$				Radial internal clearance															
				C2		CN		C3		C4									
over	incl.			min.	max.	min.	max.	min.	max.	min.	max.								
mm	inch	mm	inch																
10	0.3937	18	0.7087	0	0	9	4	3	1	18	7	11	4	25	10	18	7	33	13
18	0.7087	24	0.9449	0	0	10	4	5	2	20	8	13	5	28	11	20	8	36	14
24	0.9449	30	1.1811	1	0	11	4	5	2	20	8	13	5	28	11	23	9	41	16
30	1.1811	40	1.5748	1	0	11	4	6	2	20	8	15	6	33	13	28	11	46	18
40	1.5748	50	1.9685	1	0	11	4	6	2	23	9	18	7	36	14	30	12	51	20
50	1.9685	65	2.5591	1	0	15	6	8	3	28	11	23	9	43	17	38	15	61	24
65	2.5591	80	3.1496	1	0	15	6	10	4	30	12	25	10	51	20	46	18	71	28
80	3.1496	100	3.9370	1	0	18	7	12	5	36	14	30	12	58	23	53	21	84	33
100	3.9370	120	4.7244	2	1	20	8	15	6	41	16	36	14	66	26	61	24	97	38
120	4.7244	140	5.5118	2	1	23	9	18	7	48	19	41	16	81	32	71	28	114	45

Remarks Heat-resistant bearings with suffix HT2 have C4 clearances.

**Table 5.3(2)Tapered bore bearings**

Unit:  $\mu\text{m}/0.0001 \text{ inch}$

Nominal bore diameter $d$				Radial internal clearance															
				C2		CN		C3		C4									
over	incl.			min.	max.	min.	max.	min.	max.	min.	max.								
mm	inch	mm	inch																
24	0.9449	30	1.1811	5	2	20	8	13	5	28	11	23	9	41	16	30	12	53	21
30	1.1811	40	1.5748	6	2	20	8	15	6	33	13	28	11	46	18	40	16	64	25
40	1.5748	50	1.9685	6	2	23	9	18	7	36	14	30	12	51	20	45	18	73	29
50	1.9685	65	2.5591	8	3	28	11	23	9	43	17	38	15	61	24	55	22	90	35
65	2.5591	80	3.1496	10	4	30	12	25	10	51	20	46	18	71	28	65	26	105	41
80	3.1496	100	3.9370	12	5	36	14	30	12	58	23	53	21	84	33	75	30	120	47
100	3.9370	120	4.7244	15	6	41	16	36	14	66	26	61	24	97	38	90	35	140	55
120	4.7244	140	5.5118	18	7	48	19	41	16	81	32	71	28	114	45	105	41	160	63

## 6.Lubrication


As bearings in **NSK** bearing units have sufficient high-grade grease sealed in at the time of manufacture, there is no need for replenishment while in use. The amount of grease necessary for lubrication is, in general, very small. With the **NSK** bearing units, the amount of grease occupies about a half to a third of the space inside the bearing.

### 6.1 Maximum permissible speed of rotation

The maximum speed possible while ensuring the safety and long life of ball bearings used in the unit is limited by their size, the circumferential speed at the point where the seal comes into contact, and the load acting on them.

To indicate the maximum speed permissible, it is customary to use the value of  $dn$  or  $d_m n$  ( $d$  is the bore of the bearing;  $d_m$  is the diameter of the pitch circle= $(D+O.D.)/2$ ;  $n$  is the number of revolutions).

Problem connected with the lubrication of bearings are the generation of heat and seizures occurring at the sliding parts inside the bearing, in particular at the points where the ball is in contact with the retainer, inner and outer rings. The contact pressure at the points where friction occurs on the retainer is only



slightly affected by the load acting on the bearing; the amount of heat generated there is approximately in proportion to the sliding velocity. Therefore, this sliding velocity serves as a yardstick to measure the limit of the rotating speed of the bearing. In the case of a bearing unit, however, there is another large factor that has to be taken into account—the circumferential speed at the part where the seal is in contact.

The graph in Fig.6.1 indicates the maximum speed of rotation permissible, taking into account the aforementioned factors.

There are two common methods of locking the bearing unit onto the shaft—the set screw system and the eccentric collar system. However, in both of these systems high-speed operation will cause deformation of the inner ring, which may result in vibration of the bearing. For high-speed operation, therefore, it is recommended that an interference fit or a clearance fit with a near-zero clearance be used.

For standard bearing units with the contact type seal, the maximum speed permissible is  $120\,000/d$ . Where a higher speed is required, bearing units with the non-contact type seal, are advised. Please contact **NSK** regarding the use of the latter type. Additionally, it is necessary that the surface on which the housing is mounted be finished to as high a degree of accuracy as possible. A regularity of within  $\pm 0.05\text{mm}$ ,  $\pm 0.002\text{inch}$  is required.

### 6.2 Replenishment of grease

#### 6.2.1 Sealed-in grease

With **NSK** bearing units, no relubrication is the general rule. The standard self-lubricating type of bearing units contain high-grade lithium-based grease which, being suitable for long-term use, is ideal for sealed-type bearings. Relubrication, therefore, is unnecessary under most operating conditions.

At high temperatures, or where there is exposure to: water or excessive dust, the highest quality grease is essential. Therefore, **NSK** uses its own specially selected brands which are shown in Table 6.1. It is necessary to use the same brand when replenishing grease.

**Table 6.1 Brands of grease used in NSK bearing units**

Bearing units	Grease			Symbols	Operating temperature range °C, °F
	Name of grease	Thickening agent	Base oil		
Standard	Alvania grease S3	Li soap	Mineral oil	D1	-10°to +100°C,(+14°to +212°F).
Heat-resistant	SH44MT	Li soap	Silicone oil	HT2D1	Nomal temp.to + 130°C(266°F).
Cold-resistant	SH33L	Li soap	Silicone oil	CT1D1	-60°C(-76°F)to nomal temp.

## 6.2.2 Mixing of different kinds of grease

Whether or not different kinds of grease may be mixed usually depends on their thickeners. The commonly used criteria are shown in Table 6.2. Properties which are most susceptible to influences from mixing are viscosity, dropping point and penetration. Water and heat resisting properties as well as mechanical stability are also lowered. Therefore, when mixing in a grease which is different to that which is already in use, it is essential that the thickener (soap base) and the base oil be of the same group.

When relubricating NSK bearing units, it is advisable to use the brands of grease shown in Table 6.1

**Table 6.2 Mixing properties of grease**

Soap base	Ca	Na	Al	Ba	Li
Ca	○	△	△	×	△
Na	△	○	△	×	×
Al	△	△	○	×	×
Ba	×	×	×	○	×
Li	△	×	×	×	○

○ Mixing will not produce any appreciable change of properties.

△ Mixing may produce considerable variations of properties.

× Mixing will cause a drastic change of properties.

## 6.2.3 Relubrication frequency

Relubrication frequency varies with the kind and quality of grease used as well as the operating conditions. Therefore, it is difficult to establish a general rule, but under ordinary operating conditions, it is desirable that grease be replenished before one third (1/3) of its calculated life elapses. It is necessary, however, to take into consideration such factors as hardening of grease in the oil hole, making replenishment impossible; deterioration of grease while operation of the machine is suspended, and so forth.

In Table 6.3 below are shown standard relubrication frequencies. Irrespective of the calculated life of the grease, this list takes into consideration such factors as the rotational speed of the bearings, operating temperatures and environmental conditions, with a view to safety.

## 6.2.4 Re-greasing

The performance of a bearing is greatly influenced by the quantity of grease. In order to avoid over-filling, it is advisable to replenish the grease while the machine is in operation.

Continue to insert grease until a little oozes out from between the outer ring raceway and the periphery of the slinger, for optimum performance.

**Table 6.3 Standard relubrication frequencies**

Type of unit	Symbol	dn Value	Environmental conditions	Operating temp. °C, °F	Relubrication frequency	
					Hours	Period
Standard	D1	40 000 and below	Ordinary	-10 to +80, +14 to +176	1 500 to 3 000	6 to 12 mo.
Standard	D1	70 000 and below	Ordinary	-10 to +80, +14 to +176	1 000 to 2 000	3 to 6 mo.
Standard	D1	70 000 and below	Ordinary	+80 to +100, +176 to +212	500 to 700	1 mo.
Heat-resistant	HT2D1	70 000 and below	Ordinary	+100 to +130, +212 to +266	300 to 700	1 mo.
Cold-resistant	CT1D1	70 000 and below	Ordinary	-60 to +80, -76 to +176	1 000 to 2 000	3 to 6 mo.
Standard	D1	70 000 and below	Very dusty	-10 to +100, +14 to +212	100 to 500	1 wk. to 1 mo.
Standard	D1	70 000 and below	Exposed to water splashes	-10 to +100, +14 to +212	30 to 100	1 day to 1 wk.

## 6.3 Grease fitting

NSK bearing units are, as a general rule, provided with a grease fitting, as shown in Table 6.4, and a grease gun is used for regreasing. However, button-head and pin types may also be furnished on demand.

Grease fitting dimensions and the designation of applicable bearing units are given in Table 6.5.



**Table 6.4 Grease fitting types available for bearing units.**

Types of housing	Standard grease fitting types
Pillow type	GA type
Flange type	GA type
Take-up type	GB type
Hanger type	GA type
Cartridge type	GA type

**Table 6.5 Grease fitting dimensions and designations of applicable bearing units**

GA type (Vertical type)

Designation	d	H		B	
		mm	inch	mm	inch
GA- $\frac{1}{4}$ -28 UNF	$\frac{1}{4}$ -28 UNF	8.5	0.335	7	0.276
GA-PF $\frac{1}{8}$	G $\frac{1}{8}$	12	0.472	10	0.394
GA-PF $\frac{1}{4}$	G $\frac{1}{4}$	14	0.551	14	0.551

GB type (67.5°)

Designation	d	H		L		B	
		mm	inch	mm	inch	mm	inch
GB- $\frac{1}{4}$ -28 UNF	$\frac{1}{4}$ -28 UNF	10.5	0.413	9.3	0.366	8	0.315
GB-PF $\frac{1}{8}$	G $\frac{1}{8}$	14.2	0.559	13.5	0.531	10	0.394
GB-PF $\frac{1}{4}$	G $\frac{1}{4}$	15	0.591	13.5	0.531	14	0.551

Nominal screw size d	Series 2	Series X	Series 3
$\frac{1}{4}$ -28 UNF	203 - 209	X05 - X08	305 - 309
G $\frac{1}{8}$	210 - 215	X09 - X14	310 - 315
G $\frac{1}{4}$	216 - 218	X15 - X20	316 - 328

**Remarks** Screw size for the cartridge type is  $\frac{1}{4}$ -28 UNF.  
That for C310D1 to C328D1 is G  $\frac{1}{4}$ (PF  $\frac{1}{4}$ ).

## 6.4 standard location of the grease fitting

Standard location of grease fitting on the housing for the relubricatable bearing units of each type is illustrated below.

P, PL, Z-P, type	C-F type	FL, FLU, Z-FL type	T, Z-T type
C-P type	F, FU, Z-F (#204, #205)	C-FL type	C-T type
HP type	C-FS type	FH type	M, L, Z-M, Z-L type
UP type	FC, Z-FC type	FA type	C-M, C-L type
Except (#204, #205) F, FU, Z-F type	C-FC type	HB type	C type

## 7. Recommended Torques for Tightening Set Screws

**Table 7.1 Recommended torques for tightening set screws**

A) Metric series, applied to metric bore size.

Designation of the bearings of applicable units			Designation of set screws	Tightening torques N·m(max.)
UC201 to UC205	—	—	M 5×0.8 × 7	3.9
UC206	—	UC305 to UC306	M 6×0.75 × 8	4.9
UC207	UCX05	—	M 6×0.75 × 8	5.8
UC208 to UC210	—	—	M 8×1 ×10	7.8
UC211	UCX06 to UCX08	UC307	M 8×1 ×10	9.8
UC212	UCX09	—	M10×1.25×12	16.6
UC213 to UC215	—	UC308 to UC309	M10×1.25×12	19.6
UC216	UCX10	—	M10×1.25×12	22.5
—	UCX11 to UCX12	—	M10×1.25×12	24.5
UC217 to UC218	UCX13 to UCX15	UC310 to UC314	M12×1.5 ×13	29.4
—	UCX16 to UCX17	—	M12×1.5 ×13	34.3
—	UCX18	UC315 to UC316	M14×1.5 ×15	34.3
—	UCX20	UC317 to UC319	M16×1.5 ×18	53.9
—	—	UC320 to UC324	M18×1.5 ×20	58.8
—	—	UC326 to UC328	M20×1.5 ×25	78.4

B) Inch series, applied to inch bore size.

Designation of the bearings for the unit to which torques given are applicable			Designation of set screws	Tightening torques lbf·inch(max.)
UC201 to UC205	—	—	No.10-32UNF	34
UC206	—	UC305 to UC306	¼-28UNF	43
UC207	UCX05	—	¼-28UNF	52
UC208 to UC210	—	—	⅝-24UNF	69
UC211	UCX06 to UCX08	UC307	⅝-24UNF	86
UC212	UCX09	—	⅜-24UNF	147
UC213 to UC215	—	UC308 to UC309	⅜-24UNF	173
UC216	UCX10	—	⅜-24UNF	199
—	UCX11 to UCX12	—	⅜-24UNF	216
UC217 to UC218	UCX13 to UCX15	UC310 to UC314	½-20UNF	260
—	UCX16 to UCX17	—	½-20UNF	303
—	UCX18	UC315 to UC316	⅞-18UNF	303
—	UCX20	UC317 to UC319	⅝-18UNF	477
—	—	UC320	⅝-18UNF	520

Designation of the bearings of applicable units	Designation of set screws	Tightening torques N·m(max.)
AS201 to 205	M 5×0.8 × 7	3.4
AS206	M 6×0.75 × 8	4.4
AS207	M 6×0.75 × 8	4.9
AS208	M 8×1 ×10	6.8

Designation of the bearings for the unit to which torques given are applicable	Designation of set screws	Tightening torques lbf·inch(max.)
AS201 to 205	No.10-32UNF	30
AS206	¼-28UNF	39
AS207	¼-28UNF	43
AS208	⅝-24UNF	60

# **Contents of ball bearing units and ball bearings for bearing units**

# DIMENSION TABLE

	<i>Pages</i>		<i>Pages</i>		<i>Pages</i>		<i>Pages</i>
<b>Set screw type</b>		Take-up unit, cast housing		Rhombus flanged unit, cast housing		Rhombus flanged unit, cast housing	
Pillow block unit, cast housing		<b>UCT2</b> .....	B114	<b>UELFL2</b> .....	B198	<b>UKFL2</b> .....	B284
<b>UCP2</b> .....	B4	<b>UCT3</b> .....	B120	<b>UELFL3</b> .....	B202	<b>UKFL3</b> .....	B288
<b>UCP3</b> .....	B10	<b>UCTX</b> .....	B126	<b>UELFLU2</b> .....	B208	<b>UKFLX</b> .....	B292
<b>UCPX</b> .....	B16	Take-up stretcher units		<b>AELFB2</b> .....	B212	Take-up unit, cast housing	
<b>UCPL2</b> .....	B22	<b>UCT2-</b> .....	B130	<b>AELFD2</b> .....	B214	<b>UKT2</b> .....	B294
<b>UCHP2</b> .....	B26	Take-up type L stretcher units		<b>JELFD2</b> .....	B216	<b>UKT3</b> .....	B298
<b>UCUP2</b> .....	B30	<b>UCL2-</b> .....	B132	Round flanged unit, pressed steel housing		<b>UKTX</b> .....	B302
<b>ASPL2</b> .....	B34	Take-up type M stretcher units		<b>AELPF2</b> .....	B218	Cartridge unit, cast housing	
Pillow block unit, pressed steel housing		<b>UCM2-</b> .....	B134	<b>JELPF2</b> .....	B220	<b>UKC2</b> .....	B306
<b>ASPP2</b> .....	B38	<b>UCM3-</b> .....	B136	<b>AELRPF2</b> .....	B222	<b>UKC3</b> .....	B308
<b>ASRPP2</b> .....	B40	Take-up mini stretcher units		Rhombus flanged unit, pressed steel housing		<b>UKCX</b> .....	B310
Square flanged unit, cast housing		<b>ASPT2-</b> .....	B138	<b>AELPFL2</b> .....	B224	<b>Ball bearings</b>	
<b>UCF2</b> .....	B42	Cartridge unit, cast housing		<b>JELPFL2</b> .....	B226	Set screw type	
<b>UCF3</b> .....	B48	<b>UCC2</b> .....	B140	Take-up unit, cast housing		<b>UC2</b> .....	B312
<b>UCFX</b> .....	B54	<b>UCC3</b> .....	B142	<b>UEL2</b> .....	B228	<b>UC3</b> .....	B318
<b>UCFS3</b> .....	B60	<b>UCCX</b> .....	B146	<b>UEL3</b> .....	B232	<b>UCX</b> .....	B324
Round flanged unit, cast housing		<b>Eccentric locking collar type</b>		Take-up mini stretcher units		<b>AS2</b> .....	B328
<b>UCFC2</b> .....	B66	Pillow block unit, cast housing		<b>AELPT2-</b> .....	B238	<b>AR2</b> .....	B332
<b>UCFCX</b> .....	B72	<b>UEL2</b> .....	B148	<b>JELPT2</b> .....	B240	Eccentric locking collar type	
Rhombus flanged unit, cast housing		<b>UEL3</b> .....	B152	Cartridge unit, cast housing		<b>UEL2</b> .....	B336
<b>UCFL2</b> .....	B78	<b>UELPL2</b> .....	B158	<b>UELC2</b> .....	B242	<b>UEL3</b> .....	B340
<b>UCFL3</b> .....	B84	<b>UELHP2</b> .....	B162	<b>UELC3</b> .....	B244	<b>AEL2</b> .....	B346
<b>UCFLX</b> .....	B90	<b>UELUP2</b> .....	B164	<b>Adapter type</b>			
<b>UCFA2</b> .....	B92	<b>AELPL2</b> .....	B166	Pillow block unit, cast housing		<b>JEL2</b> .....	B348
<b>UCFH2</b> .....	B96	<b>JELPL2</b> .....	B168	<b>UKP2</b> .....	B248	<b>REL2</b> .....	B350
<b>ASFB2</b> .....	B100	Pillow block unit, pressed steel housing		<b>UKP3</b> .....	B252	Adapter type	
<b>ASFD2</b> .....	B102	<b>AELPP2</b> .....	B170	<b>UKPX</b> .....	B256	<b>UK2</b> .....	B354
Round flanged unit, pressed steel housing		<b>AELRPP2</b> .....	B172	Square flanged unit, cast housing		<b>UK3</b> .....	B358
<b>ASPF2</b> .....	B104	Square flanged unit, cast housing		<b>UKF2</b> .....	B260	<b>UKX</b> .....	B362
<b>ASRPF2</b> .....	B106	<b>UEL2</b> .....	B174	<b>UKF3</b> .....	B264	Other bearings	
Rhombus flanged unit, pressed steel housing		<b>UEL3</b> .....	B178	<b>UKFX</b> .....	B268	<b>UCS2</b> .....	B366
<b>ASPFL2</b> .....	B108	<b>UEL2U2</b> .....	B184	<b>UKFS3</b> .....	B272	<b>UCS3</b> .....	B370
Hanger unit, cast housing		<b>UELFS3</b> .....	B188	Round flanged unit, cast housing		<b>ASS2</b> .....	B374
<b>UCHB2</b> .....	B110	Round flanged unit, cast housing		<b>UKFC2</b> .....	B276	<b>UELS2</b> .....	B376
		<b>UELFC2</b> .....	B194	<b>UKFCX</b> .....	B280	<b>UELS3</b> .....	B380
						<b>AELS2</b> .....	B384
						<b>JELS2</b> .....	B386
						<b>CS2</b> .....	B388



## Pillow block unit, cast housing Set screw type



**Pressed steel dust cover type**  
Open end **Z-UCP...D1**  
Closed end **ZM-UCP...D1**

Shaft dia. mm inch	Unit number (*)	Nominal dimensions											Bolt size mm inch	Bearing number
		mm inch												
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S		
12 1/2	<b>UCP201D1</b> <b>UCP201-008D1</b>	30.2 1 3/16	127 5	95 3 3/4	38 1 1/2	13 1/2	16 5/8	14 9/16	62 2 7/16	42 1 21/32	31 1.2205	12.7 0.500	M10 3/8	UC201D1 UC201-008D1
15 9/16 5/8	<b>UCP202D1</b> <b>UCP202-009D1</b> <b>UCP202-010D1</b>	30.2 1 3/16	127 5	95 3 3/4	38 1 1/2	13 1/2	16 5/8	14 9/16	62 2 7/16	42 1 21/32	31 1.2205	12.7 0.500	M10 3/8	UC202D1 UC202-009D1 UC202-010D1
17 11/16	<b>UCP203D1</b> <b>UCP203-011D1</b>	30.2 1 3/16	127 5	95 3 3/4	38 1 1/2	13 1/2	16 5/8	14 9/16	62 2 7/16	42 1 21/32	31 1.2205	12.7 0.500	M10 3/8	UC203D1 UC203-011D1
20 3/4	<b>UCP204D1</b> <b>UCP204-012D1</b>	33.3 1 5/16	127 5	95 3 3/4	38 1 1/2	13 1/2	16 5/8	14 9/16	65 2 9/16	42 1 21/32	31 1.2205	12.7 0.500	M10 3/8	UC204D1 UC204-012D1
25 13/16 7/8 15/16 1	<b>UCP205D1</b> <b>UCP205-013D1</b> <b>UCP205-014D1</b> <b>UCP205-015D1</b> <b>UCP205-100D1</b>	36.5 1 7/16	140 5 1/2	105 4 1/8	38 1 1/2	13 1/2	16 5/8	15 19/32	71 2 25/32	42 1 21/32	34.1 1.3425	14.3 0.563	M10 3/8	UC205D1 UC205-013D1 UC205-014D1 UC205-015D1 UC205-100D1
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UCP206D1</b> <b>UCP206-101D1</b> <b>UCP206-102D1</b> <b>UCP206-103D1</b> <b>UCP206-104D1</b>	42.9 1 11/16	165 6 1/2	121 4 3/4	48 1 7/8	17 21/32	20 25/32	17 21/32	83 3 9/32	54 2 1/8	38.1 1.5000	15.9 0.626	M14 1/2	UC206D1 UC206-101D1 UC206-102D1 UC206-103D1 UC206-104D1
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UCP207D1</b> <b>UCP207-104D1</b> <b>UCP207-105D1</b> <b>UCP207-106D1</b> <b>UCP207-107D1</b>	47.6 1 7/8	167 6 9/16	127 5	48 1 7/8	17 21/32	20 25/32	18 23/32	93 3 21/32	54 2 1/8	42.9 1.6890	17.5 0.689	M14 1/2	UC207D1 UC207-104D1 UC207-105D1 UC207-106D1 UC207-107D1
40 1 1/2 1 9/16	<b>UCP208D1</b> <b>UCP208-108D1</b> <b>UCP208-109D1</b>	49.2 1 15/16	184 7 1/4	137 5 13/32	54 2 1/8	17 21/32	20 25/32	18 23/32	98 3 27/32	52 2 1/16	49.2 1.9370	19 0.748	M14 1/2	UC208D1 UC208-108D1 UC208-109D1
45 1 5/8 1 11/16 1 3/4	<b>UCP209D1</b> <b>UCP209-110D1</b> <b>UCP209-111D1</b> <b>UCP209-112D1</b>	54 2 1/8	190 7 5/8	146 5 3/4	54 2 1/8	17 21/32	20 25/32	20 25/32	106 4 3/16	60 2 3/8	49.2 1.9370	19 0.748	M14 1/2	UC209D1 UC209-110D1 UC209-111D1 UC209-112D1

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.



**Cast dust cover type**  
Open end **C-UCP...D1**  
Closed end **CM-UCP...D1**

Housing number	Unit number (*) pressed steel dust cover type	Unit number (*) cast dust cover type	Nominal dimensions				Mass of unit		
			mm inch				kg lb		
			t max.	A <sub>4</sub>	H <sub>3</sub>	A <sub>5</sub>	UCP	Z(ZM)	C(CM)
P203D1 P203D1	<b>Z(ZM)-UCP201D1</b> <b>Z(ZM)-UCP201-008D1</b>	<b>C(CM)-UCP201D1</b> <b>C(CM)-UCP201-008D1</b>	2 5/64	45 1 25/32	67 2 5/8	62 2 7/16	0.7 1.5	0.7 1.5	1.0 2.2
P203D1 P203D1 P203D1	<b>Z(ZM)-UCP202D1</b> <b>Z(ZM)-UCP202-009D1</b> <b>Z(ZM)-UCP202-010D1</b>	<b>C(CM)-UCP202D1</b> <b>C(CM)-UCP202-009D1</b> <b>C(CM)-UCP202-010D1</b>	2 5/64	45 1 25/32	67 2 5/8	62 2 7/16	0.7 1.5	0.7 1.5	1.0 2.2
P203D1 P203D1	<b>Z(ZM)-UCP203D1</b> <b>Z(ZM)-UCP203-011D1</b>	<b>C(CM)-UCP203D1</b> <b>C(CM)-UCP203-011D1</b>	2 5/64	45 1 25/32	67 2 5/8	62 2 7/16	0.7 1.5	0.7 1.5	1.0 2.2
P204D1 P204D1	<b>Z(ZM)-UCP204D1</b> <b>Z(ZM)-UCP204-012D1</b>	<b>C(CM)-UCP204D1</b> <b>C(CM)-UCP204-012D1</b>	2 5/64	45 1 25/32	70 2 3/4	62 2 7/16	0.7 1.5	0.7 1.5	0.9 2.0
P205D1 P205D1 P205D1 P205D1	<b>Z(ZM)-UCP205D1</b> <b>Z(ZM)-UCP205-013D1</b> <b>Z(ZM)-UCP205-014D1</b> <b>Z(ZM)-UCP205-015D1</b> <b>Z(ZM)-UCP205-100D1</b>	<b>C(CM)-UCP205D1</b> <b>C(CM)-UCP205-013D1</b> <b>C(CM)-UCP205-014D1</b> <b>C(CM)-UCP205-015D1</b> <b>C(CM)-UCP205-100D1</b>	2 5/64	48 1 29/32	76 3	70 2 3/4	0.8 1.8	0.9 2.0	1.1 2.4
P206D1 P206D1 P206D1 P206D1 P206D1	<b>Z(ZM)-UCP206D1</b> <b>Z(ZM)-UCP206-101D1</b> <b>Z(ZM)-UCP206-102D1</b> <b>Z(ZM)-UCP206-103D1</b> —	<b>C(CM)-UCP206D1</b> <b>C(CM)-UCP206-101D1</b> <b>C(CM)-UCP206-102D1</b> <b>C(CM)-UCP206-103D1</b> —	2 5/64	53 2 3/32	88 3 15/32	75 2 15/16	1.4 3.1	1.4 3.1	1.7 3.7
P207D1 P207D1 P207D1 P207D1 P207D1	<b>Z(ZM)-UCP207D1</b> <b>Z(ZM)-UCP207-104D1</b> <b>Z(ZM)-UCP207-105D1</b> <b>Z(ZM)-UCP207-106D1</b> —	<b>C(CM)-UCP207D1</b> <b>C(CM)-UCP207-104D1</b> <b>C(CM)-UCP207-105D1</b> <b>C(CM)-UCP207-106D1</b> —	3 1/8	60 2 3/8	99 3 29/32	80 3 5/32	1.6 3.5	1.7 3.7	2.0 4.4
P208D1 P208D1 P208D1	<b>Z(ZM)-UCP208D1</b> <b>Z(ZM)-UCP208-108D1</b> <b>Z(ZM)-UCP208-109D1</b>	<b>C(CM)-UCP208D1</b> <b>C(CM)-UCP208-108D1</b> <b>C(CM)-UCP208-109D1</b>	3 1/8	69 2 23/32	105 4 1/8	90 3 17/32	1.9 4.2	2.1 4.6	2.7 6.0
P209D1 P209D1 P209D1 P209D1	<b>Z(ZM)-UCP209D1</b> <b>Z(ZM)-UCP209-110D1</b> <b>Z(ZM)-UCP209-111D1</b> <b>Z(ZM)-UCP209-112D1</b>	<b>C(CM)-UCP209D1</b> <b>C(CM)-UCP209-110D1</b> <b>C(CM)-UCP209-111D1</b> <b>C(CM)-UCP209-112D1</b>	3 1/8	69 2 23/32	113 4 7/16	95 3 3/4	2.2 4.9	2.4 5.3	3.1 6.8

## Pillow block unit, cast housing Set screw type



**Pressed steel dust cover type**  
Open end **Z-UCP...D1**  
Closed end **ZM-UCP...D1**

Shaft dia. mm inch	Unit number (*)	Nominal dimensions											Bolt size mm inch	Bearing number
		mm inch												
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S		
50 1 3/16 1 1/8 1 5/16 2	<b>UCP210D1</b> <b>UCP210-113D1</b> <b>UCP210-114D1</b> <b>UCP210-115D1</b> <b>UCP210-200D1</b>	57.2	206	159	60	20	23	21	114	65	51.6	19	M16	<b>UC210D1</b> UC210-113D1 UC210-114D1 UC210-115D1 UC210-200D1
55 2 2 1/16 2 1/8 2 3/16	<b>UCP211D1</b> <b>UCP211-200D1</b> <b>UCP211-201D1</b> <b>UCP211-202D1</b> <b>UCP211-203D1</b>	63.5	219	171	60	20	23	23	126	65	55.6	22.2	M16	<b>UC211D1</b> UC211-200D1 UC211-201D1 UC211-202D1 UC211-203D1
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UCP212D1</b> <b>UCP212-204D1</b> <b>UCP212-205D1</b> <b>UCP212-206D1</b> <b>UCP212-207D1</b>	69.8	241	184	70	20	23	25	138	70	65.1	25.4	M16	<b>UC212D1</b> UC212-204D1 UC212-205D1 UC212-206D1 UC212-207D1
65 2 1/2 2 9/16	<b>UCP213D1</b> <b>UCP213-208D1</b> <b>UCP213-209D1</b>	76.2	265	203	70	25	28	27	151	77	65.1	25.4	M20	<b>UC213D1</b> UC213-208D1 UC213-209D1
70 2 5/8 2 11/16 2 3/4	<b>UCP214D1</b> <b>UCP214-210D1</b> <b>UCP214-211D1</b> <b>UCP214-212D1</b>	79.4	266	210	72	25	28	27	157	77	74.6	30.2	M20	<b>UC214D1</b> UC214-210D1 UC214-211D1 UC214-212D1
75 2 13/16 2 7/8 2 15/16 3	<b>UCP215D1</b> <b>UCP215-213D1</b> <b>UCP215-214D1</b> <b>UCP215-215D1</b> <b>UCP215-300D1</b>	82.6	275	217	74	25	28	28	163	80	77.8	33.3	M20	<b>UC215D1</b> UC215-213D1 UC215-214D1 UC215-215D1 UC215-300D1
80 3 1/16 3 1/8 3 3/16	<b>UCP216D1</b> <b>UCP216-301D1</b> <b>UCP216-302D1</b> <b>UCP216-303D1</b>	88.9	292	232	78	25	28	30	175	85	82.6	33.3	M20	<b>UC216D1</b> UC216-301D1 UC216-302D1 UC216-303D1

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.



**Cast dust cover type**  
Open end **C-UCP...D1**  
Closed end **CM-UCP...D1**

Housing number	Unit number (*) pressed steel dust cover type	Unit number (*) cast dust cover type	Nominal dimensions				Mass of unit		
			mm inch				kg lb		
			t max.	A <sub>4</sub>	H <sub>3</sub>	A <sub>5</sub>	UCP	Z(ZM)	C(CM)
P210D1 P210D1 P210D1 P210D1 P210D1	<b>Z(ZM)-UCP210D1</b> <b>Z(ZM)-UCP210-113D1</b> <b>Z(ZM)-UCP210-114D1</b> <b>Z(ZM)-UCP210-115D1</b> —	<b>C(CM)-UCP210D1</b> <b>C(CM)-UCP210-113D1</b> <b>C(CM)-UCP210-114D1</b> <b>C(CM)-UCP210-115D1</b> <b>C(CM)-UCP210-200D1</b>	3 1/8	76 3	119 4 11/16	100 3 15/16	2.7 6.0	2.8 6.2	3.6 7.9
P211D1 P211D1 P211D1 P211D1 P211D1	<b>Z(ZM)-UCP211D1</b> <b>Z(ZM)-UCP211-200D1</b> <b>Z(ZM)-UCP211-201D1</b> <b>Z(ZM)-UCP211-202D1</b> <b>Z(ZM)-UCP211-203D1</b>	<b>C(CM)-UCP211D1</b> <b>C(CM)-UCP211-200D1</b> <b>C(CM)-UCP211-201D1</b> <b>C(CM)-UCP211-202D1</b> <b>C(CM)-UCP211-203D1</b>	4 5/32	77 3 1/2	130 5 1/8	100 3 15/16	3.5 7.7	3.5 7.7	4.4 9.7
P212D1 P212D1 P212D1 P212D1 P212D1	<b>Z(ZM)-UCP212D1</b> <b>Z(ZM)-UCP212-204D1</b> <b>Z(ZM)-UCP212-205D1</b> <b>Z(ZM)-UCP212-206D1</b> —	<b>C(CM)-UCP212D1</b> <b>C(CM)-UCP212-204D1</b> <b>C(CM)-UCP212-205D1</b> <b>C(CM)-UCP212-206D1</b> <b>C(CM)-UCP212-207D1</b>	4 5/32	89 3 1/2	143 5 5/8	115 4 17/32	4.7 10	5.0 11	6.0 13
P213D1 P213D1 P213D1	<b>Z(ZM)-UCP213D1</b> <b>Z(ZM)-UCP213-208D1</b> <b>Z(ZM)-UCP213-209D1</b>	<b>C(CM)-UCP213D1</b> <b>C(CM)-UCP213-208D1</b> <b>C(CM)-UCP213-209D1</b>	4 5/32	91 3 19/32	155 6 3/32	120 4 23/32	5.6 12	5.8 13	7.2 16
P214D1 P214D1 P214D1 P214D1	— — — —	<b>C(CM)-UCP214D1</b> <b>C(CM)-UCP214-210D1</b> <b>C(CM)-UCP214-211D1</b> <b>C(CM)-UCP214-212D1</b>	4 5/32	— —	162 6 3/8	135 5 5/16	6.5 14	— —	8.3 18
P215D1 P215D1 P215D1 P215D1	— — — —	<b>C(CM)-UCP215D1</b> <b>C(CM)-UCP215-213D1</b> <b>C(CM)-UCP215-214D1</b> <b>C(CM)-UCP215-215D1</b> <b>C(CM)-UCP215-300D1</b>	4 5/32	— —	168 6 5/8	135 5 5/16	7.2 16	— —	9.3 21
P216D1 P216D1 P216D1 P216D1	— — — —	<b>C(CM)-UCP216D1</b> <b>C(CM)-UCP216-301D1</b> <b>C(CM)-UCP216-302D1</b> <b>C(CM)-UCP216-303D1</b>	4 5/32	— —	181 7 1/8	145 5 23/32	8.7 19	— —	11 24

## Pillow block unit, cast housing Set screw type



**Pressed steel dust cover type**  
Open end **Z-UCP...D1**  
Closed end **ZM-UCP...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup>	Nominal dimensions											Bolt size mm inch	Bearing number
		mm inch												
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S		
85 3 1/4 3 5/16 3 7/16	<b>UCP217D1</b> <b>UCP217-304D1</b> <b>UCP217-305D1</b> <b>UCP217-307D1</b>	95.2	310	247	83	25	28	32	187	85	85.7	34.1	M20	<b>UC217D1</b> UC217-304D1 UC217-305D1 UC217-307D1
90 3 1/2	<b>UCP218D1</b> <b>UCP218-308D1</b>	101.6	327	262	88	27	30	33	200	90	96	39.7	M22	<b>UC218D1</b> UC218-308D1

**Note** <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
**Remarks** Please refer to page A21 for size of grease fitting.



**Cast dust cover type**  
Open end **C-UCP...D1**  
Closed end **CM-UCP...D1**

Housing number	Unit number <sup>(1)</sup> pressed steel dust cover type	Unit number <sup>(1)</sup> cast dust cover type	Nominal dimensions				Mass of unit		
			mm inch				kg lb		
			t <sub>max.</sub>	A <sub>4</sub>	H <sub>3</sub>	A <sub>5</sub>	UCP	Z(ZM)	C(CM)
P217D1 P217D1 P217D1 P217D1	—	<b>C(CM)-UCP217D1</b> <b>C(CM)-UCP217-304D1</b> <b>C(CM)-UCP217-305D1</b> <b>C(CM)-UCP217-307D1</b>	5 13/64	—	191 7 17/32	155 6 3/32	11 24	—	13 29
P218D1 P218D1	—	<b>C(CM)-UCP218D1</b> <b>C(CM) UCP218-308D1</b>	5 13/64	—	204 8 1/32	165 6 1/2	13 29	—	16 35

## Pillow block unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S	
25 1 13/16 7/8 15/16 1	<b>UCP305D1</b> <b>UCP305-013D1</b> <b>UCP305-014D1</b> <b>UCP305-015D1</b> <b>UCP305-100D1</b>	45	175	132	45	17	20	15	85	54	38	15	M14
		1 49/64	6 7/8	5 3/16	1 25/32	2 1/32	2 5/32	1 9/32	3 11/32	2 1/8	1.4961	0.591	1/2
30 1 1/16 1 1/8 1 3/16	<b>UCP306D1</b> <b>UCP306-101D1</b> <b>UCP306-102D1</b> <b>UCP306-103D1</b>	50	180	140	50	17	20	18	95	54	43	17	M14
		1 31/32	7 3/32	5 1/2	1 31/32	2 1/32	2 5/32	2 3/32	3 3/4	2 1/8	1.6929	0.669	1/2
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UCP307D1</b> <b>UCP307-104D1</b> <b>UCP307-105D1</b> <b>UCP307-106D1</b> <b>UCP307-107D1</b>	56	210	160	56	17	25	20	106	60	48	19	M14
		2 13/64	8 9/32	6 5/16	2 7/32	2 1/32	3 1/32	2 5/32	4 3/16	2 3/8	1.8898	0.748	1/2
40 1 1/2 1 9/16	<b>UCP308D1</b> <b>UCP308-108D1</b> <b>UCP308-109D1</b>	60	220	170	60	17	27	22	116	60	52	19	M14
		2 23/64	8 21/32	6 11/16	2 3/8	2 1/32	1 1/16	7/8	4 9/16	2 3/8	2.0472	0.748	1/2
45 1 5/8 1 11/16 1 3/4	<b>UCP309D1</b> <b>UCP309-110D1</b> <b>UCP309-111D1</b> <b>UCP309-112D1</b>	67	245	190	67	20	30	24	129	65	57	22	M16
		2 41/64	9 21/32	7 15/32	2 5/8	2 5/32	1 3/16	1 5/16	5 3/32	2 9/16	2.2441	0.866	5/8
50 1 13/16 1 7/8 1 15/16	<b>UCP310D1</b> <b>UCP310-113D1</b> <b>UCP310-114D1</b> <b>UCP310-115D1</b>	75	275	212	75	20	35	27	143	75	61	22	M16
		2 61/64	10 13/16	8 11/32	2 15/16	2 5/32	1 3/8	1 1/16	5 5/8	2 15/16	2.4016	0.866	5/8
55 2 2 1/16 2 1/8 2 3/16	<b>UCP311D1</b> <b>UCP311-200D1</b> <b>UCP311-201D1</b> <b>UCP311-202D1</b> <b>UCP311-203D1</b>	80	310	236	80	20	38	30	154	85	66	25	M16
		3 5/32	12 7/32	9 9/32	3 5/32	2 5/32	1 1/2	1 3/16	6 1/16	3 11/32	2.5984	0.984	5/8

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type  
Open end **C-UCP...D1**  
Closed end **CM-UCP...D1**

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			t max.	H <sub>3</sub>	A <sub>5</sub>	UCP	C(CM)
UC305D1 UC305-013D1 UC305-014D1 UC305-015D1 UC305-100D1	P305D1 P305D1 P305D1 P305D1 P305D1	<b>C(CM)-UCP305D1</b> <b>C(CM)-UCP305-013D1</b> <b>C(CM)-UCP305-014D1</b> <b>C(CM)-UCP305-015D1</b> <b>C(CM)-UCP305-100D1</b>	2 5/64	91 3 19/32	80 3 5/32	1.4 3.1	1.8 4.0
UC306D1 UC306-101D1 UC306-102D1 UC306-103D1	P306D1 P306D1 P306D1 P306D1	<b>C(CM)-UCP306D1</b> <b>C(CM)-UCP306-101D1</b> <b>C(CM)-UCP306-102D1</b> <b>C(CM)-UCP306-103D1</b>	2 5/64	105 4 1/8	85 3 11/32	1.8 4.0	2.5 5.5
UC307D1 UC307-104D1 UC307-105D1 UC307-106D1 UC307-107D1	P307D1 P307D1 P307D1 P307D1 P307D1	<b>C(CM)-UCP307D1</b> <b>C(CM)-UCP307-104D1</b> <b>C(CM)-UCP307-105D1</b> <b>C(CM)-UCP307-106D1</b> <b>C(CM)-UCP307-107D1</b>	3 1/8	115 4 17/32	95 3 3/4	2.5 5.5	3.2 7.1
UC308D1 UC308-108D1 UC308-109D1	P308D1 P308D1 P308D1	<b>C(CM)-UCP308D1</b> <b>C(CM)-UCP308-108D1</b> <b>C(CM)-UCP308-109D1</b>	3 1/8	125 4 29/32	105 4 1/8	3.1 6.8	4.0 8.8
UC309D1 UC309-110D1 UC309-111D1 UC309-112D1	P309D1 P309D1 P309D1 P309D1	<b>C(CM)-UCP309D1</b> <b>C(CM)-UCP309-110D1</b> <b>C(CM)-UCP309-111D1</b> <b>C(CM)-UCP309-112D1</b>	3 1/8	140 5 1/2	110 4 11/32	4.1 9.0	5.4 12
UC310D1 UC310-113D1 UC310-114D1 UC310-115D1	P310D1 P310D1 P310D1 P310D1	<b>C(CM)-UCP310D1</b> <b>C(CM)-UCP310-113D1</b> <b>C(CM)-UCP310-114D1</b> <b>C(CM)-UCP310-115D1</b>	3 1/8	156 6 5/32	120 4 23/32	5.6 12	7.0 15
UC311D1 UC311-200D1 UC311-201D1 UC311-202D1 UC311-203D1	P311D1 P311D1 P311D1 P311D1 P311D1	<b>C(CM)-UCP311D1</b> <b>C(CM)-UCP311-200D1</b> <b>C(CM)-UCP311-201D1</b> <b>C(CM)-UCP311-202D1</b> <b>C(CM)-UCP311-203D1</b>	4 5/32	166 6 17/32	125 4 29/32	7.3 16	8.8 19


## Pillow block unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S	
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UCP312D1</b> <b>UCP312-204D1</b> <b>UCP312-205D1</b> <b>UCP312-206D1</b> <b>UCP312-207D1</b>	85	330	250	85	25	38	32	165	95	71	26	M20
		3 11/32	13	9 27/32	3 11/32	31/32	1 1/2	1 1/4	6 1/2	3 3/4	2.7953	1.024	3/4
65 2 1/2 2 9/16	<b>UCP313D1</b> <b>UCP313-208D1</b> <b>UCP313-209D1</b>	90	340	260	90	25	38	33	176	105	75	30	M20
		3 35/64	13 3/8	10 1/4	3 17/32	31/32	1 1/2	1 5/16	6 15/16	4 1/8	2.9528	1.181	3/4
70 2 5/8 2 11/16 2 3/4	<b>UCP314D1</b> <b>UCP314-210D1</b> <b>UCP314-211D1</b> <b>UCP314-212D1</b>	95	360	280	90	27	40	35	187	105	78	33	M22
		3 47/64	14 3/16	11 1/32	3 17/32	1 1/16	1 9/16	1 3/8	7 3/8	4 1/8	3.0709	1.299	7/8
75 2 13/16 2 7/8 2 15/16 3	<b>UCP315D1</b> <b>UCP315-213D1</b> <b>UCP315-214D1</b> <b>UCP315-215D1</b> <b>UCP315-300D1</b>	100	380	290	100	27	40	35	198	110	82	32	M22
		3 15/16	14 31/32	11 13/32	3 15/16	1 1/16	1 9/16	1 3/8	7 25/32	4 11/32	3.2283	1.260	7/8
80 3 1/16 3 1/8 3 3/16	<b>UCP316D1</b> <b>UCP316-301D1</b> <b>UCP316-302D1</b> <b>UCP316-303D1</b>	106	400	300	110	27	40	40	210	110	86	34	M22
		4 11/64	15 3/4	11 13/16	4 11/32	1 1/16	1 9/16	1 9/16	8 9/32	4 11/32	3.3858	1.339	7/8
85 3 1/4 3 5/16 3 7/16	<b>UCP317D1</b> <b>UCP317-304D1</b> <b>UCP317-305D1</b> <b>UCP317-307D1</b>	112	420	320	110	33	45	40	220	120	96	40	M27
		4 13/32	16 17/32	12 19/32	4 11/32	1 5/16	1 25/32	1 9/16	8 21/32	4 23/32	3.7795	1.575	1
90 3 7/16 3 1/2	<b>UCP318D1</b> <b>UCP318-307D1</b> <b>UCP318-308D1</b>	118	430	330	110	33	45	45	235	120	96	40	M27
		4 11/64	16 15/16	13	4 11/32	1 5/16	1 25/32	1 25/32	9 1/4	4 23/32	3.7795	1.575	1

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type  
Open end **C-UCP...D1**  
Closed end **CM-UCP...D1**

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			t max.	H <sub>3</sub>	A <sub>5</sub>	UCP	C(CM)
UC312D1 UC312-204D1 UC312-205D1 UC312-206D1 UC312-207D1	P312D1 P312D1 P312D1 P312D1 P312D1	<b>C(CM)-UCP312D1</b> <b>C(CM)-UCP312-204D1</b> <b>C(CM)-UCP312-205D1</b> <b>C(CM)-UCP312-206D1</b> <b>C(CM)-UCP312-207D1</b>	4 5/32	179 7 1/16	135 5 5/16	9.4 21	11 24
UC313D1 UC313-208D1 UC313-209D1	P313D1 P313D1 P313D1	<b>C(CM)-UCP313D1</b> <b>C(CM)-UCP313-208D1</b> <b>C(CM)-UCP313-209D1</b>	4 5/32	190 7 15/32	140 5 1/2	10 22	12 26
UC314D1 UC314-210D1 UC314-211D1 UC314-212D1	P314D1 P314D1 P314D1 P314D1	<b>C(CM)-UCP314D1</b> <b>C(CM)-UCP314-210D1</b> <b>C(CM)-UCP314-211D1</b> <b>C(CM)-UCP314-212D1</b>	4 5/32	200 7 7/8	140 5 1/2	12 26	14 31
UC315D1 UC315-213D1 UC315-214D1 UC315-215D1 UC315-300D1	P315D1 P315D1 P315D1 P315D1 P315D1	<b>C(CM)-UCP315D1</b> <b>C(CM)-UCP315-213D1</b> <b>C(CM)-UCP315-214D1</b> <b>C(CM)-UCP315-215D1</b> <b>C(CM)-UCP315-300D1</b>	4 5/32	210 8 9/32	150 5 29/32	14 31	17 37
UC316D1 UC316-301D1 UC316-302D1 UC316-303D1	P316D1 P316D1 P316D1 P316D1	<b>C(CM)-UCP316D1</b> <b>C(CM)-UCP316-301D1</b> <b>C(CM)-UCP316-302D1</b> <b>C(CM)-UCP316-303D1</b>	4 5/32	221 8 11/16	155 6 3/32	17 37	21 46
UC317D1 UC317-304D1 UC317-305D1 UC317-307D1	P317D1 P317D1 P317D1 P317D1	<b>C(CM)-UCP317D1</b> <b>C(CM)-UCP317-304D1</b> <b>C(CM)-UCP317-305D1</b> <b>C(CM)-UCP317-307D1</b>	5 13/64	235 9 1/4	170 6 11/16	19 42	24 53
UC318D1 UC318-307D1 UC318-308D1	P318D1 P318D1 P318D1	<b>C(CM)-UCP318D1</b> <b>C(CM)-UCP318-307D1</b> <b>C(CM)-UCP318-308D1</b>	5 13/64	246 9 11/16	170 6 11/16	22 49	27 60

## Pillow block unit, cast housing Set screw type



Cast dust cover type  
Open end **C-UCP...D1**  
Closed end **CM-UCP...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S	
95 3 5/8 3 11/16 3 3/4	<b>UCP319D1</b> <b>UCP319-310D1</b> <b>UCP319-311D1</b> <b>UCP319-312D1</b>	125 4 59/64	470 18 1/2	360 14 3/16	120 4 29/32	36 1 19/32	50 1 31/32	45 1 25/32	250 9 27/32	125 4 29/32	103 4.0551	41 1.614	M30 1 1/8
100 3 13/16 3 7/8 3 15/16 4	<b>UCP320D1</b> <b>UCP320-313D1</b> <b>UCP320-314D1</b> <b>UCP320-315D1</b> <b>UCP320-400D1</b>	140 5 33/64	490 19 9/32	380 14 31/32	120 4 29/32	36 1 19/32	50 1 31/32	50 1 31/32	275 10 13/16	130 5 1/8	108 4.2520	42 1.654	M30 1 1/8
105	<b>UCP321D1</b>	140	490	380	120	36	50	50	280	130	112	44	M30
110	<b>UCP322D1</b>	150	520	400	140	40	55	55	300	135	117	46	M33
120	<b>UCP324D1</b>	160	570	450	140	40	55	65	320	140	126	51	M33
130	<b>UCP326D1</b>	180	600	480	140	40	55	75	355	140	135	54	M33
140	<b>UCP328D1</b>	200	620	500	140	40	55	75	390	140	145	59	M33

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			t max.	H <sub>3</sub>	A <sub>5</sub>	UCP	C(CM)
UC319D1 UC319-310D1 UC319-311D1 UC319-312D1	P319D1 P319D1 P319D1 P319D1	<b>C(CM)-UCP319D1</b> <b>C(CM)-UCP319-310D1</b> <b>C(CM)-UCP319-311D1</b> <b>C(CM)-UCP319-312D1</b>	5 1 3/64	258 10 5/32	180 7 3/32	26 57	32 71
UC320D1 UC320-313D1 UC320-314D1 UC320-315D1 UC320-400D1	P320D1 P320D1 P320D1 P320D1 P320D1	<b>C(CM)-UCP320D1</b> <b>C(CM)-UCP320-313D1</b> <b>C(CM)-UCP320-314D1</b> <b>C(CM)-UCP320-315D1</b> <b>C(CM)-UCP320-400D1</b>	5 1 3/64	283 11 5/32	190 7 15/32	33 73	39 86
UC321D1	P321D1	<b>C(CM)-UCP321D1</b>	5	290	195	35	42
UC322D1	P322D1	<b>C(CM)-UCP322D1</b>	5	313	200	43	52
UC324D1	P324D1	<b>C(CM)-UCP324D1</b>	5	335	215	50	67
UC326D1	P326D1	<b>C(CM)-UCP326D1</b>	6	375	225	69	83
UC328D1	P328D1	<b>C(CM)-UCP328D1</b>	6	407	235	84	99

## Pillow block unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S	
25 1 3/16 7/8 15/16 1	<b>UCPX05D1</b> <b>UCPX05-013D1</b> <b>UCPX05-014D1</b> <b>UCPX05-015D1</b> <b>UCPX05-100D1</b>	44.4 1 3/4	159 6 1/4	119 4 11/16	51 2	17 2 1/32	20 25/32	18 23/32	85 3 11/32	50 1 31/32	38.1 1.5000	15.9 0.626	M14 1/2
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UCPX06D1</b> <b>UCPX06-101D1</b> <b>UCPX06-102D1</b> <b>UCPX06-103D1</b> <b>UCPX06-104D1</b>	47.6 1 7/8	175 6 7/8	127 5	57 2 1/4	17 2 1/32	20 25/32	20 25/32	93 3 21/32	54 2 1/8	42.9 1.6890	17.5 0.689	M14 1/2
35 1 5/16 1 3/8 1 7/16	<b>UCPX07D1</b> <b>UCPX07-105D1</b> <b>UCPX07-106D1</b> <b>UCPX07-107D1</b>	54 2 1/8	203 8	144 5 21/32	57 2 1/4	17 2 1/32	20 25/32	21 13/16	105 4 1/8	60 2 3/8	49.2 1.9370	19 0.748	M14 1/2
40 1 1/2 1 9/16	<b>UCPX08D1</b> <b>UCPX08-108D1</b> <b>UCPX08-109D1</b>	58.7 2 5/16	222 8 3/4	156 6 5/32	67 2 5/8	20 25/32	23 29/32	26 1 1/32	111 4 3/8	65 2 9/16	49.2 1.9370	19 0.748	M16 5/8
45 1 5/8 1 11/16 1 3/4 1 13/16	<b>UCPX09D1</b> <b>UCPX09-110D1</b> <b>UCPX09-111D1</b> <b>UCPX09-112D1</b> <b>UCPX09-113D1</b>	58.7 2 5/16	222 8 3/4	156 6 5/32	67 2 5/8	20 25/32	23 29/32	26 1 1/32	116 4 9/16	65 2 9/16	51.6 2.0315	19 0.748	M16 5/8
50 1 7/8 1 15/16 2	<b>UCPX10D1</b> <b>UCPX10-114D1</b> <b>UCPX10-115D1</b> <b>UCPX10-200D1</b>	63.5 2 1/2	241 9 1/2	171 6 23/32	73 2 7/8	20 25/32	23 29/32	27 1 1/16	126 4 31/32	70 2 3/4	55.6 2.1890	22.2 0.874	M16 5/8

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type  
Open end **C-UCP...D1**  
Closed end **CM-UCP...D1**

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			t max.	H <sub>3</sub>	A <sub>5</sub>	UCP	C(CM)
UCX05D1 UCX05-013D1 UCX05-014D1 UCX05-015D1 UCX05-100D1	PX05D1 PX05D1 PX05D1 PX05D1	<b>C(CM)-UCPX05D1</b> <b>C(CM)-UCPX05-013D1</b> <b>C(CM)-UCPX05-014D1</b> <b>C(CM)-UCPX05-015D1</b> <b>C(CM)-UCPX05-100D1</b>	2 5/64	89 3 1/2	75 2 15/16	1.4 3.1	1.8 4.0
UCX06D1 UCX06-101D1 UCX06-102D1 UCX06-103D1 UC207-104D1	PX06D1 PX06D1 PX06D1 PX06D1 PX06D1	<b>C(CM)-UCPX06D1</b> <b>C(CM)-UCPX06-101D1</b> <b>C(CM)-UCPX06-102D1</b> <b>C(CM)-UCPX06-103D1</b> <b>C(CM)-UCPX06-104D1</b>	2 5/64	99 3 29/32	80 3 5/32	1.9 4.2	2.4 5.3
UCX07D1 UCX07-105D1 UCX07-106D1 UCX07-107D1	PX07D1 PX07D1 PX07D1 PX07D1	<b>C(CM)-UCPX07D1</b> <b>C(CM)-UCPX07-105D1</b> <b>C(CM)-UCPX07-106D1</b> <b>C(CM)-UCPX07-107D1</b>	3 1/8	110 4 1/2	90 3 17/32	2.4 5.3	3.3 7.3
UCX08D1 UCX08-108D1 UCX08-109D1	PX08D1 PX08D1 PX08D1	<b>C(CM)-UCPX08D1</b> <b>C(CM)-UCPX08-108D1</b> <b>C(CM)-UCPX08-109D1</b>	3 1/8	118 4 21/32	95 3 3/4	2.9 6.4	3.8 8.4
UCX09D1 UCX09-110D1 UCX09-111D1 UCX09-112D1 UC210-113D1	PX09D1 PX09D1 PX09D1 PX09D1 PX09D1	<b>C(CM)-UCPX09D1</b> <b>C(CM)-UCPX09-110D1</b> <b>C(CM)-UCPX09-111D1</b> <b>C(CM)-UCPX09-112D1</b> <b>C(CM)-UCPX09-113D1</b>	3 1/8	120 4 23/32	100 3 15/16	3.2 7.1	4.2 9.3
UCX10D1 UCX10-114D1 UCX10-115D1 UC211-200D1	PX10D1 PX10D1 PX10D1 PX10D1	<b>C(CM)-UCPX10D1</b> <b>C(CM)-UCPX10-114D1</b> <b>C(CM)-UCPX10-115D1</b> <b>C(CM)-UCPX10-200D1</b>	3 1/8	130 5 1/8	100 3 15/16	4.1 9.0	5.4 12

## Pillow block unit, cast housing Set screw type



Cast dust cover type  
Open end **C-UCP...D1**  
Closed end **CM-UCP...D1**

Shaft dia. mm inch	Unit number (*)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S	
55 2 1/16 2 1/8 2 3/16 2 1/4 2 5/16	<b>UCPX11D1</b> <b>UCPX11-201D1</b> <b>UCPX11-202D1</b> <b>UCPX11-203D1</b> <b>UCPX11-204D1</b> <b>UCPX11-205D1</b>	69.8	260	184	79	25	28	30	137	75	65.1	25.4	M20
60 2 3/8 2 7/16	<b>UCPX12D1</b> <b>UCPX12-206D1</b> <b>UCPX12-207D1</b>	76.2	286	203	83	25	28	33	151	80	65.1	25.4	M20
65 2 1/2 2 9/16	<b>UCPX13D1</b> <b>UCPX13-208D1</b> <b>UCPX13-209D1</b>	76.2	286	203	83	25	28	33	154	80	74.6	30.2	M20
70 2 5/8 2 11/16 2 3/4	<b>UCPX14D1</b> <b>UCPX14-210D1</b> <b>UCPX14-211D1</b> <b>UCPX14-212D1</b>	88.9	330	229	89	27	30	35	170	95	77.8	33.3	M22
75 2 13/16 2 7/8 2 15/16 3	<b>UCPX15D1</b> <b>UCPX15-213D1</b> <b>UCPX15-214D1</b> <b>UCPX15-215D1</b> <b>UCPX15-300D1</b>	88.9	330	229	89	27	30	35	175	95	82.6	33.3	M22
80 3 1/16 3 1/8 3 3/16 3 1/4	<b>UCPX16D1</b> <b>UCPX16-301D1</b> <b>UCPX16-302D1</b> <b>UCPX16-303D1</b> <b>UCPX16-304D1</b>	101.6	381	283	102	27	30	40	194	110	85.7	34.1	M22
85 3 5/16 3 7/16	<b>UCPX17D1</b> <b>UCPX17-305D1</b> <b>UCPX17-307D1</b>	101.6	381	283	102	27	30	40	200	110	96	39.7	M22

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (*) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			t max.	H <sub>3</sub>	A <sub>5</sub>	UCP	C(CM)
UCX11D1 UCX11-201D1 UCX11-202D1 UCX11-203D1 UC212-204D1 UC212-205D1	PX11D1 PX11D1 PX11D1 PX11D1 PX11D1 PX11D1	<b>C(CM)-UCPX11D1</b> <b>C(CM)-UCPX11-201D1</b> <b>C(CM)-UCPX11-202D1</b> <b>C(CM)-UCPX11-203D1</b> <b>C(CM)-UCPX11-204D1</b> <b>C(CM)-UCPX11-205D1</b>	4 5/32	144 5 21/32	115 4 17/32	5.4 12	6.9 15
UCX12D1 UCX12-206D1 UCX12-207D1	PX12D1 PX12D1 PX12D1	<b>C(CM)-UCPX12D1</b> <b>C(CM)-UCPX12-206D1</b> <b>C(CM)-UCPX12-207D1</b>	4 5/32	155 6 3/32	120 4 23/32	6.8 15	8.6 19
UCX13D1 UCX13-208D1 UCX13-209D1	PX13D1 PX13D1 PX13D1	<b>C(CM)-UCPX13D1</b> <b>C(CM)-UCPX13-208D1</b> <b>C(CM)-UCPX13-209D1</b>	4 5/32	159 6 1/4	135 5 5/16	7.2 16	9.4 21
UCX14D1 UCX14-210D1 UCX14-211D1 UCX14-212D1	PX14D1 PX14D1 PX14D1 PX14D1	<b>C(CM)-UCPX14D1</b> <b>C(CM)-UCPX14-210D1</b> <b>C(CM)-UCPX14-211D1</b> <b>C(CM)-UCPX14-212D1</b>	4 5/32	175 6 7/8	135 5 5/16	9.3 21	12 26
UCX15D1 UCX15-213D1 UCX15-214D1 UCX15-215D1 UCX15-300D1	PX15D1 PX15D1 PX15D1 PX15D1 PX15D1	<b>C(CM)-UCPX15D1</b> <b>C(CM)-UCPX15-213D1</b> <b>C(CM)-UCPX15-214D1</b> <b>C(CM)-UCPX15-215D1</b> <b>C(CM)-UCPX15-300D1</b>	4 5/32	181 7 1/8	145 5 23/32	10 22	13 29
UCX16D1 UCX16-301D1 UCX16-302D1 UCX16-303D1 UC217-304D1	PX16D1 PX16D1 PX16D1 PX16D1 PX16D1	<b>C(CM)-UCPX16D1</b> <b>C(CM)-UCPX16-301D1</b> <b>C(CM)-UCPX16-302D1</b> <b>C(CM)-UCPX16-303D1</b> <b>C(CM)-UCPX16-304D1</b>	4 5/32	198 7 25/32	155 6 3/32	14 31	17 37
UCX17D1 UCX17-305D1 UCX17-307D1	PX17D1 PX17D1 PX17D1	<b>C(CM)-UCPX17D1</b> <b>C(CM)-UCPX17-305D1</b> <b>C(CM)-UCPX17-307D1</b>	5 13/64	204 8 1/32	165 6 1/2	15 33	19 42



## Pillow block unit, cast housing Set screw type



Shaft dia.  mm inch	Unit number (1)	Nominal dimensions											Bolt size  mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S	
90 3 7/16 3 1/2	<b>UCPX18D1</b> <b>UCPX18-307D1</b> <b>UCPX18-308D1</b>	101.6	381	283	111	27	30	40	206	110	104	42.9	M22
		4	15	11 5/32	4 3/8	1 1/16	1 3/16	1 9/16	8 1/8	4 11/32	4.0945	1.689	7/8
100 3 13/16 3 7/8 3 15/16 4	<b>UCPX20D1</b> <b>UCPX20-313D1</b> <b>UCPX20-314D1</b> <b>UCPX20-315D1</b> <b>UCPX20-400D1</b>	127	432	337	121	33	36	45	244	125	117.5	49.2	M27
		5	17	13 9/32	4 3/4	1 5/16	1 13/32	1 25/32	9 19/32	4 29/32	4.6260	1.937	1

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".


Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type  
Open end **C-UCP...D1**  
Closed end **CM-UCP...D1**

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			t max.	H <sub>3</sub>	A <sub>5</sub>	UCP	C(CM)
UCX18D1	PX18D1	<b>C(CM)-UCPX18D1</b>	5	208	180	16	21
UCX18-307D1	PX18D1	<b>C(CM)-UCPX18-307D1</b>	13/64	8 3/16	7 3/32	35	46
UCX18-308D1	PX18D1	<b>C(CM)-UCPX18-308D1</b>					
UCX20D1	PX20D1	<b>C(CM)-UCPX20D1</b>	5	244	195	25	29
UCX20-313D1	PX20D1	<b>C(CM)-UCPX20-313D1</b>					
UCX20-314D1	PX20D1	<b>C(CM)-UCPX20-314D1</b>					
UCX20-315D1	PX20D1	<b>C(CM)-UCPX20-315D1</b>	13/64	9 19/32	7 11/16	55	64
UCX20-400D1	PX20D1	<b>C(CM)-UCPX20-400D1</b>					

## Pillow block unit, cast housing low center height Set screw type



Shaft dia.  mm inch	Unit number <sup>(1)(2)(3)</sup>	Nominal dimensions											Bolt size  mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S	
20  3/4	UCPL204D1	31.75	127	95	38	13	16	14	64	42	31	12.7	M10
	UCPL204-012D1	1 1/4	5	3 3/4	1 1/2	1/2	5/8	9/16	2 1/2	1 1/2	1.2205	0.500	3/8
25  13/16 7/8 15/16	UCPL205D1	33.34	140	105	38	13	16	15	68	42	34.1	14.3	M10
	UCPL205-013D1												
	UCPL205-014D1												
	UCPL205-015D1	1 5/16	5 1/2	4 1/8	1 1/2	1/2	5/8	19/32	2 1/16	1 21/32	1.3425	0.563	3/8
1	UCPL205-100D1												
30  1 1/16 1 1/8 1 1/16 1 1/4	UCPL206D1	39.69	165	121	48	17	20	17	80	54	38.1	15.9	M14
	UCPL206-101D1												
	UCPL206-102D1	1 9/16	6 1/2	4 3/4	1 7/8	21/32	25/32	21/32	3 5/32	2 1/8	1.5000	0.626	1/2
	UCPL206-103D1												
1 1/4	UCPL206-104D1												
35  1 1/4 1 5/16 1 3/8 1 7/16	UCPL207D1	46.04	167	127	48	17	20	18	91	54	42.9	17.5	M14
	UCPL207-104D1												
	UCPL207-105D1	1 13/16	6 9/16	5	1 7/8	21/32	25/32	23/32	3 19/32	2 1/8	1.6890	0.689	1/2
	UCPL207-106D1												
1 7/16	UCPL207-107D1												
45  1 5/8 1 11/16 1 3/4	UCPL209D1	52.39	190	146	54	17	20	20	104	60	49.2	19	M14
	UCPL209-110D1												
	UCPL209-111D1	2 1/16	7 15/32	5 3/4	2 1/8	21/32	25/32	25/32	4 3/32	2 3/8	1.9370	0.748	1/2
1 3/4	UCPL209-112D1												
50  1 13/16 1 7/8 1 15/16	UCPL210D1	55.56	206	159	60	20	23	21	112	65	51.6	19	M16
	UCPL210-113D1												
	UCPL210-114D1												
	UCPL210-115D1	2 3/16	8 1/8	6 1/4	2 3/8	25/32	29/32	13/16	4 13/32	2 9/16	2.0315	0.748	5/8
2	UCPL210-200D1												

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> UCPL204 and UCPL205 has solid bases.

<sup>(3)</sup> UCPL208 has the same dimension as UCP208 shown in page B4.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UC204D1	PL204D1	0.7
UC204-012D1	PL204D1	1.5
UC205D1	PL205D1	0.8
UC205-013D1	PL205D1	
UC205-014D1	PL205D1	1.8
UC205-015D1	PL205D1	
UC205-100D1	PL205D1	
UC206D1	PL206D1	1.3
UC206-101D1	PL206D1	
UC206-102D1	PL206D1	2.9
UC206-103D1	PL206D1	
UC206-104D1	PL206D1	
UC207D1	PL207D1	1.6
UC207-104D1	PL207D1	
UC207-105D1	PL207D1	3.5
UC207-106D1	PL207D1	
UC207-107D1	PL207D1	
UC209D1	PL209D1	2.2
UC209-110D1	PL209D1	
UC209-111D1	PL209D1	4.9
UC209-112D1	PL209D1	
UC210D1	PL210D1	2.8
UC210-113D1	PL210D1	
UC210-114D1	PL210D1	6.2
UC210-115D1	PL210D1	
UC210-200D1	PL210D1	

## Pillow block unit, cast housing low center height Set screw type



Shaft dia.  mm inch	Unit number (1)	Nominal dimensions											Bolt size  mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S	
55	<b>UCPL211D1</b>	61.91	219	171	60	20	23	23	124	65	55.6	22.2	M16
2	<b>UCPL211-200D1</b>												
2 1/16	<b>UCPL211-201D1</b>												
2 1/8	<b>UCPL211-202D1</b>	2 7/16	8 5/8	6 23/32	2 3/8	25/32	29/32	29/32	4 7/8	2 9/16	2.1890	0.874	5/8
2 3/16	<b>UCPL211-203D1</b>												
60	<b>UCPL212D1</b>	68.26	241	184	70	20	23	25	136	70	65.1	25.4	M16
2 1/4	<b>UCPL212-204D1</b>												
2 5/16	<b>UCPL212-205D1</b>												
2 3/8	<b>UCPL212-206D1</b>	2 11/16	9 1/2	7 1/4	2 3/4	25/32	29/32	31/32	5 11/32	2 3/4	2.5630	1.000	5/8
2 7/16	<b>UCPL212-207D1</b>												

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UC211D1	PL211D1	3.4
UC211-200D1	PL211D1	
UC211-201D1	PL211D1	7.5
UC211-202D1	PL211D1	
UC211-203D1	PL211D1	
UC212D1	PL212D1	4.7
UC212-204D1	PL212D1	
UC212-205D1	PL212D1	10
UC212-206D1	PL212D1	
UC212-207D1	PL212D1	

# UCHP2

Pillow block unit, cast housing low center height  
Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	B	S	
12 1/2	<b>UCHP201D1</b> <b>UCHP201-008D1</b>	70 2 3/4	127 5	95 3 3/4	40 1 9/16	13 1/2	19 3/4	13 1/2	101 3 31/32	31 1.2205	12.7 0.500	M10 3/8
15 9/16 5/8	<b>UCHP202D1</b> <b>UCHP202-009D1</b> <b>UCHP202-010D1</b>	70 2 3/4	127 5	95 3 3/4	40 1 9/16	13 1/2	19 3/4	13 1/2	101 3 31/32	31 1.2205	12.7 0.500	M10 3/8
17 11/16	<b>UCHP203D1</b> <b>UCHP203-011D1</b>	70 2 3/4	127 5	95 3 3/4	40 1 9/16	13 1/2	19 3/4	13 1/2	101 3 31/32	31 1.2205	12.7 0.500	M10 3/8
20 3/4	<b>UCHP204D1</b> <b>UCHP204-012D1</b>	70 2 3/4	127 5	95 3 3/4	40 1 9/16	13 1/2	19 3/4	13 1/2	101 3 31/32	31 1.2205	12.7 0.500	M10 3/8
25 13/16 7/8 15/16 1	<b>UCHP205D1</b> <b>UCHP205-013D1</b> <b>UCHP205-014D1</b> <b>UCHP205-015D1</b> <b>UCHP205-100D1</b>	80 3 5/8	142 5 19/32	105 4 1/8	50 1 31/32	13 1/2	19 3/4	13 1/2	114 4 1/2	34.1 1.3425	14.3 0.563	M10 3/8
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UCHP206D1</b> <b>UCHP206-101D1</b> <b>UCHP206-102D1</b> <b>UCHP206-103D1</b> <b>UCHP206-104D1</b>	90 3 35/64	165 6 1/2	120 4 23/32	50 1 31/32	17 21/32	21 13/16	16 5/8	130 5 1/8	38.1 1.5000	15.9 0.626	M14 1/2
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UCHP207D1</b> <b>UCHP207-104D1</b> <b>UCHP207-105D1</b> <b>UCHP207-106D1</b> <b>UCHP207-107D1</b>	95 3 47/64	166 6 17/32	127 5	60 2 3/8	17 21/32	21 13/16	18 23/32	140 5 1/2	42.9 1.6890	17.5 0.689	M14 1/2
40 1 1/2 1 9/16	<b>UCHP208D1</b> <b>UCHP208-108D1</b> <b>UCHP208-109D1</b>	100 3 15/16	184 7 1/4	136 5 11/32	70 2 3/4	17 21/32	21 13/16	20 25/32	150 5 29/32	49.2 1.9370	19 0.748	M14 1/2

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UC201D1	HP204D1	0.9
UC201-008D1	HP204D1	2.0
UC202D1	HP204D1	0.9
UC202-009D1	HP204D1	2.0
UC202-010D1	HP204D1	2.0
UC203D1	HP204D1	0.9
UC203-011D1	HP204D1	2.0
UC204D1	HP204D1	0.9
UC204-012D1	HP204D1	2.0
UC205D1	HP205D1	1.2
UC205-013D1	HP205D1	2.6
UC205-014D1	HP205D1	2.6
UC205-015D1	HP205D1	2.6
UC205-100D1	HP205D1	2.6
UC206D1	HP206D1	1.8
UC206-101D1	HP206D1	4.0
UC206-102D1	HP206D1	4.0
UC206-103D1	HP206D1	4.0
UC206-104D1	HP206D1	4.0
UC207D1	HP207D1	2.3
UC207-104D1	HP207D1	5.1
UC207-105D1	HP207D1	5.1
UC207-106D1	HP207D1	5.1
UC207-107D1	HP207D1	5.1
UC208D1	HP208D1	3.2
UC208-108D1	HP208D1	7.1
UC208-109D1	HP208D1	7.1

# UCHP2

Pillow block unit, cast housing low center height  
Set screw type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	B	S	
45 1 5/8 1 11/16 1 3/4	<b>UCHP209D1</b> <b>UCHP209-110D1</b> <b>UCHP209-111D1</b> <b>UCHP209-112D1</b>	105	190	146	70	17	22	20	158	49.2	19	M14
		4 9/64	7 15/32	5 3/4	2 3/4	2 1/32	7/8	25/32	6 7/32	1.9370	0.748	1/2
50 1 13/16 1 7/8 1 15/16 2	<b>UCHP210D1</b> <b>UCHP210-113D1</b> <b>UCHP210-114D1</b> <b>UCHP210-115D1</b> <b>UCHP210-200D1</b>	110	206	159	70	20	22	22	165	51.6	19	M16
		4 21/64	8 1/8	6 1/4	2 3/4	25/32	7/8	7/8	6 1/2	2.0315	0.748	5/8

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UC209D1	HP209D1	3.5
UC209-110D1	HP209D1	
UC209-111D1	HP209D1	7.7
UC209-112D1	HP209D1	
UC210D1	HP210D1	3.9
UC210-113D1	HP210D1	
UC210-114D1	HP210D1	8.6
UC210-115D1	HP210D1	
UC210-200D1	HP210D1	

## Narrow pillow block unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions									
		mm inch									
		H	L	J	A	j	H <sub>1</sub>	H <sub>2</sub>	B	S	N
12 1/2	UCUP201D1 UCUP201-008D1	30.2 1 3/16	76 3	52 2 1/16	38 1 1/2	13 1/2	11 7/16	62 2 7/16	31 1.2205	12.7 0.500	M10×1.5
15 9/16 5/8	UCUP202D1 UCUP202-009D1 UCUP202-010D1	30.2 1 3/16	76 3	52 2 1/16	38 1 1/2	13 1/2	11 7/16	62 2 7/16	31 1.2205	12.7 0.500	M10×1.5
17 11/16	UCUP203D1 UCUP203-011D1	30.2 1 3/16	76 3	52 2 1/16	38 1 1/2	13 1/2	11 7/16	62 2 7/16	31 1.2205	12.7 0.500	M10×1.5
20 3/4	UCUP204D1 UCUP204-012D1	30.2 1 3/16	76 3	52 2 1/16	38 1 1/2	13 1/2	11 7/16	62 2 7/16	31 1.2205	12.7 0.500	M10×1.5
25 13/16 7/8 15/16 1	UCUP205D1 UCUP205-013D1 UCUP205-014D1 UCUP205-015D1 UCUP205-100D1	36.5 1 7/16	84 3 5/16	56 2 7/32	38 1 1/2	15 19/32	12 15/32	72 2 27/32	34.1 1.3425	14.3 0.563	M10×1.5
30 1 1/16 1 1/8 1 3/16 1 1/4	UCUP206D1 UCUP206-101D1 UCUP206-102D1 UCUP206-103D1 UCUP206-104D1	42.9 1 11/16	94 3 11/16	66 2 19/32	48 1 7/8	18 23/32	12 15/32	84 3 5/16	38.1 1.5000	15.9 0.629	M14×2
35 1 1/4 1 5/16 1 3/8 1 7/16	UCUP207D1 UCUP207-104D1 UCUP207-105D1 UCUP207-106D1 UCUP207-107D1	47.6 1 7/8	110 4 11/32	80 3 5/32	48 1 7/8	20 25/32	13 1/2	95 3 3/4	42.9 1.6890	17.5 0.689	M14×2
40 1 1/2 1 9/16	UCUP208D1 UCUP208-108D1 UCUP208-109D1	49.2 1 15/16	116 4 9/16	84 3 5/16	54 2 1/8	20 25/32	13 1/2	100 3 15/16	49.2 1.9370	19 0.748	M14×2

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UC201D1 UC201-008D1	UP204D1 UP204D1	0.6 1.3
UC202D1 UC202-009D1 UC202-010D1	UP204D1 UP204D1 UP204D1	0.6 1.3
UC203D1 UC203-011D1	UP204D1 UP204D1	0.6 1.3
UC204D1 UC204-012D1	UP204D1 UP204D1	0.6 1.3
UC205D1 UC205-013D1 UC205-014D1 UC205-015D1 UC205-100D1	UP205D1 UP205D1 UP205D1 UP205D1	0.7 1.5
UC206D1 UC206-101D1 UC206-102D1 UC206-103D1 UC206-104D1	UP206D1 UP206D1 UP206D1 UP206D1	1.1 2.4
UC207D1 UC207-104D1 UC207-105D1 UC207-106D1 UC207-107D1	UP207D1 UP207D1 UP207D1 UP207D1	1.6 3.5
UC208D1 UC208-108D1 UC208-109D1	UP208D1 UP208D1	1.8 4.0

# UCUP2

Narrow pillow block unit, cast housing  
Set screw type



Shaft dia.  mm inch	Unit number <sup>(1)</sup>	Nominal dimensions									
		mm inch									
		<i>H</i>	<i>L</i>	<i>J</i>	<i>A</i>	<i>j</i>	<i>H</i> <sub>1</sub>	<i>H</i> <sub>2</sub>	<i>B</i>	<i>S</i>	<i>N</i>
45 1 5/8 1 11/16 1 3/4	<b>UCUP209D1</b> <b>UCUP209-110D1</b> <b>UCUP209-111D1</b> <b>UCUP209-112D1</b>	54.2	120	90	54	25	13	108	49.2	19	M14×2
		2 9/64	4 23/32	3 17/32	2 1/8	3 1/32	1/2	4 1/4	1.9370	0.748	
50 1 13/16 1 7/8 1 15/16 2	<b>UCUP210D1</b> <b>UCUP210-113D1</b> <b>UCUP210-114D1</b> <b>UCUP210-115D1</b> <b>UCUP210-200D1</b>	57.2	130	94	60	25	14	116	51.6	19	M16×2
		2 1/4	5 1/8	3 11/16	2 3/8	3 1/32	9/16	4 9/16	2.0315	0.748	

Note <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit
		kg lb
UC209D1	UP209D1	2.1
UC209-110D1	UP209D1	
UC209-111D1	UP209D1	4.6
UC209-112D1	UP209D1	
UC210D1	UP210D1	2.6
UC210-113D1	UP210D1	
UC210-114D1	UP210D1	5.7
UC210-115D1	UP210D1	
UC210-200D1	UP210D1	

## Pillow block unit, cast housing low center height Set screw type



Shaft dia.  mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )( <sup>3</sup> )	Nominal dimensions											Bolt size  mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S	
12 1/2	<b>ASPL201</b> <b>ASPL201-008</b>	26.99 1 1/16	121 4 3/4	89 3 1/2	35 1 3/8	11 7/16	14 9/16	13 1/2	54 2 1/8	40 1 9/16	22 0.8661	6 0.236	M10 3/8
15 9/16 5/8	<b>ASPL202</b> <b>ASPL202-009</b> <b>ASPL202-010</b>	26.99 1 1/16	121 4 3/4	89 3 1/2	35 1 3/8	11 7/16	14 9/16	13 1/2	54 2 1/8	40 1 9/16	22 0.8661	6 0.236	M10 3/8
17 11/16	<b>ASPL203</b> <b>ASPL203-011</b>	26.99 1 1/16	121 4 3/4	89 3 1/2	35 1 3/8	11 7/16	14 9/16	13 1/2	54 2 1/8	40 1 9/16	22 0.8661	6 0.236	M10 3/8
20 3/4	<b>ASPL204</b> <b>ASPL204-012</b>	31.75 1 1/4	127 5	95 3 3/4	38 1 1/2	13 1/2	16 5/8	14 9/16	64 2 17/32	42 1 21/32	25 0.9843	7 0.276	M10 3/8
25 13/16 7/8 15/16 1	<b>ASPL205</b> <b>ASPL205-013</b> <b>ASPL205-014</b> <b>ASPL205-015</b> <b>ASPL205-100</b>	33.34 1 5/16	140 5 1/2	105 4 1/8	38 1 1/2	13 1/2	16 5/8	15 19/32	68 2 11/16	42 1 21/32	27 1.0630	7.5 0.295	M10 3/8
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>ASPL206</b> <b>ASPL206-101</b> <b>ASPL206-102</b> <b>ASPL206-103</b> <b>ASPL206-104</b>	39.69 1 9/16	165 6 1/2	121 4 3/4	48 1 7/8	17 21/32	20 25/32	17 21/32	80 3 5/32	54 2 1/8	29 1.1417	8 0.315	M14 1/2
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>ASPL207</b> <b>ASPL207-104</b> <b>ASPL207-105</b> <b>ASPL207-106</b> <b>ASPL207-107</b>	46.04 1 13/16	167 6 9/16	127 5	48 1 7/8	17 21/32	20 25/32	18 23/32	91 3 19/32	54 2 1/8	34 1.3386	8.5 0.335	M14 1/2
40 1 1/2 1 9/16	<b>ASP208</b> <b>ASP208-108</b> <b>ASP208-109</b>	49.2 1 15/16	184 7 1/4	137 5 13/32	54 2 1/8	17 21/32	20 25/32	18 23/32	98 3 27/32	52 2 1/16	38 1.4961	9 0.354	M14 1/2

Notes <sup>(1)</sup> ASPL201 to ASPL205 has solid bases.  
<sup>(2)</sup> If relubricatable type is needed, please order with suffix "D1".  
<sup>(3)</sup> ASPL208 has the same dimension an ASP208.

Bearing number <sup>(2)</sup>	Housing number <sup>(2)</sup>	Mass of unit kg lb
AS201 AS201-008	PL201 PL201	0.5 1.1
AS202 AS202-009 AS202-010	PL201 PL201 PL201	0.5 1.1
AS203 AS203-011	PL201 PL201	0.5 1.1
AS204 AS204-012	PL204 PL204	0.7 1.5
AS205 AS205-013 AS205-014 AS205-015 AS205-100	PL205 PL205 PL205 PL205	0.8 1.8
AS206 AS206-101 AS206-102 AS206-103 AS206-104	PL206 PL206 PL206 PL206	1.2 2.6
AS207 AS207-104 AS207-105 AS207-106 AS207-107	PL207 PL207 PL207 PL207	1.5 3.3
AS208 AS208-108 AS208-109	P208 P208 P208	1.8 4.0



# ASPL2

Pillow block unit, cast housing low center height  
Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B	S	
45 1 5/8 1 11/16 1 3/4	<b>ASPL209</b> <b>ASPL209-110</b> <b>ASPL209-111</b> <b>ASPL209-112</b>	52.39	190	146	54	17	20	20	104	60	40	9.5	M14
		2 1/16	7 15/32	5 3/4	2 1/8	2 1/32	25/32	25/32	4 3/32	2 3/8	1.578	0.374	1/2
50 1 13/16 1 7/8 1 15/16 2	<b>ASPL210</b> <b>ASPL210-113</b> <b>ASPL210-114</b> <b>ASPL210-115</b> <b>ASPL210-200</b>	55.56	206	159	60	20	23	21	112	65	42	10	M16
		2 3/16	8 1/8	6 1/4	2 3/8	25/32	29/32	1 13/16	4 13/32	2 9/16	1.635	0.394	5/8

Note (1) If relubricatable type is needed, please order with suffix "D1".

Bearing number (1)	Housing number (1)	Mass of unit kg lb
AS209	PL209	2.0
AS209-110	PL209	4.4
AS209-111	PL209	
AS209-112	PL209	
AS210	PL210	2.6
AS210-113	PL210	5.7
AS210-114	PL210	
AS210-115	PL210	
AS210-200	PL210	

## Pillow block unit, pressed steel housing Set screw type




Shaft dia.  mm inch	Unit number	Nominal dimensions										Bolt size  mm inch
		mm inch										
		<i>H</i>	<i>L</i>	<i>J</i>	<i>A</i>	<i>N</i>	<i>H</i> <sub>1</sub>	<i>H</i> <sub>2</sub>	<i>B</i>	<i>S</i>		
12 1/2	<b>ASPP201</b> <b>ASPP201-008</b>	22.2 7/8	86 3 3/8	68 2 11/16	25 31/32	9.5 3/8	3.2 0.126	43.8 1 23/32	22 0.8661	6 0.236	M8 5/16	
15 9/16 5/8	<b>ASPP202</b> <b>ASPP202-009</b> <b>ASPP202-010</b>	22.2 7/8	86 3 3/8	68 2 11/16	25 31/32	9.5 3/8	3.2 0.126	43.8 1 23/32	22 0.8661	6 0.236	M8 5/16	
17 1 1/16	<b>ASPP203</b> <b>ASPP203-011</b>	22.2 7/8	86 3 3/8	68 2 11/16	25 31/32	9.5 3/8	3.2 0.126	43.8 1 23/32	22 0.8661	6 0.236	M8 5/16	
20 3/4	<b>ASPP204</b> <b>ASPP204-012</b>	25.4 1	98 3 27/32	76 3	32 1 1/4	9.5 3/8	3.2 0.126	50.5 2	25 0.9843	7 0.276	M8 5/16	
25 1 3/16 7/8 15/16 1	<b>ASPP205</b> <b>ASPP205-013</b> <b>ASPP205-014</b> <b>ASPP205-015</b> <b>ASPP205-100</b>	28.6 1 1/8	108 4 1/4	86 3 3/8	32 1 1/4	11.5 29/64	4 0.157	56.6 2 7/32	27 1.0630	7.5 0.295	M10 3/8	
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>ASPP206</b> <b>ASPP206-101</b> <b>ASPP206-102</b> <b>ASPP206-103</b> <b>ASPP206-104</b>	33.3 1 5/16	117 4 19/32	95 3 3/4	38 1 1/2	11.5 29/64	4 0.157	66.3 2 5/8	29 1.1417	8 0.315	M10 3/8	
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>ASPP207</b> <b>ASPP207-104</b> <b>ASPP207-105</b> <b>ASPP207-106</b> <b>ASPP207-107</b>	39.7 1 9/16	129 5 3/32	106 4 3/16	42 1 21/32	11.5 29/64	4.6 0.181	78 3 1/16	34 1.3386	8.5 0.335	M10 3/8	

Note (1) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.  
The mounting surface should be flat.

Max. load (1)		Bearing number	Housing number	Mass of unit
N lbf				
radial	axial			kg lb
2 000 440	800 160	AS201 AS201-008	PP203 PP203	0.2 0.4
2 000 440	800 160	AS202 AS202-009 AS202-010	PP203 PP203 PP203	0.2 0.4
2 000 440	800 160	AS203 AS203-011	PP203 PP203	0.1 0.2
2 500 550	1 000 200	AS204 AS204-012	PP204 PP204	0.2 0.4
3 500 770	1 400 280	AS205 AS205-013 AS205-014 AS205-015 AS205-100	PP205 PP205 PP205 PP205 PP205	0.3 0.7
4 000 880	1 600 320	AS206 AS206-101 AS206-102 AS206-103 AS206-104	PP206 PP206 PP206 PP206 PP206	0.4 0.9
4 500 990	1 800 360	AS207 AS207-104 AS207-105 AS207-106 AS207-107	PP207 PP207 PP207 PP207 PP207	0.6 1.3

## Pillow block unit, pressed steel housing with rubber ring Set screw type



Shaft dia. mm inch	Unit number	Nominal dimensions									Bolt size mm inch
		mm inch									
		H	L	J	A	N	H <sub>1</sub>	H <sub>2</sub>	B	S	
12 1/2	<b>ASRPP201</b> <b>ASRPP201-008</b>	25.4 1	98 3 <sup>27</sup> / <sub>32</sub>	76 3	32 1 <sup>1</sup> / <sub>4</sub>	9.5 3/8	3.2 0.126	50.5 2	22 0.8661	6 0.236	M8 5/16
15 9/16 5/8	<b>ASRPP202</b> <b>ASRPP202-009</b> <b>ASRPP202-010</b>	25.4 1	98 3 <sup>27</sup> / <sub>32</sub>	76 3	32 1 <sup>1</sup> / <sub>4</sub>	9.5 3/8	3.2 0.126	50.5 2	22 0.8661	6 0.236	M8 5/16
17 11/16	<b>ASRPP203</b> <b>ASRPP203-011</b>	25.4 1	98 3 <sup>27</sup> / <sub>32</sub>	76 3	32 1 <sup>1</sup> / <sub>4</sub>	9.5 3/8	3.2 0.126	50.5 2	22 0.8661	6 0.236	M8 5/16
20 3/4	<b>ASRPP204</b> <b>ASRPP204-012</b>	28.6 1 <sup>1</sup> / <sub>8</sub>	108 4 <sup>1</sup> / <sub>4</sub>	86 3 <sup>3</sup> / <sub>8</sub>	32 1 <sup>1</sup> / <sub>4</sub>	11.5 29/64	4 0.157	56.6 2 <sup>7</sup> / <sub>32</sub>	25 0.9843	7 0.276	M10 3/8
25 13/16 7/8 15/16 1	<b>ASRPP205</b> <b>ASRPP205-013</b> <b>ASRPP205-014</b> <b>ASRPP205-015</b> <b>ASRPP205-100</b>	33.3 1 <sup>5</sup> / <sub>16</sub>	117 4 <sup>19</sup> / <sub>32</sub>	95 3 <sup>3</sup> / <sub>4</sub>	38 1 <sup>1</sup> / <sub>2</sub>	11.5 29/64	4 0.157	66.3 2 <sup>5</sup> / <sub>8</sub>	27 1.0630	7.5 0.295	M10 3/8
30 1 <sup>1</sup> / <sub>16</sub> 1 <sup>1</sup> / <sub>8</sub> 1 <sup>3</sup> / <sub>16</sub> 1 <sup>1</sup> / <sub>4</sub>	<b>ASRPP206</b> <b>ASRPP206-101</b> <b>ASRPP206-102</b> <b>ASRPP206-103</b> <b>ASRPP206-104</b>	39.7 1 <sup>9</sup> / <sub>16</sub>	129 5 <sup>3</sup> / <sub>32</sub>	106 4 <sup>3</sup> / <sub>16</sub>	42 1 <sup>21</sup> / <sub>32</sub>	11.5 29/64	4.6 0.181	78 3 <sup>1</sup> / <sub>16</sub>	29 1.1417	8 0.315	M10 3/8

**Note** (1) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less. The mounting surface should be flat.

**Remarks** When an anti-vibration rubber ring is used, the self alignment capability will be reduce.

Max. load (1)		Bearing number	Housing number		Mass of unit kg lb
N lbf			rubber ring	steel	
radial	axial				
1 000 220	200 40	AS201 AS201-008	R201 R201	PP204 PP204	0.2 0.4
1 000 220	200 40	AS202 AS202-009 AS202-010	R201 R201 R201	PP204 PP204 PP204	0.2 0.4
1 000 220	200 40	AS203 AS203-011	R201 R201	PP204 PP204	0.2 0.4
1 150 250	200 40	AS204 AS204-012	R204 R204	PP205 PP205	0.3 0.7
1 300	200	AS205 AS205-013 AS205-014 AS205-015 AS205-100	R205 R205 R205 R205	PP206 PP206 PP206 PP206	0.4 0.9
1 500	200	AS206 AS206-101 AS206-102 AS206-103 AS206-104	R206 R206 R206 R206	PP207 PP207 PP207 PP207	0.5 1.1

## Square flanged unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch	Bearing number
		mm inch											
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B	S			
12 1/2	<b>UCF201D1</b> <b>UCF201-008D1</b>	86 3 3/8	64 2 33/64	15 19/32	11 7/16	25.5 1	12 15/32	33.3 1 5/16	31 1.2205	12.7 0.500	M10 3/8	UC201D1 UC201-008D1	
15 9/16 5/8	<b>UCF202D1</b> <b>UCF202-009D1</b> <b>UCF202-010D1</b>	86 3 3/8	64 2 33/64	15 19/32	11 7/16	25.5 1	12 15/32	33.3 1 5/16	31 1.2205	12.7 0.500	M10 3/8	UC202D1 UC202-009D1 UC202-010D1	
17 1 1/16	<b>UCF203D1</b> <b>UCF203-011D1</b>	86 3 3/8	64 2 33/64	15 19/32	11 7/16	25.5 1	12 15/32	33.3 1 5/16	31 1.2205	12.7 0.500	M10 3/8	UC203D1 UC203-011D1	
20 3/4	<b>UCF204D1</b> <b>UCF204-012D1</b>	86 3 3/8	64 2 33/64	15 19/32	11 7/16	25.5 1	12 15/32	33.3 1 5/16	31 1.2205	12.7 0.500	M10 3/8	UC204D1 UC204-012D1	
25 1 3/16 7/8 15/16 1	<b>UCF205D1</b> <b>UCF205-013D1</b> <b>UCF205-014D1</b> <b>UCF205-015D1</b> <b>UCF205-100D1</b>	95 3 3/4	70 2 3/4	16 5/8	13 1/2	27 1 1/16	12 15/32	35.8 1 13/32	34.1 1.3425	14.3 0.563	M10 3/8	UC205D1 UC205-013D1 UC205-014D1 UC205-015D1 UC205-100D1	
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UCF206D1</b> <b>UCF206-101D1</b> <b>UCF206-102D1</b> <b>UCF206-103D1</b> <b>UCF206-104D1</b>	108 4 1/4	83 3 17/64	18 45/64	13 1/2	31 1 7/32	12 15/32	40.2 1 37/64	38.1 1.5000	15.9 0.626	M10 3/8	UC206D1 UC206-101D1 UC206-102D1 UC206-103D1 UC206-104D1	
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UCF207D1</b> <b>UCF207-104D1</b> <b>UCF207-105D1</b> <b>UCF207-106D1</b> <b>UCF207-107D1</b>	117 4 19/32	92 3 5/8	19 3/4	15 19/32	34 1 11/32	14 35/64	44.4 1 3/4	42.9 1.6890	17.5 0.689	M12 7/16	UC207D1 UC207-104D1 UC207-105D1 UC207-106D1 UC207-107D1	
40 1 1/2 1 9/16	<b>UCF208D1</b> <b>UCF208-108D1</b> <b>UCF208-109D1</b>	130 5 1/8	102 4 1/64	21 53/64	15 19/32	36 1 13/32	16 5/8	51.2 2 1/64	49.2 1.9370	19 0.748	M14 1/2	UC208D1 UC208-108D1 UC208-109D1	
45 1 5/8 1 11/16 1 3/4	<b>UCF209D1</b> <b>UCF209-110D1</b> <b>UCF209-111D1</b> <b>UCF209-112D1</b>	137 5 13/32	105 4 9/64	22 55/64	16 5/8	38 1 1/2	16 5/8	52.2 2 1/16	49.2 1.9370	19 0.748	M14 1/2	UC209D1 UC209-110D1 UC209-111D1 UC209-112D1	

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.




Pressed steel dust cover type  
Open end **Z-UCF...D1**  
Closed end **ZM-UCF...D1**

Cast dust cover type  
Open end **C-UCF...D1**  
Closed end **CM-UCF...D1**

Housing number	Unit number (1) pressed steel dust cover type	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit		
			mm inch			kg lb		
			t max.	A <sub>4</sub>	A <sub>5</sub>	UCF	Z(ZM)	C(CM)
F204D1 F204D1	<b>Z(ZM)-UCF201D1</b> <b>Z(ZM)-UCF201-008D1</b>	<b>C(CM)-UCF201D1</b> <b>C(CM)-UCF201-008D1</b>	2 5/64	38 1 1/2	46 1 13/16	0.6 1.3	0.6 1.3	0.8 1.8
F204D1 F204D1 F204D1	<b>Z(ZM)-UCF202D1</b> <b>Z(ZM)-UCF202-009D1</b> <b>Z(ZM)-UCF202-010D1</b>	<b>C(CM)-UCF202D1</b> <b>C(CM)-UCF202-009D1</b> <b>C(CM)-UCF202-010D1</b>	2 5/64	38 1 1/2	46 1 13/16	0.6 1.3	0.6 1.3	0.8 1.8
F204D1 F204D1	<b>Z(ZM)-UCF203D1</b> <b>Z(ZM)-UCF203-011D1</b>	<b>C(CM)-UCF203D1</b> <b>C(CM)-UCF203-011D1</b>	2 5/64	38 1 1/2	46 1 13/16	0.6 1.3	0.6 1.3	0.8 1.8
F204D1 F204D1	<b>Z(ZM)-UCF204D1</b> <b>Z(ZM)-UCF204-012D1</b>	<b>C(CM)-UCF204D1</b> <b>C(CM)-UCF204-012D1</b>	2 5/64	38 1 1/2	46 1 13/16	0.6 1.3	0.6 1.3	0.7 1.5
F205D1 F205D1 F205D1 F205D1	<b>Z(ZM)-UCF205D1</b> <b>Z(ZM)-UCF205-013D1</b> <b>Z(ZM)-UCF205-014D1</b> <b>Z(ZM)-UCF205-015D1</b> <b>Z(ZM)-UCF205-100D1</b>	<b>C(CM)-UCF205D1</b> <b>C(CM)-UCF205-013D1</b> <b>C(CM)-UCF205-014D1</b> <b>C(CM)-UCF205-015D1</b> <b>C(CM)-UCF205-100D1</b>	2 5/64	40 1 19/32	51 2	0.8 1.8	0.8 1.8	0.9 2.0
F206D1 F206D1 F206D1 F206D1	<b>Z(ZM)-UCF206D1</b> <b>Z(ZM)-UCF206-101D1</b> <b>Z(ZM)-UCF206-102D1</b> <b>Z(ZM)-UCF206-103D1</b> —	<b>C(CM)-UCF206D1</b> <b>C(CM)-UCF206-101D1</b> <b>C(CM)-UCF206-102D1</b> <b>C(CM)-UCF206-103D1</b> <b>C(CM)-UCF206-104D1</b>	2 5/64	45 1 3/4	56 2 7/32	1.1 2.4	1.1 2.4	1.3 2.9
F207D1 F207D1 F207D1 F207D1	<b>Z(ZM)-UCF207D1</b> <b>Z(ZM)-UCF207-104D1</b> <b>Z(ZM)-UCF207-105D1</b> <b>Z(ZM)-UCF207-106D1</b> —	<b>C(CM)-UCF207D1</b> <b>C(CM)-UCF207-104D1</b> <b>C(CM)-UCF207-105D1</b> <b>C(CM)-UCF207-106D1</b> <b>C(CM)-UCF207-107D1</b>	3 1/8	49 1 15/16	59 2 5/16	1.5 3.3	1.5 3.3	1.8 4.0
F208D1 F208D1 F208D1	<b>Z(ZM)-UCF208D1</b> <b>Z(ZM)-UCF208-108D1</b> <b>Z(ZM)-UCF208-109D1</b>	<b>C(CM)-UCF208D1</b> <b>C(CM)-UCF208-108D1</b> <b>C(CM)-UCF208-109D1</b>	3 1/8	56 2 3/16	66 2 19/32	1.7 3.7	1.8 4.0	2.2 4.9
F209D1 F209D1 F209D1 F209D1	<b>Z(ZM)-UCF209D1</b> <b>Z(ZM)-UCF209-110D1</b> <b>Z(ZM)-UCF209-111D1</b> <b>Z(ZM)-UCF209-112D1</b>	<b>C(CM)-UCF209D1</b> <b>C(CM)-UCF209-110D1</b> <b>C(CM)-UCF209-111D1</b> <b>C(CM)-UCF209-112D1</b>	3 1/8	57 2 1/4	70 2 3/4	2.1 4.6	2.2 4.9	2.6 5.7

## Square flanged unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (*)	Nominal dimensions									Bolt size mm inch	Bearing number
		mm inch										
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B	S		
50 1 13/16 1 7/8 1 15/16 2	<b>UCF210D1</b> <b>UCF210-113D1</b> <b>UCF210-114D1</b> <b>UCF210-115D1</b> <b>UCF210-200D1</b>	143	111	22	16	40	16	54.6	51.6	19	M14	UC210D1 UC210-113D1 UC210-114D1 UC210-115D1 UC210-200D1
		5 5/8	4 3/8	55/64	5/8	1 9/16	5/8	2 5/32	2.0315	0.748	1/2	
55 2 2 1/16 2 1/8 2 3/16	<b>UCF211D1</b> <b>UCF211-200D1</b> <b>UCF211-201D1</b> <b>UCF211-202D1</b> <b>UCF211-203D1</b>	162	130	25	18	43	19	58.4	55.6	22.2	M16	UC211D1 UC211-200D1 UC211-201D1 UC211-202D1 UC211-203D1
		6 3/8	5 1/8	63/64	23/32	1 11/16	3/4	2 19/64	2.1890	0.874	5/8	
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UCF212D1</b> <b>UCF212-204D1</b> <b>UCF212-205D1</b> <b>UCF212-206D1</b> <b>UCF212-207D1</b>	175	143	29	18	48	19	68.7	65.1	25.4	M16	UC212D1 UC212-204D1 UC212-205D1 UC212-206D1 UC212-207D1
		6 7/8	5 5/8	1 9/64	23/32	1 7/8	3/4	2 45/64	2.5630	1.000	5/8	
65 2 1/2 2 9/16	<b>UCF213D1</b> <b>UCF213-208D1</b> <b>UCF213-209D1</b>	187	149	30	22	50	19	69.7	65.1	25.4	M16	UC213D1 UC213-208D1 UC213-209D1
		7 3/8	5 55/64	1 3/16	7/8	1 31/32	3/4	2 3/4	2.5630	1.000	5/8	
70 2 5/8 2 11/16 2 3/4	<b>UCF214D1</b> <b>UCF214-210D1</b> <b>UCF214-211D1</b> <b>UCF214-212D1</b>	193	152	31	22	54	19	75.4	74.6	30.2	M16	UC214D1 UC214-210D1 UC214-211D1 UC214-212D1
		7 19/32	5 63/64	1 7/32	7/8	2 1/8	3/4	2 31/32	2.9370	1.189	5/8	
75 2 13/16 2 7/8 2 15/16 3	<b>UCF215D1</b> <b>UCF215-213D1</b> <b>UCF215-214D1</b> <b>UCF215-215D1</b> <b>UCF215-300D1</b>	200	159	34	22	56	19	78.5	77.8	33.3	M16	UC215D1 UC215-213D1 UC215-214D1 UC215-215D1 UC215-300D1
		7 7/8	6 17/64	1 11/32	7/8	2 7/32	3/4	3 3/32	3.0630	1.311	5/8	
80 3 1/16 3 1/8 3 3/16	<b>UCF216D1</b> <b>UCF216-301D1</b> <b>UCF216-302D1</b> <b>UCF216-303D1</b>	208	165	34	22	58	23	83.3	82.6	33.3	M20	UC216D1 UC216-301D1 UC216-302D1 UC216-303D1
		8 3/16	6 1/2	1 11/32	7/8	2 9/32	29/32	3 3/32	3.2520	1.311	3/4	

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.




Pressed steel dust cover type  
Open end **Z-UCF...D1**  
Closed end **ZM-UCF...D1**

Cast dust cover type  
Open end **C-UCF...D1**  
Closed end **CM-UCF...D1**

Housing number	Unit number (*) pressed steel dust cover type	Unit number (*) cast dust cover type	Nominal dimensions			Mass of unit		
			mm inch			kg lb		
			t max.	A <sub>4</sub>	A <sub>5</sub>	UCF	Z(ZM)	C(CM)
F210D1	<b>Z(ZM)-UCF210D1</b>	<b>C(CM)-UCF210D1</b>	3	60	72	2.5	2.5	3.0
F210D1	<b>Z(ZM)-UCF210-113D1</b>	<b>C(CM)-UCF210-113D1</b>						
F210D1	<b>Z(ZM)-UCF210-114D1</b>	<b>C(CM)-UCF210-114D1</b>						
F210D1	<b>Z(ZM)-UCF210-115D1</b>	<b>C(CM)-UCF210-115D1</b>	1/8	2 3/8	2 27/32	5.5	5.5	6.6
F210D1	—	<b>C(CM)-UCF210-200D1</b>						
F211D1	<b>Z(ZM)-UCF211D1</b>	<b>C(CM)-UCF211D1</b>	4	64	75	3.3	3.4	4.0
F211D1	<b>Z(ZM)-UCF211-200D1</b>	<b>C(CM)-UCF211-200D1</b>						
F211D1	<b>Z(ZM)-UCF211-201D1</b>	<b>C(CM)-UCF211-201D1</b>						
F211D1	<b>Z(ZM)-UCF211-202D1</b>	<b>C(CM)-UCF211-202D1</b>	5/32	2 1/2	2 15/16	7.3	7.5	8.8
F211D1	<b>Z(ZM)-UCF211-203D1</b>	<b>C(CM)-UCF211-203D1</b>						
F212D1	<b>Z(ZM)-UCF212D1</b>	<b>C(CM)-UCF212D1</b>	4	74	86	3.9	4.1	4.8
F212D1	<b>Z(ZM)-UCF212-204D1</b>	<b>C(CM)-UCF212-204D1</b>						
F212D1	<b>Z(ZM)-UCF212-205D1</b>	<b>C(CM)-UCF212-205D1</b>						
F212D1	<b>Z(ZM)-UCF212-206D1</b>	<b>C(CM)-UCF212-206D1</b>	5/32	2 29/32	3 3/8	8.6	9.0	11
F212D1	—	<b>C(CM)-UCF212-207D1</b>						
F213D1	<b>Z(ZM)-UCF213D1</b>	<b>C(CM)-UCF213D1</b>	4	76	90	5.5	5.6	6.4
F213D1	<b>Z(ZM)-UCF213-208D1</b>	<b>C(CM)-UCF213-208D1</b>	5/32	3	3 17/32	12	12	14
F213D1	<b>Z(ZM)-UCF213-209D1</b>	<b>C(CM)-UCF213-209D1</b>						
F214D1	—	<b>C(CM)-UCF214D1</b>	4	—	98	6.3	—	7.4
F214D1	—	<b>C(CM)-UCF214-210D1</b>						
F214D1	—	<b>C(CM)-UCF214-211D1</b>	5/32	—	3 27/32	14	—	16
F214D1	—	<b>C(CM)-UCF214-212D1</b>						
F215D1	—	<b>C(CM)-UCF215D1</b>	4	—	102	6.6	—	7.9
F215D1	—	<b>C(CM)-UCF215-213D1</b>						
F215D1	—	<b>C(CM)-UCF215-214D1</b>						
F215D1	—	<b>C(CM)-UCF215-215D1</b>	5/32	—	4 1/32	15	—	17
F215D1	—	<b>C(CM)-UCF215-300D1</b>						
F216D1	—	<b>C(CM)-UCF216D1</b>	4	—	106	7.9	—	9.3
F216D1	—	<b>C(CM)-UCF216-301D1</b>						
F216D1	—	<b>C(CM)-UCF216-302D1</b>	5/32	—	4 3/16	17	—	21
F216D1	—	<b>C(CM)-UCF216-303D1</b>						

## Square flanged unit, cast housing Set screw type



Shaft dia. mm inch	Unit number <sup>(1)</sup>	Nominal dimensions										Bolt size mm inch	Bearing number
		mm inch											
		<i>L</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>1</sub>	<i>A</i>	<i>N</i>	<i>A</i> <sub>0</sub>	<i>B</i>	<i>S</i>			
85	<b>UCF217D1</b>	220	175	36	24	63	23	87.6	85.7	34.1	M20	UC217D1	
3 1/4	<b>UCF217-304D1</b>											UC217-304D1	
3 5/16	<b>UCF217-305D1</b>	8 21/32	6 57/64	1 27/64	15/16	2 15/32	29/32	3 29/64	3.3740	1.343	3/4	UC217-305D1	
3 7/16	<b>UCF217-307D1</b>											UC217-307D1	
90	<b>UCF218D1</b>	235	187	40	24	68	23	96.3	96	39.7	M20	UC218D1	
3 1/2	<b>UCF218-308D1</b>	9 1/4	7 23/64	1 37/64	15/16	2 11/16	29/32	3 51/64	3.7795	1.563	3/4	UC218-308D1	

Note <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.



### Pressed steel dust cover type


Open end **Z-UCF...D1**  
Closed end **ZM-UCF...D1**

### Cast dust cover type

Open end **C-UCF...D1**  
Closed end **CM-UCF...D1**

Housing number	Unit number <sup>(1)</sup> pressed steel dust cover type	Unit number <sup>(1)</sup> cast dust cover type	Nominal dimensions			Mass of unit		
			mm inch			kg lb		
			<i>t</i> max.	<i>A</i> <sub>4</sub>	<i>A</i> <sub>5</sub>	UCF	Z(ZM)	C(CM)
F217D1	—	<b>C(CM)-UCF217D1</b>	5	—	114	9.8	—	12
F217D1	—	<b>C(CM)-UCF217-304D1</b>						
F217D1	—	<b>C(CM)-UCF217-305D1</b>	13/64	—	4 1/2	22	—	26
F217D1	—	<b>C(CM)-UCF217-307D1</b>						
F218D1	—	<b>C(CM)-UCF218D1</b>	5	—	122	12	—	13
F218D1	—	<b>C(CM)-UCF218-308D1</b>	13/64	—	4 13/16	26	—	29

## Square flanged unit, cast housing Set screw type



Cast dust cover type  
Open end **C-UCF...D1**  
Closed end **CM-UCF...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions									Bolt size mm inch
		mm inch									
		<i>L</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>1</sub>	<i>A</i>	<i>N</i>	<i>A</i> <sub>0</sub>	<i>B</i>	<i>S</i>	
25 1 3/16 7/8 15/16 1	<b>UCF305D1</b>	110	80	16	13	29	16	39	38	15	M14
	<b>UCF305-013D1</b>										
	<b>UCF305-014D1</b>	4 11/32	3 5/32	5/8	1/2	1 5/32	5/8	1 17/32	1.4961	0.591	1/2
	<b>UCF305-015D1</b>										
30 1 1/16 1 1/8 1 3/16	<b>UCF306D1</b>	125	95	18	15	32	16	44	43	17	M14
	<b>UCF306-101D1</b>										
	<b>UCF306-102D1</b>	4 29/32	3 47/64	45/64	19/32	1 1/4	5/8	1 47/64	1.6929	0.669	1/2
	<b>UCF306-103D1</b>										
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UCF307D1</b>	135	100	20	16	36	19	49	48	19	M16
	<b>UCF307-104D1</b>										
	<b>UCF307-105D1</b>	5 5/16	3 15/16	25/32	5/8	1 13/32	3/4	1 59/64	1.8898	0.748	5/8
	<b>UCF307-106D1</b>										
40 1 1/2 1 9/16	<b>UCF308D1</b>	150	112	23	17	40	19	56	52	19	M16
	<b>UCF308-108D1</b>										
	<b>UCF308-109D1</b>	5 29/32	4 13/32	29/32	21/32	1 9/16	3/4	2 13/64	2.0472	0.748	5/8
45 1 5/8 1 11/16 1 3/4	<b>UCF309D1</b>	160	125	25	18	44	19	60	57	22	M16
	<b>UCF309-110D1</b>										
	<b>UCF309-111D1</b>	6 5/16	4 59/64	63/64	23/32	1 23/32	3/4	2 23/64	2.2441	0.866	5/8
	<b>UCF309-112D1</b>										
50 1 13/16 1 7/8 1 15/16	<b>UCF310D1</b>	175	132	28	19	48	23	67	61	22	M20
	<b>UCF310-113D1</b>										
	<b>UCF310-114D1</b>	6 7/8	5 13/64	1 7/64	3/4	1 7/8	29/32	2 41/64	2.4016	0.866	3/4
	<b>UCF310-115D1</b>										
55 2 2 1/16 2 1/8 2 3/16	<b>UCF311D1</b>	185	140	30	20	52	23	71	66	25	M20
	<b>UCF311-200D1</b>										
	<b>UCF311-201D1</b>	7 9/32	5 33/64	1 3/16	25/32	2 1/16	29/32	2 51/64	2.5984	0.984	3/4
	<b>UCF311-202D1</b>										
	<b>UCF311-203D1</b>										

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions		Mass of unit	
			mm inch <i>t</i> max.	<i>A</i> <sub>5</sub>	kg lb UCF	C(CM)
UC305D1 UC305-013D1 UC305-014D1 UC305-015D1 UC305-100D1	F305D1	<b>C(CM)-UCF305D1</b>	2	56	1.1	1.4
	F305D1	<b>C(CM)-UCF305-013D1</b>				
	F305D1	<b>C(CM)-UCF305-014D1</b>	5/64	2 7/32	2.4	3.1
	F305D1	<b>C(CM)-UCF305-015D1</b>				
UC306D1 UC306-101D1 UC306-102D1 UC306-103D1	F306D1	<b>C(CM)-UCF306D1</b>	2	60	1.6	2.1
	F306D1	<b>C(CM)-UCF306-101D1</b>				
	F306D1	<b>C(CM)-UCF306-102D1</b>	5/64	2 3/8	3.5	4.6
	F306D1	<b>C(CM)-UCF306-103D1</b>				
UC307D1 UC307-104D1 UC307-105D1 UC307-106D1 UC307-107D1	F307D1	<b>C(CM)-UCF307D1</b>	3	68	2.1	2.6
	F307D1	<b>C(CM)-UCF307-104D1</b>				
	F307D1	<b>C(CM)-UCF307-105D1</b>	1/8	2 11/16	4.6	5.7
	F307D1	<b>C(CM)-UCF307-106D1</b>				
UC308D1 UC308-108D1 UC308-109D1	F308D1	<b>C(CM)-UCF308D1</b>	3	76	2.7	3.4
	F308D1	<b>C(CM)-UCF308-108D1</b>	1/8	3	6.0	7.5
	F308D1	<b>C(CM)-UCF308-109D1</b>				
UC309D1 UC309-110D1 UC309-111D1 UC309-112D1	F309D1	<b>C(CM)-UCF309D1</b>	3	80	3.4	4.3
	F309D1	<b>C(CM)-UCF309-110D1</b>				
	F309D1	<b>C(CM)-UCF309-111D1</b>	1/8	3 5/32	7.5	9.5
	F309D1	<b>C(CM)-UCF309-112D1</b>				
UC310D1 UC310-113D1 UC310-114D1 UC310-115D1	F310D1	<b>C(CM)-UCF310D1</b>	3	88	4.5	5.8
	F310D1	<b>C(CM)-UCF310-113D1</b>				
	F310D1	<b>C(CM)-UCF310-114D1</b>	1/8	3 15/32	9.9	13
	F310D1	<b>C(CM)-UCF310-115D1</b>				
UC311D1 UC311-200D1 UC311-201D1 UC311-202D1 UC311-203D1	F311D1	<b>C(CM)-UCF311D1</b>	4	92	5.3	6.7
	F311D1	<b>C(CM)-UCF311-200D1</b>				
	F311D1	<b>C(CM)-UCF311-201D1</b>	5/32	3 5/8	12	15
	F311D1	<b>C(CM)-UCF311-202D1</b>				
	<b>UCF311-203D1</b>					

## Square flanged unit, cast housing Set screw type



Cast dust cover type  
Open end **C-UCF...D1**  
Closed end **CM-UCF...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions									Bolt size mm inch
		mm inch									
		<i>L</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>1</sub>	<i>A</i>	<i>N</i>	<i>A</i> <sub>0</sub>	<i>B</i>	<i>S</i>	
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UCF312D1</b> <b>UCF312-204D1</b> <b>UCF312-205D1</b> <b>UCF312-206D1</b> <b>UCF312-207D1</b>	195	150	33	22	56	23	78	71	26	M20
		7 11/16	5 29/32	1 19/64	7/8	2 7/32	29/32	3 5/64	2.7953	1.024	3/4
65 2 1/2 2 9/16	<b>UCF313D1</b> <b>UCF313-208D1</b> <b>UCF313-209D1</b>	208	166	33	22	58	23	78	75	30	M20
		8 3/16	6 17/32	1 19/64	7/8	2 9/32	29/32	3 5/64	2.9528	1.181	3/4
70 2 5/8 2 11/16 2 3/4	<b>UCF314D1</b> <b>UCF314-210D1</b> <b>UCF314-211D1</b> <b>UCF314-212D1</b>	226	178	36	25	61	25	81	78	33	M22
		8 29/32	6 1/4	1 27/64	31/32	2 13/32	63/64	3 3/16	3.0709	1.299	7/8
75 2 13/16 2 7/8 2 15/16 3	<b>UCF315D1</b> <b>UCF315-213D1</b> <b>UCF315-214D1</b> <b>UCF315-215D1</b> <b>UCF315-300D1</b>	236	184	39	25	66	25	89	82	32	M22
		9 9/32	7 1/4	1 17/32	31/32	2 19/32	63/64	3 1/2	3.2283	1.260	7/8
80 3 1/16 3 1/8 3 3/16	<b>UCF316D1</b> <b>UCF316-301D1</b> <b>UCF316-302D1</b> <b>UCF316-303D1</b>	250	196	38	27	68	31	90	86	34	M27
		9 27/32	7 23/32	1 1/2	1 1/16	2 11/16	1 7/32	3 35/64	3.3858	1.339	1
85 3 1/4 3 5/16 3 7/16	<b>UCF317D1</b> <b>UCF317-304D1</b> <b>UCF317-305D1</b> <b>UCF317-307D1</b>	260	204	44	27	74	31	100	96	40	M27
		10 1/4	8 1/32	1 47/64	1 1/16	2 29/32	1 7/32	3 15/16	3.7795	1.575	1
90 3 7/16 3 1/2	<b>UCF318D1</b> <b>UCF318-307D1</b> <b>UCF318-308D1</b>	280	216	44	30	76	35	100	96	40	M30
		11 1/32	8 1/2	1 47/64	1 3/16	3	1 3/8	3 15/16	3.7795	1.575	1 1/8


Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions		Mass of unit	
			<i>t</i> max.	<i>A</i> <sub>5</sub>	UCF	C(CM)
			mm inch		kg lb	
UC312D1 UC312-204D1 UC312-205D1 UC312-206D1 UC312-207D1	F312D1 F312D1 F312D1 F312D1 F312D1	<b>C(CM)-UCF312D1</b> <b>C(CM)-UCF312-204D1</b> <b>C(CM)-UCF312-205D1</b> <b>C(CM)-UCF312-206D1</b> <b>C(CM)-UCF312-207D1</b>	4 5/32	100 3 15/16	6.3 14	7.8 17
UC313D1 UC313-208D1 UC313-209D1	F313D1 F313D1 F313D1	<b>C(CM)-UCF313D1</b> <b>C(CM)-UCF313-208D1</b> <b>C(CM)-UCF313-209D1</b>	4 5/32	103 4 1/16	8.0 18	9.7 21
UC314D1 UC314-210D1 UC314-211D1 UC314-212D1	F314D1 F314D1 F314D1 F314D1	<b>C(CM)-UCF314D1</b> <b>C(CM)-UCF314-210D1</b> <b>C(CM)-UCF314-211D1</b> <b>C(CM)-UCF314-212D1</b>	4 5/32	106 4 3/16	9.4 21	11 24
UC315D1 UC315-213D1 UC315-214D1 UC315-215D1 UC315-300D1	F315D1 F315D1 F315D1 F315D1 F315D1	<b>C(CM)-UCF315D1</b> <b>C(CM)-UCF315-213D1</b> <b>C(CM)-UCF315-214D1</b> <b>C(CM)-UCF315-215D1</b> <b>C(CM)-UCF315-300D1</b>	4 5/32	114 4 1/2	11 24	13 29
UC316D1 UC316-301D1 UC316-302D1 UC316-303D1	F316D1 F316D1 F316D1 F316D1	<b>C(CM)-UCF316D1</b> <b>C(CM)-UCF316-301D1</b> <b>C(CM)-UCF316-302D1</b> <b>C(CM)-UCF316-303D1</b>	4 5/32	116 4 9/16	14 31	16 35
UC317D1 UC317-304D1 UC317-305D1 UC317-307D1	F317D1 F317D1 F317D1 F317D1	<b>C(CM)-UCF317D1</b> <b>C(CM)-UCF317-304D1</b> <b>C(CM)-UCF317-305D1</b> <b>C(CM)-UCF317-307D1</b>	5 13/64	129 5 3/32	15 33	19 42
UC318D1 UC318-307D1 UC318-308D1	F318D1 F318D1 F318D1	<b>C(CM)-UCF318D1</b> <b>C(CM)-UCF318-307D1</b> <b>C(CM)-UCF318-308D1</b>	5 13/64	129 5 3/32	19 42	23 51



Square flanged unit, cast housing  
Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions									Bolt size mm inch
		mm inch									
		<i>L</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>1</sub>	<i>A</i>	<i>N</i>	<i>A</i> <sub>0</sub>	<i>B</i>	<i>S</i>	
95 3 5/8 3 11/16 3 3/4	<b>UCF319D1</b> <b>UCF319-310D1</b> <b>UCF319-311D1</b> <b>UCF319-312D1</b>	290 11 13/32	228 8 31/32	59 2 21/64	30 1 3/16	94 3 11/16	35 1 3/8	121 4 49/64	103 4.0551	41 1.614	M30 1 1/8
100 3 13/16 3 7/8 3 15/16 4	<b>UCF320D1</b> <b>UCF320-313D1</b> <b>UCF320-314D1</b> <b>UCF320-315D1</b> <b>UCF320-400D1</b>	310 12 7/32	242 9 17/32	59 2 21/64	32 1 1/4	94 3 11/16	38 1 1/2	125 4 59/64	108 4.2520	42 1.654	M33 1 1/4
105	<b>UCF321D1</b>	310	242	59	32	94	38	127	112	44	M33
110	<b>UCF322D1</b>	340	266	60	35	96	41	131	117	46	M36
120	<b>UCF324D1</b>	370	290	65	40	110	41	140	126	51	M36
130	<b>UCF326D1</b>	410	320	65	45	115	41	146	135	54	M36
140	<b>UCF328D1</b>	450	350	75	55	125	41	161	145	59	M36

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".


Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type  
Open end C-UCF...D1  
Closed end CM-UCF...D1

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions		Mass of unit	
			mm inch <i>t</i> max.	<i>A</i> <sub>5</sub>	kg lb UCF C(CM)	
UC319D1	F319D1	<b>C(CM)-UCF319D1</b>	5	149	22	25
UC319-310D1	F319D1	<b>C(CM)-UCF319-310D1</b>	13/64	5 7/8	49	55
UC319-311D1	F319D1	<b>C(CM)-UCF319-311D1</b>				
UC319-312D1	F319D1	<b>C(CM)-UCF319-312D1</b>				
UC320D1	F320D1	<b>C(CM)-UCF320D1</b>	5	154	27	32
UC320-313D1	F320D1	<b>C(CM)-UCF320-313D1</b>	13/64	6 1/16	60	71
UC320-314D1	F320D1	<b>C(CM)-UCF320-314D1</b>				
UC320-315D1	F320D1	<b>C(CM)-UCF320-315D1</b>				
UC320-400D1	F320D1	<b>C(CM)-UCF320-400D1</b>				
UC321D1	F321D1	<b>C(CM)-UCF321D1</b>	5	156	26	32
UC322D1	F322D1	<b>C(CM)-UCF322D1</b>	5	160	34	40
UC324D1	F324D1	<b>C(CM)-UCF324D1</b>	5	172	48	56
UC326D1	F326D1	<b>C(CM)-UCF326D1</b>	6	178	63	73
UC328D1	F328D1	<b>C(CM)-UCF328D1</b>	6	192	90	100

## Square flanged unit, cast housing Set screw type



Cast dust cover type  
Open end **C-UCF...D1**  
Closed end **CM-UCF...D1**


Shaft dia. mm inch	Unit number (1)	Nominal dimensions									Bolt size mm inch
		mm inch									
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B	S	
25 1 3/16 7/8 15/16 1	<b>UCFX05D1</b>	108	83	18	13	30	12	40.2	38.1	15.9	M10
	<b>UCFX05-013D1</b>										
	<b>UCFX05-014D1</b>	4 1/4	3 17/64	45/64	1/2	1 3/16	15/32	1 37/64	1.5000	0.626	3/8
	<b>UCFX05-015D1</b>										
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UCFX06D1</b>	117	92	19	14	34	16	44.4	42.9	17.5	M14
	<b>UCFX06-101D1</b>										
	<b>UCFX06-102D1</b>	4 19/32	3 5/8	3/4	9/16	1 11/32	5/8	1 3/4	1.6890	0.689	1/2
	<b>UCFX06-103D1</b>										
35 1 5/16 1 3/8 1 7/16	<b>UCFX07D1</b>	130	102	21	14	38	16	51.2	49.2	19	M14
	<b>UCFX07-105D1</b>										
	<b>UCFX07-106D1</b>	5 1/8	4 1/64	53/64	9/16	1 1/2	5/8	2 1/64	1.9370	0.748	1/2
	<b>UCFX07-107D1</b>										
40 1 1/2 1 9/16	<b>UCFX08D1</b>	137	105	22	14	40	19	52.2	49.2	19	M16
	<b>UCFX08-108D1</b>	5 13/32	4 9/64	55/64	9/16	1 9/16	3/4	2 1/16	1.9370	0.748	5/8
	<b>UCFX08-109D1</b>										
45 1 5/8 1 11/16 1 3/4 1 13/16	<b>UCFX09D1</b>	143	111	23	14	40	19	55.6	51.6	19	M16
	<b>UCFX09-110D1</b>										
	<b>UCFX09-111D1</b>	5 5/8	4 3/8	29/32	9/16	1 9/16	3/4	2 3/16	2.0315	0.748	5/8
	<b>UCFX09-112D1</b>										
50 1 7/8 1 15/16 2	<b>UCFX10D1</b>	162	130	26	20	44	19	59.4	55.6	22.2	M16
	<b>UCFX10-114D1</b>										
	<b>UCFX10-115D1</b>	6 3/8	5 1/8	1 1/32	25/32	1 23/32	3/4	2 11/32	2.1890	0.874	5/8
	<b>UCFX10-200D1</b>										

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions		Mass of unit	
			mm inch		kg lb	
			t max.	A <sub>5</sub>	UCF	C(CM)
UCX05D1	FX05D1	<b>C(CM)-UCFX05D1</b>	2	56	1.1	1.3
UCX05-013D1	FX05D1	<b>C(CM)-UCFX05-013D1</b>				
UCX05-014D1	FX05D1	<b>C(CM)-UCFX05-014D1</b>	5/64	2 7/32	2.4	2.9
UCX05-015D1	FX05D1	<b>C(CM)-UCFX05-015D1</b>				
UCX05-100D1	FX05D1	<b>C(CM)-UCFX05-100D1</b>				
UCX06D1	FX06D1	<b>C(CM)-UCFX06D1</b>	2	59	1.7	1.9
UCX06-101D1	FX06D1	<b>C(CM)-UCFX06-101D1</b>				
UCX06-102D1	FX06D1	<b>C(CM)-UCFX06-102D1</b>	5/64	2 5/16	3.7	4.2
UCX06-103D1	FX06D1	<b>C(CM)-UCFX06-103D1</b>				
UC207-104D1	FX06D1	<b>C(CM)-UCFX06-104D1</b>				
UCX07D1	FX07D1	<b>C(CM)-UCFX07D1</b>	3	66	2.1	2.5
UCX07-105D1	FX07D1	<b>C(CM)-UCFX07-105D1</b>				
UCX07-106D1	FX07D1	<b>C(CM)-UCFX07-106D1</b>	1/8	2 19/32	4.6	5.5
UCX07-107D1	FX07D1	<b>C(CM)-UCFX07-107D1</b>				
UCX08D1	FX08D1	<b>C(CM)-UCFX08D1</b>	3	70	2.3	2.7
UCX08-108D1	FX08D1	<b>C(CM)-UCFX08-108D1</b>	1/8	2 3/4	5.1	6.0
UCX08-109D1	FX08D1	<b>C(CM)-UCFX08-109D1</b>				
UCX09D1	FX09D1	<b>C(CM)-UCFX09D1</b>	3	73	2.5	3.0
UCX09-110D1	FX09D1	<b>C(CM)-UCFX09-110D1</b>				
UCX09-111D1	FX09D1	<b>C(CM)-UCFX09-111D1</b>	1/8	2 7/8	5.5	6.6
UCX09-112D1	FX09D1	<b>C(CM)-UCFX09-112D1</b>				
UC210-113D1	FX09D1	<b>C(CM)-UCFX09-113D1</b>				
UCX10D1	FX10D1	<b>C(CM)-UCFX10D1</b>	3	76	3.8	4.3
UCX10-114D1	FX10D1	<b>C(CM)-UCFX10-114D1</b>				
UCX10-115D1	FX10D1	<b>C(CM)-UCFX10-115D1</b>	1/8	3	8.4	9.5
UC211-200D1	FX10D1	<b>C(CM)-UCFX10-200D1</b>				

## Square flanged unit, cast housing Set screw type



**Cast dust cover type**  
Open end **C-UCF...D1**  
Closed end **CM-UCF...D1**


Shaft dia.  mm inch	Unit number (1)	Nominal dimensions									Bolt size  mm inch
		mm inch									
		<i>L</i>	<i>J</i>	<i>A<sub>2</sub></i>	<i>A<sub>1</sub></i>	<i>A</i>	<i>N</i>	<i>A<sub>0</sub></i>	<i>B</i>	<i>S</i>	
55 2 1/16 2 1/8 2 3/16 2 1/4 2 5/16	<b>UCFX11D1</b> <b>UCFX11-201D1</b> <b>UCFX11-202D1</b> <b>UCFX11-203D1</b> <b>UCFX11-204D1</b> <b>UCFX11-205D1</b>	175 6 7/8	143 5 5/8	29 1 9/64	20 25/32	49 1 15/16	19 3/4	68.7 2 45/64	65.1 2.5630	25.4 1.000	M16 5/8
60 2 3/8 2 7/16	<b>UCFX12D1</b> <b>UCFX12-206D1</b> <b>UCFX12-207D1</b>	187 7 3/8	149 5 55/64	34 1 11/32	21 13/16	59 2 5/16	19 3/4	73.7 2 29/32	65.1 2.5630	25.4 1.000	M16 5/8
65 2 1/2 2 9/16	<b>UCFX13D1</b> <b>UCFX13-208D1</b> <b>UCFX13-209D1</b>	187 7 3/8	149 5 55/64	34 1 11/32	21 13/16	59 2 5/16	19 3/4	78.4 3 3/32	74.6 2.9370	30.2 1.189	M16 5/8
70 2 5/8 2 11/16 2 3/4	<b>UCFX14D1</b> <b>UCFX14-210D1</b> <b>UCFX14-211D1</b> <b>UCFX14-212D1</b>	197 7 3/4	152 5 53/64	37 1 29/64	24 15/16	60 2 3/8	23 29/32	81.5 3 13/64	77.8 3.0630	33.3 1.311	M20 3/4
75 2 13/16 2 7/8 2 15/16 3	<b>UCFX15D1</b> <b>UCFX15-213D1</b> <b>UCFX15-214D1</b> <b>UCFX15-215D1</b> <b>UCFX15-300D1</b>	197 7 3/4	152 5 53/64	40 1 37/64	24 15/16	68 2 11/16	23 29/32	89.3 3 33/64	82.6 3.2520	33.3 1.311	M20 3/4
80 3 1/16 3 1/8 3 3/16 3 1/4	<b>UCFX16D1</b> <b>UCFX16-301D1</b> <b>UCFX16-302D1</b> <b>UCFX16-303D1</b> <b>UCFX16-304D1</b>	214 8 7/16	171 6 47/64	40 1 37/64	24 15/16	70 2 3/4	23 29/32	91.6 3 39/64	85.7 3.3740	34.1 1.343	M20 3/4

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions		Mass of unit	
			mm inch		kg lb	
			<i>t</i> max.	<i>A<sub>5</sub></i>	UCF	C(CM)
UCX11D1 UCX11-201D1 UCX11-202D1 UCX11-203D1 UC212-204D1 UC212-205D1	FX11D1 FX11D1 FX11D1 FX11D1 FX11D1 FX11D1	<b>C(CM)-UCFX11D1</b> <b>C(CM)-UCFX11-201D1</b> <b>C(CM)-UCFX11-202D1</b> <b>C(CM)-UCFX11-203D1</b> <b>C(CM)-UCFX11-204D1</b> <b>C(CM)-UCFX11-205D1</b>	4 5/32	86 3 3/8	4.8 11	5.5 12
UCX12D1 UCX12-206D1 UCX12-207D1	FX12D1 FX12D1 FX12D1	<b>C(CM)-UCFX12D1</b> <b>C(CM)-UCFX12-206D1</b> <b>C(CM)-UCFX12-207D1</b>	4 5/32	94 3 11/16	6.4 14	7.3 16
UCX13D1 UCX13-208D1 UCX13-209D1	FX13D1 FX13D1 FX13D1	<b>C(CM)-UCFX13D1</b> <b>C(CM)-UCFX13-208D1</b> <b>C(CM)-UCFX13-209D1</b>	4 5/32	101 3 31/32	6.7 15	7.8 17
UCX14D1 UCX14-210D1 UCX14-211D1 UCX14-212D1	FX14D1 FX14D1 FX14D1 FX14D1	<b>C(CM)-UCFX14D1</b> <b>C(CM)-UCFX14-210D1</b> <b>C(CM)-UCFX14-211D1</b> <b>C(CM)-UCFX14-212D1</b>	4 5/32	105 4 1/8	7.1 16	8.3 18
UCX15D1 UCX15-213D1 UCX15-214D1 UCX15-215D1 UCX15-300D1	FX15D1 FX15D1 FX15D1 FX15D1 FX15D1	<b>C(CM)-UCFX15D1</b> <b>C(CM)-UCFX15-213D1</b> <b>C(CM)-UCFX15-214D1</b> <b>C(CM)-UCFX15-215D1</b> <b>C(CM)-UCFX15-300D1</b>	4 5/32	112 4 13/32	8.6 19	9.9 22
UCX16D1 UCX16-301D1 UCX16-302D1 UCX16-303D1 UC217-304D1	FX16D1 FX16D1 FX16D1 FX16D1 FX16D1	<b>C(CM)-UCFX16D1</b> <b>C(CM)-UCFX16-301D1</b> <b>C(CM)-UCFX16-302D1</b> <b>C(CM)-UCFX16-303D1</b> <b>C(CM)-UCFX16-304D1</b>	4 5/32	118 4 21/32	11 24	12 26

## Square flanged unit, cast housing Set screw type



**Cast dust cover type**  
Open end **C-UCF...D1**  
Closed end **CM-UCF...D1**



Shaft dia. mm inch	Unit number (1)	Nominal dimensions									Bolt size mm inch
		mm inch									
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B	S	
85 3 5/16 3 7/16	<b>UCFX17D1</b> <b>UCFX17-305D1</b> <b>UCFX17-307D1</b>	214 8 7/16	171 6 47/64	40 1 37/64	24 1 5/16	70 2 3/4	23 29/32	96.3 3 51/64	96 3.7795	39.7 1.563	M20 3/4
90 3 7/16 3 1/2	<b>UCFX18D1</b> <b>UCFX18-307D1</b> <b>UCFX18-308D1</b>	214 8 7/16	171 6 47/64	45 1 49/64	24 1 5/16	76 3	23 29/32	106.1 4 11/64	104 4.0945	42.9 1.689	M20 3/4
100 3 13/16 3 7/8 3 15/16 4	<b>UCFX20D1</b> <b>UCFX20-313D1</b> <b>UCFX20-314D1</b> <b>UCFX20-315D1</b> <b>UCFX20-400D1</b>	268 10 9/16	211 8 5/16	59 2 21/64	31 1 7/32	97 3 13/16	31 1 7/32	127.3 5 1/64	117.5 4.6260	49.2 1.937	M27 1

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions		Mass of unit	
			mm inch		kg lb	
			t max.	A <sub>5</sub>	UCF	C(CM)
UCX17D1	FX17D1	<b>C(CM)-UCFX17D1</b>	5	122	12	14
UCX17-305D1	FX17D1	<b>C(CM)-UCFX17-305D1</b>	13/64	4 13/16	26	31
UCX17-307D1	FX17D1	<b>C(CM)-UCFX17-307D1</b>				
UCX18D1	FX18D1	<b>C(CM)-UCFX18D1</b>	5	135	13	15
UCX18-307D1	FX18D1	<b>C(CM)-UCFX18-307D1</b>	13/64	5 5/16	29	33
UCX18-308D1	FX18D1	<b>C(CM)-UCFX18-308D1</b>				
UCX20D1	FX20D1	<b>C(CM)-UCFX20D1</b>	5	146.5	21	23
UCX20-313D1	FX20D1	<b>C(CM)-UCFX20-313D1</b>				
UCX20-314D1	FX20D1	<b>C(CM)-UCFX20-314D1</b>	13/64	5 25/32	46	51
UCX20-315D1	FX20D1	<b>C(CM)-UCFX20-315D1</b>				
UCX20-400D1	FX20D1	<b>C(CM)-UCFX20-400D1</b>				

## Square flanged unit, cast housing with spigot joint Set screw type





**Cast dust cover type**  
Open end **C-UCFS...D1**  
Closed end **CM-UCFS...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		L	J	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B	S	
25 1 15/16 7/8 15/16 1	<b>UCFS305D1</b> <b>UCFS305-013D1</b> <b>UCFS305-014D1</b> <b>UCFS305-015D1</b> <b>UCFS305-100D1</b>	110	80	9	16	7	13	29	80	39	38	15	M14 1/2
30 1 1/16 1 1/8 1 3/16	<b>UCFS306D1</b> <b>UCFS306-101D1</b> <b>UCFS306-102D1</b> <b>UCFS306-103D1</b>	125	95	10	16	8	15	32	90	44	43	17	M14 1/2
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UCFS307D1</b> <b>UCFS307-104D1</b> <b>UCFS307-105D1</b> <b>UCFS307-106D1</b> <b>UCFS307-107D1</b>	135	100	11	19	9	16	36	100	49	48	19	M16 5/8
40 1 1/2 1 9/16	<b>UCFS308D1</b> <b>UCFS308-108D1</b> <b>UCFS308-109D1</b>	150	112	13	19	10	17	40	115	56	52	19	M16 5/8
45 1 5/8 1 11/16 1 3/4	<b>UCFS309D1</b> <b>UCFS309-110D1</b> <b>UCFS309-111D1</b> <b>UCFS309-112D1</b>	160	125	14	19	11	18	44	125	60	57	22	M16 5/8
50 1 13/16 1 7/8 1 15/16	<b>UCFS310D1</b> <b>UCFS310-113D1</b> <b>UCFS310-114D1</b> <b>UCFS310-115D1</b>	175	132	16	23	12	19	48	140	67	61	22	M20 3/4

**Note** (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
**Remarks** Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions		Mass of unit	
			mm t max.	inch A <sub>5</sub>	kg UCFS	lb C(CM)
UC305D1	FS305D1	<b>C(CM)-UCFS305D1</b>	2	56	1.2	1.4
UC305-013D1	FS305D1	<b>C(CM)-UCFS305-013D1</b>				
UC305-014D1	FS305D1	<b>C(CM)-UCFS305-014D1</b>	5/64	2 13/64	2.6	3.1
UC305-015D1	FS305D1	<b>C(CM)-UCFS305-015D1</b>				
UC305-100D1	FS305D1	<b>C(CM)-UCFS305-100D1</b>				
UC306D1	FS306D1	<b>C(CM)-UCFS306D1</b>	2	60	1.8	2.2
UC306-101D1	FS306D1	<b>C(CM)-UCFS306-101D1</b>				
UC306-102D1	FS306D1	<b>C(CM)-UCFS306-102D1</b>	5/64	2 23/64	4.0	4.9
UC306-103D1	FS306D1	<b>C(CM)-UCFS306-103D1</b>				
UC307D1	FS307D1	<b>C(CM)-UCFS307D1</b>	3	67	2.3	2.8
UC307-104D1	FS307D1	<b>C(CM)-UCFS307-104D1</b>				
UC307-105D1	FS307D1	<b>C(CM)-UCFS307-105D1</b>	1/8	2 41/64	5.1	6.2
UC307-106D1	FS307D1	<b>C(CM)-UCFS307-106D1</b>				
UC307-107D1	FS307D1	<b>C(CM)-UCFS307-107D1</b>				
UC308D1	FS308D1	<b>C(CM)-UCFS308D1</b>	3	76	3.1	3.6
UC308-108D1	FS308D1	<b>C(CM)-UCFS308-108D1</b>	1/8	2 63/64	6.8	7.9
UC308-109D1	FS308D1	<b>C(CM)-UCFS308-109D1</b>				
UC309D1	FS309D1	<b>C(CM)-UCFS309D1</b>	3	80	3.8	4.7
UC309-110D1	FS309D1	<b>C(CM)-UCFS309-110D1</b>				
UC309-111D1	FS309D1	<b>C(CM)-UCFS309-111D1</b>	1/8	3 5/32	8.4	10
UC309-112D1	FS309D1	<b>C(CM)-UCFS309-112D1</b>				
UC310D1	FS310D1	<b>C(CM)-UCFS310D1</b>	3	88	5.0	6.2
UC310-113D1	FS310D1	<b>C(CM)-UCFS310-113D1</b>				
UC310-114D1	FS310D1	<b>C(CM)-UCFS310-114D1</b>	1/8	3 15/32	11	14
UC310-115D1	FS310D1	<b>C(CM)-UCFS310-115D1</b>				

## Square flanged unit, cast housing with spigot joint Set screw type





Cast dust cover type  
Open end **C-UCFS...D1**  
Closed end **CM-UCFS...D1**

Shaft dia. mm inch	Unit number (*)	Nominal dimensions											Bolt size mm inch
		mm inch											
		L	J	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B	S	
55 2 2 1/16 2 1/8 2 3/16	<b>UCFS311D1</b> <b>UCFS311-200D1</b> <b>UCFS311-201D1</b> <b>UCFS311-202D1</b> <b>UCFS311-203D1</b>	185	140	17	23	13	20	52	150	71	66	25	M20 3/4
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UCFS312D1</b> <b>UCFS312-204D1</b> <b>UCFS312-205D1</b> <b>UCFS312-206D1</b> <b>UCFS312-207D1</b>	195	150	19	23	14	22	56	160	78	71	26	M20 3/4
65 2 1/2 2 9/16	<b>UCFS313D1</b> <b>UCFS313-208D1</b> <b>UCFS313-209D1</b>	208	166	15	23	18	22	58	175	78	75	30	M20 3/4
70 2 5/8 2 11/16 2 3/4	<b>UCFS314D1</b> <b>UCFS314-210D1</b> <b>UCFS314-211D1</b> <b>UCFS314-212D1</b>	226	178	18	25	18	25	61	185	81	78	33	M22 7/8
75 2 13/16 2 7/8 2 9/16 3	<b>UCFS315D1</b> <b>UCFS315-213D1</b> <b>UCFS315-214D1</b> <b>UCFS315-215D1</b> <b>UCFS315-300D1</b>	236	184	21	25	18	25	66	200	89	82	32	M22 7/8
80 3 1/16 3 3/8 3 3/16	<b>UCFS316D1</b> <b>UCFS316-301D1</b> <b>UCFS316-302D1</b> <b>UCFS316-303D1</b>	250	196	18	31	20	27	68	210	90	86	34	M27 1

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (*) cast dust cover type	Nominal dimensions		Mass of unit	
			mm inch		kg lb	
			t max.	A <sub>5</sub>	UCFS	C(CM)
UC311D1	FS311D1	<b>C(CM)-UCFS311D1</b>	4	93	5.9	7.2
UC311-200D1	FS311D1	<b>C(CM)-UCFS311-200D1</b>				
UC311-201D1	FS311D1	<b>C(CM)-UCFS311-201D1</b>				
UC311-202D1	FS311D1	<b>C(CM)-UCFS311-202D1</b>	5/32	3 21/32	13	16
UC311-203D1	FS311D1	<b>C(CM)-UCFS311-203D1</b>				
UC312D1	FS312D1	<b>C(CM)-UCFS312D1</b>	4	100	7.0	8.4
UC312-204D1	FS312D1	<b>C(CM)-UCFS312-204D1</b>				
UC312-205D1	FS312D1	<b>C(CM)-UCFS312-205D1</b>				
UC312-206D1	FS312D1	<b>C(CM)-UCFS312-206D1</b>	5/32	3 15/16	15	19
UC312-207D1	FS312D1	<b>C(CM)-UCFS312-207D1</b>				
UC313D1	FS313D1	<b>C(CM)-UCFS313D1</b>	4	103	8.6	10
UC313-208D1	FS313D1	<b>C(CM)-UCFS313-208D1</b>				
UC313-209D1	FS313D1	<b>C(CM)-UCFS313-209D1</b>	5/32	4 1/16	19	22
UC314D1	FS314D1	<b>C(CM)-UCFS314D1</b>	4	106	10	12
UC314-210D1	FS314D1	<b>C(CM)-UCFS314-210D1</b>				
UC314-211D1	FS314D1	<b>C(CM)-UCFS314-211D1</b>	5/32	4 11/64	22	26
UC314-212D1	FS314D1	<b>C(CM)-UCFS314-212D1</b>				
UC315D1	FS315D1	<b>C(CM)-UCFS315D1</b>	4	114	12	14
UC315-213D1	FS315D1	<b>C(CM)-UCFS315-213D1</b>				
UC315-214D1	FS315D1	<b>C(CM)-UCFS315-214D1</b>				
UC315-215D1	FS315D1	<b>C(CM)-UCFS315-215D1</b>	5/32	4 31/64	26	31
UC315-300D1	FS315D1	<b>C(CM)-UCFS315-300D1</b>				
UC316D1	FS316D1	<b>C(CM)-UCFS316D1</b>	4	116	14	17
UC316-301D1	FS316D1	<b>C(CM)-UCFS316-301D1</b>				
UC316-302D1	FS316D1	<b>C(CM)-UCFS316-302D1</b>	5/32	4 9/16	31	37
UC316-303D1	FS316D1	<b>C(CM)-UCFS316-303D1</b>				

## Square flanged unit, cast housing with spigot joint Set screw type



Cast dust cover type  
Open end **C-UCFS...D1**  
Closed end **CM-UCFS...D1**


Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		L	J	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B	S	
85 3 1/4	<b>UCFS317D1</b>	260	204	24	31	20	27	74	220	100	96	40	M27
3 5/16	<b>UCFS317-304D1</b>	10 1/4	8 1/2	15/16	1 7/32	25/32	1 1/16	2 29/32	8.6614	3 15/16	3.7795	1.575	1
3 7/16	<b>UCFS317-305D1</b>												
3 7/16	<b>UCFS317-307D1</b>												
90 3 7/16	<b>UCFS318D1</b>	280	216	24	35	20	30	76	240	100	96	40	M30
3 7/16	<b>UCFS318-307D1</b>	11 1/2	8 1/2	15/16	1 3/8	25/32	1 3/16	2 59/64	9.4488	3 15/16	3.7795	1.575	1 1/8
3 1/2	<b>UCFS318-308D1</b>												
95 3 5/8	<b>UCFS319D1</b>	290	228	39	35	20	30	94	250	121	103	41	M30
3 5/8	<b>UCFS319-310D1</b>	11 13/32	8 31/32	1 17/32	1 3/8	25/32	1 3/16	3 45/64	9.8425	4 49/64	4.0551	1.614	1 1/8
3 11/16	<b>UCFS319-311D1</b>												
3 3/4	<b>UCFS319-312D1</b>												
100 3 13/16	<b>UCFS320D1</b>	310	242	39	38	20	32	94	260	125	108	42	M33
3 13/16	<b>UCFS320-313D1</b>	12 7/32	9 17/32	1 17/32	1 1/2	25/32	1 1/4	3 45/64	10.2362	4 59/64	4.2520	1.654	1 1/4
3 7/8	<b>UCFS320-314D1</b>												
3 15/16	<b>UCFS320-315D1</b>												
4	<b>UCFS320-400D1</b>												
105	<b>UCFS321D1</b>	310	242	39	38	20	32	94	260	127	112	44	M33
110	<b>UCFS322D1</b>	340	266	35	41	25	35	96	300	131	117	46	M36
120	<b>UCFS324D1</b>	370	290	35	41	30	40	110	330	140	126	51	M36
130	<b>UCFS326D1</b>	410	320	35	41	30	45	115	360	146	135	54	M36
140	<b>UCFS328D1</b>	450	350	45	41	30	55	125	400	161	145	59	M36

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions		Mass of unit	
			mm inch		kg lb	
			t max.	A <sub>5</sub>	UCFS	C(CM)
UC317D1	FS317D1	<b>C(CM)-UCFS317D1</b>	5	129	17	20
UC317-304D1	FS317D1	<b>C(CM)-UCFS317-304D1</b>				
UC317-305D1	FS317D1	<b>C(CM)-UCFS317-305D1</b>	13/64	5 5/64	37	44
UC317-307D1	FS317D1	<b>C(CM)-UCFS317-307D1</b>				
UC318D1	FS318D1	<b>C(CM)-UCFS318D1</b>	5	129	20	24
UC318-307D1	FS318D1	<b>C(CM)-UCFS318-307D1</b>				
UC318-308D1	FS318D1	<b>C(CM)-UCFS318-308D1</b>	13/64	5 5/64	44	53
UC319D1	FS319D1	<b>C(CM)-UCFS319D1</b>	5	149	24	28
UC319-310D1	FS319D1	<b>C(CM)-UCFS319-310D1</b>				
UC319-311D1	FS319D1	<b>C(CM)-UCFS319-311D1</b>	13/64	5 55/64	53	62
UC319-312D1	FS319D1	<b>C(CM)-UCFS319-312D1</b>				
UC320D1	FS320D1	<b>C(CM)-UCFS320D1</b>	5	154	29	34
UC320-313D1	FS320D1	<b>C(CM)-UCFS320-313D1</b>				
UC320-314D1	FS320D1	<b>C(CM)-UCFS320-314D1</b>				
UC320-315D1	FS320D1	<b>C(CM)-UCFS320-315D1</b>	13/64	6 1/16	64	75
UC320-400D1	FS320D1	<b>C(CM)-UCFS320-400D1</b>				
UC321D1	FS321D1	<b>C(CM)-UCFS321D1</b>	5	156	28	33
UC322D1	FS322D1	<b>C(CM)-UCFS322D1</b>	5	160	38	45
UC324D1	FS324D1	<b>C(CM)-UCFS324D1</b>	5	172	52	59
UC326D1	FS326D1	<b>C(CM)-UCFS326D1</b>	6	178	69	77
UC328D1	FS328D1	<b>C(CM)-UCFS328D1</b>	6	192	98	109

## Round flanged unit, cast housing with spigot joint Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch	
		mm inch												
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B		S
12 1/2	<b>UCFC201D1</b> <b>UCFC201-008D1</b>	100 3 15/16	78 3 5/8	55.2 2 11/64	10 25/64	12 15/32	5 13/64	20.5 13/16	25.5 1	62 2.4409	33.3 1 15/16	31 1.2205	12.7 0.500	M10 3/8
15 9/16 5/8	<b>UCFC202D1</b> <b>UCFC202-009D1</b> <b>UCFC202-010D1</b>	100 3 15/16	78 3 5/8	55.2 2 11/64	10 25/64	12 15/32	5 13/64	20.5 13/16	25.5 1	62 2.4409	33.3 1 5/16	31 1.2205	12.7 0.500	M10 3/8
17 11/16	<b>UCFC203D1</b> <b>UCFC203-011D1</b>	100 3 15/16	78 3 5/8	55.2 2 11/64	10 25/64	12 15/32	5 13/64	20.5 13/16	25.5 1	62 2.4409	33.3 1 5/16	31 1.2205	12.7 0.500	M10 3/8
20 3/4	<b>UCFC204D1</b> <b>UCFC204-012D1</b>	100 3 15/16	78 3 5/8	55.2 2 11/64	10 25/64	12 15/32	5 13/64	20.5 13/16	25.5 1	62 2.4409	33.3 1 5/16	31 1.2205	12.7 0.500	M10 3/8
25 13/16 7/8 15/16	<b>UCFC205D1</b> <b>UCFC205-013D1</b> <b>UCFC205-014D1</b> <b>UCFC205-015D1</b> <b>UCFC205-100D1</b>	115 4 17/32	90 3 35/64	63.6 2 1/2	10 25/64	12 15/32	6 15/64	21 13/16	27 1 1/16	70 2.7559	35.8 1 13/32	34.1 1.3425	14.3 0.563	M10 3/8
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UCFC206D1</b> <b>UCFC206-101D1</b> <b>UCFC206-102D1</b> <b>UCFC206-103D1</b> <b>UCFC206-104D1</b>	125 4 23/32	100 3 15/16	70.7 2 25/32	10 25/64	12 15/32	8 5/16	23 29/32	31 1 7/32	80 3.1496	40.2 1 37/64	38.1 1.5000	15.9 0.629	M10 3/8
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UCFC207D1</b> <b>UCFC207-104D1</b> <b>UCFC207-105D1</b> <b>UCFC207-106D1</b> <b>UCFC207-107D1</b>	135 5 5/16	110 4 21/64	77.8 3 1/16	11 7/16	14 35/64	8 5/16	26 1 1/32	34 1 11/32	90 3.5433	44.4 1 3/4	42.9 1.6890	17.5 0.689	M12 7/16
40 1 1/2 1 9/16	<b>UCFC208D1</b> <b>UCFC208-108D1</b> <b>UCFC208-109D1</b>	145 5 23/32	120 4 23/32	84.9 3 11/32	11 7/16	14 35/64	10 25/64	26 1 1/32	36 1 27/64	100 3.9370	51.2 2 1/64	49.2 1.9370	19 0.748	M12 7/16
45 1 5/8 1 11/16 1 3/4	<b>UCFC209D1</b> <b>UCFC209-110D1</b> <b>UCFC209-111D1</b> <b>UCFC209-112D1</b>	160 6 5/16	132 5 13/64	93.3 3 43/64	10 25/64	16 5/8	12 15/32	26 1 1/32	38 1 1/2	105 4.1339	52.2 2 3/64	49.2 1.9370	19 0.748	M14 1/2

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.



Pressed steel dust cover type  
Open end **Z-UCFC...D1**  
Closed end **ZM-UCFC...D1**

Cast dust cover type  
Open end **C-UCFC...D1**  
Closed end **CM-UCFC...D1**

Bearing number	Housing number	Unit number (1) pressed steel dust cover type	Unit number (1) cast dust cover type	Nominal dimensions					Mass of unit		
				mm inch					kg lb		
				t max.	A <sub>4</sub>	A <sub>1C</sub>	A <sub>5</sub>	UCFC	Z(ZM)	C(CM)	
UC201D1	FC204D1	<b>Z(ZM)-UCFC201D1</b>	<b>C(CM)-UCFC201D1</b>	2 5/64	38 1 1/2	20.5 13/16	46 1 13/16	0.8 1.8	0.8 1.8	0.9 2.0	
UC201-008D1	FC204D1	<b>Z(ZM)-UCFC201-008D1</b>	<b>C(CM)-UCFC201-008D1</b>	2 5/64	38 1 1/2	20.5 13/16	46 1 13/16	0.8 1.8	0.8 1.8	0.9 2.0	
UC202D1	FC204D1	<b>Z(ZM)-UCFC202D1</b>	<b>C(CM)-UCFC202D1</b>	2 5/64	38 1 1/2	20.5 13/16	46 1 13/16	0.8 1.8	0.8 1.8	0.9 2.0	
UC202-009D1	FC204D1	<b>Z(ZM)-UCFC202-009D1</b>	<b>C(CM)-UCFC202-009D1</b>	2 5/64	38 1 1/2	20.5 13/16	46 1 13/16	0.8 1.8	0.8 1.8	0.9 2.0	
UC202-010D1	FC204D1	<b>Z(ZM)-UCFC202-010D1</b>	<b>C(CM)-UCFC202-010D1</b>	2 5/64	38 1 1/2	20.5 13/16	46 1 13/16	0.8 1.8	0.8 1.8	0.9 2.0	
UC203D1	FC204D1	<b>Z(ZM)-UCFC203D1</b>	<b>C(CM)-UCFC203D1</b>	2 5/64	38 1 1/2	20.5 13/16	46 1 13/16	0.8 1.8	0.8 1.8	0.9 2.0	
UC203-011D1	FC204D1	<b>Z(ZM)-UCFC203-011D1</b>	<b>C(CM)-UCFC203-011D1</b>	2 5/64	38 1 1/2	20.5 13/16	46 1 13/16	0.8 1.8	0.8 1.8	0.9 2.0	
UC204D1	FC204D1	<b>Z(ZM)-UCFC204D1</b>	<b>C(CM)-UCFC204D1</b>	2 5/64	38 1 1/2	20.5 13/16	46 1 13/16	0.7 1.5	0.7 1.5	0.9 2.0	
UC204-012D1	FC204D1	<b>Z(ZM)-UCFC204-012D1</b>	<b>C(CM)-UCFC204-012D1</b>	2 5/64	38 1 1/2	20.5 13/16	46 1 13/16	0.7 1.5	0.7 1.5	0.9 2.0	
UC205D1	FC205D1	<b>Z(ZM)-UCFC205D1</b>	<b>C(CM)-UCFC205D1</b>	2 5/64	40 1 19/32	22 7/8	51 2	1.0 2.2	1.0 2.2	1.2 2.6	
UC205-013D1	FC205D1	<b>Z(ZM)-UCFC205-013D1</b>	<b>C(CM)-UCFC205-013D1</b>	2 5/64	40 1 19/32	22 7/8	51 2	1.0 2.2	1.0 2.2	1.2 2.6	
UC205-014D1	FC205D1	<b>Z(ZM)-UCFC205-014D1</b>	<b>C(CM)-UCFC205-014D1</b>	2 5/64	40 1 19/32	22 7/8	51 2	1.0 2.2	1.0 2.2	1.2 2.6	
UC205-015D1	FC205D1	<b>Z(ZM)-UCFC205-015D1</b>	<b>C(CM)-UCFC205-015D1</b>	2 5/64	40 1 19/32	22 7/8	51 2	1.0 2.2	1.0 2.2	1.2 2.6	
UC205-100D1	FC205D1	<b>Z(ZM)-UCFC205-100D1</b>	<b>C(CM)-UCFC205-100D1</b>	2 5/64	40 1 19/32	22 7/8	51 2	1.0 2.2	1.0 2.2	1.2 2.6	
UC206D1	FC206D1	<b>Z(ZM)-UCFC206D1</b>	<b>C(CM)-UCFC206D1</b>	2 5/64	45 1 3/4	24.5 31/32	56 2 13/64	1.3 2.9	1.4 3.1	1.6 3.5	
UC206-101D1	FC206D1	<b>Z(ZM)-UCFC206-101D1</b>	<b>C(CM)-UCFC206-101D1</b>	2 5/64	45 1 3/4	24.5 31/32	56 2 13/64	1.3 2.9	1.4 3.1	1.6 3.5	
UC206-102D1	FC206D1	<b>Z(ZM)-UCFC206-102D1</b>	<b>C(CM)-UCFC206-102D1</b>	2 5/64	45 1 3/4	24.5 31/32	56 2 13/64	1.3 2.9	1.4 3.1	1.6 3.5	
UC206-103D1	FC206D1	<b>Z(ZM)-UCFC206-103D1</b>	<b>C(CM)-UCFC206-103D1</b>	2 5/64	45 1 3/4	24.5 31/32	56 2 13/64	1.3 2.9	1.4 3.1	1.6 3.5	
UC206-104D1	FC206D1	—	<b>C(CM)-UCFC206-104D1</b>	2 5/64	45 1 3/4	24.5 31/32	56 2 13/64	1.3 2.9	1.4 3.1	1.6 3.5	
UC207D1	FC207D1	<b>Z(ZM)-UCFC207D1</b>	<b>C(CM)-UCFC207D1</b>	3 1/8	49 1 15/16	26 1 1/32	59 2 21/64	1.6 3.5	1.7 3.7	1.9 4.2	
UC207-104D1	FC207D1	<b>Z(ZM)-UCFC207-104D1</b>	<b>C(CM)-UCFC207-104D1</b>	3 1/8	49 1 15/16	26 1 1/32	59 2 21/64	1.6 3.5	1.7 3.7	1.9 4.2	
UC207-105D1	FC207D1	<b>Z(ZM)-UCFC207-105D1</b>	<b>C(CM)-UCFC207-105D1</b>	3 1/8	49 1 15/16	26 1 1/32	59 2 21/64	1.6 3.5	1.7 3.7	1.9 4.2	
UC207-106D1	FC207D1	<b>Z(ZM)-UCFC207-106D1</b>	<b>C(CM)-UCFC207-106D1</b>	3 1/8	49 1 15/16	26 1 1/32	59 2 21/64	1.6 3.5	1.7 3.7	1.9 4.2	
UC207-107D1	FC207D1	—	<b>C(CM)-UCFC207-107D1</b>	3 1/8	49 1 15/16	26 1 1/32	59 2 21/64	1.6 3.5	1.7 3.7	1.9 4.2	
UC208D1	FC208D1	<b>Z(ZM)-UCFC208D1</b>	<b>C(CM)-UCFC208D1</b>	3 1/8	56 2 3/16	27.5 1 5/64	66 2 19/32	2.0 4.4	2.1 4.6	2.4 5.3	
UC208-108D1	FC208D1	<b>Z(ZM)-UCFC208-108D1</b>	<b>C(CM)-UCFC208-108D1</b>	3 1/8	56 2 3/16	27.5 1 5/64	66 2 19/32	2.0 4.4	2.1 4.6	2.4 5.3	
UC208-109D1	FC208D1	<b>Z(ZM)-UCFC208-109D1</b>	<b>C(CM)-UCFC208-109D1</b>	3 1/8	56 2 3/16	27.5 1 5/64	66 2 19/32	2.0 4.4	2.1 4.6	2.4 5.3	
UC209D1	FC209D1	<b>Z(ZM)-UCFC209D1</b>	<b>C(CM)-UCFC209D1</b>	3 1/8	57 2 1/4	28 1 7/64	70 2 3/4	2.7 6.0	2.7 6.0	3.2 7.1	
UC209-110D1	FC209D1	<b>Z(ZM)-UCFC209-110D1</b>	<b>C(CM)-UCFC209-110D1</b>	3 1/8	57 2 1/4	28 1 7/64	70 2 3/4	2.7 6.0	2.7 6.0	3.2 7.1	
UC209-111D1	FC209D1	<b>Z(ZM)-UCFC209-111D1</b>	<b>C(CM)-UCFC209-111D1</b>	3 1/8	57 2 1/4	28 1 7/64	70 2 3/4	2.7 6.0	2.7 6.0	3.2 7.1	
UC209-112D1	FC209D1	<b>Z(ZM)-UCFC209-112D1</b>	<b>C(CM)-UCFC209-112D1</b>	3 1/8	57 2 1/4	28 1 7/64	70 2 3/4	2.7 6.0	2.7 6.0	3.2 7.1	



## Round flanged unit, cast housing with spigot joint Set screw type



Pressed steel dust cover type  
Open end **Z-UCFC...D1**  
Closed end **ZM-UCFC...D1**

Cast dust cover type  
Open end **C-UCFC...D1**  
Closed end **CM-UCFC...D1**


Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch	
		mm inch												
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B		S
50	<b>UCFC210D1</b>	165	138	97.6	10	16	12	28	40	110	54.6	51.6	19	M14
1 <sup>3</sup> / <sub>16</sub>	<b>UCFC210-113D1</b>													
1 <sup>7</sup> / <sub>8</sub>	<b>UCFC210-114D1</b>	6 <sup>1</sup> / <sub>2</sub>	5 <sup>7</sup> / <sub>16</sub>	3 <sup>27</sup> / <sub>32</sub>	2 <sup>5</sup> / <sub>64</sub>	5 <sup>5</sup> / <sub>8</sub>	1 <sup>15</sup> / <sub>32</sub>	1 <sup>9</sup> / <sub>32</sub>	1 <sup>37</sup> / <sub>64</sub>	4.3307	2 <sup>5</sup> / <sub>32</sub>	2.0315	0.748	1/2
1 <sup>15</sup> / <sub>16</sub>	<b>UCFC210-115D1</b>													
2	<b>UCFC210-200D1</b>													
55	<b>UCFC211D1</b>	185	150	106.1	13	19	12	31	43	125	58.4	55.6	22.2	M16
2	<b>UCFC211-200D1</b>													
2 <sup>1</sup> / <sub>16</sub>	<b>UCFC211-201D1</b>	7 <sup>9</sup> / <sub>32</sub>	5 <sup>29</sup> / <sub>32</sub>	4 <sup>11</sup> / <sub>64</sub>	3 <sup>3</sup> / <sub>64</sub>	3 <sup>3</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>32</sub>	1 <sup>7</sup> / <sub>32</sub>	1 <sup>11</sup> / <sub>16</sub>	4.9213	2 <sup>19</sup> / <sub>64</sub>	2.1890	0.874	5/8
2 <sup>1</sup> / <sub>8</sub>	<b>UCFC211-202D1</b>													
2 <sup>3</sup> / <sub>16</sub>	<b>UCFC211-203D1</b>													
60	<b>UCFC212D1</b>	195	160	113.1	17	19	12	36	48	135	68.7	65.1	25.4	M16
2 <sup>1</sup> / <sub>4</sub>	<b>UCFC212-204D1</b>													
2 <sup>5</sup> / <sub>16</sub>	<b>UCFC212-205D1</b>	7 <sup>11</sup> / <sub>16</sub>	6 <sup>19</sup> / <sub>64</sub>	4 <sup>29</sup> / <sub>64</sub>	4 <sup>3</sup> / <sub>64</sub>	3 <sup>3</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>32</sub>	1 <sup>13</sup> / <sub>32</sub>	1 <sup>57</sup> / <sub>64</sub>	5.3150	2 <sup>45</sup> / <sub>64</sub>	2.5630	1.000	5/8
2 <sup>3</sup> / <sub>8</sub>	<b>UCFC212-206D1</b>													
2 <sup>7</sup> / <sub>16</sub>	<b>UCFC212-207D1</b>													
65	<b>UCFC213D1</b>	205	170	120.2	16	19	14	36	50	145	69.7	65.1	25.4	M16
2 <sup>1</sup> / <sub>2</sub>	<b>UCFC213-208D1</b>	8 <sup>1</sup> / <sub>16</sub>	6 <sup>11</sup> / <sub>16</sub>	4 <sup>47</sup> / <sub>64</sub>	5 <sup>8</sup> / <sub>8</sub>	3 <sup>3</sup> / <sub>4</sub>	3 <sup>5</sup> / <sub>64</sub>	1 <sup>13</sup> / <sub>32</sub>	1 <sup>31</sup> / <sub>32</sub>	5.7087	2 <sup>3</sup> / <sub>4</sub>	2.5630	1.000	5/8
2 <sup>9</sup> / <sub>16</sub>	<b>UCFC213-209D1</b>													
70	<b>UCFC214D1</b>	215	177	125.2	17	19	14	40	54	150	75.4	74.6	30.2	M16
2 <sup>5</sup> / <sub>8</sub>	<b>UCFC214-210D1</b>													
2 <sup>1</sup> / <sub>16</sub>	<b>UCFC214-211D1</b>	8 <sup>15</sup> / <sub>32</sub>	6 <sup>31</sup> / <sub>32</sub>	4 <sup>59</sup> / <sub>64</sub>	4 <sup>3</sup> / <sub>64</sub>	3 <sup>3</sup> / <sub>4</sub>	3 <sup>5</sup> / <sub>64</sub>	1 <sup>37</sup> / <sub>64</sub>	2 <sup>1</sup> / <sub>8</sub>	5.9055	2 <sup>31</sup> / <sub>32</sub>	2.9370	1.189	5/8
2 <sup>3</sup> / <sub>4</sub>	<b>UCFC214-212D1</b>													
75	<b>UCFC215D1</b>	220	184	130.1	18	19	16	40	56	160	78.5	77.8	33.3	M16
2 <sup>3</sup> / <sub>16</sub>	<b>UCFC215-213D1</b>													
2 <sup>7</sup> / <sub>8</sub>	<b>UCFC215-214D1</b>	8 <sup>21</sup> / <sub>32</sub>	7 <sup>1</sup> / <sub>4</sub>	5 <sup>1</sup> / <sub>8</sub>	4 <sup>5</sup> / <sub>64</sub>	3 <sup>3</sup> / <sub>4</sub>	5 <sup>5</sup> / <sub>8</sub>	1 <sup>37</sup> / <sub>64</sub>	2 <sup>13</sup> / <sub>64</sub>	6.2992	3 <sup>3</sup> / <sub>32</sub>	3.0630	1.311	5/8
2 <sup>9</sup> / <sub>16</sub>	<b>UCFC215-215D1</b>													
3	<b>UCFC215-300D1</b>													
80	<b>UCFC216D1</b>	240	200	141.4	18	23	16	42	58	170	83.3	82.6	33.3	M20
3 <sup>1</sup> / <sub>16</sub>	<b>UCFC216-301D1</b>													
3 <sup>3</sup> / <sub>8</sub>	<b>UCFC216-302D1</b>	9 <sup>7</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>8</sub>	5 <sup>9</sup> / <sub>16</sub>	4 <sup>5</sup> / <sub>64</sub>	2 <sup>9</sup> / <sub>32</sub>	5 <sup>5</sup> / <sub>8</sub>	1 <sup>21</sup> / <sub>32</sub>	2 <sup>9</sup> / <sub>32</sub>	6.6929	3 <sup>9</sup> / <sub>32</sub>	3.2520	1.311	3/4
3 <sup>3</sup> / <sub>16</sub>	<b>UCFC216-303D1</b>													

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) pressed steel dust cover type	Unit number (1) cast dust cover type	Nominal dimensions				Mass of unit		
				mm inch				kg lb		
				t max.	A <sub>4</sub>	A <sub>1C</sub>	A <sub>5</sub>	UCFC	Z(ZM)	C(CM)
UC210D1	FC210D1	<b>Z(ZM)-UCFC210D1</b>	<b>C(CM)-UCFC210D1</b>	3	60	29	72	3.0	3.1	3.6
UC210-113D1	FC210D1	<b>Z(ZM)-UCFC210-113D1</b>	<b>C(CM)-UCFC210-113D1</b>							
UC210-114D1	FC210D1	<b>Z(ZM)-UCFC210-114D1</b>	<b>C(CM)-UCFC210-114D1</b>	1/8	2 <sup>3</sup> / <sub>8</sub>	1 <sup>5</sup> / <sub>32</sub>	2 <sup>59</sup> / <sub>64</sub>	6.6	6.8	7.9
UC210-115D1	FC210D1	<b>Z(ZM)-UCFC210-115D1</b>	<b>C(CM)-UCFC210-115D1</b>							
UC210-200D1	FC210D1	—	<b>C(CM)-UCFC210-200D1</b>							
UC211D1	FC211D1	<b>Z(ZM)-UCFC211D1</b>	<b>C(CM)-UCFC211D1</b>	4	64	32.5	75	4.1	4.2	4.8
UC211-200D1	FC211D1	<b>Z(ZM)-UCFC211-200D1</b>	<b>C(CM)-UCFC211-200D1</b>							
UC211-201D1	FC211D1	<b>Z(ZM)-UCFC211-201D1</b>	<b>C(CM)-UCFC211-201D1</b>	5/32	2 <sup>1</sup> / <sub>2</sub>	1 <sup>9</sup> / <sub>32</sub>	2 <sup>61</sup> / <sub>64</sub>	9.0	9.3	11
UC211-202D1	FC211D1	<b>Z(ZM)-UCFC211-202D1</b>	<b>C(CM)-UCFC211-202D1</b>							
UC211-203D1	FC211D1	<b>Z(ZM)-UCFC211-203D1</b>	<b>C(CM)-UCFC211-203D1</b>							
UC212D1	FC212D1	<b>Z(ZM)-UCFC212D1</b>	<b>C(CM)-UCFC212D1</b>	4	74	38	86	4.9	5.1	5.9
UC212-204D1	FC212D1	<b>Z(ZM)-UCFC212-204D1</b>	<b>C(CM)-UCFC212-204D1</b>							
UC212-205D1	FC212D1	<b>Z(ZM)-UCFC212-205D1</b>	<b>C(CM)-UCFC212-205D1</b>	5/32	2 <sup>29</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>2</sub>	3 <sup>25</sup> / <sub>64</sub>	11	11	13
UC212-206D1	FC212D1	<b>Z(ZM)-UCFC212-206D1</b>	<b>C(CM)-UCFC212-206D1</b>							
UC212-207D1	FC212D1	—	<b>C(CM)-UCFC212-207D1</b>							
UC213D1	FC213D1	<b>Z(ZM)-UCFC213D1</b>	<b>C(CM)-UCFC213D1</b>	4	76	38	89.5	5.8	6.0	6.8
UC213-208D1	FC213D1	<b>Z(ZM)-UCFC213-208D1</b>	<b>C(CM)-UCFC213-208D1</b>	5/32	3	1 <sup>1</sup> / <sub>2</sub>	3 <sup>17</sup> / <sub>32</sub>	13	13	15
UC213-209D1	FC213D1	<b>Z(ZM)-UCFC213-209D1</b>	<b>C(CM)-UCFC213-209D1</b>							
UC214D1	FC214D1	—	<b>C(CM)-UCFC214D1</b>	4	—	39.5	98	7.0	—	8.0
UC214-210D1	FC214D1	—	<b>C(CM)-UCFC214-210D1</b>							
UC214-211D1	FC214D1	—	<b>C(CM)-UCFC214-211D1</b>	5/32	—	1 <sup>9</sup> / <sub>16</sub>	3 <sup>55</sup> / <sub>64</sub>	15	—	18
UC214-212D1	FC214D1	—	<b>C(CM)-UCFC214-212D1</b>							
UC215D1	FC215D1	—	<b>C(CM)-UCFC215D1</b>	4	—	43	102	7.4	—	8.8
UC215-213D1	FC215D1	—	<b>C(CM)-UCFC215-213D1</b>							
UC215-214D1	FC215D1	—	<b>C(CM)-UCFC215-214D1</b>	5/32	—	1 <sup>11</sup> / <sub>16</sub>	4 <sup>1</sup> / <sub>64</sub>	16	—	19
UC215-215D1	FC215D1	—	<b>C(CM)-UCFC215-215D1</b>							
UC215-300D1	FC215D1	—	<b>C(CM)-UCFC215-300D1</b>							
UC216D1	FC216D1	—	<b>C(CM)-UCFC216D1</b>	4	—	43	106	9.1	—	10
UC216-301D1	FC216D1	—	<b>C(CM)-UCFC216-301D1</b>							
UC216-302D1	FC216D1	—	<b>C(CM)-UCFC216-302D1</b>	5/32	—	1 <sup>11</sup> / <sub>16</sub>	4 <sup>1</sup> / <sub>64</sub>	20	—	22
UC216-303D1	FC216D1	—	<b>C(CM)-UCFC216-303D1</b>							


# UCFC2

Round flanged unit, cast housing with spigot joint  
Set screw type



Shaft dia. mm inch	Unit number <sup>(1)</sup>	Nominal dimensions												Bolt size mm inch
		mm inch												
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B	S	
85 3 3/4	UCFC217D1 UCFC217-304D1	250	208	147.1	18	23	18	45	63	180	87.6	85.7	34.1	M20
3 5/16 3 7/16	UCFC217-305D1 UCFC217-307D1	9 27/32	8 3/16	5 51/64	45/64	29/32	45/64	1 25/32	2 31/64	7.0866	3 29/64	3.3740	1.343	3/4
90 3 1/2	UCFC218D1 UCFC218-308D1	265	220	155.6	22	23	18	50	68	190	96.3	96	39.7	M20
		10 7/16	8 21/32	6 1/8	55/64	29/32	45/64	1 31/32	2 43/64	7.4803	3 51/64	3.7795	1.563	3/4

Note <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.



Pressed steel dust cover type  
Open end Z-UCFC...D1  
Closed end ZM-UCFC...D1

Cast dust cover type  
Open end C-UCFC...D1  
Closed end CM-UCFC...D1

Bearing number	Housing number	Unit number <sup>(1)</sup> pressed steel dust cover type	Unit number <sup>(1)</sup> cast dust cover type	Nominal dimensions				Mass of unit		
				mm inch				kg lb		
				t max.	A <sub>4</sub>	A <sub>1C</sub>	A <sub>5</sub>	UCFC	Z(ZM)	C(CM)
UC217D1	FC217D1	—	C(CM)-UCFC217D1	5	—	45.5	114	11	—	12
UC217-304D1	FC217D1	—	C(CM)-UCFC217-304D1	13/64	—	1 51/64	4 31/64	24	—	26
UC217-305D1	FC217D1	—	C(CM)-UCFC217-305D1	—	—	—	—	—	—	—
UC217-307D1	FC217D1	—	C(CM)-UCFC217-307D1	—	—	—	—	—	—	—
UC218D1	FC218D1	—	C(CM)-UCFC218D1	5	—	50	122	13	—	15
UC218-308D1	FC218D1	—	C(CM)-UCFC218-308D1	13/64	—	1 31/32	4 51/64	29	—	33

## Round flanged unit, cast housing with spigot joint Set screw type




Shaft dia. mm inch	Unit number <sup>(1)</sup>	Nominal dimensions												Bolt size mm inch
		mm inch												
		<i>L</i>	<i>J</i>	<i>(J<sub>1</sub>)</i>	<i>A<sub>2</sub></i>	<i>N</i>	<i>A<sub>3</sub></i>	<i>A<sub>1</sub></i>	<i>A</i>	<i>H<sub>3</sub></i>	<i>A<sub>0</sub></i>	<i>B</i>	<i>S</i>	
25 1 3/16 7/8 15/16 1	UCFCX05D1 UCFCX05-013D1 UCFCX05-014D1 UCFCX05-015D1 UCFCX05-100D1	111 4 3/8	92 3 5/8	65.1 2 9/16	10 25/64	9.5 3/8	6 1/4	24 1 5/16	30 1 3/16	76 2.9921	38.2 1 1/2	38.1 1.5000	15.9 0.626	M8 5/16
30 1 1/16 1 1/8 1 3/16 1 1/4	UCFCX06D1 UCFCX06-101D1 UCFCX06-102D1 UCFCX06-103D1 UCFCX06-104D1	127 5	105 4 9/64	74.2 2 59/64	8 5/16	12 15/32	9.5 3/8	22.5 7/8	32 1 27/64	85 3.3465	42.9 1 11/16	42.9 1.6890	17.5 0.689	M10 3/8
35 1 5/16 1 3/8 1 7/16	UCFCX07D1 UCFCX07-105D1 UCFCX07-106D1 UCFCX07-107D1	133 5 1/4	111 4 3/8	78.5 3 3/32	9 23/64	12 15/32	11 7/16	26 1 1/32	37 1 29/64	92 3.6220	50.2 1 31/32	49.2 1.9370	19 0.748	M10 3/8
40 1 1/2 1 9/16	UCFCX08D1 UCFCX08-108D1 UCFCX08-109D1	133 5 1/4	111 4 3/8	78.5 3 3/32	9 23/64	12 15/32	11 7/16	26 1 1/32	37 1 29/64	92 3.6220	50.2 1 31/32	49.2 1.9370	19 0.748	M10 3/8
45 1 5/8 1 11/16 1 3/4 1 13/16	UCFCX09D1 UCFCX09-110D1 UCFCX09-111D1 UCFCX09-112D1 UCFCX09-113D1	155 6 3/32	130 5 1/6	91.9 3 3/8	8 5/16	14 35/64	12 15/32	25 31/32	37 1 29/64	108 4.2520	52.6 2 5/64	51.6 2.0315	19 0.748	M12 7/16
50 1 7/8 1 15/16 2	UCFCX10D1 UCFCX10-114D1 UCFCX10-115D1 UCFCX10-200D1	162 6 3/8	136 5 23/64	96.2 3 25/32	7 9/32	14 35/64	16 5/8	25 31/32	41 1 39/64	118 4.6457	56.4 2 7/32	55.6 2.1890	22.2 0.874	M12 7/16

Note <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number <sup>(1)</sup>	Mass of unit kg lb
UCX05D1	FCX05D1	1.2
UCX05-013D1	FCX05D1	2.6
UCX05-014D1	FCX05D1	
UCX05-015D1	FCX05D1	
UCX05-100D1	FCX05D1	1.7
UCX06D1	FCX06D1	
UCX06-101D1	FCX06D1	
UCX06-102D1	FCX06D1	
UCX06-103D1	FCX06D1	
UC207-104D1	FCX06D1	3.7
UCX07D1	FCX07D1	
UCX07-105D1	FCX07D1	
UCX07-106D1	FCX07D1	4.2
UCX07-107D1	FCX07D1	
UCX08D1	FCX08D1	2.0
UCX08-108D1	FCX08D1	
UCX08-109D1	FCX08D1	4.4
UCX09D1	FCX09D1	
UCX09-110D1	FCX09D1	2.6
UCX09-111D1	FCX09D1	
UCX09-112D1	FCX09D1	
UC210-113D1	FCX09D1	5.7
UCX10D1	FCX10D1	
UCX10-114D1	FCX10D1	3.1
UCX10-115D1	FCX10D1	
UC211-200D1	FCX10D1	
		6.8

## Round flanged unit, cast housing with spigot joint Set screw type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions												Bolt size mm inch
		mm inch												
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B	S	
55 2 1/16 2 1/8	<b>UCFCX11D1</b> <b>UCFCX11-201D1</b> <b>UCFCX11-202D1</b>	180	152	107.5	4	16	22	26	48	127	65.7	65.1	25.4	M14
2 3/16 2 1/4 2 5/16	<b>UCFCX11-203D1</b> <b>UCFCX11-204D1</b> <b>UCFCX11-205D1</b>	7 3/32	5 53/64	4 15/64	5/32	5/8	55/64	1 1/32	1 57/64	5.0000	2 19/32	2.5630	1.000	1/2
60 2 3/8 2 7/16	<b>UCFCX12D1</b> <b>UCFCX12-206D1</b> <b>UCFCX12-207D1</b>	194	165	116.7	11	16	20	33	53	140	70.7	65.1	25.4	M14
		7 5/8	6 1/2	4 19/32	7/16	5/8	25/32	1 5/16	2 5/64	5.5118	2 25/32	2.5630	1.000	1/2
65 2 1/2 2 9/16	<b>UCFCX13D1</b> <b>UCFCX13-208D1</b> <b>UCFCX13-209D1</b>	194	165	116.7	11	16	20	33	53	140	75.4	74.6	30.2	M14
		7 5/8	6 1/2	4 19/32	7/16	5/8	25/32	1 5/16	2 5/64	5.5118	2 31/32	2.9370	1.189	1/2
70 2 5/8 2 11/16 2 3/4	<b>UCFCX14D1</b> <b>UCFCX14-210D1</b> <b>UCFCX14-211D1</b> <b>UCFCX14-212D1</b>	222	190	134.4	14	19	20	36	56	164	78.5	77.8	33.3	M16
		8 3/4	7 31/64	5 9/32	35/64	3/4	25/32	1 13/32	2 13/64	6.4567	3 3/32	3.0630	1.311	5/8
75 2 13/16 2 7/8 2 15/16 3	<b>UCFCX15D1</b> <b>UCFCX15-213D1</b> <b>UCFCX15-214D1</b> <b>UCFCX15-215D1</b> <b>UCFCX15-300D1</b>	222	190	134.4	12	19	22	35	57	164	83.3	82.6	33.3	M16
		8 3/4	7 31/64	5 9/32	15/32	3/4	55/64	1 3/8	2 1/4	6.4567	3 9/32	3.2520	1.311	5/8
80 3 1/16 3 1/8 3 3/16 3 1/4	<b>UCFCX16D1</b> <b>UCFCX16-301D1</b> <b>UCFCX16-302D1</b> <b>UCFCX16-303D1</b> <b>UCFCX16-304D1</b>	260	219	154.9	10	23	25	36	61	186	86.6	85.7	34.1	M20
		10 1/4	8 5/8	6 3/32	25/64	29/32	63/64	1 13/32	2 13/32	7.3228	3 13/32	3.3740	1.343	3/4
85 3 5/16 3 7/16	<b>UCFCX17D1</b> <b>UCFCX17-305D1</b> <b>UCFCX17-307D1</b>	260	219	154.9	10	23	25	36	61	186	91.3	96	39.7	M20
		10 1/4	8 5/8	6 3/32	25/64	29/32	63/64	1 13/32	2 13/32	7.3228	3 19/32	3.7795	1.563	3/4

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing (1)	Mass of unit kg lb
UCX11D1	FCX11D1	4.2
UCX11-201D1	FCX11D1	
UCX11-202D1	FCX11D1	
UCX11-203D1	FCX11D1	9.3
UC212-204D1	FCX11D1	
UC212-205D1	FCX11D1	
UCX12D1	FCX12D1	5.5
UCX12-206D1	FCX12D1	
UCX12-207D1	FCX12D1	12
UCX13D1	FCX13D1	5.7
UCX13-208D1	FCX13D1	
UCX13-209D1	FCX13D1	13
UCX14D1	FCX14D1	7.3
UCX14-210D1	FCX14D1	
UCX14-211D1	FCX14D1	16
UCX14-212D1	FCX14D1	
UCX15D1	FCX15D1	8.0
UCX15-213D1	FCX15D1	
UCX15-214D1	FCX15D1	
UCX15-215D1	FCX15D1	18
UCX15-300D1	FCX15D1	
UCX16D1	FCX16D1	12
UCX16-301D1	FCX16D1	
UCX16-302D1	FCX16D1	
UCX16-303D1	FCX16D1	26
UC217-304D1	FCX16D1	
UCX17D1	FCX17D1	12
UCX17-305D1	FCX17D1	
UCX17-307D1	FCX17D1	26

## Round flanged unit, cast housing with spigot joint Set screw type



Shaft dia.  mm inch	Unit number <sup>(1)</sup>	Nominal dimensions												Bolt size  mm inch
		mm inch												
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B	S	
90 3 <sup>7</sup> / <sub>16</sub> 3 <sup>1</sup> / <sub>2</sub>	<b>UCFCX18D1</b> <b>UCFCX18-307D1</b> <b>UCFCX18-308D1</b>	260 10 <sup>1</sup> / <sub>4</sub>	219 8 <sup>5</sup> / <sub>8</sub>	154.9 6 <sup>3</sup> / <sub>32</sub>	12 15 <sub>32</sub>	23 29 <sub>32</sub>	28 1 <sup>7</sup> / <sub>64</sub>	43 1 <sup>11</sup> / <sub>16</sub>	71 2 <sup>51</sup> / <sub>64</sub>	186 7.3228	101.1 3 <sup>63</sup> / <sub>64</sub>	104 4.0945	42.9 1.689	M20 3/4
100 3 <sup>13</sup> / <sub>16</sub> 3 <sup>7</sup> / <sub>8</sub> 3 <sup>15</sup> / <sub>16</sub> 4	<b>UCFCX20D1</b> <b>UCFCX20-313D1</b> <b>UCFCX20-314D1</b> <b>UCFCX20-315D1</b> <b>UCFCX20-400D1</b>	276 10 <sup>7</sup> / <sub>8</sub>	238 9 <sup>3</sup> / <sub>8</sub>	168.3 6 <sup>5</sup> / <sub>8</sub>	22 55 <sub>64</sub>	23 29 <sub>32</sub>	28 1 <sup>7</sup> / <sub>64</sub>	66 2 <sup>19</sup> / <sub>32</sub>	94 3 <sup>45</sup> / <sub>64</sub>	206 8.1102	118.3 4 <sup>21</sup> / <sub>32</sub>	117.5 4.6260	49.2 1.937	M20 3/4

Note <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing <sup>(1)</sup> number	Mass of unit  kg lb
UCX18D1	FCX18D1	12
UCX18-307D1	FCX18D1	26
UCX18-308D1	FCX18D1	
UCX20D1	FCX20D1	18
UCX20-313D1	FCX20D1	
UCX20-314D1	FCX20D1	40
UCX20-315D1	FCX20D1	
UCX20-400D1	FCX20D1	

## Rhombus flanged unit, cast housing Set screw type




Pressed steel dust cover type  
Open end **Z-UCFL...D1**  
Closed end **ZM-UCFL...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch	Bearing number
		mm inch											
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B	S		
12 1/2	UCFL201D1	113	90	15	11	25.5	12	60	33.3	31	12.7	M10	UC201D1
	UCFL201-008D1	4 7/16	3 35/64	19/32	7/16	1	15/32	2 3/8	1 5/16	1.2205	0.500	3/8	UC201-008D1
15 9/16 5/8	UCFL202D1	113	90	15	11	25.5	12	60	33.3	31	12.7	M10	UC202D1
	UCFL202-009D1	4 7/16	3 35/64	19/32	7/16	1	15/32	2 3/8	1 5/16	1.2205	0.500	3/8	UC202-009D1
	UCFL202-010D1	4 7/16	3 35/64	19/32	7/16	1	15/32	2 3/8	1 5/16	1.2205	0.500	3/8	UC202-010D1
17 1 1/16	UCFL203D1	113	90	15	11	25.5	12	60	33.3	31	12.7	M10	UC203D1
	UCFL203-011D1	4 7/16	3 35/64	19/32	7/16	1	15/32	2 3/8	1 5/16	1.2205	0.500	3/8	UC203-011D1
20 3/4	UCFL204D1	113	90	15	11	25.5	12	60	33.3	31	12.7	M10	UC204D1
	UCFL204-012D1	4 7/16	3 35/64	19/32	7/16	1	15/32	2 3/8	1 5/16	1.2205	0.500	3/8	UC204-012D1
25 1 9/16 7/8 1 5/16	UCFL205D1	130	99	16	13	27	16	68	35.8	34.1	14.3	M14	UC205D1
	UCFL205-013D1												UC205-013D1
	UCFL205-014D1	5 1/8	3 57/64	5/8	1/2	1 1/16	5/8	2 11/16	1 13/32	1.3425	0.563	1/2	UC205-014D1
	UCFL205-015D1												UC205-015D1
1	UCFL205-100D1												UC205-100D1
30 1 1/16 1 1/8 1 3/16 1 1/4	UCFL206D1	148	117	18	13	31	16	80	40.2	38.1	15.9	M14	UC206D1
	UCFL206-101D1												UC206-101D1
	UCFL206-102D1	5 13/16	4 39/64	45/64	1/2	1 7/32	5/8	3 5/32	1 37/64	1.5000	0.626	1/2	UC206-102D1
	UCFL206-103D1												UC206-103D1
	UCFL206-104D1												UC206-104D1
35 1 1/4 1 5/16 1 3/8 1 7/16	UCFL207D1	161	130	19	15	34	16	90	44.4	42.9	17.5	M14	UC207D1
	UCFL207-104D1												UC207-104D1
	UCFL207-105D1	6 11/32	5 1/8	3/4	19/32	1 11/32	5/8	3 17/32	1 3/4	1.6890	0.689	1/2	UC207-105D1
	UCFL207-106D1												UC207-106D1
	UCFL207-107D1												UC207-107D1
40 1 1/2 1 9/16	UCFL208D1	175	144	21	15	36	16	100	51.2	49.2	19	M14	UC208D1
	UCFL208-108D1	6 7/8	5 43/64	53/64	19/32	1 13/32	5/8	3 15/16	2 1/64	1.9370	0.748	1/2	UC208-108D1
	UCFL208-109D1												UC208-109D1

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type  
Open end **C-UCFL...D1**  
Closed end **CM-UCFL...D1**

Housing number	Unit number (1) pressed steel dust cover type	Unit number (1) cast dust cover type	Nominal dimensions					Mass of unit		
			mm inch					kg lb		
			t max.	A <sub>4</sub>	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UCFL	Z(ZM)	C(CM)
FL204D1	Z(ZM)-UCFL201D1	C(CM)-UCFL201D1	2	38	46	67	30	0.5	0.5	0.6
FL204D1	Z(ZM)-UCFL201-008D1	C(CM)-UCFL201-008D1	5/64	1 1/2	1 13/16	2 5/8	1 3/16	1.1	1.1	1.3
FL204D1	Z(ZM)-UCFL202D1	C(CM)-UCFL202D1	2	38	46	67	30	0.5	0.5	0.6
FL204D1	Z(ZM)-UCFL202-009D1	C(CM)-UCFL202-009D1	5/64	1 1/2	1 13/16	2 5/8	1 3/16	1.1	1.1	1.3
FL204D1	Z(ZM)-UCFL202-010D1	C(CM)-UCFL202-010D1	5/64	1 1/2	1 13/16	2 5/8	1 3/16	1.1	1.1	1.3
FL204D1	Z(ZM)-UCFL203D1	C(CM)-UCFL203D1	2	38	46	67	30	0.5	0.5	0.6
FL204D1	Z(ZM)-UCFL203-011D1	C(CM)-UCFL203-011D1	5/64	1 1/2	1 13/16	2 5/8	1 3/16	1.1	1.1	1.3
FL204D1	Z(ZM)-UCFL204D1	C(CM)-UCFL204D1	2	38	46	67	30	0.4	0.4	0.6
FL204D1	Z(ZM)-UCFL204-012D1	C(CM)-UCFL204-012D1	5/64	1 1/2	1 13/16	2 5/8	1 3/16	0.9	0.9	1.3
FL205D1	Z(ZM)-UCFL205D1	C(CM)-UCFL205D1	2	40	51	74	34	0.6	0.6	0.8
FL205D1	Z(ZM)-UCFL205-013D1	C(CM)-UCFL205-013D1								
FL205D1	Z(ZM)-UCFL205-014D1	C(CM)-UCFL205-014D1	5/64	1 19/32	2	2 29/32	1 11/32	1.3	1.3	1.8
FL205D1	Z(ZM)-UCFL205-015D1	C(CM)-UCFL205-015D1								
FL205D1	Z(ZM)-UCFL205-100D1	C(CM)-UCFL205-100D1								
FL206D1	Z(ZM)-UCFL206D1	C(CM)-UCFL206D1	2	45	56	85	40	0.9	0.9	1.2
FL206D1	Z(ZM)-UCFL206-101D1	C(CM)-UCFL206-101D1								
FL206D1	Z(ZM)-UCFL206-102D1	C(CM)-UCFL206-102D1	5/64	1 3/4	2 7/32	3 11/32	1 9/16	2.0	2.0	2.6
FL206D1	Z(ZM)-UCFL206-103D1	C(CM)-UCFL206-103D1								
FL206D1	—	C(CM)-UCFL206-104D1								
FL207D1	Z(ZM)-UCFL207D1	C(CM)-UCFL207D1	3	49	59	97	45	1.2	1.2	1.4
FL207D1	Z(ZM)-UCFL207-104D1	C(CM)-UCFL207-104D1								
FL207D1	Z(ZM)-UCFL207-105D1	C(CM)-UCFL207-105D1	1/8	1 15/16	2 5/16	3 13/16	1 25/32	2.6	2.6	3.1
FL207D1	Z(ZM)-UCFL207-106D1	C(CM)-UCFL207-106D1								
FL207D1	—	C(CM)-UCFL207-107D1								
FL208D1	Z(ZM)-UCFL208D1	C(CM)-UCFL208D1	3	56	66	106	50	1.5	1.5	1.9
FL208D1	Z(ZM)-UCFL208-108D1	C(CM)-UCFL208-108D1	1/8	2 3/16	2 19/32	4 3/16	1 31/32	3.3	3.3	4.2
FL208D1	Z(ZM)-UCFL208-109D1	C(CM)-UCFL208-109D1								

## Rhombus flanged unit, cast housing Set screw type



**Pressed steel dust cover type**  
Open end **Z-UCFL...D1**  
Closed end **ZM-UCFL...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch	Bearing number
		mm inch											
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B	S		
45 1 5/8 1 1/16 1 3/4	UCFL209D1 UCFL209-110D1 UCFL209-111D1 UCFL209-112D1	188	148	22	16	38	19	108	52.2	49.2	19	M16	UC209D1 UC209-110D1 UC209-111D1 UC209-112D1
50 1 3/16 1 7/8 1 5/16 2	UCFL210D1 UCFL210-113D1 UCFL210-114D1 UCFL210-115D1 UCFL210-200D1	197	157	22	16	40	19	115	54.6	51.6	19	M16	UC210D1 UC210-113D1 UC210-114D1 UC210-115D1 UC210-200D1
55 2 2 1/16 2 1/8 2 3/16	UCFL211D1 UCFL211-200D1 UCFL211-201D1 UCFL211-202D1 UCFL211-203D1	224	184	25	18	43	19	130	58.4	55.6	22.2	M16	UC211D1 UC211-200D1 UC211-201D1 UC211-202D1 UC211-203D1
60 2 1/4 2 5/16 2 3/8 2 7/16	UCFL212D1 UCFL212-204D1 UCFL212-205D1 UCFL212-206D1 UCFL212-207D1	250	202	29	18	48	23	140	68.7	65.1	25.4	M20	UC212D1 UC212-204D1 UC212-205D1 UC212-206D1 UC212-207D1
65 2 1/2 2 9/16	UCFL213D1 UCFL213-208D1 UCFL213-209D1	258	210	30	22	50	23	155	69.7	65.1	25.4	M20	UC213D1 UC213-208D1 UC213-209D1
70 2 5/8 2 11/16 2 3/4	UCFL214D1 UCFL214-210D1 UCFL214-211D1 UCFL214-212D1	265	216	31	22	54	23	160	75.4	74.6	30.2	M20	UC214D1 UC214-210D1 UC214-211D1 UC214-212D1

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.



**Cast dust cover type**  
Open end **C-UCFL...D1**  
Closed end **CM-UCFL...D1**

Housing number	Unit number (1) pressed steel dust cover type	Unit number (1) cast dust cover type	Nominal dimensions					Mass of unit		
			mm inch					kg lb		
			t max.	A <sub>4</sub>	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UCFL	Z(ZM)	C(CM)
FL209D1 FL209D1 FL209D1 FL209D1	Z(ZM)-UCFL209D1 Z(ZM)-UCFL209-110D1 Z(ZM)-UCFL209-111D1 Z(ZM)-UCFL209-112D1	C(CM)-UCFL209D1 C(CM)-UCFL209-110D1 C(CM)-UCFL209-111D1 C(CM)-UCFL209-112D1	3 1/8	57 2 1/4	70 2 3/4	113 4 7/16	54 2 1/8	1.8 4.0	1.9 4.2	2.3 5.1
FL210D1 FL210D1 FL210D1 FL210D1 FL210D1	Z(ZM)-UCFL210D1 Z(ZM)-UCFL210-113D1 Z(ZM)-UCFL210-114D1 Z(ZM)-UCFL210-115D1 —	C(CM)-UCFL210D1 C(CM)-UCFL210-113D1 C(CM)-UCFL210-114D1 C(CM)-UCFL210-115D1 C(CM)-UCFL210-200D1	3 1/8	60 2 3/8	72 2 27/32	120 4 23/32	58 2 9/32	2.0 4.4	2.1 4.6	2.7 6.0
FL211D1 FL211D1 FL211D1 FL211D1 FL211D1	Z(ZM)-UCFL211D1 Z(ZM)-UCFL211-200D1 Z(ZM)-UCFL211-201D1 Z(ZM)-UCFL211-202D1 Z(ZM)-UCFL211-203D1	C(CM)-UCFL211D1 C(CM)-UCFL211-200D1 C(CM)-UCFL211-201D1 C(CM)-UCFL211-202D1 C(CM)-UCFL211-203D1	4 5/32	64 2 1/2	75 2 15/16	133 5 1/4	65 2 9/16	2.9 6.4	3.0 6.6	3.4 7.5
FL212D1 FL212D1 FL212D1 FL212D1 FL212D1	Z(ZM)-UCFL212D1 Z(ZM)-UCFL212-204D1 Z(ZM)-UCFL212-205D1 Z(ZM)-UCFL212-206D1 —	C(CM)-UCFL212D1 C(CM)-UCFL212-204D1 C(CM)-UCFL212-205D1 C(CM)-UCFL212-206D1 C(CM)-UCFL212-207D1	4 5/32	74 2 29/32	86 3 3/8	144 5 21/32	70 2 3/4	3.8 8.4	4.0 8.8	4.6 10
FL213D1 FL213D1 FL213D1	Z(ZM)-UCFL213D1 Z(ZM)-UCFL213-208D1 Z(ZM)-UCFL213-209D1	C(CM)-UCFL213D1 C(CM)-UCFL213-208D1 C(CM)-UCFL213-209D1	4 5/32	76 3	90 3 17/32	157 6 3/16	78 3 1/16	4.8 11	4.9 11	5.8 13
FL214D1 FL214D1 FL214D1 FL214D1	— — — —	C(CM)-UCFL214D1 C(CM)-UCFL214-210D1 C(CM)-UCFL214-211D1 C(CM)-UCFL214-212D1	4 5/32	— —	98 3 27/32	164 6 15/32	80 3 5/32	5.4 12	— —	7.7 17

## Rhombus flanged unit, cast housing Set screw type




**Pressed steel dust cover type**  
Open end **Z-UCFL...D1**  
Closed end **ZM-UCFL...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup>	Nominal dimensions											Bolt size mm inch	Bearing number
		mm inch												
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B	S			
75 2 <sup>13</sup> / <sub>16</sub> 2 <sup>7</sup> / <sub>8</sub> 2 <sup>15</sup> / <sub>16</sub> 3	<b>UCFL215D1</b> <b>UCFL215-213D1</b> <b>UCFL215-214D1</b> <b>UCFL215-215D1</b> <b>UCFL215-300D1</b>	275	225	34	22	56	23	165	78.5	77.8	33.3	M20	<b>UC215D1</b> UC215-213D1 UC215-214D1 UC215-215D1 UC215-300D1	
		10 <sup>13</sup> / <sub>16</sub>	8 <sup>55</sup> / <sub>64</sub>	1 <sup>11</sup> / <sub>32</sub>	7/8	2 <sup>7</sup> / <sub>32</sub>	2 <sup>29</sup> / <sub>32</sub>	6 <sup>1</sup> / <sub>2</sub>	3 <sup>3</sup> / <sub>32</sub>	3.0630	1.311	3/4		
80 3 <sup>1</sup> / <sub>16</sub> 3 <sup>1</sup> / <sub>8</sub> 3 <sup>3</sup> / <sub>16</sub>	<b>UCFL216D1</b> <b>UCFL216-301D1</b> <b>UCFL216-302D1</b> <b>UCFL216-303D1</b>	290	233	34	22	58	25	180	83.3	82.6	33.3	M22	<b>UC216D1</b> UC216-301D1 UC216-302D1 UC216-303D1	
		11 <sup>13</sup> / <sub>32</sub>	9 <sup>11</sup> / <sub>64</sub>	1 <sup>11</sup> / <sub>32</sub>	7/8	2 <sup>9</sup> / <sub>32</sub>	6 <sup>3</sup> / <sub>64</sub>	7 <sup>3</sup> / <sub>32</sub>	3 <sup>9</sup> / <sub>32</sub>	3.2520	1.311	7/8		
85 3 <sup>1</sup> / <sub>4</sub> 3 <sup>5</sup> / <sub>16</sub> 3 <sup>7</sup> / <sub>16</sub>	<b>UCFL217D1</b> <b>UCFL217-304D1</b> <b>UCFL217-305D1</b> <b>UCFL217-307D1</b>	305	248	36	24	63	25	190	87.6	85.7	34.1	M22	<b>UC217D1</b> UC217-304D1 UC217-305D1 UC217-307D1	
		12	9 <sup>49</sup> / <sub>64</sub>	1 <sup>27</sup> / <sub>64</sub>	1 <sup>5</sup> / <sub>16</sub>	2 <sup>15</sup> / <sub>32</sub>	6 <sup>3</sup> / <sub>64</sub>	7 <sup>15</sup> / <sub>32</sub>	3 <sup>29</sup> / <sub>64</sub>	3.3740	1.343	7/8		
90 3 <sup>1</sup> / <sub>2</sub>	<b>UCFL218D1</b> <b>UCFL218-308D1</b>	320	265	40	24	68	25	205	96.3	96	39.7	M22	<b>UC218D1</b> UC218-308D1	
		12 <sup>19</sup> / <sub>32</sub>	10 <sup>7</sup> / <sub>16</sub>	1 <sup>37</sup> / <sub>64</sub>	1 <sup>5</sup> / <sub>16</sub>	2 <sup>11</sup> / <sub>16</sub>	6 <sup>3</sup> / <sub>64</sub>	8 <sup>1</sup> / <sub>16</sub>	3 <sup>51</sup> / <sub>64</sub>	3.7795	1.563	7/8		

Note <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.




**Cast dust cover type**  
Open end **C-UCFL...D1**  
Closed end **CM-UCFL...D1**

Housing number	Unit number pressed steel dust cover type	Unit number <sup>(1)</sup> cast dust cover type	Nominal dimensions					Mass of unit		
			mm inch					kg lb		
			t max.	A <sub>4</sub>	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UCFL	Z(ZM)	C(CM)
FL215D1	—	<b>C(CM)-UCFL215D1</b>	4	—	102	169	82	6.0	—	7.1
FL215D1	—	<b>C(CM)-UCFL215-213D1</b>	—	—	—	—	—	—	—	—
FL215D1	—	<b>C(CM)-UCFL215-214D1</b>	5 <sup>5</sup> / <sub>32</sub>	—	4 <sup>1</sup> / <sub>32</sub>	6 <sup>21</sup> / <sub>32</sub>	3 <sup>7</sup> / <sub>32</sub>	13	—	16
FL215D1	—	<b>C(CM)-UCFL215-215D1</b>	—	—	—	—	—	—	—	—
FL215D1	—	<b>C(CM)-UCFL215-300D1</b>	—	—	—	—	—	—	—	—
FL216D1	—	<b>C(CM)-UCFL216D1</b>	4	—	106	183	90	7.4	—	8.6
FL216D1	—	<b>C(CM)-UCFL216-301D1</b>	—	—	—	—	—	—	—	—
FL216D1	—	<b>C(CM)-UCFL216-302D1</b>	5 <sup>5</sup> / <sub>32</sub>	—	4 <sup>3</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>32</sub>	3 <sup>17</sup> / <sub>32</sub>	16	—	19
FL216D1	—	<b>C(CM)-UCFL216-303D1</b>	—	—	—	—	—	—	—	—
FL217D1	—	<b>C(CM)-UCFL217D1</b>	5	—	114	192	95	8.8	—	10
FL217D1	—	<b>C(CM)-UCFL217-304D1</b>	—	—	—	—	—	—	—	—
FL217D1	—	<b>C(CM)-UCFL217-305D1</b>	1 <sup>13</sup> / <sub>64</sub>	—	4 <sup>1</sup> / <sub>2</sub>	7 <sup>9</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>4</sub>	19	—	22
FL217D1	—	<b>C(CM)-UCFL217-307D1</b>	—	—	—	—	—	—	—	—
FL218D1	—	<b>C(CM)-UCFL218D1</b>	5	—	122	205	102	11	—	13
FL218D1	—	<b>C(CM)-UCFL218-308D1</b>	1 <sup>13</sup> / <sub>64</sub>	—	4 <sup>13</sup> / <sub>16</sub>	8 <sup>1</sup> / <sub>16</sub>	4 <sup>1</sup> / <sub>32</sub>	24	—	29



## Rhombus flanged unit, cast housing Set screw type



Cast dust cover type  
Open end **C-UCFL...D1**  
Closed end **CM-UCFL...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B	S	
25 1 3/16	<b>UCFL305D1</b>	150	113	16	13	29	19	80	39	38	15	M16
7/8	<b>UCFL305-013D1</b>											
15/16	<b>UCFL305-014D1</b>	5 29/32	4 29/64	5/8	1/2	1 5/32	3/4	3 5/32	1 17/32	1.4961	0.591	5/8
1	<b>UCFL305-015D1</b>											
	<b>UCFL305-100D1</b>											
30 1 1/16	<b>UCFL306D1</b>	180	134	18	15	32	23	90	44	43	17	M20
1 1/8	<b>UCFL306-101D1</b>											
1 3/8	<b>UCFL306-102D1</b>	7 3/32	5 9/32	45/64	19/32	1 1/4	29/32	3 17/32	1 47/64	1.6929	0.669	3/4
1 3/16	<b>UCFL306-103D1</b>											
35 1 1/4	<b>UCFL307D1</b>	185	141	20	16	36	23	100	49	48	19	M20
1 5/16	<b>UCFL307-104D1</b>											
1 3/8	<b>UCFL307-105D1</b>	7 9/32	5 35/64	25/32	5/8	1 13/32	29/32	3 15/16	1 59/64	1.8898	0.748	3/4
1 7/16	<b>UCFL307-106D1</b>											
	<b>UCFL307-107D1</b>											
40 1 1/2	<b>UCFL308D1</b>	200	158	23	17	40	23	112	56	52	19	M20
1 9/16	<b>UCFL308-108D1</b>	7 7/8	6 7/32	29/32	21/32	1 9/16	29/32	4 13/32	2 13/64	2.0472	0.748	3/4
	<b>UCFL308-109D1</b>											
45 1 5/8	<b>UCFL309D1</b>	230	177	25	18	44	25	125	60	57	22	M22
1 11/16	<b>UCFL309-110D1</b>											
1 3/4	<b>UCFL309-111D1</b>	9 1/16	6 31/32	63/64	23/32	1 23/32	63/64	4 29/32	2 23/64	2.2441	0.866	7/8
	<b>UCFL309-112D1</b>											
50 1 13/16	<b>UCFL310D1</b>	240	187	28	19	48	25	140	67	61	22	M22
1 7/8	<b>UCFL310-113D1</b>											
1 15/16	<b>UCFL310-114D1</b>	9 7/16	7 23/64	1 7/64	3/4	1 7/8	63/64	5 1/2	2 41/64	2.4016	0.866	7/8
	<b>UCFL310-115D1</b>											

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions				Mass of unit	
			mm inch				kg lb	
			t max.	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UCFL	C(CM)
UC305D1	FL305D1	<b>C(CM)-UCFL305D1</b>	2	56	86	40	0.9	1.2
UC305-013D1	FL305D1	<b>C(CM)-UCFL305-013D1</b>						
UC305-014D1	FL305D1	<b>C(CM)-UCFL305-014D1</b>	5/64	2 7/32	3 3/8	1 9/16	2.0	2.6
UC305-015D1	FL305D1	<b>C(CM)-UCFL305-015D1</b>						
UC305-100D1	FL305D1	<b>C(CM)-UCFL305-100D1</b>						
UC306D1	FL306D1	<b>C(CM)-UCFL306D1</b>	2	60	101	45	1.4	1.7
UC306-101D1	FL306D1	<b>C(CM)-UCFL306-101D1</b>						
UC306-102D1	FL306D1	<b>C(CM)-UCFL306-102D1</b>	5/64	2 3/8	3 31/32	1 25/32	3.1	3.7
UC306-103D1	FL306D1	<b>C(CM)-UCFL306-103D1</b>						
UC307D1	FL307D1	<b>C(CM)-UCFL307D1</b>	3	68	110	50	1.7	2.1
UC307-104D1	FL307D1	<b>C(CM)-UCFL307-104D1</b>						
UC307-105D1	FL307D1	<b>C(CM)-UCFL307-105D1</b>	1/8	2 11/16	4 1 1/2	1 31/32	3.7	4.6
UC307-106D1	FL307D1	<b>C(CM)-UCFL307-106D1</b>						
UC307-107D1	FL307D1	<b>C(CM)-UCFL307-107D1</b>						
UC308D1	FL308D1	<b>C(CM)-UCFL308D1</b>	3	76	122	56	2.2	2.9
UC308-108D1	FL308D1	<b>C(CM)-UCFL308-108D1</b>	1/8	3	4 13/16	2 7/32	4.9	6.4
UC308-109D1	FL308D1	<b>C(CM)-UCFL308-109D1</b>						
UC309D1	FL309D1	<b>C(CM)-UCFL309D1</b>	3	80	135	62	3.0	3.8
UC309-110D1	FL309D1	<b>C(CM)-UCFL309-110D1</b>						
UC309-111D1	FL309D1	<b>C(CM)-UCFL309-111D1</b>	1/8	3 5/32	5 5/16	2 7/16	6.6	8.4
UC309-112D1	FL309D1	<b>C(CM)-UCFL309-112D1</b>						
UC310D1	FL310D1	<b>C(CM)-UCFL310D1</b>	3	88	152	70	4.1	5.0
UC310-113D1	FL310D1	<b>C(CM)-UCFL310-113D1</b>						
UC310-114D1	FL310D1	<b>C(CM)-UCFL310-114D1</b>	1/8	3 15/32	5 31/32	2 3/4	9.0	11
UC310-115D1	FL310D1	<b>C(CM)-UCFL310-115D1</b>						

## Rhombus flanged unit, cast housing Set screw type




Cast dust cover type  
Open end **C-UCFL...D1**  
Closed end **CM-UCFL...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B	S	
55 2 2 1/16 2 1/8 2 3/16	<b>UCFL311D1</b> <b>UCFL311-200D1</b> <b>UCFL311-201D1</b> <b>UCFL311-202D1</b> <b>UCFL311-203D1</b>	250 9 27/32	198 7 51/64	30 1 3/16	20 25/32	52 2 1/16	25 63/64	150 5 29/32	71 2 51/64	66 2.5984	25 0.984	M22 7/8
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UCFL312D1</b> <b>UCFL312-204D1</b> <b>UCFL312-205D1</b> <b>UCFL312-206D1</b> <b>UCFL312-207D1</b>	270 10 5/8	212 8 11/32	33 1 19/64	22 7/8	56 2 7/32	31 1 7/32	160 6 5/16	78 3 5/64	71 2.7953	26 1.024	M27 1
65 2 1/2 2 9/16	<b>UCFL313D1</b> <b>UCFL313-208D1</b> <b>UCFL313-209D1</b>	295 11 5/8	240 9 29/64	33 1 19/64	25 31/32	58 2 9/32	31 1 7/32	175 6 7/8	78 3 5/64	75 2.9528	30 1.181	M27 1
70 2 5/8 2 11/16 2 3/4	<b>UCFL314D1</b> <b>UCFL314-210D1</b> <b>UCFL314-211D1</b> <b>UCFL314-212D1</b>	315 12 13/32	250 9 27/32	36 1 27/64	28 1 3/32	61 2 13/32	35 1 3/8	185 7 9/32	81 3 3/16	78 3.0709	33 1.299	M30 1 1/8
75 2 13/16 2 7/8 2 15/16 3	<b>UCFL315D1</b> <b>UCFL315-213D1</b> <b>UCFL315-214D1</b> <b>UCFL315-215D1</b> <b>UCFL315-300D1</b>	320 12 19/32	260 10 15/64	39 1 17/32	30 1 3/16	66 2 19/32	35 1 3/8	195 7 11/16	89 3 1/2	82 3.2283	32 1.260	M30 1 1/8
80 3 1/16 3 1/8 3 3/16	<b>UCFL316D1</b> <b>UCFL316-301D1</b> <b>UCFL316-302D1</b> <b>UCFL316-303D1</b>	355 13 31/32	285 11 7/32	38 1 1/2	32 1 1/4	68 2 11/16	38 1 1/2	210 8 9/32	90 3 35/64	86 3.3858	34 1.339	M33 1 1/4

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions				Mass of unit	
			mm inch				kg lb	
			t max.	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UCFL	C(CM)
UC311D1 UC311-200D1 UC311-201D1 UC311-202D1 UC311-203D1	FL311D1 FL311D1 FL311D1 FL311D1 FL311D1	<b>C(CM)-UCFL311D1</b> <b>C(CM)-UCFL311-200D1</b> <b>C(CM)-UCFL311-201D1</b> <b>C(CM)-UCFL311-202D1</b> <b>C(CM)-UCFL311-203D1</b>	4 5/32	92 3 5/8	162 6 3/8	75 2 15/16	4.6 10	5.9 13
UC312D1 UC312-204D1 UC312-205D1 UC312-206D1 UC312-207D1	FL312D1 FL312D1 FL312D1 FL312D1 FL312D1	<b>C(CM)-UCFL312D1</b> <b>C(CM)-UCFL312-204D1</b> <b>C(CM)-UCFL312-205D1</b> <b>C(CM)-UCFL312-206D1</b> <b>C(CM)-UCFL312-207D1</b>	4 5/32	100 3 15/16	175 6 7/8	80 3 5/32	5.7 13	7.7 17
UC313D1 UC313-208D1 UC313-209D1	FL313D1 FL313D1 FL313D1	<b>C(CM)-UCFL313D1</b> <b>C(CM)-UCFL313-208D1</b> <b>C(CM)-UCFL313-209D1</b>	4 5/32	103 4 1/16	189 7 7/16	88 3 15/32	7.6 17	9.9 22
UC314D1 UC314-210D1 UC314-211D1 UC314-212D1	FL314D1 FL314D1 FL314D1 FL314D1	<b>C(CM)-UCFL314D1</b> <b>C(CM)-UCFL314-210D1</b> <b>C(CM)-UCFL314-211D1</b> <b>C(CM)-UCFL314-212D1</b>	4 5/32	106 4 3/16	198 7 25/32	92 3 5/8	8.6 19	11 24
UC315D1 UC315-213D1 UC315-214D1 UC315-215D1 UC315-300D1	FL315D1 FL315D1 FL315D1 FL315D1 FL315D1	<b>C(CM)-UCFL315D1</b> <b>C(CM)-UCFL315-213D1</b> <b>C(CM)-UCFL315-214D1</b> <b>C(CM)-UCFL315-215D1</b> <b>C(CM)-UCFL315-300D1</b>	4 5/32	114 4 1/2	210 8 9/32	98 3 27/32	9.9 22	12 26
UC316D1 UC316-301D1 UC316-302D1 UC316-303D1	FL316D1 FL316D1 FL316D1 FL316D1	<b>C(CM)-UCFL316D1</b> <b>C(CM)-UCFL316-301D1</b> <b>C(CM)-UCFL316-302D1</b> <b>C(CM)-UCFL316-303D1</b>	4 5/32	116 4 9/16	222 8 3/4	105 4 1/8	13 29	16 35

## Rhombus flanged unit, cast housing Set screw type



Cast dust cover type  
Open end **C-UCFL...D1**  
Closed end **CM-UCFL...D1**


Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B	S	
85 3 1/4	<b>UCFL317D1</b> <b>UCFL317-304D1</b> <b>UCFL317-305D1</b> <b>UCFL317-307D1</b>	370	300	44	32	74	38	220	100	96	40	M33
3 5/16 3 7/16		14 9/16	11 13/16	1 47/64	1 1/4	2 29/32	1 1/2	8 21/32	3 15/16	3.7795	1.575	1 1/4
90 3 7/16 3 1/2	<b>UCFL318D1</b> <b>UCFL318-307D1</b> <b>UCFL318-308D1</b>	385	315	44	36	76	38	235	100	96	40	M33
		15 5/32	12 13/32	1 47/64	1 13/32	3	1 1/2	9 1/4	3 15/16	3.7795	1.575	1 1/4
95 3 5/8 3 11/16 3 3/4	<b>UCFL319D1</b> <b>UCFL319-310D1</b> <b>UCFL319-311D1</b> <b>UCFL319-312D1</b>	405	330	59	40	94	41	250	121	103	41	M36
		15 15/16	12 63/64	2 51/64	1 9/16	3 11/16	1 39/64	9 27/32	4 49/64	4.0551	1.614	1 3/8
100 3 13/16 3 7/8 3 15/16 4	<b>UCFL320D1</b> <b>UCFL320-313D1</b> <b>UCFL320-314D1</b> <b>UCFL320-315D1</b> <b>UCFL320-400D1</b>	440	360	59	40	94	44	270	125	108	42	M39
		17 5/16	14 11/64	2 21/64	1 9/16	3 11/16	1 47/64	10 5/8	4 59/64	4.2520	1.654	1 1/2
105	<b>UCFL321D1</b>	440	360	59	40	94	44	270	127	112	44	M39
110	<b>UCFL322D1</b>	470	390	60	42	96	44	300	131	117	46	M39
120	<b>UCFL324D1</b>	520	430	65	48	110	47	330	140	126	51	M42
130	<b>UCFL326D1</b>	550	460	65	50	115	47	360	146	135	54	M42
140	<b>UCFL328D1</b>	600	500	75	60	125	51	400	161	145	59	M45

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions				Mass of unit	
			mm inch				kg lb	
			t max.	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UCFL	C(CM)
UC317D1	FL317D1	<b>C(CM)-UCFL317D1</b>	5	127	234	110	15	18
UC317-304D1	FL317D1	<b>C(CM)-UCFL317-304D1</b>						
UC317-305D1	FL317D1	<b>C(CM)-UCFL317-305D1</b>	13/64	5	9 7/32	4 11/32	33	40
UC317-307D1	FL317D1	<b>C(CM)-UCFL317-307D1</b>						
UC318D1	FL318D1	<b>C(CM)-UCFL318D1</b>	5	129	247	118	17	21
UC318-307D1	FL318D1	<b>C(CM)-UCFL318-307D1</b>						
UC318-308D1	FL318D1	<b>C(CM)-UCFL318-308D1</b>	13/64	5 3/32	9 23/32	4 21/32	37	46
UC319D1	FL319D1	<b>C(CM)-UCFL319D1</b>	5	149	260	125	22	26
UC319-310D1	FL319D1	<b>C(CM)-UCFL319-310D1</b>						
UC319-311D1	FL319D1	<b>C(CM)-UCFL319-311D1</b>	13/64	5 7/8	10 1/4	4 29/32	49	57
UC319-312D1	FL319D1	<b>C(CM)-UCFL319-312D1</b>						
UC320D1	FL320D1	<b>C(CM)-UCFL320D1</b>	5	154	280	135	26	31
UC320-313D1	FL320D1	<b>C(CM)-UCFL320-313D1</b>						
UC320-314D1	FL320D1	<b>C(CM)-UCFL320-314D1</b>						
UC320-315D1	FL320D1	<b>C(CM)-UCFL320-315D1</b>	13/64	6 1/16	11 1/32	5 5/16	57	68
UC320-400D1	FL320D1	<b>C(CM)-UCFL320-400D1</b>						
UC321D1	FL321D1	<b>C(CM)-UCFL321D1</b>	5	156	287	135	27	32
UC322D1	FL322D1	<b>C(CM)-UCFL322D1</b>	5	160	315	150	34	39
UC324D1	FL324D1	<b>C(CM)-UCFL324D1</b>	5	172	342	165	48	52
UC326D1	FL326D1	<b>C(CM)-UCFL326D1</b>	6	178	376	180	58	64
UC328D1	FL328D1	<b>C(CM)-UCFL328D1</b>	6	192	410	200	81	90

## Rhombus flanged unit, cast housing Set screw type



Cast dust cover type  
Open end **C-UCFL...D1**  
Closed end **CM-UCFL...D1**


Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B	S	
25 1 3/16 7/8 1 5/16 1	<b>UCFLX05D1</b> <b>UCFLX05-013D1</b> <b>UCFLX05-014D1</b> <b>UCFLX05-015D1</b> <b>UCFLX05-100D1</b>	141 5 9/16	117 4 39/64	18 45/64	13 1/2	30 1 3/16	12 15/32	83 3 9/32	40.2 1 37/64	38.1 1.5000	15.9 0.626	M10 3/8
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UCFLX06D1</b> <b>UCFLX06-101D1</b> <b>UCFLX06-102D1</b> <b>UCFLX06-103D1</b> <b>UCFLX06-104D1</b>	156 6 5/32	130 5 1/8	19 3/4	15 19/32	34 1 11/32	16 5/8	95 3 3/4	44.4 1 3/4	42.9 1.6890	17.5 0.689	M14 1/2
35 1 5/16 1 3/8 1 7/16	<b>UCFLX07D1</b> <b>UCFLX07-105D1</b> <b>UCFLX07-106D1</b> <b>UCFLX07-107D1</b>	171 6 23/32	144 5 43/64	21 53/64	16 5/8	38 1 1/2	16 5/8	105 4 1/8	51.2 2 1/64	49.2 1.9370	19 0.748	M14 1/2
40 1 1/2 1 9/16	<b>UCFLX08D1</b> <b>UCFLX08-108D1</b> <b>UCFLX08-109D1</b>	179 7 1/16	148 5 53/64	22 55/64	16 5/8	40 1 9/16	16 5/8	111 4 3/8	52.2 2 1/16	49.2 1.9370	19 0.748	M14 1/2
45 1 5/8 1 11/16 1 3/4 1 13/16	<b>UCFLX09D1</b> <b>UCFLX09-110D1</b> <b>UCFLX09-111D1</b> <b>UCFLX09-112D1</b> <b>UCFLX09-113D1</b>	189 7 7/16	157 6 3/16	23 29/32	16 5/8	40 1 9/16	16 5/8	116 4 9/16	55.6 2 3/16	51.6 2.0315	19 0.748	M14 1/2
50 1 7/8 1 15/16 2	<b>UCFLX10D1</b> <b>UCFLX10-114D1</b> <b>UCFLX10-115D1</b> <b>UCFLX10-200D1</b>	216 8 1/2	184 7 1/4	26 1 1/32	18 23/32	44 1 23/32	19 3/4	133 5 1/4	59.4 2 11/32	55.6 2.1890	22.2 0.874	M16 5/8

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions				Mass of unit	
			mm inch				kg lb	
			t max.	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UCFL	C(CM)
UCX05D1 UCX05-013D1 UCX05-014D1 UCX05-015D1 UCX05-100D1	FLX05D1 FLX05D1 FLX05D1 FLX05D1 FLX05D1	<b>C(CM)-UCFLX05D1</b> <b>C(CM)-UCFLX05-013D1</b> <b>C(CM)-UCFLX05-014D1</b> <b>C(CM)-UCFLX05-015D1</b> <b>C(CM)-UCFLX05-100D1</b>	2 5/64	56 2 7/32	86 3 3/8	41.5 1 5/8	1.0 2.2	1.2 2.6
UCX06D1 UCX06-101D1 UCX06-102D1 UCX06-103D1 UC207-104D1	FLX06D1 FLX06D1 FLX06D1 FLX06D1 FLX06D1	<b>C(CM)-UCFLX06D1</b> <b>C(CM)-UCFLX06-101D1</b> <b>C(CM)-UCFLX06-102D1</b> <b>C(CM)-UCFLX06-103D1</b> <b>C(CM)-UCFLX06-104D1</b>	2 5/64	59 2 5/16	98.5 3 7/8	47.5 1 7/8	1.5 3.3	1.8 4.0
UCX07D1 UCX07-105D1 UCX07-106D1 UCX07-107D1	FLX07D1 FLX07D1 FLX07D1 FLX07D1	<b>C(CM)-UCFLX07D1</b> <b>C(CM)-UCFLX07-105D1</b> <b>C(CM)-UCFLX07-106D1</b> <b>C(CM)-UCFLX07-107D1</b>	3 1/8	66 2 19/32	108.5 4 9/32	52.5 2 1/16	1.8 4.0	2.2 4.9
UCX08D1 UCX08-108D1 UCX08-109D1	FLX08D1 FLX08D1 FLX08D1	<b>C(CM)-UCFLX08D1</b> <b>C(CM)-UCFLX08-108D1</b> <b>C(CM)-UCFLX08-109D1</b>	3 1/8	70 2 3/4	114.5 4 1/4	55.5 2 3/16	2.0 4.4	2.4 5.3
UCX09D1 UCX09-110D1 UCX09-111D1 UCX09-112D1 UC210-113D1	FLX09D1 FLX09D1 FLX09D1 FLX09D1 FLX09D1	<b>C(CM)-UCFLX09D1</b> <b>C(CM)-UCFLX09-110D1</b> <b>C(CM)-UCFLX09-111D1</b> <b>C(CM)-UCFLX09-112D1</b> <b>C(CM)-UCFLX09-113D1</b>	3 1/8	73 2 7/8	119.5 4 29/32	58 2 9/32	2.2 4.9	2.7 6.0
UCX10D1 UCX10-114D1 UCX10-115D1 UC211-200D1	FLX10D1 FLX10D1 FLX10D1 FLX10D1	<b>C(CM)-UCFLX10D1</b> <b>C(CM)-UCFLX10-114D1</b> <b>C(CM)-UCFLX10-115D1</b> <b>C(CM)-UCFLX10-200D1</b>	3 1/8	76 3	133.5 5 1/4	66.5 2 5/8	3.0 6.6	3.6 7.9

## Modified rhombus flanged unit, cast housing Set screw type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions												Bolt size mm inch
		mm inch												
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	N <sub>1</sub>	L	L <sub>1</sub>	A <sub>0</sub>	B	S	
12	UCFA201D1	98	78	15	12	25.5	10	40	60	50	33.3	31	12.7	M8
1/2	UCFA201-008D1	3 <sup>27</sup> / <sub>32</sub>	3 <sup>1</sup> / <sub>16</sub>	19 <sup>1</sup> / <sub>32</sub>	15 <sup>1</sup> / <sub>32</sub>	1	25 <sup>1</sup> / <sub>64</sub>	1 <sup>9</sup> / <sub>16</sub>	2 <sup>3</sup> / <sub>8</sub>	1 <sup>31</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>16</sub>	1.2205	0.500	5 <sup>1</sup> / <sub>16</sub>
15	UCFA202D1	98	78	15	12	25.5	10	40	60	50	33.3	31	12.7	M8
9/16	UCFA202-009D1	3 <sup>27</sup> / <sub>32</sub>	3 <sup>1</sup> / <sub>16</sub>	19 <sup>1</sup> / <sub>32</sub>	15 <sup>1</sup> / <sub>32</sub>	1	25 <sup>1</sup> / <sub>64</sub>	1 <sup>9</sup> / <sub>16</sub>	2 <sup>3</sup> / <sub>8</sub>	1 <sup>31</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>16</sub>	1.2205	0.500	5 <sup>1</sup> / <sub>16</sub>
5/8	UCFA202-010D1													
17	UCFA203D1	98	78	15	12	25.5	10	40	60	50	33.3	31	12.7	M8
11/16	UCFA203-011D1	3 <sup>27</sup> / <sub>32</sub>	3 <sup>1</sup> / <sub>16</sub>	19 <sup>1</sup> / <sub>32</sub>	15 <sup>1</sup> / <sub>32</sub>	1	25 <sup>1</sup> / <sub>64</sub>	1 <sup>9</sup> / <sub>16</sub>	2 <sup>3</sup> / <sub>8</sub>	1 <sup>31</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>16</sub>	1.2205	0.500	5 <sup>1</sup> / <sub>16</sub>
20	UCFA204D1	98	78	15	12	25.5	10	40	60	50	33.3	31	12.7	M8
3/4	UCFA204-012D1	3 <sup>27</sup> / <sub>32</sub>	3 <sup>1</sup> / <sub>16</sub>	19 <sup>1</sup> / <sub>32</sub>	15 <sup>1</sup> / <sub>32</sub>	1	25 <sup>1</sup> / <sub>64</sub>	1 <sup>9</sup> / <sub>16</sub>	2 <sup>3</sup> / <sub>8</sub>	1 <sup>31</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>16</sub>	1.2205	0.500	5 <sup>1</sup> / <sub>16</sub>
25	UCFA205D1	124	96	15	14	26.5	13	49	70	64	34.8	34.1	14.3	M10
19/16	UCFA205-013D1													
7/8	UCFA205-014D1	4 <sup>7</sup> / <sub>8</sub>	3 <sup>25</sup> / <sub>32</sub>	19 <sup>1</sup> / <sub>32</sub>	9 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>32</sub>	33 <sup>1</sup> / <sub>64</sub>	1 <sup>15</sup> / <sub>16</sub>	2 <sup>3</sup> / <sub>4</sub>	2 <sup>17</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>8</sub>	1.3425	0.563	3 <sup>1</sup> / <sub>8</sub>
15/16	UCFA205-015D1													
1	UCFA205-100D1													
30	UCFA206D1	141	115	18	14	31	13	53	80	68	40.2	38.1	15.9	M10
1 1/16	UCFA206-101D1													
1 1/8	UCFA206-102D1	5 <sup>9</sup> / <sub>16</sub>	4 <sup>17</sup> / <sub>32</sub>	45 <sup>1</sup> / <sub>64</sub>	9 <sup>1</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>32</sub>	33 <sup>1</sup> / <sub>64</sub>	2 <sup>3</sup> / <sub>32</sub>	3 <sup>5</sup> / <sub>32</sub>	2 <sup>11</sup> / <sub>16</sub>	1 <sup>37</sup> / <sub>64</sub>	1.5000	0.626	3 <sup>1</sup> / <sub>8</sub>
1 3/16	UCFA206-103D1													
1 1/4	UCFA206-104D1													
35	UCFA207D1	155	128	20	16	34	15	60	90	75	45.4	42.9	17.5	M12
1 1/4	UCFA207-104D1													
1 5/16	UCFA207-105D1	6 <sup>3</sup> / <sub>32</sub>	5 <sup>1</sup> / <sub>32</sub>	25 <sup>1</sup> / <sub>32</sub>	5 <sup>1</sup> / <sub>8</sub>	1 <sup>11</sup> / <sub>32</sub>	19 <sup>1</sup> / <sub>32</sub>	2 <sup>3</sup> / <sub>8</sub>	3 <sup>17</sup> / <sub>32</sub>	2 <sup>15</sup> / <sub>16</sub>	1 <sup>25</sup> / <sub>32</sub>	1.6890	0.689	7 <sup>1</sup> / <sub>16</sub>
1 3/8	UCFA207-106D1													
1 7/16	UCFA207-107D1													
40	UCFA208D1	171	142	22	16	36	15	69	100	84	52.2	49.2	19	M12
1 1/2	UCFA208-108D1	6 <sup>23</sup> / <sub>32</sub>	5 <sup>19</sup> / <sub>32</sub>	55 <sup>1</sup> / <sub>64</sub>	5 <sup>1</sup> / <sub>8</sub>	1 <sup>13</sup> / <sub>32</sub>	19 <sup>1</sup> / <sub>32</sub>	2 <sup>23</sup> / <sub>32</sub>	3 <sup>15</sup> / <sub>16</sub>	3 <sup>5</sup> / <sub>16</sub>	2 <sup>1</sup> / <sub>16</sub>	1.9370	0.748	7 <sup>1</sup> / <sub>16</sub>
1 9/16	UCFA208-109D1													

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UC201D1	FA204D1	0.5
UC201-008D1	FA204D1	1.1
UC202D1	FA204D1	0.5
UC202-009D1	FA204D1	1.1
UC202-010D1	FA204D1	1.1
UC203D1	FA204D1	0.5
UC203-011D1	FA204D1	1.1
UC204D1	FA204D1	0.5
UC204-012D1	FA204D1	1.1
UC205D1	FA205D1	0.7
UC205-013D1	FA205D1	
UC205-014D1	FA205D1	1.5
UC205-015D1	FA205D1	
UC205-100D1	FA205D1	
UC206D1	FA206D1	0.9
UC206-101D1	FA206D1	
UC206-102D1	FA206D1	2.0
UC206-103D1	FA206D1	
UC206-104D1	FA206D1	
UC207D1	FA207D1	1.2
UC207-104D1	FA207D1	
UC207-105D1	FA207D1	2.6
UC207-106D1	FA207D1	
UC207-107D1	FA207D1	
UC208D1	FA208D1	1.5
UC208-108D1	FA208D1	3.3
UC208-109D1	FA208D1	

## Modified rhombus flanged unit, cast housing Set screw type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions												Bolt size mm inch
		mm inch												
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	N <sub>1</sub>	L	L <sub>1</sub>	A <sub>0</sub>	B	S	
45 1 5/8 1 11/16 1 3/4	<b>UCFA209D1</b> <b>UCFA209-110D1</b> <b>UCFA209-111D1</b> <b>UCFA209-112D1</b>	179 7 1/16	146 5 3/4	22 55/64	18 23/32	38 1 1/2	17 43/64	72 2 27/32	110 4 11/32	88 3 15/32	52.2 2 1/16	49.2 1.9370	19 0.748	M14 1/2
50 1 13/16 1 7/8 1 15/16 2	<b>UCFA210D1</b> <b>UCFA210-113D1</b> <b>UCFA210-114D1</b> <b>UCFA210-115D1</b> <b>UCFA210-200D1</b>	189 7 7/16	155 6 3/32	22 55/64	18 23/32	40 1 9/16	17 43/64	75 2 15/16	115 4 17/32	92 3 5/8	54.6 2 5/32	51.6 2.0315	19 0.748	M14 1/2
55 2 2 1/16 2 1/8 2 3/16	<b>UCFA211D1</b> <b>UCFA211-200D1</b> <b>UCFA211-201D1</b> <b>UCFA211-202D1</b> <b>UCFA211-203D1</b>	216 8 1/8	182 7 5/32	26 1 1/32	20 25/32	43 1 1/16	17 43/64	85 3 11/32	130 5 1/8	102 4 1/32	59.4 2 11/32	55.6 2.1890	22.2 0.874	M14 1/2

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UC209D1	FA209D1	1.9
UC209-110D1	FA209D1	4.2
UC209-111D1	FA209D1	4.2
UC209-112D1	FA209D1	4.2
UC210D1	FA210D1	2.2
UC210-113D1	FA210D1	4.9
UC210-114D1	FA210D1	4.9
UC210-115D1	FA210D1	4.9
UC210-200D1	FA210D1	4.9
UC211D1	FA211D1	2.9
UC211-200D1	FA211D1	6.4
UC211-201D1	FA211D1	6.4
UC211-202D1	FA211D1	6.4
UC211-203D1	FA211D1	6.4

## Modified flanged unit, cast housing Set screw type




Shaft dia. mm inch	Unit number (*)	Nominal dimensions													
		mm inch													
		H <sub>3</sub>	J	A <sub>2</sub>	A <sub>1</sub>	A	N	H	H <sub>1</sub>	L <sub>1</sub>	H <sub>2</sub>	L	A <sub>0</sub>	B	S
12 1/2	UCFH201D1 UCFH201-008D1	110 4 11/32	32 1 17/64	15 19/32	13 1/2	25.5 1	10 25/64	42 1 21/32	27 1 1/16	52 2 1/16	52 2 1/16	62 2 7/16	33.3 1 5/16	31 1.2205	12.7 0.500
15 9/16 5/8	UCFH202D1 UCFH202-009D1 UCFH202-010D1	110 4 11/32	32 1 17/64	15 19/32	13 1/2	25.5 1	10 25/64	42 1 21/32	27 1 1/16	52 2 1/16	52 2 1/16	62 2 7/16	33.3 1 5/16	31 1.2205	12.7 0.500
17 11/16	UCFH203D1 UCFH203-011D1	110 4 11/32	32 1 17/64	15 19/32	13 1/2	25.5 1	10 25/64	42 1 21/32	27 1 1/16	52 2 1/16	52 2 1/16	62 2 7/16	33.3 1 5/16	31 1.2205	12.7 0.500
20 3/4	UCFH204D1 UCFH204-012D1	110 4 11/32	32 1 17/64	15 19/32	13 1/2	25.5 1	10 25/64	42 1 21/32	27 1 1/16	52 2 1/16	52 2 1/16	62 2 7/16	33.3 1 5/16	31 1.2205	12.7 0.500
25 1 3/16 7/8 1 5/16	UCFH205D1 UCFH205-013D1 UCFH205-014D1 UCFH205-015D1	116 4 9/16	34 1 11/32	16 5/8	13 1/2	27 1 1/16	10 25/64	45 1 49/64	27 1 1/16	56 2 7/32	52 2 1/16	68 2 11/16	35.8 1 13/32	34.1 1.3425	14.3 0.563
1 UCFH205-100D1															
30 1 1/16 1 1/8 1 3/16 1 1/4	UCFH206D1 UCFH206-101D1 UCFH206-102D1 UCFH206-103D1 UCFH206-104D1	130 5 1/8	40 1 37/64	18 45/64	13 1/2	31 1 7/32	10 25/64	50 1 31/32	29 1 9/64	65 2 9/16	55 2 5/32	78 3 1/16	40.2 1 37/64	38.1 1.5000	15.9 0.626
35 1 1/4 1 5/16 1 3/8 1 7/16	UCFH207D1 UCFH207-104D1 UCFH207-105D1 UCFH207-106D1 UCFH207-107D1	144 5 21/32	46 1 13/16	19 3/4	15 19/32	34 1 11/32	10 25/64	55 2 1/64	32 1 17/64	70 2 3/4	62 2 7/16	90 3 17/32	44.4 1 3/4	42.9 1.6890	17.5 0.689

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bolt size mm inch	Bearing number	Housing number	Mass of unit kg lb
M8 5/16	UC201D1 UC201-008D1	FH204D1 FH204D1	0.6 1.3
M8 5/16	UC202D1 UC202-009D1 UC202-010D1	FH204D1 FH204D1 FH204D1	0.6 1.3 1.3
M8 5/16	UC203D1 UC203-011D1	FH204D1 FH204D1	0.6 1.3
M8 5/16	UC204D1 UC204-012D1	FH204D1 FH204D1	0.6 1.3
M8 5/16	UC205D1 UC205-013D1 UC205-014D1 UC205-015D1 UC205-100D1	FH205D1 FH205D1 FH205D1 FH205D1 FH205D1	0.7 1.5 1.5 1.5 1.5
M8 5/16	UC206D1 UC206-101D1 UC206-102D1 UC206-103D1 UC206-104D1	FH206D1 FH206D1 FH206D1 FH206D1 FH206D1	0.9 2.0 2.0 2.0 2.0
M8 5/16	UC207D1 UC207-104D1 UC207-105D1 UC207-106D1 UC207-107D1	FH207D1 FH207D1 FH207D1 FH207D1 FH207D1	1.3 2.9 2.9 2.9 2.9

## Modified flanged unit, cast housing Set screw type



Shaft dia. mm inch	Unit number <sup>(1)</sup>	Nominal dimensions														
		mm inch														
		$H_3$	$J$	$A_2$	$A_1$	$A$	$N$	$H$	$H_1$	$L_1$	$H_2$	$L$	$A_0$	$B$	$S$	
40	UCFH208D1	164	50	21	16	36	12	60	41	78	72	100	51.2	49.2	19	
1 1/2	UCFH208-108D1	6 15/32	1 31/32	53/64	5/8	1 13/32	15/32	2 23/64	1 39/64	3 1/16	2 27/32	3 15/16	2 1/64	1.9370	0.748	
1 9/16	UCFH208-109D1															
45	UCFH209D1	174	54	22	18	38	12	65	43	80	76	106	52.2	49.2	19	
1 5/8	UCFH209-110D1	6 27/32	2 1/8	55/64	23/32	1 1/2	15/32	2 9/16	1 11/16	3 5/32	3	4 3/16	2 1/16	1.9370	0.748	
1 11/16	UCFH209-111D1															
1 3/4	UCFH209-112D1															
50	UCFH210D1	184	58	22	18	40	12	68	46	86	82	112	54.6	51.6	19	
1 13/16	UCFH210-113D1															
1 7/8	UCFH210-114D1	7 1/4	2 9/32	55/64	23/32	1 9/16	15/32	2 43/64	1 13/16	3 3/8	3 7/32	4 13/32	2 5/32	2.0315	0.748	
1 15/16	UCFH210-115D1															
2	UCFH210-200D1															

**Note** <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

**Remarks** Please refer to page A21 for size of grease fitting.

Bolt size mm inch	Bearing number	Housing number	Mass of unit kg lb
M10	UC208D1	FH208D1	1.8
3/8	UC208-108D1	FH208D1	4.0
	UC208-109D1	FH208D1	
M10	UC209D1	FH209D1	2.1
	UC209-110D1	FH209D1	
3/8	UC209-111D1	FH209D1	4.6
	UC209-112D1	FH209D1	
M10	UC210D1	FH210D1	2.4
	UC210-113D1	FH210D1	
3/8	UC210-114D1	FH210D1	5.3
	UC210-115D1	FH210D1	
	UC210-200D1	FH210D1	



## Light rhombus flanged unit, cast housing Set screw type




Shaft dia. mm inch	Unit number (*)	Nominal dimensions										Bolt size mm inch
		<i>H</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>1</sub>	<i>A</i>	<i>N</i>	<i>L</i>	<i>A</i> <sub>0</sub>	<i>B</i>	<i>S</i>	
12 1/2	ASFB201	81	63.5	9.5	9.5	18	7	56	25.5	22	6	M6
	ASFB201-008	3 3/16	2 1/2	3/8	3/8	23/32	9/32	2 7/32	1	0.8661	0.236	1/4
15 9/16 5/8	ASFB202	81	63.5	9.5	9.5	18	7	56	25.5	22	6	M6
	ASFB202-009 ASFB202-010	3 3/16	2 1/2	3/8	3/8	23/32	9/32	2 7/32	1	0.8661	0.236	1/4
17 1/2	ASFB203	81	63.5	9.5	9.5	18	7	56	25.5	22	6	M6
	ASFB203-011	3 3/16	2 1/2	3/8	3/8	23/32	9/32	2 7/32	1	0.8661	0.236	1/4
20 3/4	ASFB204	90	71.5	11	11	20	10	61	29	25	7	M8
	ASFB204-012	3 17/32	2 19/16	7/16	7/16	25/32	25/64	2 13/32	1 9/64	0.9843	0.276	5/16
25 13/16 7/8 15/16 1	ASFB205	95	76	11	11	20	10	64	30.5	27	7.5	M8
	ASFB205-013											
	ASFB205-014	3 3/4	2 63/64	7/16	7/16	25/32	25/64	2 17/32	1 13/64	1.0630	0.295	5/16
	ASFB205-015 ASFB205-100											
30 1 1/16 1 1/8 1 3/16 1 1/4	ASFB206	113	90.5	12	12	22.5	12	76	33	29	8	M10
	ASFB206-101											
	ASFB206-102	4 7/16	3 9/16	15/32	15/32	7/8	15/32	3	1 19/64	1.1417	0.315	3/8
	ASFB206-103 ASFB206-104											
35 1 1/4 1 5/16 1 3/8 1 7/16	ASFB207	122	100	11	13	24	12	89	36.5	34	8.5	M10
	ASFB207-104											
	ASFB207-105	4 13/16	3 15/16	7/16	1/2	15/16	15/32	3 1/2	1 7/16	1.3386	0.335	3/8
	ASFB207-106 ASFB207-107											

Note (\*) If relubricatable type is needed, please order with suffix "D1".

Bearing number	Housing number	Mass of unit kg lb
AS201	FB201	0.3
AS201-008	FB201	0.7
AS202	FB201	0.3
AS202-009	FB201	0.7
AS202-010	FB201	0.7
AS203	FB201	0.2
AS203-011	FB201	0.4
AS204	FB204	0.3
AS204-012	FB204	0.7
AS205	FB205	0.3
AS205-013	FB205	
AS205-014	FB205	0.7
AS205-015	FB205	
AS205-100	FB205	
AS206	FB206	0.5
AS206-101	FB206	
AS206-102	FB206	1.1
AS206-103	FB206	
AS206-104	FB206	
AS207	FB207	0.8
AS207-104	FB207	
AS207-105	FB207	1.8
AS207-106	FB207	
AS207-107	FB207	

## Light rhombus flanged unit, cast housing Set screw type



Shaft dia. mm inch	Unit number <sup>(1)</sup>	Nominal dimensions									Bolt size mm inch
		<i>H</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i>	<i>N</i>	<i>L</i>	<i>A</i> <sub>0</sub>	<i>B</i>	<i>S</i>	
12 1/2	<b>ASFD201</b> <b>ASFD201-008</b>	81 3 3/16	63 2 31/64	8.5 21/64	15 19/32	7 9/32	59 2 5/16	24.5 31/32	22 0.8661	6 0.236	M6 1/4
15 9/16 5/8	<b>ASFD202</b> <b>ASFD202-009</b> <b>ASFD202-010</b>	81 3 3/16	63 2 31/64	8.5 21/64	15 19/32	7 9/32	59 2 5/16	24.5 31/32	22 0.8661	6 0.236	M6 1/4
17 11/16	<b>ASFD203</b> <b>ASFD203-011</b>	81 3 3/16	63 2 31/64	8.5 21/64	15 19/32	7 9/32	59 2 5/16	24.5 31/32	22 0.8661	6 0.236	M6 1/4
20 3/4	<b>ASFD204</b> <b>ASFD204-012</b>	90 3 17/32	71 2 51/64	9.5 3/8	17 21/32	10 25/64	67 2 5/8	27.5 1 5/64	25 0.9843	7 0.276	M8 5/16
25 13/16 7/8 15/16 1	<b>ASFD205</b> <b>ASFD205-013</b> <b>ASFD205-014</b> <b>ASFD205-015</b> <b>ASFD205-100</b>	95 3 3/4	76 2 63/64	9.5 3/8	17 21/32	10 25/64	71 2 25/32	29 1 9/64	27 1.0630	7.5 0.295	M8 5/16
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>ASFD206</b> <b>ASFD206-101</b> <b>ASFD206-102</b> <b>ASFD206-103</b> <b>ASFD206-104</b>	113 4 7/16	90 3 35/64	12 15/32	21 13/16	12 15/32	84 3 5/16	33 1 19/64	29 1.1417	8 0.315	M10 3/8
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>ASFD207</b> <b>ASFD207-104</b> <b>ASFD207-105</b> <b>ASFD207-106</b> <b>ASFD207-107</b>	125 4 29/32	100 3 15/16	12.5 31/64	22 7/8	12 15/32	94 3 11/16	38 1 1/2	34 1.3386	8.5 0.335	M10 3/8
40 1 1/2 1 9/16	<b>ASFD208</b> <b>ASFD208-108</b> <b>ASFD208-109</b>	148 5 13/16	119 4 11/16	14.5 37/64	25 31/32	13.5 17/32	104 4 3/32	43.5 1 23/32	38 1.4961	9 0.354	M12 9/16

Note <sup>(1)</sup> If relubricatable type is needed, please order with suffix "A-" "D1". Example: A-ASFD201D1

Bearing number	Housing number	Mass of unit kg lb
AS201	FD201	0.3
AS201-008	FD201	0.7
AS202	FD201	0.3
AS202-009	FD201	0.7
AS202-010	FD201	0.7
AS203	FD201	0.3
AS203-011	FD201	0.7
AS204	FD204	0.4
AS204-012	FD204	0.9
AS205	FD205	0.5
AS205-013	FD205	1.1
AS205-014	FD205	1.1
AS205-015	FD205	1.1
AS205-100	FD205	1.1
AS206	FD206	0.8
AS206-101	FD206	1.8
AS206-102	FD206	1.8
AS206-103	FD206	1.8
AS206-104	FD206	1.8
AS207	FD207	0.9
AS207-104	FD207	2.0
AS207-105	FD207	2.0
AS207-106	FD207	2.0
AS207-107	FD207	2.0
AS208	FD208	1.3
AS208-108	FD208	2.9
AS208-109	FD208	2.9

# ASPF2

Round flanged unit, pressed steel housing  
Set screw type



Shaft dia. mm inch	Unit number	Nominal dimensions								Bolt size mm inch
		mm inch								
		H	J	A <sub>1</sub>	N <sup>(1)</sup>	A	B	S	H <sub>1</sub> min.	
12 1/2	<b>ASPF201</b> <b>ASPF201-008</b>	81 3 3/16	63.5 2 1/2	4 0.157	7.1 9/32	14 9/16	22 0.8661	6 0.236	49 1 15/16	M6 1/4
15 9/16 5/8	<b>ASPF202</b> <b>ASPF202-009</b> <b>ASPF202-010</b>	81 3 3/16	63.5 2 1/2	4 0.157	7.1 9/32	14 9/16	22 0.8661	6 0.236	49 1 15/16	M6 1/4
17 1 1/16	<b>ASPF203</b> <b>ASPF203-011</b>	81 3 3/16	63.5 2 1/2	4 0.157	7.1 9/32	14 9/16	22 0.8661	6 0.236	49 1 15/16	M6 1/4
20 3/4	<b>ASPF204</b> <b>ASPF204-012</b>	90 3 35/64	71.5 2 13/16	4 0.157	9 23/64	16 5/8	25 0.9843	7 0.276	56 2 7/32	M8 5/16
25 1 3/16 7/8 15/16 1	<b>ASPF205</b> <b>ASPF205-013</b> <b>ASPF205-014</b> <b>ASPF205-015</b> <b>ASPF205-100</b>	95 3 3/4	76 2 63/64	4 0.157	9 23/64	18 23/32	27 1.0630	7.5 0.295	60 2 3/8	M8 5/16
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>ASPF206</b> <b>ASPF206-101</b> <b>ASPF206-102</b> <b>ASPF206-103</b> <b>ASPF206-104</b>	113 4 7/16	90.5 3 9/16	5.2 0.205	11 7/16	18 23/32	29 1.1417	8 0.315	71 2 13/16	M10 3/8
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>ASPF207</b> <b>ASPF207-104</b> <b>ASPF207-105</b> <b>ASPF207-106</b> <b>ASPF207-107</b>	122 4 13/16	100 3 15/16	5.2 0.205	11 7/16	20 25/32	34 1.3386	8.5 0.335	81 3 3/16	M10 3/8
40 1 1/2 1 9/16	<b>ASPF208</b> <b>ASPF208-108</b> <b>ASPF208-109</b>	148 5 13/16	119 4 11/16	6.8 0.268	13.5 17/32	21 13/16	38 1.4961	9 0.354	91 3 19/32	M12 1/2

Notes (1) ASPF208 has four bolt holes.

(2) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.

Max. load <sup>(2)</sup> recommended		Bearing number	Housing number	Mass of unit kg lb
N lbf				
radial	axial			
2 700 600	1 350 300	AS201 AS201-008	PF203 PF203	0.2 0.4
2 700 600	1 350 300	AS202 AS202-009 AS202-010	PF203 PF203 PF203	0.2 0.4
2 700 600	1 350 300	AS203 AS203-011	PF203 PF203	0.2 0.4
3 000 660	1 500 330	AS204 AS204-012	PF204 PF204	0.2 0.4
4 000 880	2 000 440	AS205 AS205-013 AS205-014 AS205-015 AS205-100	PF205 PF205 PF205 PF205 PF205	0.3 0.7
5 000 1 100	2 500 550	AS206 AS206-101 AS206-102 AS206-103 AS206-104	PF206 PF206 PF206 PF206 PF206	0.4 0.9
6 000 1 300	3 000 650	AS207 AS207-104 AS207-105 AS207-106 AS207-107	PF207 PF207 PF207 PF207 PF207	0.6 1.3
7 000 1 500	3 500 750	AS208 AS208-108 AS208-109	PF208 PF208 PF208	0.9 2.0

## Round flanged unit, pressed steel housing with rubber ring Set screw type



Shaft dia.  mm inch	Unit number	Nominal dimensions									Bolt size  mm inch
		mm inch									
		<i>H</i>	<i>J</i>	<i>A</i> <sub>1</sub>	<i>N</i>	<i>A</i>	<i>B</i>	<i>S</i>	<i>H</i> <sub>1</sub> min.		
12  1/2	<b>ASRPF201</b>	90	71.5	4	9	16	22	6	56	M8	
	<b>ASRPF201-008</b>	3 <sup>35</sup> / <sub>64</sub>	2 <sup>13</sup> / <sub>16</sub>	0.157	23/ <sub>64</sub>	5/ <sub>8</sub>	0.8661	0.236	2 <sup>7</sup> / <sub>32</sub>	5/ <sub>16</sub>	
15  9/ <sub>16</sub> 5/ <sub>8</sub>	<b>ASRPF202</b>	90	71.5	4	9	16	22	6	56	M8	
	<b>ASRPF202-009</b> <b>ASRPF202-010</b>	3 <sup>35</sup> / <sub>64</sub>	2 <sup>13</sup> / <sub>16</sub>	0.157	23/ <sub>64</sub>	5/ <sub>8</sub>	0.8661	0.236	2 <sup>7</sup> / <sub>32</sub>	5/ <sub>16</sub>	
17  11/ <sub>16</sub>	<b>ASRPF203</b>	90	71.5	4	9	16	22	6	56	M8	
	<b>ASRPF203-011</b>	3 <sup>35</sup> / <sub>64</sub>	2 <sup>13</sup> / <sub>16</sub>	0.157	23/ <sub>64</sub>	5/ <sub>8</sub>	0.8661	0.236	2 <sup>7</sup> / <sub>32</sub>	5/ <sub>16</sub>	
20  3/4	<b>ASRPF204</b>	95	76	4	9	18	25	7	60	M8	
	<b>ASRPF204-012</b>	3 <sup>3</sup> / <sub>4</sub>	2 <sup>63</sup> / <sub>64</sub>	0.157	23/ <sub>64</sub>	23/ <sub>32</sub>	0.9843	0.276	2 <sup>3</sup> / <sub>8</sub>	5/ <sub>16</sub>	
25  13/ <sub>16</sub> 7/ <sub>8</sub> 15/ <sub>16</sub> 1	<b>ASRPF205</b>	113	90.5	5.2	11	18	27	7.5	71	M10	
	<b>ASRPF205-013</b>										
	<b>ASRPF205-014</b>	4 <sup>7</sup> / <sub>16</sub>	3 <sup>9</sup> / <sub>16</sub>	0.205	7/ <sub>16</sub>	23/ <sub>32</sub>	1.0630	0.295	2 <sup>13</sup> / <sub>16</sub>	3/ <sub>8</sub>	
	<b>ASRPF205-015</b> <b>ASRPF205-100</b>										
30  1 1/ <sub>16</sub> 1 1/ <sub>8</sub> 1 3/ <sub>16</sub> 1 1/ <sub>4</sub>	<b>ASRPF206</b>	122	100	5.2	11	20	29	8	81	M10	
	<b>ASRPF206-101</b>										
	<b>ASRPF206-102</b>	4 <sup>13</sup> / <sub>16</sub>	3 <sup>15</sup> / <sub>16</sub>	0.205	7/ <sub>16</sub>	25/ <sub>32</sub>	1.1417	0.315	3 <sup>3</sup> / <sub>16</sub>	3/ <sub>8</sub>	
	<b>ASRPF206-103</b> <b>ASRPF206-104</b>										

**Note** (1) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.

**Remarks** When an anti-vibration rubber ring is used, the self alignment capability will be reduce.

Max. load (1) recommended		Bearing number	Housing number		Mass of unit  kg lb
N lbf			rubber ring	steel	
radial	axial				
1 000 220	200 40	AS201	R201	PF204	0.2
		AS201-008	R201	PF204	0.4
1 000 220	200 40	AS202	R201	PF204	0.2
		AS202-009 AS202-010	R201	PF204	0.4
1 000 220	200 40	AS203	R201	PF204	0.2
		AS203-011	R201	PF204	0.4
1 150 250	200 40	AS204	R204	PF205	0.2
		AS204-012	R204	PF205	0.4
1 300 280	200 40	AS205	R205	PF206	0.3
		AS205-013	R205	PF206	
		AS205-014	R205	PF206	0.7
		AS205-015 AS205-100	R205	PF206	
1 500 330	200 40	AS206	R206	PF207	0.5
		AS206-101	R206	PF207	
		AS206-102	R206	PF207	1.1
		AS206-103 AS206-104	R206	PF207	

## Rhombus flanged unit, pressed steel housing Set screw type




Shaft dia.  mm inch	Unit number	Nominal dimensions										Bolt size  mm inch
		H	J	A <sub>1</sub>	N	mm		L	B	S	H <sub>1</sub> min.	
						A	A					
12 1/2	<b>ASPFL201</b> <b>ASPFL201-008</b>	81 3 3/16	63.5 2 1/2	4 0.157	7.1 9/32	14 9/16	59 2 5/16	22 0.8661	6 0.236	49 1 15/16	M6 1/4	
15 9/16 5/8	<b>ASPFL202</b> <b>ASPFL202-009</b> <b>ASPFL202-010</b>	81 3 3/16	63.5 2 1/2	4 0.157	7.1 9/32	14 9/16	59 2 5/16	22 0.8661	6 0.236	49 1 15/16	M6 1/4	
17 11/16	<b>ASPFL203</b> <b>ASPFL203-011</b>	81 3 3/16	63.5 2 1/2	4 0.157	7.1 9/32	14 9/16	59 2 5/16	22 0.8661	6 0.236	49 1 15/16	M6 1/4	
20 3/4	<b>ASPFL204</b> <b>ASPFL204-012</b>	90 3 5/8	71.5 2 13/16	4 0.157	9 23/64	16 5/8	67 2 5/8	25 0.9843	7 0.276	56 27/32	M8 5/16	
25 13/16 7/8 15/16 1	<b>ASPFL205</b> <b>ASPFL205-013</b> <b>ASPFL205-014</b> <b>ASPFL205-015</b> <b>ASPFL205-100</b>	95 3 3/4	76 2 63/64	4 0.157	9 23/64	18 23/32	71 2 25/32	27 1.0630	7.5 0.295	60 2 3/8	M8 5/16	
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>ASPFL206</b> <b>ASPFL206-101</b> <b>ASPFL206-102</b> <b>ASPFL206-103</b> <b>ASPFL206-104</b>	113 4 7/16	90.5 3 9/16	5.2 0.205	11 7/16	18 23/32	84 3 5/16	29 1.1417	8 0.315	71 2 13/16	M10 3/8	
35 1 1/4 1 5/16 1 3/8 1 1/2	<b>ASPFL207</b> <b>ASPFL207-104</b> <b>ASPFL207-105</b> <b>ASPFL207-106</b> <b>ASPFL207-107</b>	122 4 13/16	100 3 15/16	5.2 0.205	11 7/16	20 25/32	94 3 11/16	34 1.3386	8.5 0.335	81 3 3/16	M10 3/8	
40 1 1/2 1 9/16	<b>ASPFL208</b> <b>ASPFL208-108</b> <b>ASPFL208-109</b>	148 5 53/64	119 4 11/16	6.8 0.268	13.5 17/32	21 53/64	100 3 15/16	38 1.4961	9 0.354	91 3 19/32	M12 1/2	

Note (1) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.

Max. load (1)		Bearing number	Housing number	Mass of unit
N lbf				
radial	axial			
2 700 600	1 350 300	AS201 AS201-008	PFL203 PFL203	0.2 0.4
2 700 600	1 350 300	AS202 AS202-009 AS202-010	PFL203 PFL203 PFL203	0.2 0.4
2 700 600	1 350 300	AS203 AS203-011	PFL203 PFL203	0.2 0.4
3 000 660	1 500 330	AS204 AS204-012	PFL204 PFL204	0.2 0.4
4 000 880	2 000 440	AS205 AS205-013 AS205-014 AS205-015 AS205-100	PFL205 PFL205 PFL205 PFL205	0.3 0.7
5 000 1 100	2 500 550	AS206 AS206-101 AS206-102 AS206-103 AS206-104	PFL206 PFL206 PFL206 PFL206	0.4 0.9
6 000 1 300	3 000 650	AS207 AS207-104 AS207-105 AS207-106 AS207-107	PFL207 PFL207 PFL207 PFL207	0.6 1.3
6 000 1 300	3 000 650	AS208 AS208-108 AS208-109	PFL208 PFL208 PFL208	0.8 1.8

# UCHB2

## Hanger unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions									
		mm inch									
		L	H <sub>1</sub>	c	A	H	N	D	j	B	S
12 1/2	UCHB201D1	64	96	0	21	64	Rp 3/4	40	19	31	12.7
	UCHB201-008D1	2 17/32	3 25/32	0	13/16	2 33/64	Rp 3/4	1 9/16	3/4	1.2205	0.500
15 9/16 5/8	UCHB202D1	64	96	0	21	64	Rp 3/4	40	19	31	12.7
	UCHB202-009D1	2 17/32	3 25/32	0	13/16	2 33/64	Rp 3/4	1 9/16	3/4	1.2205	0.500
	UCHB202-010D1										
17 11/16	UCHB203D1	64	96	0	21	64	Rp 3/4	40	19	31	12.7
	UCHB203-011D1	2 17/32	3 25/32	0	13/16	2 33/64	Rp 3/4	1 9/16	3/4	1.2205	0.500
20 3/4	UCHB204D1	64	96	0	21	64	Rp 3/4	40	19	31	12.7
	UCHB204-012D1	2 17/32	3 25/32	0	13/16	2 33/64	Rp 3/4	1 9/16	3/4	1.2205	0.500
25 13/16 7/8 15/16 1	UCHB205D1	78	103	0	24	64	Rp 3/4	40	19	34.1	14.3
	UCHB205-013D1										
	UCHB205-014D1	3 1/16	4 1/16	0	15/16	2 33/64	Rp 3/4	1 9/16	3/4	1.3425	0.563
	UCHB205-015D1										
30 1 1/16 1 1/8 1 3/16 1 1/4	UCHB206D1	78	103	0	28	64	Rp 3/4	40	19	38.1	15.9
	UCHB206-101D1										
	UCHB206-102D1	3 1/16	4 1/16	0	1 3/32	2 33/64	Rp 3/4	1 9/16	3/4	1.5000	0.626
	UCHB206-103D1										
35 1 1/4 1 5/16 1 3/8 1 7/16	UCHB207D1	92	116	0	30	70	Rp 3/4	40	19	42.9	17.5
	UCHB207-104D1										
	UCHB207-105D1	3 5/8	4 9/16	0	1 3/16	2 3/4	Rp 3/4	1 9/16	3/4	1.6890	0.689
	UCHB207-106D1										
40 1 1/2 1 9/16	UCHB208D1	96	121	2	33	73	Rp 3/4	40	19	49.2	19
	UCHB208-108D1	3 25/32	4 3/4	3/32	1 5/16	2 7/8	Rp 3/4	1 9/16	3/4	1.9370	0.748
	UCHB208-109D1										

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Nominal Designation of Thread N	Nominal dimensions mm				
	Major Diameter of Internal Thread	Pitch Diameter	Minor Diameter of Internal Thread	Tolerances	Mounting Bolt size
Rp 3/4 (PS 3/4)	26.441	25.279	24.117	±0.142	R 3/4 (PT 3/4)
Rp 1 (PS 1)	33.249	31.770	30.291	±0.181	R 1 (PT 1)
Rp 1 1/4 (PS 1 1/4)	41.910	40.431	38.952	±0.181	R 1 1/4 (PT 1 1/4)
Rp 1 1/2 (PS 1 1/2)	47.803	46.324	44.845	±0.181	R 1 1/2 (PT 1 1/2)

Bearing number	Housing number	Mass of unit kg lb
UC201D1	HB204D1	1.0
UC201-008D1	HB204D1	2.2
UC202D1	HB204D1	0.9
UC202-009D1	HB204D1	2.0
UC202-010D1	HB204D1	
UC203D1	HB204D1	0.9
UC203-011D1	HB204D1	2.0
UC204D1	HB204D1	0.9
UC204-012D1	HB204D1	2.0
UC205D1	HB205D1	0.9
UC205-013D1	HB205D1	
UC205-014D1	HB205D1	2.0
UC205-015D1	HB205D1	
UC205-100D1	HB205D1	
UC206D1	HB206D1	0.8
UC206-101D1	HB206D1	
UC206-102D1	HB206D1	1.8
UC206-103D1	HB206D1	
UC206-104D1	HB206D1	
UC207D1	HB207D1	1.2
UC207-104D1	HB207D1	
UC207-105D1	HB207D1	2.6
UC207-106D1	HB207D1	
UC207-107D1	HB207D1	
UC208D1	HB208D1	1.3
UC208-108D1	HB208D1	2.9
UC208-109D1	HB208D1	

## Hanger unit, cast housing Set screw type



Shaft dia. mm inch	Unit number <sup>(1)</sup>	Nominal dimensions									
		mm inch									
		<i>L</i>	<i>H</i> <sub>1</sub>	<i>c</i>	<i>A</i>	<i>H</i>	<i>N</i>	<i>D</i>	<i>j</i>	<i>B</i>	<i>S</i>
45 1 5/8 1 11/16 1 3/4	<b>UCHB209D1</b> <b>UCHB209-110D1</b> <b>UCHB209-111D1</b> <b>UCHB209-112D1</b>	108 4 1/4	136 5 11/32	5 3/16	35 1 3/8	82 3 15/64	Rp1 Rp1	48 1 7/8	21 13/16	49.2 1.9370	19 0.748
50 1 13/16 1 7/8 1 15/16 2	<b>UCHB210D1</b> <b>UCHB210-113D1</b> <b>UCHB210-114D1</b> <b>UCHB210-115D1</b> <b>UCHB210-200D1</b>	118 4 21/32	142 5 19/32	5 3/16	37 1 15/32	83 3 17/64	Rp1 Rp1	48 1 7/8	21 13/16	51.6 2.0315	19 0.748
55 2 2 1/16 2 1/8 2 3/16	<b>UCHB211D1</b> <b>UCHB211-200D1</b> <b>UCHB211-201D1</b> <b>UCHB211-202D1</b> <b>UCHB211-203D1</b>	126 4 31/32	158 6 7/32	7 9/32	38 1 1/2	95 3 47/64	Rp1 1/4 Rp1 1/4	60 2 3/8	25 31/32	55.6 2.1890	22.2 0.874
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UCHB212D1</b> <b>UCHB212-204D1</b> <b>UCHB212-205D1</b> <b>UCHB212-206D1</b> <b>UCHB212-207D1</b>	142 5 19/32	173 6 13/16	9 11/32	42 1 21/32	102 4 1/64	Rp1 1/4 Rp1 1/4	60 2 3/8	28 1 3/32	65.1 2.5630	25.4 1.000
65 2 1/2	<b>UCHB213D1</b> <b>UCHB213-208D1</b>	166 6 17/32	200 7 7/8	9.5 3/8	44 1 23/32	117 4 39/64	Rp1 1/2 Rp1 1/2	70 2 3/4	32 1 1/4	65.1 2.5630	25.4 1.000

Note <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Nominal Designation of Thread <i>N</i>	Nominal dimensions mm				
	Major Diameter of Internal Thread	Pitch Diameter	Minor Diameter of Internal Thread	Tolerances	Mounting Bolt size
Rp 3/4 (PS 3/4)	26.441	25.279	24.117	±0.142	R 3/4 (PT 3/4)
Rp1 (PS1)	33.249	31.770	30.291	±0.181	R1 (PT1)
Rp1 1/4 (PS1 1/4)	41.910	40.431	38.952	±0.181	R1 1/4 (PT1 1/4)
Rp1 1/2 (PS1 1/2)	47.803	46.324	44.845	±0.181	R1 1/2 (PT1 1/2)

Bearing number	Housing number	Mass of unit kg lb
UC209D1	HB209D1	1.8
UC209-110D1	HB209D1	4.0
UC209-111D1	HB209D1	4.0
UC209-112D1	HB209D1	4.0
UC210D1	HB210D1	2.2
UC210-113D1	HB210D1	4.9
UC210-114D1	HB210D1	4.9
UC210-115D1	HB210D1	4.9
UC210-200D1	HB210D1	4.9
UC211D1	HB211D1	2.8
UC211-200D1	HB211D1	6.2
UC211-201D1	HB211D1	6.2
UC211-202D1	HB211D1	6.2
UC211-203D1	HB211D1	6.2
UC212D1	HB212D1	3.7
UC212-204D1	HB212D1	8.2
UC212-205D1	HB212D1	8.2
UC212-206D1	HB212D1	8.2
UC212-207D1	HB212D1	8.2
UC213D1	HB213D1	5.7
UC213-208D1	HB213D1	13

## Take-up unit, cast housing Set screw type



Pressed steel dust cover type  
Open end **Z-UCT...D1**  
Closed end **ZM-UCT...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions															
		mm inch															
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B$	$S$
12 1/2	<b>UCT201D1</b> <b>UCT201-008D1</b>	16 5/8	12 15/32	51 2	32 1 1/4	19 3/4	51 2	12 0.472	76 2 63/64	89 3 1/2	94 3 1/16	21 13/16	32 1 1/4	33 1 5/16	61 2 13/32	31 1.2205	12.7 0.500
15 9/16 5/8	<b>UCT202D1</b> <b>UCT202-009D1</b> <b>UCT202-010D1</b>	16 5/8	12 15/32	51 2	32 1 1/4	19 3/4	51 2	12 0.472	76 2 63/64	89 3 1/2	94 3 1/16	21 13/16	32 1 1/4	33 1 5/16	61 2 13/32	31 1.2205	12.7 0.500
17 11/16	<b>UCT203D1</b> <b>UCT203-011D1</b>	16 5/8	12 15/32	51 2	32 1 1/4	19 3/4	51 2	12 0.472	76 2 63/64	89 3 1/2	94 3 1/16	21 13/16	32 1 1/4	33 1 5/16	61 2 13/32	31 1.2205	12.7 0.500
20 3/4	<b>UCT204D1</b> <b>UCT204-012D1</b>	16 5/8	12 15/32	51 2	32 1 1/4	19 3/4	51 2	12 0.472	76 2 63/64	89 3 1/2	94 3 1/16	21 13/16	32 1 1/4	33 1 5/16	61 2 13/32	31 1.2205	12.7 0.500
25 13/16 7/8 15/16 1	<b>UCT205D1</b> <b>UCT205-013D1</b> <b>UCT205-014D1</b> <b>UCT205-015D1</b> <b>UCT205-100D1</b>	16 5/8	12 15/32	51 2	32 1 1/4	19 3/4	51 2	12 0.472	76 2 63/64	89 3 1/2	97 3 13/16	24 15/16	32 1 1/4	35 1 3/8	62 2 7/16	34.1 1.3425	14.3 0.563
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UCT206D1</b> <b>UCT206-101D1</b> <b>UCT206-102D1</b> <b>UCT206-103D1</b> <b>UCT206-104D1</b>	16 5/8	12 15/32	56 2 7/32	37 1 15/32	22 7/8	57 2 1/4	12 0.472	89 3 1/2	102 4 1/32	113 4 7/16	28 1 3/32	37 1 15/32	43 1 11/16	70 2 3/4	38.1 1.5000	15.9 0.626
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UCT207D1</b> <b>UCT207-104D1</b> <b>UCT207-105D1</b> <b>UCT207-106D1</b> <b>UCT207-107D1</b>	16 5/8	15 19/32	64 2 17/32	37 1 15/32	22 7/8	64 2 17/32	12 0.472	89 3 1/2	102 4 1/32	129 5 3/32	30 1 3/16	37 1 3/16	51 1 5/32	78 2	42.9 1.6890	17.5 0.689
40 1 1/2 1 9/16	<b>UCT208D1</b> <b>UCT208-108D1</b> <b>UCT208-109D1</b>	19 3/4	18 23/32	83 3 9/32	49 1 15/16	29 1 5/32	83 3 9/32	16 0.630	102 4 1/64	114 4 1/2	144 5 21/32	33 1 5/16	49 1 15/16	56 2 7/32	88 3 15/32	49.2 1.9370	19 0.748

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type  
Open end **C-UCT...D1**  
Closed end **CM-UCT...D1**

Bearing number	Housing number	Unit number (1) pressed steel dust cover type	Unit number (1) cast dust cover type	Nominal dimensions				Mass of unit		
				mm inch				kg lb		
				$t$ max.	$A_4$	$L_4$	$A_5$	UCT	Z(ZM)	C(CM)
UC201D1 UC201-008D1	T204D1 T204D1	<b>Z(ZM)-UCT201D1</b> <b>Z(ZM)-UCT201-008D1</b>	<b>C(CM)-UCT201D1</b> <b>C(CM)-UCT201-008D1</b>	2 5/64	45 1 25/32	97 3 13/16	62 2 7/16	0.6 1.3	0.8 1.8	1.1 2.4
UC202D1 UC202-009D1 UC202-010D1	T204D1 T204D1 T204D1	<b>Z(ZM)-UCT202D1</b> <b>Z(ZM)-UCT202-009D1</b> <b>Z(ZM)-UCT202-010D1</b>	<b>C(CM)-UCT202D1</b> <b>C(CM)-UCT202-009D1</b> <b>C(CM)-UCT202-010D1</b>	2 5/64	45 1 25/32	97 3 13/16	62 2 7/16	0.6 1.3	0.8 1.8	1.1 2.4
UC203D1 UC203-011D1	T204D1 T204D1	<b>Z(ZM)-UCT203D1</b> <b>Z(ZM)-UCT203-011D1</b>	<b>C(CM)-UCT203D1</b> <b>C(CM)-UCT203-011D1</b>	2 5/64	45 1 35/32	97 3 13/16	62 2 7/16	0.6 1.3	0.8 1.8	1.0 2.2
UC204D1 UC204-012D1	T204D1 T204D1	<b>Z(ZM)-UCT204D1</b> <b>Z(ZM)-UCT204-012D1</b>	<b>C(CM)-UCT204D1</b> <b>C(CM)-UCT204-012D1</b>	2 5/64	45 1 25/32	97 3 13/16	62 2 7/16	0.6 1.3	0.8 1.8	1.0 2.2
UC205D1 UC205-013D1 UC205-014D1 UC205-015D1 UC205-100D1	T205D1 T205D1 T205D1 T205D1 T205D1	<b>Z(ZM)-UCT205D1</b> <b>Z(ZM)-UCT205-013D1</b> <b>Z(ZM)-UCT205-014D1</b> <b>Z(ZM)-UCT205-015D1</b> <b>Z(ZM)-UCT205-100D1</b>	<b>C(CM)-UCT205D1</b> <b>C(CM)-UCT205-013D1</b> <b>C(CM)-UCT205-014D1</b> <b>C(CM)-UCT205-015D1</b> <b>C(CM)-UCT205-100D1</b>	2 5/64	48 1 29/32	100.5 3 31/32	70 2 3/4	0.8 1.8	0.9 2.0	1.1 2.4
UC206D1 UC206-101D1 UC206-102D1 UC206-103D1 UC206-104D1	T206D1 T206D1 T206D1 T206D1 T206D1	<b>Z(ZM)-UCT206D1</b> <b>Z(ZM)-UCT206-101D1</b> <b>Z(ZM)-UCT206-102D1</b> <b>Z(ZM)-UCT206-103D1</b> —	<b>C(CM)-UCT206D1</b> <b>C(CM)-UCT206-101D1</b> <b>C(CM)-UCT206-102D1</b> <b>C(CM)-UCT206-103D1</b> <b>C(CM)-UCT206-104D1</b>	2 5/64	53 2 3/32	113.5 4 15/32	75 2 15/16	1.3 2.9	1.3 2.9	1.7 3.7
UC207D1 UC207-104D1 UC207-105D1 UC207-106D1 UC207-107D1	T207D1 T207D1 T207D1 T207D1 T207D1	<b>Z(ZM)-UCT207D1</b> <b>Z(ZM)-UCT207-104D1</b> <b>Z(ZM)-UCT207-105D1</b> <b>Z(ZM)-UCT207-106D1</b> —	<b>C(CM)-UCT207D1</b> <b>C(CM)-UCT207-104D1</b> <b>C(CM)-UCT207-105D1</b> <b>C(CM)-UCT207-106D1</b> <b>C(CM)-UCT207-107D1</b>	3 1/8	60 2 11/32	129 5 3/32	80 3 5/32	1.6 3.5	1.7 3.7	2.1 4.6
UC208D1 UC208-108D1 UC208-109D1	T208D1 T208D1 T208D1	<b>Z(ZM)-UCT208D1</b> <b>Z(ZM)-UCT208-108D1</b> <b>Z(ZM)-UCT208-109D1</b>	<b>C(CM)-UCT208D1</b> <b>C(CM)-UCT208-108D1</b> <b>C(CM)-UCT208-109D1</b>	3 1/8	69 2 23/32	144 5 21/32	90 3 17/32	2.4 5.3	2.5 5.5	3.1 6.8



## Take-up unit, cast housing Set screw type



Pressed steel dust cover type  
Open end **Z-UCT...D1**  
Closed end **ZM-UCT...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions															
		mm inch															
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B$	$S$
45 1 5/8 1 11/16 1 3/4	UCT209D1 UCT209-110D1 UCT209-111D1 UCT209-112D1	19	18	83	49	29	83	16	102	117	145	35	49	57	88	49.2	19
		3/4	23/32	3 9/32	1 15/16	1 5/32	3 9/32	0.630	4 1/64	4 19/32	5 29/32	1 3/8	1 15/16	2 1/4	3 15/32	1.9370	0.748
50 1 13/16 1 7/8 1 15/16 2	UCT210D1 UCT210-113D1 UCT210-114D1 UCT210-115D1 UCT210-200D1	19	18	83	49	29	86	16	102	117	151	37	49	59	92	51.6	19
		3/4	23/32	3 9/32	1 15/16	1 5/32	3 3/8	0.630	4 1/64	4 19/32	5 15/16	1 15/32	1 15/16	2 5/8	3 5/8	2.0315	0.748
55 2 2 1/16 2 1/8 2 3/16	UCT211D1 UCT211-200D1 UCT211-201D1 UCT211-202D1 UCT211-203D1	25	21	102	64	35	95	22	130	146	171	38	64	65	106	55.6	22.2
		3 1/32	1 3/16	4 1/32	2 17/32	1 3/8	3 3/4	0.866	5 1/8	5 3/4	6 23/32	1 1/2	2 17/32	2 9/16	4 3/16	2.1890	0.874
60 2 1/4 2 7/16 2 3/8 2 7/16	UCT212D1 UCT212-204D1 UCT212-205D1 UCT212-206D1 UCT212-207D1	32	21	102	64	35	102	22	130	146	194	42	64	75	119	65.1	25.4
		1 1/4	1 3/16	4 1/32	2 17/32	1 3/8	4 1/32	0.866	5 1/8	5 3/4	7 5/8	1 21/32	2 17/32	2 15/16	4 11/16	2.5630	1.000
65 2 1/2 2 9/16	UCT213D1 UCT213-208D1 UCT213-209D1	32	23	111	70	41	121	26	151	167	224	44	70	87	137	65.1	25.4
		1 1/4	29/32	4 3/8	2 3/4	1 5/8	4 3/4	1.024	5 15/16	6 9/16	8 13/16	1 29/32	2 3/4	3 7/16	5 13/32	2.5630	1.000
70 2 5/8 2 11/16 2 3/4	UCT214D1 UCT214-210D1 UCT214-211D1 UCT214-212D1	32	23	111	70	41	121	26	151	167	224	46	70	87	137	74.6	30.2
		1 1/4	29/32	4 3/8	2 3/4	1 5/8	4 3/4	1.024	5 15/16	6 9/16	8 13/16	1 13/16	2 3/4	3 7/16	5 13/32	2.9370	1.189

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type  
Open end **C-UCT...D1**  
Closed end **CM-UCT...D1**

Bearing number	Housing number	Unit number (1) pressed steel dust cover type	Unit number (1) cast dust cover type	Nominal dimensions				Mass of unit		
				mm inch				kg lb		
				$t$ max.	$A_4$	$L_4$	$A_5$	UCT	Z(ZM)	C(CM)
UC209D1 UC209-110D1 UC209-111D1 UC209-112D1	T209D1 T209D1 T209D1 T209D1	Z(ZM)-UCT209D1 Z(ZM)-UCT209-110D1 Z(ZM)-UCT209-111D1 Z(ZM)-UCT209-112D1	C(CM)-UCT209D1 C(CM)-UCT209-110D1 C(CM)-UCT209-111D1 C(CM)-UCT209-112D1	3 1/8	69 2 23/32	145.5 5 23/32	95 3 3/4	2.4 5.3	2.5 5.5	3.3 7.3
UC210D1 UC210-113D1 UC210-114D1 UC210-115D1 UC210-200D1	T210D1 T210D1 T210D1 T210D1 T210D1	Z(ZM)-UCT210D1 Z(ZM)-UCT210-113D1 Z(ZM)-UCT210-114D1 Z(ZM)-UCT210-115D1 —	C(CM)-UCT210D1 C(CM)-UCT210-113D1 C(CM)-UCT210-114D1 C(CM)-UCT210-115D1 C(CM)-UCT210-200D1	3 1/8	76 3	152 5 31/32	100 3 15/16	2.6 5.7	2.7 6.0	3.6 7.9
UC211D1 UC211-200D1 UC211-201D1 UC211-202D1 UC211-203D1	T211D1 T211D1 T211D1 T211D1 T211D1	Z(ZM)-UCT211D1 Z(ZM)-UCT211-200D1 Z(ZM)-UCT211-201D1 Z(ZM)-UCT211-202D1 Z(ZM)-UCT211-203D1	C(CM)-UCT211D1 C(CM)-UCT211-200D1 C(CM)-UCT211-201D1 C(CM)-UCT211-202D1 C(CM)-UCT211-203D1	4 5/32	77 3 1/32	171.5 6 3/4	100 3 15/16	3.9 8.6	4.1 9.0	5.0 11
UC212D1 UC212-204D1 UC212-205D1 UC212-206D1 UC212-207D1	T212D1 T212D1 T212D1 T212D1 T212D1	Z(ZM)-UCT212D1 Z(ZM)-UCT212-204D1 Z(ZM)-UCT212-205D1 Z(ZM)-UCT212-206D1 —	C(CM)-UCT212D1 C(CM)-UCT212-204D1 C(CM)-UCT212-205D1 C(CM)-UCT212-206D1 C(CM)-UCT212-207D1	4 5/32	89 3 1/2	194 7 5/8	115 4 17/32	4.8 11	5.1 11	6.1 13
UC213D1 UC213-208D1 UC213-209D1	T213D1 T213D1 T213D1	Z(ZM)-UCT213D1 Z(ZM)-UCT213-208D1 Z(ZM)-UCT213-209D1	C(CM)-UCT213D1 C(CM)-UCT213-208D1 C(CM)-UCT213-209D1	4 5/32	91 3 19/32	224 8 13/16	120 4 23/32	7.0 15	7.3 16	8.4 19
UC214D1 UC214-210D1 UC214-211D1 UC214-212D1	T214D1 T214D1 T214D1 T214D1	— — — —	C(CM)-UCT214D1 C(CM)-UCT214-201D1 C(CM)-UCT214-211D1 C(CM)-UCT214-212D1	4 5/32	— —	224 8 13/16	135 5 5/16	7.0 15	— —	9.1 20

## Take-up unit, cast housing Set screw type




Pressed steel dust cover type  
Open end **Z-UCT...D1**  
Closed end **ZM-UCT...D1**

Shaft dia. mm inch	Unit number (1)	Nominal dimensions															
		mm inch															
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B$	$S$
75 2 <sup>13</sup> / <sub>16</sub> 2 <sup>7</sup> / <sub>8</sub> 2 <sup>15</sup> / <sub>16</sub> 3	<b>UCT215D1</b> <b>UCT215-213D1</b> <b>UCT215-214D1</b> <b>UCT215-215D1</b> <b>UCT215-300D1</b>	32	23	111	70	41	121	26	151	167	232	48	70	92	140	77.8	33.3
80 3 <sup>1</sup> / <sub>16</sub> 3 <sup>1</sup> / <sub>8</sub> 3 <sup>3</sup> / <sub>16</sub>	<b>UCT216D1</b> <b>UCT216-301D1</b> <b>UCT216-302D1</b> <b>UCT216-303D1</b>	32	23	111	70	41	121	26	165	184	235	51	70	95	140	82.6	33.3
85 3 <sup>1</sup> / <sub>4</sub> 3 <sup>5</sup> / <sub>16</sub> 3 <sup>7</sup> / <sub>16</sub>	<b>UCT217D1</b> <b>UCT217-304D1</b> <b>UCT217-305D1</b> <b>UCT217-307D1</b>	38	31	124	73	48	157	30	173	198	260	54	73	98	162	85.7	34.1
		1 <sup>1</sup> / <sub>2</sub>	1 <sup>1</sup> / <sub>32</sub>	4 <sup>7</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>8</sub>	6 <sup>3</sup> / <sub>16</sub>	1.181	6 <sup>13</sup> / <sub>16</sub>	7 <sup>25</sup> / <sub>32</sub>	10 <sup>1</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>8</sub>	3 <sup>27</sup> / <sub>32</sub>	6 <sup>3</sup> / <sub>8</sub>	3.3740	1.343

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type  
Open end **C-UCT...D1**  
Closed end **CM-UCT...D1**

Bearing number	Housing number	Unit number (1) pressed steel dust cover type	Unit number (1) cast dust cover type	Nominal dimensions					Mass of unit		
				mm inch					kg lb		
				$t$ max.	$A_4$	$L_4$	$A_5$	UCT	Z(ZM)	C(CM)	
UC215D1 UC215-213D1 UC215-214D1 UC215-215D1 UC215-300D1	T215D1 T215D1 T215D1 T215D1 T215D1	— — — — —	<b>C(CM)-UCT215D1</b> <b>C(CM)-UCT215-213D1</b> <b>C(CM)-UCT215-214D1</b> <b>C(CM)-UCT215-215D1</b> <b>C(CM)-UCT215-300D1</b>	4     5 <sup>5</sup> / <sub>32</sub>	—     —	232     9 <sup>1</sup> / <sub>8</sub>	135     5 <sup>5</sup> / <sub>16</sub>	7.4     16	—     —	9.8     22	
UC216D1 UC216-301D1 UC216-302D1 UC216-303D1	T216D1 T216D1 T216D1 T216D1	— — — —	<b>C(CM)-UCT216D1</b> <b>C(CM)-UCT216-301D1</b> <b>C(CM)-UCT216-302D1</b> <b>C(CM)-UCT216-303D1</b>	4    5 <sup>5</sup> / <sub>32</sub>	—    —	235    9 <sup>1</sup> / <sub>4</sub>	145    5 <sup>23</sup> / <sub>32</sub>	8.2    18	—    —	11    24	
UC217D1 UC217-304D1 UC217-305D1 UC217-307D1	T217D1 T217D1 T217D1 T217D1	— — — —	<b>C(CM)-UCT217D1</b> <b>C(CM)-UCT217-304D1</b> <b>C(CM)-UCT217-305D1</b> <b>C(CM)-UCT217-307D1</b>	5    13 <sup>3</sup> / <sub>64</sub>	—    —	260    10 <sup>1</sup> / <sub>4</sub>	155    6 <sup>3</sup> / <sub>32</sub>	11    24	—    —	14    31	

## Take-up unit, cast housing Set screw type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions															
		mm inch															
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B$	$S$
25 13/16 7/8 15/16 1	<b>UCT305D1</b> <b>UCT305-013D1</b> <b>UCT305-014D1</b> <b>UCT305-015D1</b> <b>UCT305-100D1</b>	16	14	62	36	26	65	12	80	89	122	26	36	46	76	38	15
		5/8	9/16	27/16	113/32	11/32	29/16	0.472	35/32	31/2	413/16	11/32	113/32	113/16	3	1.4961	0.591
30 1 1/16 1 1/8 1 3/16	<b>UCT306D1</b> <b>UCT306-101D1</b> <b>UCT306-102D1</b> <b>UCT306-103D1</b>	18	16	70	41	28	74	16	90	100	137	28	41	52	85	43	17
		23/32	5/8	23/4	15/8	13/32	229/32	0.630	335/64	315/16	513/32	13/32	15/8	21/16	311/32	1.6929	0.669
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UCT307D1</b> <b>UCT307-104D1</b> <b>UCT307-105D1</b> <b>UCT307-106D1</b> <b>UCT307-107D1</b>	20	17	75	45	30	80	16	100	111	150	32	45	56	94	48	19
		25/32	21/32	215/16	125/32	13/16	35/32	0.630	315/16	43/8	529/32	1/4	125/32	27/32	311/16	1.8898	0.748
40 1 1/2 1 9/16	<b>UCT308D1</b> <b>UCT308-108D1</b> <b>UCT308-109D1</b>	22	19	83	50	32	89	18	112	124	162	34	50	62	100	52	19
		7/8	3/4	39/32	131/32	11/4	31/2	0.709	413/32	47/8	63/8	111/32	131/32	27/16	315/16	2.0472	0.748
45 1 5/8 1 11/16 1 3/4	<b>UCT309D1</b> <b>UCT309-110D1</b> <b>UCT309-111D1</b> <b>UCT309-112D1</b>	24	20	90	55	34	97	18	125	138	178	38	55	68	110	57	22
		15/16	25/32	317/32	25/32	111/32	313/16	0.709	459/64	57/16	7	11/2	25/32	211/16	411/32	2.2441	0.866
50 1 13/16 1 7/8 1 15/16	<b>UCT310D1</b> <b>UCT310-113D1</b> <b>UCT310-114D1</b> <b>UCT310-115D1</b>	27	22	98	61	37	106	20	140	151	192	40	61	74	118	61	22
		11/16	7/8	327/32	213/32	115/32	43/16	0.787	533/64	515/16	73/16	19/16	213/32	229/32	421/32	2.4016	0.866

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Cast dust cover type  
Open end **C-UCT...D1**  
Closed end **CM-UCT...D1**


Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			$t$ max.	$L_4$	$A_5$	UCT	C(CM)
UC305D1 UC305-013D1 UC305-014D1 UC305-015D1 UC305-100D1	T305D1 T305D1 T305D1 T305D1 T305D1	<b>C(CM)-UCT305D1</b> <b>C(CM)-UCT305-013D1</b> <b>C(CM)-UCT305-014D1</b> <b>C(CM)-UCT305-015D1</b> <b>C(CM)-UCT305-100D1</b>	2 5/64	122 413/16	80 35/32	1.4 3.1	1.7 3.7
UC306D1 UC306-101D1 UC306-102D1 UC306-103D1	T306D1 T306D1 T306D1 T306D1	<b>C(CM)-UCT306D1</b> <b>C(CM)-UCT306-101D1</b> <b>C(CM)-UCT306-102D1</b> <b>C(CM)-UCT306-103D1</b>	2 5/64	139 515/32	85 311/32	1.8 4.0	2.4 5.3
UC307D1 UC307-104D1 UC307-105D1 UC307-106D1 UC307-107D1	T307D1 T307D1 T307D1 T307D1 T307D1	<b>C(CM)-UCT307D1</b> <b>C(CM)-UCT307-104D1</b> <b>C(CM)-UCT307-105D1</b> <b>C(CM)-UCT307-106D1</b> <b>C(CM)-UCT307-107D1</b>	3 1/8	152 531/32	95 33/4	2.3 5.1	3.2 7.1
UC308D1 UC308-108D1 UC308-109D1	T308D1 T308D1 T308D1	<b>C(CM)-UCT308D1</b> <b>C(CM)-UCT308-108D1</b> <b>C(CM)-UCT308-109D1</b>	3 1/8	164 615/32	105 41/8	3.0 6.6	4.2 9.3
UC309D1 UC309-110D1 UC309-111D1 UC309-112D1	T309D1 T309D1 T309D1 T309D1	<b>C(CM)-UCT309D1</b> <b>C(CM)-UCT309-110D1</b> <b>C(CM)-UCT309-111D1</b> <b>C(CM)-UCT309-112D1</b>	3 1/8	181 71/8	110 411/32	4.0 8.8	5.4 12
UC310D1 UC310-113D1 UC310-114D1 UC310-115D1	T310D1 T310D1 T310D1 T310D1	<b>C(CM)-UCT310D1</b> <b>C(CM)-UCT310-113D1</b> <b>C(CM)-UCT310-114D1</b> <b>C(CM)-UCT310-115D1</b>	3 1/8	197 73/4	120 423/32	5.0 11	7.0 15

## Take-up unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions															
		mm inch															
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B$	$S$
55 2 2 1/16 2 1/8 2 3/16	<b>UCT311D1</b> <b>UCT311-200D1</b> <b>UCT311-201D1</b> <b>UCT311-202D1</b> <b>UCT311-203D1</b>	29	23	105	66	39	115	22	150	163	207	44	66	80	127	66	25
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UCT312D1</b> <b>UCT312-204D1</b> <b>UCT312-205D1</b> <b>UCT312-206D1</b> <b>UCT312-207D1</b>	31	25	113	71	41	123	22	160	178	220	46	71	85	135	71	26
65 2 1/2 2 9/16	<b>UCT313D1</b> <b>UCT313-208D1</b> <b>UCT313-209D1</b>	32	27	116	70	43	134	26	170	190	238	50	80	92	146	75	30
70 2 5/8 2 11/16 2 3/4	<b>UCT314D1</b> <b>UCT314-210D1</b> <b>UCT314-211D1</b> <b>UCT314-212D1</b>	36	27	130	85	46	140	26	180	202	252	52	90	97	155	78	33
75 2 13/16 2 7/8 2 15/16 3	<b>UCT315D1</b> <b>UCT315-213D1</b> <b>UCT315-214D1</b> <b>UCT315-215D1</b> <b>UCT315-300D1</b>	36	27	132	85	46	150	26	192	216	262	55	90	102	160	82	32
80 3 1/16 3 1/8 3 3/16	<b>UCT316D1</b> <b>UCT316-301D1</b> <b>UCT316-302D1</b> <b>UCT316-303D1</b>	42	30	150	98	53	160	30	204	230	282	60	102	108	174	86	34

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.




Cast dust cover type  
Open end **C-UCT...D1**  
Closed end **CM-UCT...D1**

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			$t$ max.	$L_4$	$A_5$	UCT	C(CM)
UC311D1 UC311-200D1 UC311-201D1 UC311-202D1 UC311-203D1	T311D1 T311D1 T311D1 T311D1 T311D1	<b>C(CM)-UCT311D1</b> <b>C(CM)-UCT311-200D1</b> <b>C(CM)-UCT311-201D1</b> <b>C(CM)-UCT311-202D1</b> <b>C(CM)-UCT311-203D1</b>	4 5/32	211 8 5/16	125 4 29/32	6.3 14	8.4 19
UC312D1 UC312-204D1 UC312-205D1 UC312-206D1 UC312-207D1	T312D1 T312D1 T312D1 T312D1 T312D1	<b>C(CM)-UCT312D1</b> <b>C(CM)-UCT312-204D1</b> <b>C(CM)-UCT312-205D1</b> <b>C(CM)-UCT312-206D1</b> <b>C(CM)-UCT312-207D1</b>	4 5/32	227 8 15/16	135 5 5/16	7.6 17	10 22
UC313D1 UC313-208D1 UC313-209D1	T313D1 T313D1 T313D1	<b>C(CM)-UCT313D1</b> <b>C(CM)-UCT313-208D1</b> <b>C(CM)-UCT313-209D1</b>	4 5/32	244 9 19/32	140 5 1/2	9.4 21	12 26
UC314D1 UC314-210D1 UC314-211D1 UC314-212D1	T314D1 T314D1 T314D1 T314D1	<b>C(CM)-UCT314D1</b> <b>C(CM)-UCT314-210D1</b> <b>C(CM)-UCT314-211D1</b> <b>C(CM)-UCT314-212D1</b>	4 5/32	258 10 5/32	140 5 1/2	11 24	14 31
UC315D1 UC315-213D1 UC315-214D1 UC315-215D1 UC315-300D1	T315D1 T315D1 T315D1 T315D1 T315D1	<b>C(CM)-UCT315D1</b> <b>C(CM)-UCT315-213D1</b> <b>C(CM)-UCT315-214D1</b> <b>C(CM)-UCT315-215D1</b> <b>C(CM)-UCT315-300D1</b>	4 5/32	268 10 9/16	150 5 29/32	13 29	17 37
UC316D1 UC316-301D1 UC316-302D1 UC316-303D1	T316D1 T316D1 T316D1 T316D1	<b>C(CM)-UCT316D1</b> <b>C(CM)-UCT316-301D1</b> <b>C(CM)-UCT316-302D1</b> <b>C(CM)-UCT316-303D1</b>	4 5/32	287 11 5/16	155 6 3/32	16 35	20 44


# UCT3

## Take-up unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions															
		mm inch															
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B$	$S$
85 3 1/4 3 5/16 3 7/16	UCT317D1 UCT317-304D1 UCT317-305D1 UCT317-307D1	42	32	152	98	53	170	32	214	240	298	64	102	115	183	96	40
90 3 7/16 3 1/2	UCT318D1 UCT318-307D1 UCT318-308D1	46	32	160	106	57	175	32	228	255	312	66	110	120	192	96	40
95 3 5/8 3 11/16 3 3/4	UCT319D1 UCT319-310D1 UCT319-311D1 UCT319-312D1	46	33	165	106	57	180	35	240	270	322	72	110	125	197	103	41
100 3 13/16 3 7/8 3 15/16 4	UCT320D1 UCT320-313D1 UCT320-314D1 UCT320-315D1 UCT320-400D1	48	34	175	115	59	200	35	260	290	345	75	120	135	210	108	42
105	UCT321D1	48	34	175	115	59	200	35	260	290	347	75	120	135	212	112	44
110	UCT322D1	52	40	185	125	65	215	38	285	320	385	80	130	150	235	117	46
120	UCT324D1	60	44	210	140	70	230	45	320	355	432	90	140	165	267	126	51
130	UCT326D1	65	47	220	150	75	240	50	350	385	465	100	150	180	285	135	54
140	UCT328D1	70	52	230	160	80	255	50	380	415	515	100	155	200	315	145	59



Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type  
Open end **C-UCT...D1**  
Closed end **CM-UCT...D1**

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			$t$ max.	$L_4$	$A_5$	UCT	C(CM)
UC317D1 UC317-304D1 UC317-305D1 UC317-307D1	T317D1 T317D1 T317D1 T317D1	C(CM)-UCT317D1 C(CM)-UCT317-304D1 C(CM)-UCT317-305D1 C(CM)-UCT317-307D1	5 13/64	303 11 15/16	170 6 11/16	19 42	25 55
UC318D1 UC318-307D1 UC318-308D1	T318D1 T318D1 T318D1	C(CM)-UCT318D1 C(CM)-UCT318-307D1 C(CM)-UCT318-308D1	5 13/64	317 12 15/32	170 6 11/16	21 46	27 60
UC319D1 UC319-310D1 UC319-311D1 UC319-312D1	T319D1 T319D1 T319D1 T319D1	C(CM)-UCT319D1 C(CM)-UCT319-310D1 C(CM)-UCT319-311D1 C(CM)-UCT319-312D1	5 13/64	327 12 7/8	180 7 3/32	24 53	31 68
UC320D1 UC320-313D1 UC320-314D1 UC320-315D1 UC320-400D1	T320D1 T320D1 T320D1 T320D1 T320D1	C(CM)-UCT320D1 C(CM)-UCT320-313D1 C(CM)-UCT320-314D1 C(CM)-UCT320-315D1 C(CM)-UCT320-400D1	5 13/64	350 13 25/32	190 7 15/32	30 66	38 84
UC321D1	T321D1	C(CM)-UCT321D1	5	359	195	32	43
UC322D1	T322D1	C(CM)-UCT322D1	5	395	200	40	55
UC324D1	T324D1	C(CM)-UCT324D1	5	439	215	55	71
UC326D1	T326D1	C(CM)-UCT326D1	6	476	225	69	92
UC328D1	T328D1	C(CM)-UCT328D1	6	519	235	84	111

## Take-up unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions															
		mm inch															
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B$	$S$
25 1 3/16 7/8 15/16 1	<b>UCTX05D1</b> <b>UCTX05-013D1</b> <b>UCTX05-014D1</b> <b>UCTX05-015D1</b> <b>UCTX05-100D1</b>	16	12	56	37	22	57	12	89	102	113	28	37	43	70	38.1	15.9
		5/8	15/32	2 7/32	1 15/32	7/8	2 1/4	0.472	3 1/2	4 1/32	4 7/16	1 3/32	1 15/32	1 11/16	2 3/4	1.5000	0.626
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UCTX06D1</b> <b>UCTX06-101D1</b> <b>UCTX06-102D1</b> <b>UCTX06-103D1</b> <b>UCTX06-104D1</b>	16	15	64	37	22	64	12	89	102	129	30	37	51	78	42.9	17.5
		5/8	19/32	2 17/32	1 15/32	7/8	2 17/32	0.472	3 1/2	4 1/32	5 3/32	1 3/16	1 15/32	2	3 1/16	1.6890	0.689
35 1 5/16 1 3/8 1 7/16	<b>UCTX07D1</b> <b>UCTX07-105D1</b> <b>UCTX07-106D1</b> <b>UCTX07-107D1</b>	19	17	83	49	29	83	16	102	114	144	36	49	56	88	49.2	19
		3/4	2 1/32	3 9/32	1 15/16	1 5/32	3 3/32	0.630	4 1/4	4 1/2	5 21/32	1 13/32	1 15/16	2 7/32	3 5/32	1.9370	0.748
40 1 1/2 1 9/16	<b>UCTX08D1</b> <b>UCTX08-108D1</b> <b>UCTX08-109D1</b>	19	17	83	49	29	83	16	102	117	144	36	49	57	87	49.2	19
		3/4	2 1/32	3 9/32	1 15/16	1 5/32	3 3/32	0.630	4 1/4	4 19/32	5 21/32	1 13/32	1 15/16	2 1/4	3 7/16	1.9370	0.748
45 1 5/8 1 11/16 1 3/4 1 13/16	<b>UCTX09D1</b> <b>UCTX09-110D1</b> <b>UCTX09-111D1</b> <b>UCTX09-112D1</b> <b>UCTX09-113D1</b>	19	18	83	49	29	86	16	102	117	151	38	49	59	92	51.6	19
		3/4	2 3/32	3 9/32	1 15/16	1 5/32	3 3/8	0.630	4 1/4	4 19/32	5 15/16	1 1/2	1 15/16	2 5/16	3 5/8	2.0315	0.748
50 1 7/8 1 15/16 2	<b>UCTX10D1</b> <b>UCTX10-114D1</b> <b>UCTX10-115D1</b> <b>UCTX10-200D1</b>	25	21	102	64	35	95	22	130	146	171	42	64	65	106	55.6	22.2
		3 1/32	1 3/16	4 1/32	2 17/32	1 3/8	3 3/4	0.866	5 1/8	5 3/4	6 23/32	1 21/32	2 17/32	2 9/16	4 3/16	2.1890	0.874



Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Cast dust cover type  
Open end **C-UCT...D1**  
Closed end **CM-UCT...D1**

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			$t$ max.	$L_4$	$A_5$	UCT	C(CM)
UCX05D1 UCX05-013D1 UCX05-014D1 UCX05-015D1 UCX05-100D1	TX05D1 TX05D1 TX05D1 TX05D1 TX05D1	<b>C(CM)-UCTX05D1</b> <b>C(CM)-UCTX05-013D1</b> <b>C(CM)-UCTX05-014D1</b> <b>C(CM)-UCTX05-015D1</b> <b>C(CM)-UCTX05-100D1</b>	2 5/64	113.5 4 15/32	75 2 15/16	1.4 3.1	1.8 4.0
UCX06D1 UCX06-101D1 UCX06-102D1 UCX06-103D1 UC207-104D1	TX06D1 TX06D1 TX06D1 TX06D1 TX06D1	<b>C(CM)-UCTX06D1</b> <b>C(CM)-UCTX06-101D1</b> <b>C(CM)-UCTX06-102D1</b> <b>C(CM)-UCTX06-103D1</b> <b>C(CM)-UCTX06-104D1</b>	2 5/64	129 5 3/32	80 3 5/32	1.8 4.0	2.3 5.1
UCX07D1 UCX07-105D1 UCX07-106D1 UCX07-107D1	TX07D1 TX07D1 TX07D1 TX07D1	<b>C(CM)-UCTX07D1</b> <b>C(CM)-UCTX07-105D1</b> <b>C(CM)-UCTX07-106D1</b> <b>C(CM)-UCTX07-107D1</b>	3 1/8	144 5 21/32	90 3 17/32	2.6 5.7	3.5 7.7
UCX08D1 UCX08-108D1 UCX08-109D1	TX08D1 TX08D1 TX08D1	<b>C(CM)-UCTX08D1</b> <b>C(CM)-UCTX08-108D1</b> <b>C(CM)-UCTX08-109D1</b>	3 1/8	144.5 5 11/16	95 3 3/4	2.6 5.7	3.5 7.7
UCX09D1 UCX09-110D1 UCX09-111D1 UCX09-112D1 UC210-113D1	TX09D1 TX09D1 TX09D1 TX09D1 TX09D1	<b>C(CM)-UCTX09D1</b> <b>C(CM)-UCTX09-110D1</b> <b>C(CM)-UCTX09-111D1</b> <b>C(CM)-UCTX09-112D1</b> <b>C(CM)-UCTX09-113D1</b>	3 1/8	152 5 31/32	100 3 15/16	2.7 6.0	3.7 8.2
UCX10D1 UCX10-114D1 UCX10-115D1 UC211-200D1	TX10D1 TX10D1 TX10D1 TX10D1	<b>C(CM)-UCTX10D1</b> <b>C(CM)-UCTX10-114D1</b> <b>C(CM)-UCTX10-115D1</b> <b>C(CM)-UCTX10-200D1</b>	3 1/8	171.5 6 3/4	100 3 15/16	4.2 9.3	5.4 12

## Take-up unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions															
		mm inch															
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B$	$S$
55 2 1/16 2 1/8 2 3/16 2 1/4 2 5/16	<b>UCTX11D1</b> <b>UCTX11-201D1</b> <b>UCTX11-202D1</b> <b>UCTX11-203D1</b> <b>UCTX11-204D1</b> <b>UCTX11-205D1</b>	32	21	102	64	35	102	22	130	146	194	44	64	75	119	65.1	25.4
60 2 3/8 2 7/16	<b>UCTX12D1</b> <b>UCTX12-206D1</b> <b>UCTX12-207D1</b>	32	23	111	70	41	121	26	151	167	224	48	70	87	137	65.1	25.4
65 2 1/2 2 9/16	<b>UCTX13D1</b> <b>UCTX13-208D1</b> <b>UCTX13-209D1</b>	32	23	111	70	41	121	26	151	167	224	48	70	87	137	74.6	30.2
70 2 5/8 2 11/16 2 3/4	<b>UCTX14D1</b> <b>UCTX14-210D1</b> <b>UCTX14-211D1</b> <b>UCTX14-212D1</b>	32	23	111	70	41	121	26	151	167	232	48	70	92	140	77.8	33.3
75 2 13/16 2 7/8 2 15/16 3	<b>UCTX15D1</b> <b>UCTX15-213D1</b> <b>UCTX15-214D1</b> <b>UCTX15-215D1</b> <b>UCTX15-300D1</b>	32	23	111	70	41	121	28	165	184	235	48	70	95	140	82.6	33.3
80 3 1/16 3 1/8 3 3/16 3 1/4	<b>UCTX16D1</b> <b>UCTX16-301D1</b> <b>UCTX16-302D1</b> <b>UCTX16-303D1</b> <b>UCTX16-304D1</b>	38	30	124	73	48	157	28	173	198	260	54	73	98	162	85.7	34.1
85 3 5/16 3 7/16	<b>UCTX17D1</b> <b>UCTX17-305D1</b> <b>UCTX17-307D1</b>	38	30	124	73	48	157	28	173	198	260	54	73	98	162	96	39.7


Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Cast dust cover type  
Open end **C-UCT---D1**  
Closed end **CM-UCT---D1**

Bearing number	Housing number	Unit number (1) cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			$t$ max.	$L_4$	$A_5$	UCT	C(CM)
UCX11D1 UCX11-201D1 UCX11-202D1 UCX11-203D1 UC212-204D1 UC212-205D1	TX11D1 TX11D1 TX11D1 TX11D1 TX11D1 TX11D1	<b>C(CM)-UCTX11D1</b> <b>C(CM)-UCTX11-201D1</b> <b>C(CM)-UCTX11-202D1</b> <b>C(CM)-UCTX11-203D1</b> <b>C(CM)-UCTX11-204D1</b> <b>C(CM)-UCTX11-205D1</b>	4 5/32	194 7 5/8	115 4 17/32	5.2 11	6.7 15
UCX12D1 UCX12-206D1 UCX12-207D1	TX12D1 TX12D1 TX12D1	<b>C(CM)-UCTX12D1</b> <b>C(CM)-UCTX12-206D1</b> <b>C(CM)-UCTX12-207D1</b>	4 5/32	224 8 13/16	120 4 23/32	7.2 16	9.0 20
UCX13D1 UCX13-208D1 UCX13-209D1	TX13D1 TX13D1 TX13D1	<b>C(CM)-UCTX13D1</b> <b>C(CM)-UCTX13-208D1</b> <b>C(CM)-UCTX13-209D1</b>	4 5/32	224 8 13/16	135 5 5/16	7.5 17	9.8 22
UCX14D1 UCX14-210D1 UCX14-211D1 UCX14-212D1	TX14D1 TX14D1 TX14D1 TX14D1	<b>C(CM)-UCTX14D1</b> <b>C(CM)-UCTX14-210D1</b> <b>C(CM)-UCTX14-211D1</b> <b>C(CM)-UCTX14-212D1</b>	4 5/32	232 9 1/8	135 5 5/16	7.7 17	10 22
UCX15D1 UCX15-213D1 UCX15-214D1 UCX15-215D1 UCX15-300D1	TX15D1 TX15D1 TX15D1 TX15D1 TX15D1	<b>C(CM)-UCTX15D1</b> <b>C(CM)-UCTX15-213D1</b> <b>C(CM)-UCTX15-214D1</b> <b>C(CM)-UCTX15-215D1</b> <b>C(CM)-UCTX15-300D1</b>	4 5/32	235 9 1/4	145 5 23/32	8.3 18	11 24
UCX16D1 UCX16-301D1 UCX16-302D1 UCX16-303D1 UC217-304D1	TX16D1 TX16D1 TX16D1 TX16D1 TX16D1	<b>C(CM)-UCTX16D1</b> <b>C(CM)-UCTX16-301D1</b> <b>C(CM)-UCTX16-302D1</b> <b>C(CM)-UCTX16-303D1</b> <b>C(CM)-UCTX16-304D1</b>	4 5/32	260 10 1/4	155 6 3/32	11 24	14 31
UCX17D1 UCX17-305D1 UCX17-307D1	TX17D1 TX17D1 TX17D1	<b>C(CM)-UCTX17D1</b> <b>C(CM)-UCTX17-305D1</b> <b>C(CM)-UCTX17-307D1</b>	5 13/64	262 10 5/16	165 6 1/2	11 24	15 33

## Take-up stretcher units™ Set screw type



Shaft dia. mm	Unit number <sup>(1)</sup>	Nominal dimensions																
		mm																
		L	H	J	J <sub>1</sub>	J <sub>3</sub>	A <sub>1</sub>	A <sub>2</sub>	A	P <sub>1</sub>	P <sub>2</sub>	P <sub>3</sub>	N	L <sub>1</sub>	A <sub>3</sub>	B	S	k square
12	UCT201-15	317	199	150	69	154	6	30	50	19	117	64	12	370	48.3	31	12.7	9
15	UCT202-15	317	199	150	69	154	6	30	50	19	117	64	12	370	48.3	31	12.7	9
17	UCT203-15	317	199	150	69	154	6	30	50	19	117	64	12	370	48.3	31	12.7	9
20	UCT204-15	317	199	150	69	154	6	30	50	19	117	64	12	370	48.3	31	12.7	9
25	UCT205-15	317	199	150	68	154	6	30	50	19	117	64	12	370	49.8	34.1	14.3	9
30	UCT206-15	337	212	150	73	166	6	32	50	19	127	64	12	393	54.2	38.1	15.9	10
35	UCT207-23	429	212	230	80	166	6	32	50	19	173	64	12	485	57.4	42.9	17.5	10
40	UCT208-30	520	233	300	88	192	6	32	50	22	217	64	12	596	62.2	49.2	19	15
45	UCT209-30	520	233	300	88	192	6	32	50	22	217	64	12	596	62.2	49.2	19	15
50	UCT210-30	524	233	300	92	192	6	35	50	22	219	64	15	599	67.6	51.6	19	15
55	UCT211-30	542	285	300	93	240	8	38	65	22	230	60	15	630	71.4	55.6	22.2	17
60	UCT212-30	568	285	300	103	240	8	38	65	22	243	60	15	657	77.7	65.1	25.4	17
65	UCT213-30	606	306	300	125	260	8	43	65	22	260	64	15	705	82.7	65.1	25.4	23

Notes <sup>(1)</sup> If relubricatable type is needed, please order with suffix "D1".

<sup>(2)</sup> The Stretcher Units is designed to only take a horizontal radial load, in line with the adjustment direction. Axial loads or vertical radial loads can deform or break the housing.

Adjustment screw size	Bolt size	Max. load <sup>(2)</sup> recommended N	Bearing number	Mass of unit kg
TM16 × 3	M10	7 650	UC201D1	5.0
TM16 × 3	M10	7 650	UC202D1	5.0
TM16 × 3	M10	7 650	UC203D1	5.0
TM16 × 3	M10	7 650	UC204D1	5.0
TM16 × 3	M10	7 850	UC205D1	5.0
TM18 × 4	M10	9 810	UC206D1	5.7
TM18 × 4	M10	12 750	UC207D1	6.8
TM25 × 5	M10	15 690	UC208D1	11
TM25 × 5	M10	15 690	UC209D1	11
TM25 × 5	M12	16 670	UC210D1	11
TM30 × 6	M12	19 610	UC211D1	18
TM30 × 6	M12	21 570	UC212D1	20
TM30 × 6	M12	23 530	UC213D1	23



## Take-up type L stretcher units™ Set screw type



Shaft dia. mm	Unit number <sup>(1)</sup>	Nominal dimensions									Bolt size	Max. load <sup>(2)</sup> recommended N
		H	L	J	J <sub>2</sub>	mm		H <sub>1</sub>	B	S		
20	UCL204-10	77	430	370	100	320	135	146	31	12.7	M12	1 960
	UCL204-20	77	530	470	200	420	135	146	31	12.7	M12	1 960
	UCL204-30	77	630	570	300	520	135	146	31	12.7	M12	1 960
	UCL204-40	77	730	670	400	620	135	146	31	12.7	M12	1 960
25	UCL205-10	82	440	380	100	330	140	156	34.1	14.3	M12	2 250
	UCL205-20	82	540	480	200	430	140	156	34.1	14.3	M12	2 250
	UCL205-30	82	640	580	300	530	140	156	34.1	14.3	M12	2 250
	UCL205-40	82	740	680	400	630	140	156	34.1	14.3	M12	2 250
30	UCL206-10	87	450	390	100	340	145	166	38.1	15.9	M12	3 230
	UCL206-20	87	550	490	200	440	145	166	38.1	15.9	M12	3 230
	UCL206-30	87	650	590	300	540	145	166	38.1	15.9	M12	3 230
	UCL206-40	87	750	690	400	640	145	166	38.1	15.9	M12	3 230
35	UCL207-10	92	460	400	100	350	150	176	42.9	17.5	M12	4 210
	UCL207-20	92	560	500	200	450	150	176	42.9	17.5	M12	4 210
	UCL207-30	92	660	600	300	550	150	176	42.9	17.5	M12	4 210
	UCL207-40	92	760	700	400	650	150	176	42.9	17.5	M12	4 210
40	UCL208-10	97	470	410	100	360	155	186	49.2	19	M12	4 500
	UCL208-20	97	570	510	200	460	155	186	49.2	19	M12	4 500
	UCL208-30	97	670	610	300	560	155	186	49.2	19	M12	4 500
	UCL208-40	97	770	710	400	660	155	186	49.2	19	M12	4 500
45	UCL209-10	100	480	420	100	370	160	192	49.2	19	M12	4 500
	UCL209-20	100	580	520	200	470	160	192	49.2	19	M12	4 500
	UCL209-30	100	680	620	300	570	160	192	49.2	19	M12	4 500
	UCL209-40	100	780	720	400	670	160	192	49.2	19	M12	4 500

Bearing number	Mass of unit kg
UC204D1	6.3
UC204D1	7.0
UC204D1	7.7
UC204D1	8.4
UC205D1	6.8
UC205D1	7.5
UC205D1	8.2
UC205D1	8.9
UC206D1	7.3
UC206D1	8.0
UC206D1	8.7
UC206D1	9.4
UC207D1	7.8
UC207D1	8.5
UC207D1	9.2
UC207D1	9.9
UC208D1	8.3
UC208D1	9.0
UC208D1	9.7
UC208D1	10
UC209D1	8.7
UC209D1	9.4
UC209D1	10
UC209D1	11

Notes <sup>(1)</sup> If relubricatable type is needed, please order with suffix "D1".

<sup>(2)</sup> The Stretcher Units is designed to only take a horizontal radial load, in line with the adjustment direction. Axial loads or vertical radial loads can deform or break the housing.

## Take-up type M stretcher units™ Set screw type



Shaft dia. mm	Unit number <sup>(1)</sup>	Nominal dimensions									Bolt size	Max. load <sup>(2)</sup> recommended N
		H	L	J	J <sub>2</sub>	mm		H <sub>1</sub>	B	S		
40	UCM208-50	97	870	810	500	760	155	190	49.2	19	M18	5 190
	UCM208-60	97	970	910	600	860	155	190	49.2	19	M18	5 190
	UCM208-70	97	1070	1010	700	960	155	190	49.2	19	M18	5 190
	UCM208-80	97	1170	1110	800	1060	155	190	49.2	19	M18	5 190
	UCM208-90	97	1270	1210	900	1160	155	190	49.2	19	M18	5 190
45	UCM209-50	102	880	820	500	770	160	200	49.2	19	M18	5 880
	UCM209-60	102	980	920	600	870	160	200	49.2	19	M18	5 880
	UCM209-70	102	1080	1020	700	970	160	200	49.2	19	M18	5 880
	UCM209-80	102	1180	1120	800	1070	160	200	49.2	19	M18	5 880
	UCM209-90	102	1280	1220	900	1170	160	200	49.2	19	M18	5 880
50	UCM210-50	107	890	830	500	780	165	210	51.6	19	M18	6 460
	UCM210-60	107	990	930	600	880	165	210	51.6	19	M18	6 460
	UCM210-70	107	1090	1030	700	980	165	210	51.6	19	M18	6 460
	UCM210-80	107	1190	1130	800	1080	165	210	51.6	19	M18	6 460
	UCM210-90	107	1290	1230	900	1180	165	210	51.6	19	M18	6 460
55	UCM211-50	115	910	850	500	800	175	230	55.6	22.2	M18	6 460
	UCM211-60	115	1010	950	600	900	175	230	55.6	22.2	M18	6 460
	UCM211-70	115	1110	1050	700	1000	175	230	55.6	22.2	M18	6 460
	UCM211-80	115	1210	1150	800	1100	175	230	55.6	22.2	M18	6 460
	UCM211-90	115	1310	1250	900	1200	175	230	55.6	22.2	M18	6 460
60	UCM212-50	120	920	860	500	810	180	240	65.1	25.4	M18	6 460
	UCM212-60	120	1020	960	600	910	180	240	65.1	25.4	M18	6 460
	UCM212-70	120	1120	1060	700	1010	180	240	65.1	25.4	M18	6 460
	UCM212-80	120	1220	1160	800	1110	180	240	65.1	25.4	M18	6 460
	UCM212-90	120	1320	1260	900	1210	180	240	65.1	25.4	M18	6 460
65	UCM213-50	125	940	880	500	830	190	250	65.1	25.4	M18	6 460
	UCM213-60	125	1040	980	600	930	190	250	65.1	25.4	M18	6 460
	UCM213-70	125	1140	1080	700	1030	190	250	65.1	25.4	M18	6 460
	UCM213-80	125	1240	1180	800	1130	190	250	65.1	25.4	M18	6 460
	UCM213-90	125	1340	1280	900	1230	190	250	65.1	25.4	M18	6 460

Bearing number	Mass of unit kg
UC208D1	20
UC208D1	22
UC208D1	23
UC208D1	24
UC208D1	30
UC209D1	21
UC209D1	23
UC209D1	24
UC209D1	30
UC209D1	32
UC210D1	23
UC210D1	24
UC210D1	30
UC210D1	32
UC210D1	33
UC211D1	25
UC211D1	27
UC211D1	32
UC211D1	34
UC211D1	36
UC212D1	28
UC212D1	29
UC212D1	35
UC212D1	36
UC212D1	38
UC213D1	30
UC213D1	31
UC213D1	36
UC213D1	38
UC213D1	40

Notes <sup>(1)</sup> If relubricatable type is needed, please order with suffix "D1".

<sup>(2)</sup> The Stretcher Units is designed to only take a horizontal radial load, in line with the adjustment direction. Axial loads or vertical radial loads can deform or break the housing.

Take-up type M stretcher units™  
Set screw type



Shaft dia. mm	Unit number (1)	Nominal dimensions									Bolt size	Max. load (2) recommended N	Bearing number	Mass of unit kg
		H	L	J	J <sub>2</sub>	mm L <sub>1</sub> J <sub>1</sub>		H <sub>1</sub>	B	S				
65	UCM313-50	145	940	880	500	830	190	285	75	30	M18	16 260	UC313D1	47
	UCM313-60	145	1040	980	600	930	190	285	75	30	M18	16 260	UC313D1	50
	UCM313-70	145	1140	1080	700	1030	190	285	75	30	M18	16 260	UC313D1	53
	UCM313-80	145	1240	1180	800	1130	190	285	75	30	M18	16 260	UC313D1	55
	UCM313-90	145	1340	1280	900	1230	190	285	75	30	M18	16 260	UC313D1	58
70	UCM314-50	150	960	900	500	850	200	295	78	33	M18	19 600	UC314D1	49
	UCM314-60	150	1060	1000	600	950	200	295	78	33	M18	19 600	UC314D1	52
	UCM314-70	150	1160	1100	700	1050	200	295	78	33	M18	19 600	UC314D1	55
	UCM314-80	150	1260	1200	800	1150	200	295	78	33	M18	19 600	UC314D1	58
	UCM314-90	150	1360	1300	900	1250	200	295	78	33	M18	19 600	UC314D1	61
75	UCM315-50	155	980	920	500	870	210	305	82	32	M18	19 600	UC315D1	52
	UCM315-60	155	1080	1020	600	970	210	305	82	32	M18	19 600	UC315D1	55
	UCM315-70	155	1180	1120	700	1070	210	305	82	32	M18	19 600	UC315D1	58
	UCM315-80	155	1280	1220	800	1170	210	305	82	32	M18	19 600	UC315D1	60
	UCM315-90	155	1380	1320	900	1270	210	305	82	32	M18	19 600	UC315D1	63
80	UCM316-50	160	1000	940	500	890	220	315	86	34	M18	19 600	UC316D1	54
	UCM316-60	160	1100	1040	600	990	220	315	86	34	M18	19 600	UC316D1	57
	UCM316-70	160	1200	1140	700	1090	220	315	86	34	M18	19 600	UC316D1	60
	UCM316-80	160	1300	1240	800	1190	220	315	86	34	M18	19 600	UC316D1	63
	UCM316-90	160	1400	1340	900	1290	220	315	86	34	M18	19 600	UC316D1	66
85	UCM317-50	165	1020	960	500	910	230	325	96	40	M18	19 600	UC317D1	60
	UCM317-60	165	1120	1060	600	1010	230	325	96	40	M18	19 600	UC317D1	63
	UCM317-70	165	1220	1160	700	1110	230	325	96	40	M18	19 600	UC317D1	65
	UCM317-80	165	1320	1260	800	1210	230	325	96	40	M18	19 600	UC317D1	68
	UCM317-90	165	1420	1360	900	1310	230	325	96	40	M18	19 600	UC317D1	71


Notes (1) If relubricatable type is needed, please order with suffix "D1".  
(2) The Stretcher Units is designed to only take a horizontal radial load, in line with the adjustment direction. Axial loads or vertical radial loads can deform or break the housing.



Shaft dia. mm	Unit number (1)	Nominal dimensions											Bolt size	Max. load (2) recommended N	Bearing number	Mass of unit kg
		H	L	J	J <sub>2</sub>	mm L <sub>1</sub> L <sub>2</sub>		J <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	B	S				
90	UCM318-50	170	1050	990	500	940	—	245	335	—	96	40	M18	19 600	UC318D1	65
	UCM318-60	170	1150	1090	600	1040	—	245	335	—	96	40	M18	19 600	UC318D1	68
	UCM318-70	170	1250	1190	700	1140	—	245	335	—	96	40	M18	19 600	UC318D1	71
	UCM318-80	170	1350	1290	800	1240	—	245	335	—	96	40	M18	19 600	UC318D1	74
	UCM318-90	170	1450	1390	900	1340	—	245	335	—	96	40	M18	19 600	UC318D1	77
95	UCM319-50	185	1180	1100	500	1021	775	300	377	400	103	41	M24	19 600	UC319D1	105
	UCM319-60	185	1280	1200	600	1121	875	300	377	400	103	41	M24	19 600	UC319D1	109
	UCM319-70	185	1380	1300	700	1221	975	300	377	400	103	41	M24	19 600	UC319D1	112
	UCM319-80	185	1480	1400	800	1321	1075	300	377	400	103	41	M24	19 600	UC319D1	116
	UCM319-90	185	1580	1500	900	1421	1175	300	377	400	103	41	M24	19 600	UC319D1	120
100	UCM320-50	200	1220	1140	500	1063	809	320	403	430	108	42	M24	19 600	UC320D1	111
	UCM320-60	200	1320	1240	600	1163	909	320	403	430	108	42	M24	19 600	UC320D1	116
	UCM320-70	200	1420	1340	700	1263	1009	320	403	430	108	42	M24	19 600	UC320D1	120
	UCM320-80	200	1520	1440	800	1363	1109	320	403	430	108	42	M24	19 600	UC320D1	124
	UCM320-90	200	1620	1540	900	1463	1209	320	403	430	108	42	M24	19 600	UC320D1	129

Notes (1) If relubricatable type is needed, please order with suffix "D1".  
(2) The Stretcher Units is designed to only take a horizontal radial load, in line with the adjustment direction. Axial loads or vertical radial loads can deform or break the housing.

## Take-up mini stretcher units™ Set screw type



Shaft dia. mm inch	Unit number	Nominal dimensions			Bolt size mm inch	Max. load (1) recommended N lbf
		A	B	S		
12 1/2	ASPT201-10	31	22	6	M10	3 430
	ASPT201-008-10	1 7/32	0.8661	0.236	3/8	770
15 9/16 5/8	ASPT202-10	31	22	6	M10	3 430
	ASPT202-009-10 ASPT202-010-10	1 7/32	0.8661	0.236	3/8	770
17 11/16	ASPT203-10	31	22	6	M10	3 430
	ASPT203-011-10	1 7/32	0.8661	0.236	3/8	770
20 3/4	ASPT204-10	33	25	7	M10	3 430
	ASPT204-012-10	1 19/64	0.9843	0.276	3/8	770
25 13/16 7/8 15/16 1	ASPT205-10	34.5	27	7.5	M10	3 430
	ASPT205-013-10					
	ASPT205-014-10					
	ASPT205-015-10 ASPT205-100-10	1 23/64	1.0630	0.295	3/8	770

Note (1) The Stretcher Units is designed to only take a horizontal radial load, in line with the adjustment direction. Axial loads or vertical radial loads can deform or break the housing.

Bearing number	Mass of unit kg lb
AS201	1.1
AS201-008	2.4
AS202	1.1
AS202-009 AS202-010	2.4
AS203	1.1
AS203-011	2.4
AS204	1.1
AS204-012	2.4
AS205	1.1
AS205-013 AS205-014 AS205-015 AS205-100	2.4

Cartridge unit, cast housing  
Set screw type



Shaft dia. mm inch	Unit number (*)	Nominal dimensions mm inch					Bearing number	Housing number	Mass of unit kg lb
		H	A	r	B	S			
12 1/2	UCC201D1	72	20	2	31	12.7	UC201D1	C204D1	0.5
	UCC201-008D1	2.8346	25/32	0.079	1.2205	0.500	UC201-008D1	C204D1	1.1
15 9/16 5/8	UCC202D1	72	20	2	31	12.7	UC202D1	C204D1	0.5
	UCC202-009D1	2.8346	25/32	0.079	1.2205	0.500	UC202-009D1	C204D1	1.1
	UCC202-010D1						UC202-010D1	C204D1	
17 11/16	UCC203D1	72	20	2	31	12.7	UC203D1	C204D1	0.5
	UCC203-011D1	2.8346	25/32	0.079	1.2205	0.500	UC203-011D1	C204D1	1.1
20 3/4	UCC204D1	72	20	2	31	12.7	UC204D1	C204D1	0.5
	UCC204-012D1	2.8346	25/32	0.079	1.2205	0.500	UC204-012D1	C204D1	1.1
25 13/16 7/8 15/16 1	UCC205D1	80	22	2	34.1	14.3	UC205D1	C205D1	0.6
	UCC205-013D1						UC205-013D1	C205D1	
	UCC205-014D1	3.1496	55/64	0.079	1.3425	0.563	UC205-014D1	C205D1	1.3
	UCC205-015D1						UC205-015D1	C205D1	
30 1 1/16 1 1/8 1 3/16 1 1/4	UCC206D1	85	27	2	38.1	15.9	UC206D1	C206D1	0.8
	UCC206-101D1						UC206-101D1	C206D1	
	UCC206-102D1	3.3465	1 1/16	0.079	1.5000	0.626	UC206-102D1	C206D1	1.8
	UCC206-103D1						UC206-103D1	C206D1	
35 1 1/4 1 5/16 1 3/8 1 7/16	UCC207D1	90	28	2	42.9	17.5	UC207D1	C207D1	0.9
	UCC207-104D1						UC207-104D1	C207D1	
	UCC207-105D1	3.5433	1 7/64	0.079	1.6890	0.689	UC207-105D1	C207D1	2.0
	UCC207-106D1						UC207-106D1	C207D1	
UCC207-107D1							UC207-107D1	C207D1	

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.



Shaft dia. mm inch	Unit number (*)	Nominal dimensions mm inch					Bearing number	Housing number	Mass of unit kg lb	
		H	A	r	B	S				
40 1 1/2 1 9/16	UCC208D1	100	30	2.5	49.2	19	UC208D1	C208D1	1.2	
	UCC208-108D1	3.9370	1 3/16	0.098	1.9370	0.748	UC208-108D1	C208D1	2.6	
	UCC208-109D1						UC208-109D1	C208D1		
45 1 5/8 1 11/16 1 3/4	UCC209D1	110	31	2.5	49.2	19	UC209D1	C209D1	1.5	
	UCC209-110D1						UC209-110D1	C209D1		
	UCC209-111D1	4.3307	1 7/32	0.098	1.9370	0.748	UC209-111D1	C209D1	3.3	
50 1 13/16 1 7/8 1 15/16 2	UCC210D1	120	33	2.5	51.6	19	UC210D1	C210D1	1.9	
	UCC210-113D1						UC210-113D1	C210D1		
	UCC210-114D1	4.7244	1 19/64	0.098	2.0315	0.748	UC210-114D1	C210D1	4.2	
	UCC210-115D1						UC210-115D1	C210D1		
55 2 2 1/16 2 1/8 2 3/16	UCC211D1	125	35	2.5	55.6	22.2	UC211D1	C211D1	2.1	
	UCC211-200D1						UC211-200D1	C211D1		
	UCC211-201D1	4.9213	1 3/8	0.098	2.1890	0.874	UC211-201D1	C211D1	4.6	
	UCC211-202D1						UC211-202D1	C211D1		
60 2 1/4 2 5/16 2 3/8 2 7/16	UCC212D1	130	38	2.5	65.1	25.4	UC212D1	C212D1	2.5	
	UCC212-204D1						UC212-204D1	C212D1		
	UCC212-205D1	5.1181	1 1/2	0.098	2.5630	1.000	UC212-205D1	C212D1	5.5	
	UCC212-206D1						UC212-206D1	C212D1		
UCC212-207D1							UC212-207D1	C212D1		
	65 2 1/2 2 9/16	UCC213D1	140	40	3	65.1	25.4	UC213D1	C213D1	3.0
		UCC213-208D1	5.5118	1 37/64	0.118	2.5630	1.000	UC213-208D1	C213D1	6.6
UCC213-209D1						UC213-209D1	C213D1			

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.


## Cartridge unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions					Bearing number	Housing number	Mass of unit kg lb
		mm inch							
		H	A	r	B	S			
25	<b>UCC305D1</b>	90	26	2.5	38	15	UC305D1	C305D1	1.0
$\frac{13}{16}$	<b>UCC305-013D1</b>	3.5433	$1\frac{1}{32}$	0.098	1.4961	0.591	UC305-013D1	C305D1	2.2
$\frac{7}{8}$	<b>UCC305-014D1</b>						UC305-014D1	C305D1	
$\frac{15}{16}$	<b>UCC305-015D1</b>						UC305-015D1	C305D1	
1	<b>UCC305-100D1</b>						UC305-100D1	C305D1	
30	<b>UCC306D1</b>	100	28	2.5	43	17	UC306D1	C306D1	1.3
$\frac{11}{16}$	<b>UCC306-101D1</b>	3.9370	$1\frac{7}{64}$	0.098	1.6929	0.669	UC306-101D1	C306D1	2.9
$\frac{11}{8}$	<b>UCC306-102D1</b>						UC306-102D1	C306D1	
$\frac{3}{16}$	<b>UCC306-103D1</b>						UC306-103D1	C306D1	
35	<b>UCC307D1</b>	110	32	3	48	19	UC307D1	C307D1	1.7
$\frac{11}{4}$	<b>UCC307-104D1</b>	4.3307	$1\frac{17}{64}$	0.118	1.8898	0.748	UC307-104D1	C307D1	3.7
$\frac{5}{16}$	<b>UCC307-105D1</b>						UC307-105D1	C307D1	
$\frac{3}{8}$	<b>UCC307-106D1</b>						UC307-106D1	C307D1	
$\frac{7}{16}$	<b>UCC307-107D1</b>						UC307-107D1	C307D1	
40	<b>UCC308D1</b>	120	34	3	52	19	UC308D1	C308D1	2.1
$\frac{11}{2}$	<b>UCC308-108D1</b>	4.7244	$1\frac{11}{32}$	0.118	2.0472	0.748	UC308-108D1	C308D1	4.6
$\frac{9}{16}$	<b>UCC308-109D1</b>						UC308-109D1	C308D1	
45	<b>UCC309D1</b>	130	38	3.5	57	22	UC309D1	C309D1	2.7
$\frac{5}{8}$	<b>UCC309-110D1</b>	5.1181	$1\frac{1}{2}$	0.138	2.2441	0.866	UC309-110D1	C309D1	6.0
$\frac{11}{16}$	<b>UCC309-111D1</b>						UC309-111D1	C309D1	
$\frac{3}{4}$	<b>UCC309-112D1</b>						UC309-112D1	C309D1	
50	<b>UCC310D1</b>	140	40	3.5	61	22	UC310D1	C310D1	3.3
$\frac{13}{16}$	<b>UCC310-113D1</b>	5.5118	$1\frac{37}{64}$	0.138	2.4016	0.866	UC310-113D1	C310D1	7.3
$\frac{7}{8}$	<b>UCC310-114D1</b>						UC310-114D1	C310D1	
$\frac{15}{16}$	<b>UCC310-115D1</b>						UC310-115D1	C310D1	

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.



Shaft dia. mm inch	Unit number (1)	Nominal dimensions					Bearing number	Housing number	Mass of unit kg lb
		mm inch							
		H	A	r	B	S			
55	<b>UCC311D1</b>	150	44	3.5	66	25	UC311D1	C311D1	4.0
2	<b>UCC311-200D1</b>	5.9055	$1\frac{47}{64}$	0.138	2.5984	0.984	UC311-200D1	C311D1	8.8
$2\frac{1}{16}$	<b>UCC311-201D1</b>						UC311-201D1	C311D1	
$2\frac{1}{8}$	<b>UCC311-202D1</b>						UC311-202D1	C311D1	
$2\frac{3}{16}$	<b>UCC311-203D1</b>						UC311-203D1	C311D1	
60	<b>UCC312D1</b>	160	46	3.5	71	26	UC312D1	C312D1	4.8
$2\frac{1}{4}$	<b>UCC312-204D1</b>	6.2992	$1\frac{13}{16}$	0.138	2.7953	1.024	UC312-204D1	C312D1	11
$2\frac{5}{16}$	<b>UCC312-205D1</b>						UC312-205D1	C312D1	
$2\frac{3}{8}$	<b>UCC312-206D1</b>						UC312-206D1	C312D1	
$2\frac{7}{16}$	<b>UCC312-207D1</b>						UC312-207D1	C312D1	
65	<b>UCC313D1</b>	170	50	3.5	75	30	UC313D1	C313D1	5.8
$2\frac{1}{2}$	<b>UCC313-208D1</b>	6.6929	$1\frac{31}{32}$	0.138	2.9528	1.181	UC313-208D1	C313D1	13
$2\frac{9}{16}$	<b>UCC313-209D1</b>						UC313-209D1	C313D1	
70	<b>UCC314D1</b>	180	52	4	78	33	UC314D1	C314D1	6.8
$2\frac{5}{8}$	<b>UCC314-210D1</b>	7.0866	$2\frac{3}{64}$	0.157	3.0709	1.299	UC314-210D1	C314D1	15
$2\frac{11}{16}$	<b>UCC314-211D1</b>						UC314-211D1	C314D1	
$2\frac{3}{4}$	<b>UCC314-212D1</b>						UC314-212D1	C314D1	
75	<b>UCC315D1</b>	190	55	4	82	32	UC315D1	C315D1	7.9
$2\frac{13}{16}$	<b>UCC315-213D1</b>	7.4803	$2\frac{11}{64}$	0.157	3.2283	1.260	UC315-213D1	C315D1	17
$2\frac{7}{8}$	<b>UCC315-214D1</b>						UC315-214D1	C315D1	
$2\frac{15}{16}$	<b>UCC315-215D1</b>						UC315-215D1	C315D1	
3	<b>UCC315-300D1</b>						UC315-300D1	C315D1	
80	<b>UCC316D1</b>	200	60	4	86	34	UC316D1	C316D1	9.3
$3\frac{1}{16}$	<b>UCC316-301D1</b>	7.8740	$2\frac{23}{64}$	0.157	3.3858	1.339	UC316-301D1	C316D1	21
$3\frac{1}{8}$	<b>UCC316-302D1</b>						UC316-302D1	C316D1	
$3\frac{3}{16}$	<b>UCC316-303D1</b>						UC316-303D1	C316D1	

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

## Cartridge unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions					Bearing number	Housing number	Mass of unit kg lb
		<i>H</i>	<i>A</i>	<i>r</i>	<i>B</i>	<i>S</i>			
85 3 1/4	<b>UCC317D1</b>	215	64	4	96	40	UC317D1	C317D1	11
3 5/16	<b>UCC317-304D1</b>	8.4646	2 33/64	0.157	3.7795	1.575	UC317-304D1	C317D1	24
3 7/16	<b>UCC317-305D1</b>						UC317-305D1	C317D1	
	<b>UCC317-307D1</b>						UC317-307D1	C317D1	
90 3 1/2	<b>UCC318D1</b>	225	66	4	96	40	UC318D1	C318D1	13
	<b>UCC318-308D1</b>	8.8583	2 19/32	0.157	3.7795	1.575	UC318-308D1	C318D1	29
95 3 5/8	<b>UCC319D1</b>	240	72	4	103	41	UC319D1	C319D1	16
3 11/16	<b>UCC319-310D1</b>	9.4488	2 53/64	0.157	4.0551	1.614	UC319-310D1	C319D1	35
3 3/4	<b>UCC319-311D1</b>						UC319-311D1	C319D1	
	<b>UCC319-312D1</b>						UC319-312D1	C319D1	
100 3 9/16	<b>UCC320D1</b>	260	75	4	108	42	UC320D1	C320D1	20
3 7/8	<b>UCC320-313D1</b>	10.2362	2 61/64	0.157	4.2520	1.654	UC320-313D1	C320D1	44
3 15/16	<b>UCC320-314D1</b>						UC320-314D1	C320D1	
	<b>UCC320-315D1</b>						UC320-315D1	C320D1	
4	<b>UCC320-400D1</b>						UC320-400D1	C320D1	
105	<b>UCC321D1</b>	260	75	4	112	44	UC321D1	C321D1	19
110	<b>UCC322D1</b>	300	80	5	117	46	UC322D1	C322D1	29
120	<b>UCC324D1</b>	320	90	5	126	51	UC324D1	C324D1	36
130	<b>UCC326D1</b>	340	100	5	135	54	UC326D1	C326D1	43
140	<b>UCC328D1</b>	360	100	5	145	59	UC328D1	C328D1	50

**Note** (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

**Remarks** Please refer to page A21 for size of grease fitting.


## Cartridge unit, cast housing Set screw type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions					Bearing number	Housing number	Mass of unit kg lb
		mm inch							
		H	A	r	B	S			
25	<b>UCCX05D1</b>	90	27	2	38.1	15.9	<b>UCX05D1</b>	<b>CX05D1</b>	1.1
$\frac{13}{16}$	<b>UCCX05-013D1</b>	3.5433	$1\frac{1}{16}$	0.079	1.5000	0.626	UCX05-013D1	CX05D1	2.4
$\frac{7}{8}$	<b>UCCX05-014D1</b>						UCX05-014D1	CX05D1	
$\frac{15}{16}$	<b>UCCX05-015D1</b>						UCX05-015D1	CX05D1	
1	<b>UCCX05-100D1</b>						UCX05-100D1	CX05D1	
30	<b>UCCX06D1</b>	100	30	2.5	42.9	17.5	<b>UCX06D1</b>	<b>CX06D1</b>	1.6
$1\frac{1}{16}$	<b>UCCX06-101D1</b>	3.9370	$1\frac{3}{16}$	0.098	1.6890	0.689	UCX06-101D1	CX06D1	3.5
$1\frac{1}{8}$	<b>UCCX06-102D1</b>						UCX06-102D1	CX06D1	
$1\frac{3}{16}$	<b>UCCX06-103D1</b>						UCX06-103D1	CX06D1	
$1\frac{1}{4}$	<b>UCCX06-104D1</b>						UC207-104D1	CX06D1	
35	<b>UCCX07D1</b>	110	34	2.5	49.2	19	<b>UCX07D1</b>	<b>CX07D1</b>	1.8
$1\frac{5}{16}$	<b>UCCX07-105D1</b>	4.3307	$1\frac{11}{32}$	0.098	1.9370	0.748	UCX07-105D1	CX07D1	4.0
$1\frac{3}{8}$	<b>UCCX07-106D1</b>						UCX07-106D1	CX07D1	
$1\frac{7}{16}$	<b>UCCX07-107D1</b>						UCX07-107D1	CX07D1	
40	<b>UCCX08D1</b>	120	38	2.5	49.2	19	<b>UCX08D1</b>	<b>CX08D1</b>	2.5
$1\frac{1}{2}$	<b>UCCX08-108D1</b>	4.7244	$1\frac{1}{2}$	0.098	1.9370	0.748	UCX08-108D1	CX08D1	5.5
$1\frac{9}{16}$	<b>UCCX08-109D1</b>						UCX08-109D1	CX08D1	
45	<b>UCCX09D1</b>	120	38	2.5	51.6	19	<b>UCX09D1</b>	<b>CX09D1</b>	2.2
$1\frac{5}{8}$	<b>UCCX09-110D1</b>	4.7244	$1\frac{1}{2}$	0.098	2.0315	0.748	UCX09-110D1	CX09D1	4.9
$1\frac{11}{16}$	<b>UCCX09-111D1</b>						UCX09-111D1	CX09D1	
$1\frac{3}{4}$	<b>UCCX09-112D1</b>						UCX09-112D1	CX09D1	
$1\frac{13}{16}$	<b>UCCX09-113D1</b>						UC210-113D1	CX09D1	
50	<b>UCCX10D1</b>	130	40	2.5	55.6	22.2	<b>UCX10D1</b>	<b>CX10D1</b>	2.7
$1\frac{7}{8}$	<b>UCCX10-114D1</b>	5.1181	$1\frac{37}{64}$	0.098	2.1890	0.874	UCX10-114D1	CX10D1	6.0
$1\frac{15}{16}$	<b>UCCX10-115D1</b>						UCX10-115D1	CX10D1	
2	<b>UCCX10-200D1</b>						UC211-200D1	CX10D1	

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.



Shaft dia. mm inch	Unit number (1)	Nominal dimensions					Bearing number	Housing number	Mass of unit kg lb
		mm inch							
		H	A	r	B	S			
55	<b>UCCX11D1</b>	150	42	3	65.1	25.4	<b>UCX11D1</b>	<b>CX11D1</b>	4.1
$2\frac{1}{16}$	<b>UCCX11-201D1</b>	5.9055	$1\frac{21}{32}$	0.118	2.5630	1.000	UCX11-201D1	CX11D1	9.0
$2\frac{1}{8}$	<b>UCCX11-202D1</b>						UCX11-202D1	CX11D1	
$2\frac{3}{16}$	<b>UCCX11-203D1</b>						UCX11-203D1	CX11D1	
$2\frac{1}{4}$	<b>UCCX11-204D1</b>						UC212-204D1	CX11D1	
$2\frac{5}{16}$	<b>UCCX11-205D1</b>						UC212-205D1	CX11D1	
60	<b>UCCX12D1</b>	160	44	3	65.1	25.4	<b>UCX12D1</b>	<b>CX12D1</b>	3.9
$2\frac{3}{8}$	<b>UCCX12-206D1</b>	6.2992	$1\frac{47}{64}$	0.118	2.5630	1.000	UCX12-206D1	CX12D1	8.6
$2\frac{7}{16}$	<b>UCCX12-207D1</b>						UCX12-207D1	CX12D1	

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.



## Pillow block unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	S	
20 3/4	UEL204D1W3	33.3	127	95	38	13	16	14	65	42	43.7	17.1	M10
	UEL204-012D1W3	1 5/16	5	3 3/4	1 1/2	1/2	5/8	9/16	2 9/16	1 21/32	1.720	0.673	3/8
25 13/16 7/8 15/16	UEL205D1W3	36.5	140	105	38	13	16	15	71	42	44.4	17.45	M10
	UEL205-013D1W3	1 7/16	5 1/2	4 1/8	1 1/2	1/2	5/8	19/32	2 25/32	1 21/32	1.748	0.687	3/8
	UEL205-014D1W3												
	UEL205-015D1W3												
1	UEL205-100D1W3												
30 1 1/16 1 1/8 1 3/16 1 1/4	UEL206D1W3	42.9	165	121	48	17	20	17	83	54	48.4	18.25	M14
	UEL206-101D1W3	1 11/16	6 1/2	4 3/4	1 7/8	21/32	25/32	21/32	3 9/32	2 1/8	1.906	0.719	1/2
	UEL206-102D1W3												
	UEL206-103D1W3												
1 1/4	UEL206-104D1W3												
35 1 1/4 1 5/16 1 3/8 1 7/16	UEL207D1W3	47.6	167	127	48	17	20	18	93	54	51.1	18.8	M14
	UEL207-104D1W3	1 7/8	6 9/16	5	1 7/8	21/32	25/32	23/32	3 21/32	2 1/8	2.012	0.740	1/2
	UEL207-105D1W3												
	UEL207-106D1W3												
1 7/16	UEL207-107D1W3												
40 1 1/2 1 9/16	UEL208D1W3	49.2	184	137	54	17	20	18	98	52	56.3	21.4	M14
	UEL208-108D1W3	1 15/16	7 1/4	5 13/32	2 1/8	21/32	25/32	23/32	3 27/32	2 1/16	2.217	0.843	1/2
	UEL208-109D1W3												
45 1 5/8 1 11/16 1 3/4	UEL209D1W3	54	190	146	54	17	20	20	106	60	56.3	21.4	M14
	UEL209-110D1W3	2 1/8	7 15/32	5 3/4	2 1/8	21/32	25/32	25/32	4 3/16	2 3/8	2.217	0.843	1/2
	UEL209-111D1W3												
1 3/4	UEL209-112D1W3												
50 1 13/16 1 7/8 1 15/16 2	UEL210D1W3	57.2	206	159	60	20	23	21	114	65	62.7	24.6	M16
	UEL210-113D1W3	2 1/4	8 1/8	6 1/4	2 3/8	25/32	29/32	13/16	4 1/2	2 9/16	2.469	0.969	5/8
	UEL210-114D1W3												
	UEL210-115D1W3												
2	UEL210-200D1W3												

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL204D1W3	P204D1	0.8
UEL204-012D1W3	P204D1	1.8
UEL205D1W3	P205D1	0.9
UEL205-013D1W3	P205D1	2.0
UEL205-014D1W3	P205D1	
UEL205-015D1W3	P205D1	
UEL205-100D1W3	P205D1	
UEL206D1W3	P206D1	1.5
UEL206-101D1W3	P206D1	3.3
UEL206-102D1W3	P206D1	
UEL206-103D1W3	P206D1	
UEL206-104D1W3	P206D1	
UEL207D1W3	P207D1	1.8
UEL207-104D1W3	P207D1	4.0
UEL207-105D1W3	P207D1	
UEL207-106D1W3	P207D1	
UEL207-107D1W3	P207D1	
UEL208D1W3	P208D1	2.1
UEL208-108D1W3	P208D1	4.6
UEL208-109D1W3	P208D1	
UEL209D1W3	P209D1	2.3
UEL209-110D1W3	P209D1	5.1
UEL209-111D1W3	P209D1	
UEL209-112D1W3	P209D1	
UEL210D1W3	P210D1	2.9
UEL210-113D1W3	P210D1	6.4
UEL210-114D1W3	P210D1	
UEL210-115D1W3	P210D1	
UEL210-200D1W3	P210D1	

## Pillow block unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	S	
55 2 2 1/16 2 1/8 2 3/16	<b>UEL211D1W3</b> <b>UEL211-200D1W3</b> <b>UEL211-201D1W3</b> <b>UEL211-202D1W3</b> <b>UEL211-203D1W3</b>	63.5	219	171	60	20	23	23	126	65	71.4	27.75	M16
		2 1/2	8 5/8	6 23/32	2 3/8	25/32	29/32	29/32	4 31/32	2 9/16	2.811	1.093	5/8
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UEL212D1W3</b> <b>UEL212-204D1W3</b> <b>UEL212-205D1W3</b> <b>UEL212-206D1W3</b> <b>UEL212-207D1W3</b>	69.8	241	184	70	20	23	25	138	70	77.8	30.95	M16
		2 3/4	9 1/2	7 1/4	2 3/4	25/32	29/32	31/32	5 7/16	2 3/4	3.063	1.219	5/8
65 2 1/2 2 9/16	<b>UEL213D1W3</b> <b>UEL213-208D1W3</b> <b>UEL213-209D1W3</b>	76.2	265	203	70	25	28	27	151	77	85.7	34.15	M20
		3	10 7/16	8	2 3/4	31/32	1 3/32	1 1/16	5 15/16	3 1/32	3.374	1.344	3/4
70 2 5/8 2 11/16 2 3/4	<b>UEL214D1W3</b> <b>UEL214-210D1W3</b> <b>UEL214-211D1W3</b> <b>UEL214-212D1W3</b>	79.4	266	210	72	25	28	27	157	77	85.7	34.15	M20
		3 1/8	10 15/32	8 9/32	2 27/32	31/32	1 3/32	1 1/16	6 3/16	3 1/32	3.374	1.344	3/4
75 2 13/16 2 7/8 2 15/16 3	<b>UEL215D1W3</b> <b>UEL215-213D1W3</b> <b>UEL215-214D1W3</b> <b>UEL215-215D1W3</b> <b>UEL215-300D1W3</b>	82.6	275	217	74	25	28	28	163	80	92	37.3	M20
		3 1/4	10 13/16	8 17/32	2 29/32	31/32	1 3/32	1 3/32	6 19/32	3 5/32	3.622	1.469	3/4

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL211D1W3	P211D1	3.7
UEL211-200D1W3	P211D1	8.2
UEL211-201D1W3	P211D1	
UEL211-202D1W3	P211D1	
UEL211-203D1W3	P211D1	
UEL212D1W3	P212D1	5.0
UEL212-204D1W3	P212D1	11
UEL212-205D1W3	P212D1	
UEL212-206D1W3	P212D1	
UEL212-207D1W3	P212D1	
UEL213D1W3	P213D1	6.2
UEL213-208D1W3	P213D1	14
UEL213-209D1W3	P213D1	
UEL214D1W3	P214D1	6.9
UEL214-210D1W3	P214D1	15
UEL214-211D1W3	P214D1	
UEL214-212D1W3	P214D1	
UEL215D1W3	P215D1	7.6
UEL215-213D1W3	P215D1	17
UEL215-214D1W3	P215D1	
UEL215-215D1W3	P215D1	
UEL215-300D1W3	P215D1	

## Pillow block unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	S	
25 1 3/16 7/8 15/16 1	<b>UEL305D1W3</b> <b>UEL305-013D1W3</b> <b>UEL305-014D1W3</b> <b>UEL305-015D1W3</b> <b>UEL305-100D1W3</b>	45 1 49/64	175 6 7/8	132 5 3/16	45 1 25/32	17 21/32	20 25/32	15 19/32	85 3 11/32	54 2 1/8	46.8 1.843	16.7 0.657	M14 1/2
30 1 1/16 1 1/8 1 3/16	<b>UEL306D1W3</b> <b>UEL306-101D1W3</b> <b>UEL306-102D1W3</b> <b>UEL306-103D1W3</b>	50 1 31/32	180 7 3/32	140 5 1/2	50 1 31/32	17 21/32	20 25/32	18 23/32	95 3 3/4	54 2 1/8	50 1.969	17.5 0.689	M14 1/2
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UEL307D1W3</b> <b>UEL307-104D1W3</b> <b>UEL307-105D1W3</b> <b>UEL307-106D1W3</b> <b>UEL307-107D1W3</b>	56 2 13/64	210 8 9/32	160 6 5/16	56 2 1/32	17 21/32	25 31/32	20 25/32	106 4 3/16	60 2 3/8	51.6 2.031	18.3 0.720	M14 1/2
40 1 1/2 1 9/16	<b>UEL308D1W3</b> <b>UEL308-108D1W3</b> <b>UEL308-109D1W3</b>	60 2 23/64	220 8 21/32	170 6 11/16	60 2 3/8	17 21/32	27 1 1/16	22 7/8	116 4 9/16	60 2 3/8	57.1 2.248	19.8 0.780	M14 1/2
45 1 5/8 1 11/16 1 3/4	<b>UEL309D1W3</b> <b>UEL309-110D1W3</b> <b>UEL309-111D1W3</b> <b>UEL309-112D1W3</b>	67 2 41/64	245 9 21/32	190 7 15/32	67 2 5/8	20 25/32	30 1 3/16	24 15/16	129 5 3/32	65 2 9/16	58.7 2.311	19.8 0.780	M16 5/8
50 1 13/16 1 7/8 1 15/16	<b>UEL310D1W3</b> <b>UEL310-113D1W3</b> <b>UEL310-114D1W3</b> <b>UEL310-115D1W3</b>	75 2 61/64	275 10 13/16	212 8 11/32	75 2 15/16	20 25/32	35 1 3/8	27 1 1/16	143 5 5/8	75 2 15/16	66.6 2.622	24.6 0.969	M16 5/8

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL305D1W3	P305D1	1.5
UEL305-013D1W3	P305D1	3.3
UEL305-014D1W3	P305D1	
UEL305-015D1W3	P305D1	
UEL305-100D1W3	P305D1	
UEL306D1W3	P306D1	1.9
UEL306-101D1W3	P306D1	4.2
UEL306-102D1W3	P306D1	
UEL306-103D1W3	P306D1	
UEL307D1W3	P307D1	2.6
UEL307-104D1W3	P307D1	5.7
UEL307-105D1W3	P307D1	
UEL307-106D1W3	P307D1	
UEL307-107D1W3	P307D1	
UEL308D1W3	P308D1	3.2
UEL308-108D1W3	P308D1	7.1
UEL308-109D1W3	P308D1	
UEL309D1W3	P309D1	4.2
UEL309-110D1W3	P309D1	9.3
UEL309-111D1W3	P309D1	
UEL309-112D1W3	P309D1	
UEL310D1W3	P310D1	5.8
UEL310-113D1W3	P310D1	13
UEL310-114D1W3	P310D1	
UEL310-115D1W3	P310D1	

## Pillow block unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	S	
55 2 2 1/16 2 1/8 2 3/16	UEL311-1D1W3 UEL311-200D1W3 UEL311-201D1W3 UEL311-202D1W3 UEL311-203D1W3	80 3 5/32	310 12 7/32	236 9 9/32	80 3 5/32	20 25/32	38 1 1/2	30 1 3/16	154 6 1/16	85 3 11/32	73 2.874	27.8 1.094	M16 5/8
60 2 1/4 2 5/16 2 3/8 2 7/16	UEL312-1D1W3 UEL312-204D1W3 UEL312-205D1W3 UEL312-206D1W3 UEL312-207D1W3	85 3 11/32	330 13	250 9 27/32	85 3 11/32	25 31/32	38 1 1/2	32 1 1/4	165 6 1/2	95 3 3/4	79.4 3.126	30.95 1.219	M20 3/4
65 2 1/2 2 9/16	UEL313-1D1W3 UEL313-208D1W3 UEL313-209D1W3	90 3 35/64	340 13 3/8	260 10 1/4	90 3 17/32	25 31/32	38 1 1/2	33 1 5/16	176 6 15/16	105 4 1/8	85.7 3.374	32.55 1.281	M20 3/4
70 2 5/8 2 11/16 2 3/4	UEL314-1D1W3 UEL314-210D1W3 UEL314-211D1W3 UEL314-212D1W3	95 3 47/64	360 14 3/16	280 11 1/32	90 3 17/32	27 1 1/16	40 1 9/16	35 1 3/8	187 7 3/8	105 4 1/8	92.1 3.626	34.15 1.344	M22 7/8
75 2 13/16 2 7/8 2 15/16 3	UEL315-1D1W3 UEL315-213D1W3 UEL315-214D1W3 UEL315-215D1W3 UEL315-300D1W3	100 3 15/16	380 14 31/32	290 11 13/32	100 3 15/16	27 1 1/16	40 1 9/16	35 1 3/8	198 7 25/32	110 4 11/32	100 3.937	37.3 1.469	M22 7/8
80 3 1/16 3 1/8 3 3/16	UEL316-1D1W3 UEL316-301D1W3 UEL316-302D1W3 UEL316-303D1W3	106 4 11/64	400 15 3/4	300 11 13/16	110 4 11/32	27 1 1/16	40 1 9/16	40 1 9/16	210 8 9/32	110 4 11/32	106.4 4.189	40.5 1.594	M22 7/8

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL311D1W3 UEL311-200D1W3 UEL311-201D1W3 UEL311-202D1W3 UEL311-203D1W3	P311D1 P311D1 P311D1 P311D1 P311D1	7.6 17
UEL312D1W3 UEL312-204D1W3 UEL312-205D1W3 UEL312-206D1W3 UEL312-207D1W3	P312D1 P312D1 P312D1 P312D1 P312D1	9.7 21
UEL313D1W3 UEL313-208D1W3 UEL313-209D1W3	P313D1 P313D1 P313D1	11 24
UEL314D1W3 UEL314-210D1W3 UEL314-211D1W3 UEL314-212D1W3	P314D1 P314D1 P314D1 P314D1	12 26
UEL315D1W3 UEL315-213D1W3 UEL315-214D1W3 UEL315-215D1W3 UEL315-300D1W3	P315D1 P315D1 P315D1 P315D1 P315D1	15 33
UEL316D1W3 UEL316-301D1W3 UEL316-302D1W3 UEL316-303D1W3	P316D1 P316D1 P316D1 P316D1	18 40

## Pillow block unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	S	
85 3 1/4 3 5/16 3 7/16	<b>UEL317D1W3</b> <b>UEL317-304D1W3</b> <b>UEL317-305D1W3</b> <b>UEL317-307D1W3</b>	112	420	320	110	33	45	40	220	120	109.5	42.05	M27
		4 13/32	16 17/32	12 19/32	4 11/32	1 5/16	1 25/32	1 9/16	8 21/32	4 23/32	4.311	1.656	1
90 3 7/16 3 1/2	<b>UEL318D1W3</b> <b>UEL318-307D1W3</b> <b>UEL318-308D1W3</b>	118	430	330	110	33	45	45	235	120	115.9	43.65	M27
		4 41/64	16 15/16	13	4 1/2	1 5/16	1 25/32	1 25/32	9 1/4	4 23/32	4.563	1.719	1
95 3 5/8 3 11/16 3 3/4	<b>UEL319D1W3</b> <b>UEL319-310D1W3</b> <b>UEL319-311D1W3</b> <b>UEL319-312D1W3</b>	125	470	360	120	36	50	45	250	125	122.3	38.9	M30
		4 59/64	18 1/2	14 3/16	4 23/32	1 13/32	1 31/32	1 25/32	9 27/32	4 29/32	4.815	1.531	1 1/8
100 3 13/16 3 7/8 3 15/16 4	<b>UEL320D1W3</b> <b>UEL320-313D1W3</b> <b>UEL320-314D1W3</b> <b>UEL320-315D1W3</b> <b>UEL320-400D1W3</b>	140	490	380	120	36	50	50	275	130	128.6	50	M30
		5 33/64	19 9/32	14 31/32	4 23/32	1 13/32	1 31/32	1 31/32	10 13/16	5 1/8	5.063	1.969	1 1/8
105	<b>UEL321D1W3</b>	140	490	380	120	36	50	50	280	130	139.7	48.4	M30
110	<b>UEL322D1W3</b>	150	520	400	140	40	55	55	300	135	141.3	49.2	M33

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL317D1W3	P317D1	21
UEL317-304D1W3	P317D1	46
UEL317-305D1W3	P317D1	46
UEL317-307D1W3	P317D1	46
UEL318D1W3	P318D1	23
UEL318-307D1W3	P318D1	51
UEL318-308D1W3	P318D1	51
UEL319D1W3	P319D1	28
UEL319-310D1W3	P319D1	62
UEL319-311D1W3	P319D1	62
UEL319-312D1W3	P319D1	62
UEL320D1W3	P320D1	35
UEL320-313D1W3	P320D1	77
UEL320-314D1W3	P320D1	77
UEL320-315D1W3	P320D1	77
UEL320-400D1W3	P320D1	77
UEL321D1W3	P321D1	37
UEL322D1W3	P322D1	46

## Pillow block unit, cast housing low center height Eccentric locking collar type



Shaft dia.  mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )( <sup>3</sup> )	Nominal dimensions											Bolt size  mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	S	
20  3/4	UELPL204D1W3	31.75	127	95	38	13	16	14	64	42	43.7	17.1	M10
	UELPL204-012D1W3	1 1/4	5	3 3/4	1 1/2	1/2	5/8	9/16	2 17/32	1 21/32	1.720	0.673	3/8
25  13/16 7/8 15/16	UELPL205D1W3	33.34	140	105	38	13	16	15	68	42	44.4	17.45	M10
	UELPL205-013D1W3												
	UELPL205-014D1W3												
	UELPL205-015D1W3	1 5/16	5 1/2	4 1/8	1 1/2	1/2	5/8	19/32	2 11/16	1 21/32	1.748	0.687	3/8
1	UELPL205-100D1W3												
30  1 1/16 1 1/8 1 1/4	UELPL206D1W3	39.69	165	121	48	17	20	17	80	54	48.4	18.25	M14
	UELPL206-101D1W3												
	UELPL206-102D1W3	1 9/16	6 1/2	4 3/4	1 7/8	21/32	25/32	21/32	3 5/32	2 1/8	1.906	0.719	1/2
	UELPL206-103D1W3												
1 1/4	UELPL206-104D1W3												
35  1 1/4 1 5/16 3/8 1 3/8 1 7/16	UELPL207D1W3	46.04	167	127	48	17	20	18	91	54	51.1	18.8	M14
	UELPL207-104D1W3												
	UELPL207-105D1W3	1 13/16	6 9/16	5	1 7/8	21/32	25/32	23/32	3 19/32	2 1/8	2.012	0.740	1/2
	UELPL207-106D1W3												
1 7/16	UELPL207-107D1W3												
45  1 5/8 1 11/16 3/4	UELPL209D1W3	52.39	190	146	54	17	20	20	104	60	56.3	21.4	M14
	UELPL209-110D1W3												
	UELPL209-111D1W3	2 1/16	7 15/32	5 3/4	2 1/8	21/32	25/32	25/32	4 3/32	2 3/8	2.217	0.843	1/2
	UELPL209-112D1W3												
50  1 13/16 1 7/8 1 15/16	UELPL210D1W3	55.56	206	159	60	20	23	21	112	65	62.7	24.6	M16
	UELPL210-113D1W3												
	UELPL210-114D1W3	2 3/16	8 1/8	6 1/4	2 3/8	25/32	29/32	13/16	4 13/32	2 9/16	2.469	0.969	5/8
	UELPL210-115D1W3												
2	UELPL210-200D1W3												

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> UELPL204 and UELPL205 has solid bases.

<sup>(3)</sup> UELPL208 has the same dimension as UELP208 shown in page B148.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL204D1W3	PL204D1	0.8
UEL204-012D1W3	PL204D1	1.8
UEL205D1W3	PL205D1	0.9
UEL205-013D1W3	PL205D1	
UEL205-014D1W3	PL205D1	2.0
UEL205-015D1W3	PL205D1	
UEL205-100D1W3	PL205D1	
UEL206D1W3	PL206D1	1.4
UEL206-101D1W3	PL206D1	
UEL206-102D1W3	PL206D1	3.1
UEL206-103D1W3	PL206D1	
UEL206-104D1W3	PL206D1	
UEL207D1W3	PL207D1	1.7
UEL207-104D1W3	PL207D1	
UEL207-105D1W3	PL207D1	3.7
UEL207-106D1W3	PL207D1	
UEL207-107D1W3	PL207D1	
UEL209D1W3	PL209D1	2.3
UEL209-110D1W3	PL209D1	
UEL209-111D1W3	PL209D1	5.1
UEL209-112D1W3	PL209D1	
UEL210D1W3	PL210D1	3.0
UEL210-113D1W3	PL210D1	
UEL210-114D1W3	PL210D1	6.6
UEL210-115D1W3	PL210D1	
UEL210-200D1W3	PL210D1	

# UELPL2

Pillow block unit, cast housing low center height  
Eccentric locking collar type




Shaft dia. mm inch	Unit number (*)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	S	
55	<b>UELPL211D1W3</b>	61.91	219	171	60	20	23	23	124	65	71.4	27.75	M16
2 2 1/16	<b>UELPL211-200D1W3</b>	2 7/16	8 5/8	6 23/32	2 3/8	25/32	29/32	29/32	4 7/8	2 9/16	2.811	1.093	5/8
2 1/8	<b>UELPL211-201D1W3</b>												
2 3/8	<b>UELPL211-202D1W3</b>												
2 3/16	<b>UELPL211-203D1W3</b>												
60	<b>UELPL212D1W3</b>	68.26	241	184	70	20	23	25	136	70	77.8	30.95	M16
2 1/4	<b>UELPL212-204D1W3</b>	2 11/16	9 1/2	7 1/4	2 3/4	25/32	29/32	31/32	5 11/32	2 3/4	3.063	1.219	5/8
2 5/16	<b>UELPL212-205D1W3</b>												
2 3/8	<b>UELPL212-206D1W3</b>												
2 7/16	<b>UELPL212-207D1W3</b>												

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL211D1W3	PL211D1	3.7
UEL211-200D1W3	PL211D1	8.2
UEL211-201D1W3	PL211D1	
UEL211-202D1W3	PL211D1	
UEL211-203D1W3	PL211D1	
UEL212D1W3	PL212D1	5.0
UEL212-204D1W3	PL212D1	11
UEL212-205D1W3	PL212D1	
UEL212-206D1W3	PL212D1	
UEL212-207D1W3	PL212D1	

## Pillow block unit, cast housing high center height Eccentric locking collar type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	B <sub>1</sub>	S	
20 3/4	UELHP204D1W3	70	127	95	40	13	19	13	101	43.7	17.1	M10
	UELHP204-012D1W3	2 3/4	5	3 3/4	1 9/16	1/2	3/4	1/2	3 31/32	1.720	0.673	3/8
25 1 3/16 7/8 15/16	UELHP205D1W3	80	142	105	50	13	19	13	114	44.4	17.45	M10
	UELHP205-013D1W3											
	UELHP205-014D1W3											
	UELHP205-015D1W3	3 5/32	5 19/32	4 1/8	1 31/32	1/2	3/4	1/2	4 1/2	1.748	0.687	3/8
1	UELHP205-100D1W3											
30 1 1/16 1 1/8 1 3/16 1 1/4	UELHP206D1W3	90	165	120	50	17	21	16	130	48.4	18.25	M14
	UELHP206-101D1W3											
	UELHP206-102D1W3											
	UELHP206-103D1W3	3 35/64	6 1/2	4 23/32	1 31/32	21/32	13/16	5/8	5 1/8	1.906	0.719	1/2
1 1/4	UELHP206-104D1W3											
35 1 1/4 1 5/16 1 3/8 1 7/16	UELHP207D1W3	95	166	127	60	17	21	18	140	51.1	18.8	M14
	UELHP207-104D1W3											
	UELHP207-105D1W3											
	UELHP207-106D1W3	3 47/64	6 17/32	5	2 3/8	21/32	13/16	23/32	5 1/2	2.012	0.740	1/2
1 7/16	UELHP207-107D1W3											
40 1 1/2 1 9/16	UELHP208D1W3	100	184	136	70	17	21	20	150	56.3	21.4	M14
	UELHP208-108D1W3											
	UELHP208-109D1W3	3 15/16	7 1/4	5 11/32	2 3/4	21/32	13/16	25/32	5 29/32	2.217	0.843	1/2
45 1 5/8 1 11/16 1 3/4	UELHP209D1W3	105	190	146	70	17	22	20	158	56.3	21.4	M14
	UELHP209-110D1W3											
	UELHP209-111D1W3											
	UELHP209-112D1W3	4 9/64	7 15/32	5 3/4	2 3/4	21/32	7/8	25/32	6 7/32	2.217	0.843	1/2
50 1 13/16 1 7/8 1 15/16 2	UELHP210D1W3	110	206	159	70	20	22	22	165	62.7	24.6	M16
	UELHP210-113D1W3											
	UELHP210-114D1W3											
	UELHP210-115D1W3	4 21/64	8 1/8	6 1/4	2 3/4	25/32	7/8	7/8	6 1/2	2.469	0.969	5/8
2	UELHP210-200D1W3											

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".


Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL204D1W3	HP204D1	0.9
UEL204-012D1W3	HP204D1	2.0
UEL205D1W3	HP205D1	1.3
UEL205-013D1W3	HP205D1	
UEL205-014D1W3	HP205D1	
UEL205-015D1W3	HP205D1	2.9
UEL205-100D1W3	HP205D1	
UEL206D1W3	HP206D1	1.9
UEL206-101D1W3	HP206D1	
UEL206-102D1W3	HP206D1	
UEL206-103D1W3	HP206D1	4.2
UEL206-104D1W3	HP206D1	
UEL207D1W3	HP207D1	2.4
UEL207-104D1W3	HP207D1	
UEL207-105D1W3	HP207D1	
UEL207-106D1W3	HP207D1	5.3
UEL207-107D1W3	HP207D1	
UEL208D1W3	HP208D1	3.3
UEL208-108D1W3	HP208D1	
UEL208-109D1W3	HP208D1	7.3
UEL209D1W3	HP209D1	3.7
UEL209-110D1W3	HP209D1	
UEL209-111D1W3	HP209D1	
UEL209-112D1W3	HP209D1	8.2
UEL210D1W3	HP210D1	4.1
UEL210-113D1W3	HP210D1	
UEL210-114D1W3	HP210D1	
UEL210-115D1W3	HP210D1	9.0
UEL210-200D1W3	HP210D1	



# UELUP2

Narrow pillow block unit, cast housing  
Eccentric locking collar type




Shaft dia.  mm inch	Unit number (1)	Nominal dimensions									
		mm inch									
		H	L	J	A	j	H <sub>1</sub>	H <sub>2</sub>	B <sub>1</sub>	S	N
20  3/4	UELUP204D1W3	30.2	76	52	38	13	11	62	43.7	17.1	M10×1.5
	UELUP204-012D1W3	1 3/16	3	2 1/16	1 1/2	1/2	7/16	2 7/16	1.720	0.673	M10×1.5
25  13/16 7/8 15/16 1	UELUP205D1W3	36.5	84	56	38	15	12	72	44.4	17.45	M10×1.5
	UELUP205-013D1W3										
	UELUP205-014D1W3										
	UELUP205-015D1W3	1 7/16	3 5/16	2 7/32	1 1/2	19/32	15/32	2 27/32	1.748	0.687	M10×1.5
1	UELUP205-100D1W3										
30  1 1/16 1 1/8 1 3/16 1 1/4	UELUP206D1W3	42.9	94	66	48	18	12	84	48.4	18.25	M14×2
	UELUP206-101D1W3										
	UELUP206-102D1W3										
	UELUP206-103D1W3	1 11/16	3 11/16	2 19/32	1 7/8	23/32	15/32	3 5/16	1.906	0.719	M14×2
1 1/4	UELUP206-104D1W3										
35  1 1/4 1 5/16 1 3/8 1 7/16	UELUP207D1W3	47.6	110	80	48	20	13	95	51.1	18.8	M14×2
	UELUP207-104D1W3										
	UELUP207-105D1W3										
	UELUP207-106D1W3	1 7/8	4 11/32	3 5/32	1 7/8	25/32	1/2	3 3/4	2.012	0.740	M14×2
1 7/16	UELUP207-107D1W3										
40  1 1/2 1 9/16	UELUP208D1W3	49.2	116	84	54	20	13	100	56.3	21.4	M14×2
	UELUP208-108D1W3										
	UELUP208-109D1W3	1 15/16	4 9/16	3 5/16	2 1/8	25/32	1/2	3 15/16	2.217	0.843	M14×2
45  1 5/8 1 11/16 1 3/4	UELUP209D1W3	54.2	120	90	54	25	13	108	56.3	21.4	M14×2
	UELUP209-110D1W3										
	UELUP209-111D1W3										
	UELUP209-112D1W3	2 9/64	4 23/32	3 17/32	2 1/8	31/32	1/2	4 1/4	2.217	0.843	M14×2
50  1 13/16 1 7/8 1 15/16 2	UELUP210D1W3	57.2	130	94	60	25	14	116	62.7	24.6	M16×2
	UELUP210-113D1W3										
	UELUP210-114D1W3										
	UELUP210-115D1W3	2 1/4	5 1/8	3 11/16	2 3/8	31/32	9/16	4 9/16	2.469	0.969	M16×2
2	UELUP210-200D1W3										

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL204D1W3	UP204D1	0.6
UEL204-012D1W3	UP204D1	1.3
UEL205D1W3	UP205D1	0.8
UEL205-013D1W3	UP205D1	
UEL205-014D1W3	UP205D1	1.8
UEL205-015D1W3	UP205D1	
UEL205-100D1W3	UP205D1	
UEL206D1W3	UP206D1	1.3
UEL206-101D1W3	UP206D1	
UEL206-102D1W3	UP206D1	2.9
UEL206-103D1W3	UP206D1	
UEL206-104D1W3	UP206D1	
UEL207D1W3	UP207D1	1.7
UEL207-104D1W3	UP207D1	
UEL207-105D1W3	UP207D1	3.7
UEL207-106D1W3	UP207D1	
UEL207-107D1W3	UP207D1	
UEL208D1W3	UP208D1	2.0
UEL208-108D1W3	UP208D1	4.4
UEL208-109D1W3	UP208D1	
UEL209D1W3	UP209D1	2.3
UEL209-110D1W3	UP209D1	
UEL209-111D1W3	UP209D1	5.1
UEL209-112D1W3	UP209D1	
UEL210D1W3	UP210D1	2.8
UEL210-113D1W3	UP210D1	
UEL210-114D1W3	UP210D1	6.2
UEL210-115D1W3	UP210D1	
UEL210-200D1W3	UP210D1	

## Pillow block unit, cast housing low center height Eccentric locking collar type



Shaft dia.  mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions												Bolt size  mm inch
		mm inch												
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	S		
12 1/2	AELPL201W3	26.99	121	89	35	11	14	13	54	40	28.6	6.5	M10	
	AELPL201-008W3	1 1/16	4 3/4	3 1/2	1 3/8	7/16	9/16	1/2	2 1/8	1 9/16	1.126	0.256	3/8	
15 9/16 5/8	AELPL202W3	26.99	121	89	35	11	14	13	54	40	28.6	6.5	M10	
	AELPL202-009W3	1 1/16	4 3/4	3 1/2	1 3/8	7/16	9/16	1/2	2 1/8	1 9/16	1.126	0.256	3/8	
	AELPL202-010W3													
17 11/16	AELPL203W3	26.99	121	89	35	11	14	13	54	40	28.6	6.5	M10	
	AELPL203-011W3	1 1/16	4 3/4	3 1/2	1 3/8	7/16	9/16	1/2	2 1/8	1 9/16	1.126	0.256	3/8	
20 3/4	AELPL204W3	31.75	127	95	38	13	16	14	64	42	31	7.5	M10	
	AELPL204-012W3	1 1/4	5	3 3/4	1 1/2	1/2	5/8	9/16	2 17/32	1 21/32	1.220	0.295	3/8	
25 13/16 7/8 15/16 1	AELPL205W3	33.34	140	105	38	13	16	15	68	42	31	7.5	M10	
	AELPL205-013W3													
	AELPL205-014W3	1 5/16	5 1/2	4 1/8	1 1/2	1/2	5/8	19/32	2 11/16	1 21/32	1.220	0.295	3/8	
	AELPL205-015W3													
AELPL205-100W3														
30 1 1/16 1 1/8 1 3/16 1 1/4	AELPL206W3	39.69	165	121	48	17	20	17	80	54	35.7	9	M14	
	AELPL206-101W3													
	AELPL206-102W3	1 9/16	6 1/2	4 3/4	1 7/8	21/32	25/32	21/32	3 5/32	2 1/8	1.406	0.354	1/2	
	AELPL206-103W3													
AELPL206-104W3														
35 1 1/4 1 5/16 1 3/8 1 7/16	AELPL207W3	46.04	167	127	48	17	20	18	91	54	38.9	9.5	M14	
	AELPL207-104W3													
	AELPL207-105W3	1 13/16	6 9/16	5	1 7/8	21/32	25/32	23/32	3 19/32	2 1/8	1.531	0.374	1/2	
	AELPL207-106W3													
AELPL207-107W3														

Notes (1) AELPL201 to AELPL205 has solid base.  
(2) If relubricatable type is needed, please order with suffix "D1".

Bearing number	Housing number	Mass of unit kg lb
AEL201W3	PL201	0.5
AEL201-008W3	PL201	1.1
AEL202W3	PL201	0.5
AEL202-009W3	PL201	1.1
AEL202-010W3	PL201	
AEL203W3	PL201	0.5
AEL203-011W3	PL201	1.1
AEL204W3	PL204	0.7
AEL204-012W3	PL204	1.5
AEL205W3	PL205	0.8
AEL205-013W3	PL205	
AEL205-014W3	PL205	1.8
AEL205-015W3	PL205	
AEL205-100W3	PL205	
AEL206W3	PL206	1.3
AEL206-101W3	PL206	
AEL206-102W3	PL206	2.9
AEL206-103W3	PL206	
AEL206-104W3	PL206	
AEL207W3	PL207	1.6
AEL207-104W3	PL207	
AEL207-105W3	PL207	3.5
AEL207-106W3	PL207	
AEL207-107W3	PL207	

## Pillow block unit, cast housing low center height Eccentric locking collar type




Shaft dia.  mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions											Bolt size  mm inch
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	S	
12 1/2	JELPL201W3	26.99	121	89	35	11	14	13	54	40	28.6	6.5	M10
	JELPL201-008W3	1 1/16	4 3/4	3 1/2	1 3/8	7/16	9/16	1/2	2 1/8	1 9/16	1.126	0.256	3/8
15 9/16 5/8	JELPL202W3	26.99	121	89	35	11	14	13	54	40	28.6	6.5	M10
	JELPL202-009W3	1 1/16	4 3/4	3 1/2	1 3/8	7/16	9/16	1/2	2 1/8	1 9/16	1.126	0.256	3/8
	JELPL202-010W3												
17 11/16	JELPL203W3	26.99	121	89	35	11	14	13	54	40	28.6	6.5	M10
	JELPL203-011W3	1 1/16	4 3/4	3 1/2	1 3/8	7/16	9/16	1/2	2 1/8	1 9/16	1.126	0.256	3/8
20 3/4	JELPL204W3	31.75	127	95	38	13	16	14	64	42	31	7.5	M10
	JELPL204-012W3	1 1/4	5	3 3/4	1 1/2	1/2	5/8	9/16	2 17/32	1 21/32	1.220	0.295	3/8
25 13/16 7/8 15/16 1	JELPL205W3	33.34	140	105	38	13	16	15	68	42	31	7.5	M10
	JELPL205-013W3												
	JELPL205-014W3	1 5/16	5 1/2	4 1/8	1 1/2	1/2	5/8	19/32	2 11/16	1 21/32	1.220	0.295	3/8
	JELPL205-015W3												
JELPL205-100W3													
30 1 1/16 1 1/8 1 3/16 1 1/4	JELPL206W3	39.69	165	121	48	17	20	17	80	54	35.7	9	M14
	JELPL206-101W3												
	JELPL206-102W3	1 9/16	6 1/2	4 3/4	1 7/8	21/32	25/32	21/32	3 5/32	2 1/8	1.406	0.354	1/2
	JELPL206-103W3												
JELPL206-104W3													
35 1 1/4 1 5/16 1 3/8 1 7/16	JELPL207W3	46.04	167	127	48	17	20	18	91	54	38.9	9.5	M14
	JELPL207-104W3												
	JELPL207-105W3	1 13/16	6 9/16	5	1 7/8	21/32	25/32	23/32	3 19/32	2 1/8	1.531	0.374	1/2
	JELPL207-106W3												
JELPL207-107W3													

Notes <sup>(1)</sup> JELPL201 to JELPL205 have solid bases.

<sup>(2)</sup> If relubricatable type is needed, please order with suffix "D1".

Bearing number	Housing number	Mass of unit kg lb
JEL201W3	PL201	0.5
JEL201-008W3	PL201	1.1
JEL202W3	PL201	0.5
JEL202-009W3	PL201	1.1
JEL202-010W3	PL201	
JEL203W3	PL201	0.5
JEL203-011W3	PL201	1.1
JEL204W3	PL204	0.7
JEL204-012W3	PL204	1.5
JEL205W3	PL205	0.8
JEL205-013W3	PL205	
JEL205-014W3	PL205	1.8
JEL205-015W3	PL205	
JEL205-100W3	PL205	
JEL206W3	PL206	1.3
JEL206-101W3	PL206	
JEL206-102W3	PL206	2.9
JEL206-103W3	PL206	
JEL206-104W3	PL206	
JEL207W3	PL207	1.6
JEL207-104W3	PL207	
JEL207-105W3	PL207	3.5
JEL207-106W3	PL207	
JEL207-107W3	PL207	

## Pillow block unit, pressed steel housing Eccentric locking collar type




Shaft dia. mm inch	Unit number	Nominal dimensions									Bolt size mm inch
		mm inch									
		H	L	J	A	N	H <sub>1</sub>	H <sub>2</sub>	B <sub>1</sub>	S	
12 1/2	AELPP201W3	22.2	86	68	25	9.5	3.2	43.8	28.6	6.5	M8
	AELPP201-008W3	7/8	3 3/8	2 1/16	31/32	3/8	0.126	1 23/32	1.126	0.256	5/16
15 9/16 5/8	AELPP202W3	22.2	86	68	25	9.5	3.2	43.8	28.6	6.5	M8
	AELPP202-009W3 AELPP202-010W3	7/8	3 3/8	2 1/16	31/32	3/8	0.126	1 23/32	1.126	0.256	5/16
17 11/16	AELPP203W3	22.2	86	68	25	9.5	3.2	43.8	28.6	6.5	M8
	AELPP203-011W3	7/8	3 3/8	2 1/16	31/32	3/8	0.126	1 23/32	1.126	0.256	5/16
20 3/4	AELPP204W3	25.4	98	76	32	9.5	3.2	50.5	31	7.5	M8
	AELPP204-012W3	1	3 27/32	3	1 1/4	3/8	0.126	2	1.220	0.295	5/16
25 13/16 7/8 15/16 1	AELPP205W3	28.6	108	86	32	11.5	4	56.6	31	7.5	M10
	AELPP205-013W3										
	AELPP205-014W3 AELPP205-015W3 AELPP205-100W3	1 1/8	4 1/4	3 3/8	1 1/4	29/64	0.157	2 7/32	1.220	0.295	3/8
30 1 1/16 1 1/8 1 3/16 1 1/4	AELPP206W3	33.3	117	95	38	11.5	4	66.3	35.7	9	M10
	AELPP206-101W3										
	AELPP206-102W3 AELPP206-103W3 AELPP206-104W3	1 5/16	4 19/32	3 3/4	1 1/2	29/64	0.157	2 5/8	1.406	0.354	3/8
35 1 1/4 1 5/16 1 3/8 1 7/16	AELPP207W3	39.7	129	106	42	11.5	4.6	78	38.9	9.5	M10
	AELPP207-104W3										
	AELPP207-105W3 AELPP207-106W3 AELPP207-107W3	1 9/16	5 3/32	4 3/16	1 21/32	29/64	0.181	3 1/16	1.531	0.374	3/8

Note (1) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.  
The mounting surface should be flat.

Max. load (1) recommended N lbf		Bearing number	Housing number	Mass of unit kg lb
radial	axial			
2 000 440	800 160	AEL201W3	PP203	0.2
		AEL201-008W3	PP203	0.4
2 000 440	800 160	AEL202W3	PP203	0.2
		AEL202-009W3 AEL202-010W3	PP203 PP203	0.4
2 000 440	800 160	AEL203W3	PP203	0.2
		AEL203-011W3	PP203	0.4
2 500 550	1 000 200	AEL204W3	PP204	0.3
		AEL204-012W3	PP204	0.7
3 500 770	1 400 280	AEL205W3	PP205	0.3
		AEL205-013W3 AEL205-014W3 AEL205-015W3 AEL205-100W3	PP205 PP205 PP205 PP205	0.7
4 000 880	1 600 320	AEL206W3	PP206	0.5
		AEL206-101W3 AEL206-102W3 AEL206-103W3 AEL206-104W3	PP206 PP206 PP206 PP206	1.1
4 500 990	1 800 360	AEL207W3	PP207	0.8
		AEL207-104W3 AEL207-105W3 AEL207-106W3 AEL207-107W3	PP207 PP207 PP207 PP207	1.8

## Pillow block unit, pressed steel housing with rubber ring Eccentric locking collar type





Shaft dia.  mm inch	Unit number	Nominal dimensions									Bolt size  mm inch
		mm inch									
		H	L	J	A	N	H <sub>1</sub>	H <sub>2</sub>	B <sub>1</sub>	S	
12  1/2	AELRPP201W3	25.4	98	76	32	9.5	3.2	50.5	28.6	6.5	M8
	AELRPP201-008W3	1	3 <sup>27</sup> / <sub>32</sub>	3	1 <sup>1</sup> / <sub>4</sub>	<sup>3</sup> / <sub>8</sub>	0.126	2	1.126	0.256	<sup>5</sup> / <sub>16</sub>
15  9/16 5/8	AELRPP202W3	25.4	98	76	32	9.5	3.2	50.5	28.6	6.5	M8
	AELRPP202-009W3 AELRPP202-010W3	1	3 <sup>27</sup> / <sub>32</sub>	3	1 <sup>1</sup> / <sub>4</sub>	<sup>3</sup> / <sub>8</sub>	0.126	2	1.126	0.256	<sup>5</sup> / <sub>16</sub>
17  11/16	AELRPP203W3	25.4	98	76	32	9.5	3.2	50.5	28.6	6.5	M8
	AELRPP203-011W3	1	3 <sup>27</sup> / <sub>32</sub>	3	1 <sup>1</sup> / <sub>4</sub>	<sup>3</sup> / <sub>8</sub>	0.126	2	1.126	0.256	<sup>5</sup> / <sub>16</sub>
20  3/4	AELRPP204W3	28.6	108	86	32	11.5	4	56.6	31	7.5	M10
	AELRPP204-012W3	1 <sup>1</sup> / <sub>8</sub>	4 <sup>1</sup> / <sub>4</sub>	3 <sup>3</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>4</sub>	<sup>29</sup> / <sub>64</sub>	0.157	2 <sup>7</sup> / <sub>32</sub>	1.220	0.295	<sup>3</sup> / <sub>8</sub>
25  13/16 7/8 15/16 1	AELRPP205W3	33.3	117	95	38	11.5	4	66.3	31	7.5	M10
	AELRPP205-013W3	1 <sup>5</sup> / <sub>16</sub>	4 <sup>19</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>2</sub>	<sup>29</sup> / <sub>64</sub>	0.157	2 <sup>5</sup> / <sub>8</sub>	1.220	0.295	<sup>3</sup> / <sub>8</sub>
	AELRPP205-014W3										
	AELRPP205-015W3										
AELRPP205-100W3											
30  1 1/16 1 1/8 1 3/16 1 1/4	AELRPP206W3	39.7	129	106	42	11.5	4.6	78	35.7	9	M10
	AELRPP206-101W3	1 <sup>9</sup> / <sub>16</sub>	5 <sup>3</sup> / <sub>32</sub>	4 <sup>3</sup> / <sub>16</sub>	1 <sup>21</sup> / <sub>32</sub>	<sup>29</sup> / <sub>64</sub>	0.181	3 <sup>1</sup> / <sub>16</sub>	1.406	0.354	<sup>3</sup> / <sub>8</sub>
	AELRPP206-102W3										
	AELRPP206-103W3										
AELRPP206-104W3											

**Note** (1) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.  
The mounting surface should be flat.

**Remarks** When an anti-vibration rubber ring is used, the self alignment capability will be reduce.

Max. load (1) recommended N lbf		Bearing number	Housing number		Mass of unit kg lb
radial	axial		rubber ring	steel	
1 000 220	200 40	AEL201W3	R201	PP204	0.2
		AEL201-008W3	R201	PP204	0.4
1 000 220	200 40	AEL202W3	R202	PP204	0.2
		AEL202-009W3 AEL202-010W3	R202 R202	PP204 PP204	0.4
1 000 220	200 40	AEL203W3	R203	PP204	0.2
		AEL203-011W3	R203	PP204	0.4
1 150 250	200 40	AEL204W3	R204	PP205	0.3
		AEL204-012W3	R204	PP205	0.7
1 300 280	200 40	AEL205W3	R205	PP206	0.4
		AEL205-013W3	R205	PP206	0.9
		AEL205-014W3	R205	PP206	
		AEL205-015W3 AEL205-100W3	R205 R205	PP206 PP206	
1 500 330	200 40	AEL206W3	R206	PP207	
		AEL206-101W3	R206	PP207	1.3
		AEL206-102W3	R206	PP207	
		AEL206-103W3 AEL206-104W3	R206 R206	PP207 PP207	

## Square flanged unit, cast housing Eccentric locking collar type




Shaft dia.  mm inch	Unit number (1)	Nominal dimensions										Bolt size  mm inch
		mm inch										
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B <sub>1</sub>	S	F min.	
20  3/4	UELF204D1W3	86	64	15	11	25.5	12	41.6	43.7	17.1	34	M10
	UELF204-012D1W3	3 3/8	2 33/64	19/32	7/16	1	15/32	1 41/64	1.720	0.673	1.339	3/8
25  13/16 7/8 15/16 1	UELF205D1W3	95	70	16	13	27	12	42.95	44.4	17.45	38	M10
	UELF205-013D1W3	3 3/4	2 3/4	5/8	1/2	1 1/16	15/32	1 11/16	1.748	0.687	1.496	3/8
	UELF205-014D1W3											
	UELF205-015D1W3											
UELF205-100D1W3												
30  1 1/16 1 1/8 1 1/16 1 1/4	UELF206D1W3	108	83	18	13	31	12	48.15	48.4	18.25	45	M10
	UELF206-101D1W3	4 1/4	3 17/64	45/64	1/2	1 7/32	15/32	1 57/64	1.906	0.719	1.772	3/8
	UELF206-102D1W3											
	UELF206-103D1W3											
UELF206-104D1W3												
35  1 1/4 1 5/16 1 3/8 1 7/16	UELF207D1W3	117	92	19	15	34	14	51.3	51.1	18.8	51	M12
	UELF207-104D1W3	4 19/32	3 5/8	3/4	19/32	1 11/32	35/64	2 1/64	2.012	0.740	2.008	7/16
	UELF207-105D1W3											
	UELF207-106D1W3											
UELF207-107D1W3												
40  1 1/2 1 9/16	UELF208D1W3	130	102	21	15	36	16	55.9	56.3	21.4	57	M14
	UELF208-108D1W3	5 1/8	4 1/64	53/64	19/32	1 13/32	5/8	2 13/64	2.217	0.843	2.244	1/2
	UELF208-109D1W3											
UELF209D1W3												
45  1 5/8 1 11/16 1 3/4	UELF209D1W3	137	105	22	16	38	16	56.9	56.3	21.4	62	M14
	UELF209-110D1W3	5 13/32	4 9/64	55/64	5/8	1 1/2	5/8	2 15/64	2.217	0.843	2.441	1/2
	UELF209-111D1W3											
UELF209-112D1W3												
50  1 13/16 1 7/8 1 15/16 2	UELF210D1W3	143	111	22	16	40	16	60.1	62.7	24.6	67	M14
	UELF210-113D1W3	5 5/8	4 3/8	55/64	5/8	1 9/16	5/8	2 23/64	2.469	0.969	2.638	1/2
	UELF210-114D1W3											
	UELF210-115D1W3											
UELF210-200D1W3												

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting

Bearing number	Housing number	Mass of unit kg lb
UEL204D1W3	F204D1	0.6
UEL204-012D1W3	F204D1	1.3
UEL205D1W3	F205D1	0.9
UEL205-013D1W3	F205D1	2.0
UEL205-014D1W3	F205D1	
UEL205-015D1W3	F205D1	
UEL205-100D1W3	F205D1	
UEL206D1W3	F206D1	1.2
UEL206-101D1W3	F206D1	2.6
UEL206-102D1W3	F206D1	
UEL206-103D1W3	F206D1	
UEL206-104D1W3	F206D1	
UEL207D1W3	F207D1	1.6
UEL207-104D1W3	F207D1	3.5
UEL207-105D1W3	F207D1	
UEL207-106D1W3	F207D1	
UEL207-107D1W3	F207D1	
UEL208D1W3	F208D1	1.9
UEL208-108D1W3	F208D1	4.2
UEL208-109D1W3	F208D1	
UEL209D1W3	F209D1	2.3
UEL209-110D1W3	F209D1	5.1
UEL209-111D1W3	F209D1	
UEL209-112D1W3	F209D1	
UEL210D1W3	F210D1	
UEL210-113D1W3	F210D1	6.0
UEL210-114D1W3	F210D1	
UEL210-115D1W3	F210D1	
UEL210-200D1W3	F210D1	

## Square flanged unit, cast housing Eccentric locking collar type



Shaft dia.  mm inch	Unit number (1)	Nominal dimensions										Bolt size  mm inch
		mm inch										
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B <sub>1</sub>	S	F <sub>min.</sub>	
55	<b>UELF211D1W3</b>	162	130	25	18	43	19	68.65	71.4	27.75	73	M16
2	<b>UELF211-200D1W3</b>											
2 1/16	<b>UELF211-201D1W3</b>											
2 1/8	<b>UELF211-202D1W3</b>	6 3/8	5 1/8	63/64	23/32	1 11/16	3/4	2 45/64	2.811	1.093	2.874	5/8
2 3/16	<b>UELF211-203D1W3</b>											
60	<b>UELF212D1W3</b>	175	143	29	18	48	19	75.85	77.8	30.95	81	M16
2 1/4	<b>UELF212-204D1W3</b>											
2 5/16	<b>UELF212-205D1W3</b>											
2 3/8	<b>UELF212-206D1W3</b>	6 7/8	5 5/8	1 9/64	23/32	1 7/8	3/4	2 63/64	3.063	1.219	3.189	5/8
2 7/16	<b>UELF212-207D1W3</b>											
65	<b>UELF213D1W3</b>	187	149	30	22	50	19	81.55	85.7	34.15	87	M16
2 1/2	<b>UELF213-208D1W3</b>											
2 9/16	<b>UELF213-209D1W3</b>	7 3/8	5 55/64	1 3/16	7/8	1 31/32	3/4	3 13/64	3.374	1.344	3.425	5/8
70	<b>UELF214D1W3</b>	193	152	31	22	54	19	82.55	85.7	34.15	91	M16
2 5/8	<b>UELF214-210D1W3</b>											
2 11/16	<b>UELF214-211D1W3</b>											
2 3/4	<b>UELF214-212D1W3</b>	7 19/32	5 63/64	1 7/32	7/8	2 1/8	3/4	3 1/4	3.374	1.344	3.583	5/8
75	<b>UELF215D1W3</b>	200	159	34	22	56	19	88.7	92	37.3	97	M16
2 13/16	<b>UELF215-213D1W3</b>											
2 7/8	<b>UELF215-214D1W3</b>											
2 15/16	<b>UELF215-215D1W3</b>	7 7/8	6 7/64	1 11/32	7/8	2 7/32	3/4	3 31/64	3.622	1.469	3.819	5/8
3	<b>UELF215-300D1W3</b>											


Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
<b>UEL211D1W3</b>	<b>F211D1</b>	3.6
UEL211-200D1W3	F211D1	
UEL211-201D1W3	F211D1	7.9
UEL211-202D1W3	F211D1	
UEL211-203D1W3	F211D1	
<b>UEL212D1W3</b>	<b>F212D1</b>	4.2
UEL212-204D1W3	F212D1	
UEL212-205D1W3	F212D1	9.3
UEL212-206D1W3	F212D1	
UEL212-207D1W3	F212D1	
<b>UEL213D1W3</b>	<b>F213D1</b>	6.1
UEL213-208D1W3	F213D1	13
UEL213-209D1W3	F213D1	
<b>UEL214D1W3</b>	<b>F214D1</b>	6.6
UEL214-210D1W3	F214D1	
UEL214-211D1W3	F214D1	15
UEL214-212D1W3	F214D1	
<b>UEL215D1W3</b>	<b>F215D1</b>	6.9
UEL215-213D1W3	F215D1	
UEL215-214D1W3	F215D1	15
UEL215-215D1W3	F215D1	
UEL215-300D1W3	F215D1	

# UELF3

Square flanged unit, cast housing  
Eccentric locking collar type



Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )	Nominal dimensions										Bolt size mm inch
		mm inch										
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B <sub>1</sub>	S	F min.	
25 $\frac{13}{16}$ $\frac{7}{8}$ $\frac{15}{16}$ 1	UELF305D1W3	110	80	16	13	29	16	46.1	46.8	16.7	41	M14
	UELF305-013D1W3											
	UELF305-014D1W3											
	UELF305-015D1W3											
	UELF305-100D1W3	4 $\frac{11}{32}$	3 $\frac{5}{32}$	$\frac{5}{8}$	$\frac{1}{2}$	1 $\frac{5}{32}$	$\frac{5}{8}$	1 $\frac{13}{16}$	1.843	0.657	1.614	$\frac{1}{2}$
30 $1\frac{1}{16}$ $1\frac{1}{8}$ $1\frac{3}{16}$	UELF306D1W3	125	95	18	15	32	16	50.5	50	17.5	49	M14
	UELF306-101D1W3											
	UELF306-102D1W3											
	UELF306-103D1W3											
	UELF306-104D1W3	4 $\frac{29}{32}$	3 $\frac{47}{64}$	$\frac{45}{64}$	$\frac{19}{32}$	1 $\frac{1}{4}$	$\frac{5}{8}$	1 $\frac{63}{64}$	1.969	0.689	1.929	$\frac{1}{2}$
35 $1\frac{1}{4}$ $1\frac{5}{16}$ $1\frac{3}{8}$ $1\frac{7}{16}$	UELF307D1W3	135	100	20	16	36	19	53.3	51.6	18.3	—	M16
	UELF307-104D1W3											
	UELF307-105D1W3											
	UELF307-106D1W3											
	UELF307-107D1W3	5 $\frac{5}{16}$	3 $\frac{15}{16}$	$\frac{25}{32}$	$\frac{5}{8}$	1 $\frac{13}{32}$	$\frac{3}{4}$	2 $\frac{3}{32}$	2.031	0.720	—	$\frac{5}{8}$
40 $1\frac{1}{2}$ $1\frac{9}{16}$	UELF308D1W3	150	112	23	17	40	19	60.3	57.1	19.8	—	M16
	UELF308-108D1W3											
	UELF308-109D1W3											
	UELF308-110D1W3	5 $\frac{29}{32}$	4 $\frac{13}{32}$	$\frac{29}{32}$	$\frac{21}{32}$	1 $\frac{9}{16}$	$\frac{3}{4}$	2 $\frac{3}{8}$	2.248	0.780	—	$\frac{5}{8}$
45 $1\frac{5}{8}$ $1\frac{11}{16}$ $1\frac{3}{4}$	UELF309D1W3	160	125	25	18	44	19	63.9	58.7	19.8	—	M16
	UELF309-110D1W3											
	UELF309-111D1W3											
	UELF309-112D1W3											
	UELF309-113D1W3	6 $\frac{5}{16}$	4 $\frac{59}{64}$	$\frac{63}{64}$	$\frac{23}{32}$	1 $\frac{23}{32}$	$\frac{3}{4}$	2 $\frac{33}{64}$	2.311	0.780	—	$\frac{5}{8}$
50 $1\frac{13}{16}$ $1\frac{1}{2}$ $1\frac{15}{16}$	UELF310D1W3	175	132	28	19	48	23	70	66.6	24.6	—	M20
	UELF310-113D1W3											
	UELF310-114D1W3											
	UELF310-115D1W3											
	UELF310-116D1W3	6 $\frac{7}{8}$	5 $\frac{13}{64}$	1 $\frac{7}{64}$	$\frac{3}{4}$	1 $\frac{7}{8}$	$\frac{29}{32}$	2 $\frac{3}{4}$	2.622	0.969	—	$\frac{3}{4}$

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".


<sup>(2)</sup> Inner race face does not protrude from the housing face except UELF305 and UELF316.

Remarks Please refer to page A21 for size of grease fitting

Bearing number	Housing number	Mass of unit kg lb
UELF305D1W3	F305D1	1.2
UELF305-013D1W3	F305D1	
UELF305-014D1W3	F305D1	2.6
UELF305-015D1W3	F305D1	
UELF305-100D1W3	F305D1	
UELF306D1W3	F306D1	1.8
UELF306-101D1W3	F306D1	
UELF306-102D1W3	F306D1	4.0
UELF306-103D1W3	F306D1	
UELF307D1W3	F307D1	2.2
UELF307-104D1W3	F307D1	
UELF307-105D1W3	F307D1	4.9
UELF307-106D1W3	F307D1	
UELF307-107D1W3	F307D1	
UELF308D1W3	F308D1	2.9
UELF308-108D1W3	F308D1	
UELF308-109D1W3	F308D1	6.4
UELF309D1W3	F309D1	3.6
UELF309-110D1W3	F309D1	
UELF309-111D1W3	F309D1	7.9
UELF309-112D1W3	F309D1	
UELF310D1W3	F310D1	4.6
UELF310-113D1W3	F310D1	
UELF310-114D1W3	F310D1	10
UELF310-115D1W3	F310D1	



## Square flanged unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions										Bolt size mm inch
		mm inch										
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B <sub>1</sub>	S	F min.	
55 2 2 1/16 2 1/8 2 3/16	<b>UELF311D1W3</b> <b>UELF311-200D1W3</b> <b>UELF311-201D1W3</b> <b>UELF311-202D1W3</b> <b>UELF311-203D1W3</b>	185	140	30	20	52	23	75.2	73	27.8	—	M20
		7 9/32	5 33/64	1 3/16	25/32	2 1/16	29/32	2 61/64	2.874	1.094	—	3/4
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UELF312D1W3</b> <b>UELF312-204D1W3</b> <b>UELF312-205D1W3</b> <b>UELF312-206D1W3</b> <b>UELF312-207D1W3</b>	195	150	33	22	56	23	81.45	79.4	30.95	—	M20
		7 11/16	5 29/32	1 19/64	7/8	2 7/32	29/32	3 13/64	3.126	1.219	—	3/4
65 2 1/2 2 9/16	<b>UELF313D1W3</b> <b>UELF313-208D1W3</b> <b>UELF313-209D1W3</b>	208	166	33	22	58	23	86.15	85.7	32.55	93	M20
		8 3/16	6 17/32	1 19/64	7/8	2 9/32	29/32	3 25/64	3.374	1.281	3.661	3/4
70 2 5/8 2 11/16 2 3/4	<b>UELF314D1W3</b> <b>UELF314-210D1W3</b> <b>UELF314-211D1W3</b> <b>UELF314-212D1W3</b>	226	178	36	25	61	25	93.95	92.1	34.15	—	M22
		8 29/32	6 1/64	1 27/64	31/32	2 13/32	63/64	3 45/64	3.626	1.344	—	7/8
75 2 13/16 2 7/8 2 15/16 3	<b>UELF315D1W3</b> <b>UELF315-213D1W3</b> <b>UELF315-214D1W3</b> <b>UELF315-215D1W3</b> <b>UELF315-300D1W3</b>	236	184	39	25	66	25	101.7	100	37.3	106	M22
		9 9/32	7 1/4	1 17/32	31/32	2 19/32	63/64	4	3.937	1.469	4.173	7/8
80 3 1/16 3 1/8 3 3/16	<b>UELF316D1W3</b> <b>UELF316-301D1W3</b> <b>UELF316-302D1W3</b> <b>UELF316-303D1W3</b>	250	196	38	27	68	31	103.9	106.4	40.5	112	M27
		9 27/32	7 23/32	1 1/2	1 1/16	2 11/16	1 7/32	4 3/32	4.189	1.594	4.409	1


Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Inner race face does not protrude from the housing face except UELF305 and UELF316.

Remarks Please refer to page A21 for size of grease fitting

Bearing number	Housing number	Mass of unit kg lb
UEL311D1W3	F311D1	5.6
UEL311-200D1W3	F311D1	12
UEL311-201D1W3	F311D1	
UEL311-202D1W3	F311D1	
UEL311-203D1W3	F311D1	
UEL312D1W3	F312D1	6.7
UEL312-204D1W3	F312D1	15
UEL312-205D1W3	F312D1	
UEL312-206D1W3	F312D1	
UEL312-207D1W3	F312D1	
UEL313D1W3	F313D1	8.4
UEL313-208D1W3	F313D1	19
UEL313-209D1W3	F313D1	
UEL314D1W3	F314D1	10
UEL314-210D1W3	F314D1	22
UEL314-211D1W3	F314D1	
UEL314-212D1W3	F314D1	
UEL315D1W3	F315D1	12
UEL315-213D1W3	F315D1	26
UEL315-214D1W3	F315D1	
UEL315-215D1W3	F315D1	
UEL315-300D1W3	F315D1	
UEL316D1W3	F316D1	15
UEL316-301D1W3	F316D1	33
UEL316-302D1W3	F316D1	
UEL316-303D1W3	F316D1	

# UELF3

Square flanged unit, cast housing  
Eccentric locking collar type



Shaft dia.  mm inch	Unit number <sup>(1)</sup> / <sub>(2)</sub>	Nominal dimensions										Bolt size  mm inch
		mm inch										
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B <sub>1</sub>	S	F min.	
85 3 1/4 3 5/16 3 7/16	UELF317D1W3 UELF317-304D1W3 UELF317-305D1W3 UELF317-307D1W3	260 10 1/4	204 8 1/2	44 1 7/16	27 1 1/16	74 2 29/32	31 1 1/32	111.45 4.311	109.5 4.311	42.05 1.656	119 4.685	M27 1
90 3 7/16 3 1/2	UELF318D1W3 UELF318-307D1W3 UELF318-308D1W3	280 11 1/32	216 8 1/2	44 1 7/16	30 1 3/16	76 3	35 1 3/8	116.25 4.563	115.9 4.563	43.65 1.719	125 4.921	M30 1 1/8
95 3 5/8 3 11/16 3 3/4	UELF319D1W3 UELF319-310D1W3 UELF319-311D1W3 UELF319-312D1W3	290 11 13/32	228 8 31/32	59 2 21/64	30 1 3/16	94 3 11/16	35 1 3/8	142.4 5.39/64	122.3 4.815	38.9 1.531	— —	M30 1 1/8
100 3 13/16 3 7/8 3 15/16 4	UELF320D1W3 UELF320-313D1W3 UELF320-314D1W3 UELF320-315D1W3 UELF320-400D1W3	310 12 7/32	242 9 17/32	59 2 21/64	32 1 1/4	94 3 11/16	38 1 1/2	137.6 5.063	128.6 5.063	50 1.969	— —	M33 1 1/4
105	UELF321D1W3	310	242	59	32	94	38	150.3	139.7	48.4	—	M33
110	UELF322D1W3	340	266	60	35	96	41	152.1	141.3	49.2	—	M36


Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Inner race face does not protrude from the housing face except UELF305 and UELF316.

Remarks Please refer to page A21 for size of grease fitting

Bearing number	Housing number	Mass of unit kg lb
UEL317D1W3	F317D1	16
UEL317-304D1W3	F317D1	35
UEL317-305D1W3	F317D1	
UEL317-307D1W3	F317D1	
UEL318D1W3	F318D1	20
UEL318-308D1W3	F318D1	44
UEL318-308D1W3	F318D1	
UEL319D1W3	F319D1	24
UEL319-310D1W3	F319D1	53
UEL319-311D1W3	F319D1	
UEL319-312D1W3	F319D1	
UEL320D1W3	F320D1	29
UEL320-313D1W3	F320D1	64
UEL320-314D1W3	F320D1	
UEL320-315D1W3	F320D1	
UEL320-400D1W3	F320D1	
UEL321D1W3	F321D1	28
UEL322D1W3	F322D1	37

## Square flanged unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions									Bolt size mm inch
		mm inch									
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B <sub>1</sub>	S	
20 3/4	<b>UELFU204D1W3</b> <b>UELFU204-012D1W3</b>	86 3 3/8	63.5 2 1/2	19 3/4	15 19/32	29.5 1 5/32	11.5 29/64	45.6 1 51/64	43.7 1.720	17.1 0.673	M10 3/8
25 13/16 7/8 15/16	<b>UELFU205D1W3</b> <b>UELFU205-013D1W3</b> <b>UELFU205-014D1W3</b> <b>UELFU205-015D1W3</b>	96 3 25/32	70 2 3/4	19 3/4	15 19/32	30 1 3/16	11.5 29/64	45.95 1 13/16	44.4 1.748	17.45 0.687	M10 3/8
1	<b>UELFU205-100D1W3</b>										
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UELFU206D1W3</b> <b>UELFU206-101D1W3</b> <b>UELFU206-102D1W3</b> <b>UELFU206-103D1W3</b> <b>UELFU206-104D1W3</b>	109 4 9/32	82.5 3 1/4	20 25/32	16 5/8	33 1 5/16	11.5 29/64	50.15 1 31/32	48.4 1.906	18.25 0.719	M10 3/8
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UELFU207D1W3</b> <b>UELFU207-104D1W3</b> <b>UELFU207-105D1W3</b> <b>UELFU207-106D1W3</b> <b>UELFU207-107D1W3</b>	118 4 21/32	92 3 5/8	21 53/64	17 21/32	36 1 13/32	14 35/64	53.3 2 3/32	51.1 2.012	18.8 0.740	M12 1/2
40 1 1/2 1 9/16	<b>UELFU208D1W3</b> <b>UELFU208-108D1W3</b> <b>UELFU208-109D1W3</b>	131 5 5/32	101.5 4	24 15/16	17 21/32	39 1 17/32	14 35/64	58.9 2 5/16	56.3 2.217	21.4 0.843	M12 1/2
45 1 5/8 1 11/16 1 3/4	<b>UELFU209D1W3</b> <b>UELFU209-110D1W3</b> <b>UELFU209-111D1W3</b> <b>UELFU209-112D1W3</b>	137 5 13/32	105 4 9/64	24 15/16	18 23/32	40 1 9/16	16 5/8	58.9 2 5/16	56.3 2.217	21.4 0.843	M14 1/2
50 1 13/16 1 7/8 1 15/16 2	<b>UELFU210D1W3</b> <b>UELFU210-113D1W3</b> <b>UELFU210-114D1W3</b> <b>UELFU210-115D1W3</b> <b>UELFU210-200D1W3</b>	144 5 21/32	111 4 3/8	28 1 7/64	20 25/32	46 1 13/16	18 45/64	66.1 2 39/64	62.7 2.469	24.6 0.969	M16 5/8

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
<b>UEL204D1W3</b> UEL204-012D1W3	<b>FU204D1</b> FU204D1	0.8 1.8
<b>UEL205D1W3</b> UEL205-013D1W3 UEL205-014D1W3 UEL205-015D1W3 UEL205-100D1W3	<b>FU205D1</b> FU205D1 FU205D1 FU205D1 FU205D1	1.0 2.2
<b>UEL206D1W3</b> UEL206-101D1W3 UEL206-102D1W3 UEL206-103D1W3 UEL206-104D1W3	<b>FU206D1</b> FU206D1 FU206D1 FU206D1 FU206D1	1.4 3.1
<b>UEL207D1W3</b> UEL207-104D1W3 UEL207-105D1W3 UEL207-106D1W3 UEL207-107D1W3	<b>FU207D1</b> FU207D1 FU207D1 FU207D1 FU207D1	1.7 3.7
<b>UEL208D1W3</b> UEL208-108D1W3 UEL208-109D1W3	<b>FU208D1</b> FU208D1 FU208D1	2.2 4.9
<b>UEL209D1W3</b> UEL209-110D1W3 UEL209-111D1W3 UEL209-112D1W3	<b>FU209D1</b> FU209D1 FU209D1 FU209D1	2.4 5.3
<b>UEL210D1W3</b> UEL210-113D1W3 UEL210-114D1W3 UEL210-115D1W3 UEL210-200D1W3	<b>FU210D1</b> FU210D1 FU210D1 FU210D1 FU210D1	2.9 6.4

Square flanged unit, cast housing  
Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions									Bolt size mm inch
		mm inch									
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B <sub>1</sub>	S	
55	UELFU211D1W3	163	130	31	21	49	18	74.65	71.4	27.75	M16
2	UELFU211-200D1W3	6 <sup>13</sup> / <sub>32</sub>	5 <sup>1</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>16</sub>	1 <sup>15</sup> / <sub>16</sub>	4 <sup>5</sup> / <sub>64</sub>	2 <sup>15</sup> / <sub>16</sub>	2.811	1.093	5 <sup>5</sup> / <sub>8</sub>
2 <sup>1</sup> / <sub>16</sub>	UELFU211-201D1W3										
2 <sup>1</sup> / <sub>8</sub>	UELFU211-202D1W3										
2 <sup>3</sup> / <sub>16</sub>	UELFU211-203D1W3										
60	UELFU212D1W3	175	143	34	21	53	18	80.85	77.8	30.95	M16
2 <sup>1</sup> / <sub>4</sub>	UELFU212-204D1W3	6 <sup>7</sup> / <sub>8</sub>	5 <sup>5</sup> / <sub>8</sub>	1 <sup>11</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>16</sub>	2 <sup>3</sup> / <sub>32</sub>	4 <sup>5</sup> / <sub>64</sub>	3 <sup>3</sup> / <sub>16</sub>	3.063	1.219	5 <sup>5</sup> / <sub>8</sub>
2 <sup>5</sup> / <sub>16</sub>	UELFU212-205D1W3										
2 <sup>3</sup> / <sub>8</sub>	UELFU212-206D1W3										
2 <sup>7</sup> / <sub>16</sub>	UELFU212-207D1W3										
65	UELFU213D1W3	187	149	38	22	59	20.5	89.55	85.7	34.15	M18
2 <sup>1</sup> / <sub>2</sub>	UELFU213-208D1W3	7 <sup>3</sup> / <sub>8</sub>	5 <sup>55</sup> / <sub>64</sub>	1 <sup>1</sup> / <sub>2</sub>	7 <sup>7</sup> / <sub>8</sub>	2 <sup>5</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	3 <sup>17</sup> / <sub>32</sub>	3.374	1.344	5 <sup>5</sup> / <sub>8</sub>
2 <sup>9</sup> / <sub>16</sub>	UELFU213-209D1W3										
70	UELFU214D1W3	193	152	38	22	62	20.5	89.55	85.7	34.15	M18
2 <sup>5</sup> / <sub>8</sub>	UELFU214-210D1W3	7 <sup>19</sup> / <sub>32</sub>	5 <sup>63</sup> / <sub>64</sub>	1 <sup>1</sup> / <sub>2</sub>	7 <sup>7</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	3 <sup>17</sup> / <sub>32</sub>	3.374	1.344	5 <sup>5</sup> / <sub>8</sub>
2 <sup>11</sup> / <sub>16</sub>	UELFU214-211D1W3										
2 <sup>3</sup> / <sub>4</sub>	UELFU214-212D1W3										
75	UELFU215D1W3	200	159	41	22	64	20.5	95.7	92	37.3	M18
2 <sup>13</sup> / <sub>16</sub>	UELFU215-213D1W3	7 <sup>7</sup> / <sub>8</sub>	6 <sup>17</sup> / <sub>64</sub>	1 <sup>39</sup> / <sub>64</sub>	7 <sup>7</sup> / <sub>8</sub>	2 <sup>33</sup> / <sub>64</sub>	1 <sup>3</sup> / <sub>16</sub>	3 <sup>19</sup> / <sub>64</sub>	3.622	1.469	5 <sup>5</sup> / <sub>8</sub>
2 <sup>7</sup> / <sub>8</sub>	UELFU215-214D1W3										
2 <sup>15</sup> / <sub>16</sub>	UELFU215-215D1W3										
3	UELFU215-300D1W3										

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL211D1W3	FU211D1	3.9
UEL211-200D1W3	FU211D1	8.6
UEL211-201D1W3	FU211D1	
UEL211-202D1W3	FU211D1	
UEL211-203D1W3	FU211D1	
UEL212D1W3	FU212D1	4.7
UEL212-204D1W3	FU212D1	10
UEL212-205D1W3	FU212D1	
UEL212-206D1W3	FU212D1	
UEL212-207D1W3	FU212D1	
UEL213D1W3	FU213D1	6.3
UEL213-208D1W3	FU213D1	14
UEL213-209D1W3	FU213D1	
UEL214D1W3	FU214D1	6.7
UEL214-210D1W3	FU214D1	15
UEL214-211D1W3	FU214D1	
UEL214-212D1W3	FU214D1	
UEL215D1W3	FU215D1	7.0
UEL215-213D1W3	FU215D1	15
UEL215-214D1W3	FU215D1	
UEL215-215D1W3	FU215D1	
UEL215-300D1W3	FU215D1	

## Square flanged unit, cast housing with spigot joint Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		L	J	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>	S	
25 1 3/16 7/8 15/16 1	UELFS305D1W3	110	80	9	16	7	13	29	80	46.1	46.8	16.7	M14
	UELFS305-013D1W3												
	UELFS305-014D1W3	4 11/32	3 5/32	23/64	5/8	9/32	1/2	1 9/64	3.1496	1 13/16	1.843	0.657	1/2
	UELFS305-015D1W3												
	UELFS305-100D1W3												
30 1 1/16 1 1/8 1 3/16	UELFS306D1W3	125	95	10	16	8	15	32	90	50.5	50	17.5	M14
	UELFS306-101D1W3												
	UELFS306-102D1W3	4 29/32	3 47/64	25/64	5/8	5/16	19/32	1 17/64	3.5433	1 63/64	1.969	0.689	1/2
	UELFS306-103D1W3												
35 1 1/4 1 5/16 1 3/8 1 7/16	UELFS307D1W3	135	100	11	19	9	16	36	100	53.3	51.6	18.3	M16
	UELFS307-104D1W3												
	UELFS307-105D1W3	5 5/16	3 15/16	7/16	3/4	23/64	5/8	1 13/32	3.9370	2 3/32	2.031	0.720	5/8
	UELFS307-106D1W3												
	UELFS307-107D1W3												
40 1 1/2 1 9/16	UELFS308D1W3	150	112	13	19	10	17	40	115	60.3	57.1	19.8	M16
	UELFS308-108D1W3												
	UELFS308-109D1W3	5 29/32	4 13/32	39/64	3/4	25/64	21/32	1 9/16	4.5276	2 3/8	2.248	0.780	5/8
45 1 5/8 1 11/16 1 3/4	UELFS309D1W3	160	125	14	19	11	18	44	125	63.9	58.7	19.8	M16
	UELFS309-110D1W3												
	UELFS309-111D1W3	6 5/16	4 59/64	35/64	3/4	7/16	23/32	1 47/64	4.9213	2 33/64	2.311	0.780	5/8
	UELFS309-112D1W3												
50 1 13/16 1 7/8 1 15/16	UELFS310D1W3	175	132	16	23	12	19	48	140	70	66.6	24.6	M20
	UELFS310-113D1W3												
	UELFS310-114D1W3	6 7/8	5 13/64	5/8	29/32	15/32	3/4	1 57/64	5.5118	2 3/4	2.622	0.969	3/4
	UELFS310-115D1W3												

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL305D1W3	FS305D1	1.3
UEL305-013D1W3	FS305D1	
UEL305-014D1W3	FS305D1	2.9
UEL305-015D1W3	FS305D1	
UEL305-100D1W3	FS305D1	
UEL306D1W3	FS306D1	1.9
UEL306-101D1W3	FS306D1	
UEL306-102D1W3	FS306D1	4.2
UEL306-103D1W3	FS306D1	
UEL307D1W3	FS307D1	2.3
UEL307-104D1W3	FS307D1	
UEL307-105D1W3	FS307D1	5.1
UEL307-106D1W3	FS307D1	
UEL307-107D1W3	FS307D1	
UEL308D1W3	FS308D1	3.3
UEL308-108D1W3	FS308D1	
UEL308-109D1W3	FS308D1	7.3
UEL309D1W3	FS309D1	4.0
UEL309-110D1W3	FS309D1	
UEL309-111D1W3	FS309D1	8.8
UEL309-112D1W3	FS309D1	
UEL310D1W3	FS310D1	5.2
UEL310-113D1W3	FS310D1	
UEL310-114D1W3	FS310D1	11
UEL310-115D1W3	FS310D1	

## Square flanged unit, cast housing with spigot joint Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		L	J	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>	S	
55 2 2 1/16 2 1/8 2 3/16	UELFS311D1W3 UELFS311-200D1W3 UELFS311-201D1W3 UELFS311-202D1W3 UELFS311-203D1W3	185	140	17	23	13	20	52	150	75.2	73	27.8	M20 3/4
60 2 1/4 2 5/16 2 3/8 2 7/16	UELFS312D1W3 UELFS312-204D1W3 UELFS312-205D1W3 UELFS312-206D1W3 UELFS312-207D1W3	195	150	19	23	14	22	56	160	81.45	79.4	30.95	M20 3/4
65 2 1/2 2 9/16	UELFS313D1W3 UELFS313-208D1W3 UELFS313-209D1W3	208	166	15	23	18	22	58	175	86.15	85.7	32.55	M20 3/4
70 2 5/8 2 11/16 2 3/4	UELFS314D1W3 UELFS314-210D1W3 UELFS314-211D1W3 UELFS314-212D1W3	226	178	18	25	18	25	61	185	93.95	92.1	34.15	M22 7/8
75 2 13/16 2 7/8 2 15/16 3	UELFS315D1W3 UELFS315-213D1W3 UELFS315-214D1W3 UELFS315-215D1W3 UELFS315-300D1W3	236	184	21	25	18	25	66	200	101.7	100	37.3	M22 7/8
80 3 1/16 3 1/8 3 3/16	UELFS316D1W3 UELFS316-301D1W3 UELFS316-302D1W3 UELFS316-303D1W3	250	196	18	31	20	27	68	210	103.9	106.4	40.5	M27 1

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL311D1W3	FS311D1	6.2
UEL311-200D1W3	FS311D1	14
UEL311-201D1W3	FS311D1	
UEL311-202D1W3	FS311D1	
UEL311-203D1W3	FS311D1	
UEL312D1W3	FS312D1	7.4
UEL312-204D1W3	FS312D1	16
UEL312-205D1W3	FS312D1	
UEL312-206D1W3	FS312D1	
UEL312-207D1W3	FS312D1	
UEL313D1W3	FS313D1	9.0
UEL313-208D1W3	FS313D1	20
UEL313-209D1W3	FS313D1	
UEL314D1W3	FS314D1	11
UEL314-210D1W3	FS314D1	24
UEL314-211D1W3	FS314D1	
UEL314-212D1W3	FS314D1	
UEL315D1W3	FS315D1	13
UEL315-213D1W3	FS315D1	29
UEL315-214D1W3	FS315D1	
UEL315-215D1W3	FS315D1	
UEL315-300D1W3	FS315D1	
UEL316D1W3	FS316D1	16
UEL316-301D1W3	FS316D1	35
UEL316-302D1W3	FS316D1	
UEL316-303D1W3	FS316D1	

## Square flanged unit, cast housing with spigot joint Eccentric locking collar type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		L	J	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>	S	
85 3 1/4 3 5/16 3 7/16	<b>UELFS317D1W3</b> <b>UELFS317-304D1W3</b> <b>UELFS317-305D1W3</b> <b>UELFS317-307D1W3</b>	260 10 1/4	204 8 1/2	24 15/16	31 1 7/32	20 25/32	27 1 1/16	74 2 29/32	220 8.6614	111.45 4 25/64	109.5 4.311	42.05 1.656	M27 1
90 3 7/16 3 1/2	<b>UELFS318D1W3</b> <b>UELFS318-307D1W3</b> <b>UELFS318-308D1W3</b>	280 11 1/32	216 8 1/2	24 15/16	35 1 3/8	20 25/32	30 1 3/16	76 2 53/64	240 9.4488	116.25 4 37/64	115.9 4.563	43.65 1.719	M30 1 1/8
95 3 5/8 3 11/16 3 3/4	<b>UELFS319D1W3</b> <b>UELFS319-310D1W3</b> <b>UELFS319-311D1W3</b> <b>UELFS319-312D1W3</b>	290 11 13/32	228 8 31/32	39 1 17/32	35 1 3/8	20 25/32	30 1 3/16	94 3 45/64	250 9.8425	142.4 5 39/64	122.3 4.815	38.9 1.531	M30 1 1/8
100 3 13/16 3 7/8 3 15/16 4	<b>UELFS320D1W3</b> <b>UELFS320-313D1W3</b> <b>UELFS320-314D1W3</b> <b>UELFS320-315D1W3</b> <b>UELFS320-400D1W3</b>	310 12 7/32	242 9 17/32	39 1 17/32	38 1 1/2	20 25/32	32 1 1/4	94 3 45/64	260 10.2362	137.6 5 27/64	128.6 5.063	50 1.969	M33 1 1/4
105	<b>UELFS321D1W3</b>	310	242	39	38	20	32	94	260	150.3	139.7	48.4	M33
110	<b>UELFS322D1W3</b>	340	266	35	41	25	35	96	300	152.1	141.3	49.2	M36

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL317D1W3	FS317D1	18
UEL317-304D1W3	FS317D1	40
UEL317-305D1W3	FS317D1	40
UEL317-307D1W3	FS317D1	40
UEL318D1W3	FS318D1	22
UEL318-307D1W3	FS318D1	49
UEL318-308D1W3	FS318D1	49
UEL319D1W3	FS319D1	26
UEL319-310D1W3	FS319D1	57
UEL319-311D1W3	FS319D1	57
UEL319-312D1W3	FS319D1	57
UEL320D1W3	FS320D1	31
UEL320-313D1W3	FS320D1	68
UEL320-314D1W3	FS320D1	68
UEL320-315D1W3	FS320D1	68
UEL320-400D1W3	FS320D1	68
UEL321D1W3	FS321D1	31
UEL322D1W3	FS322D1	41

## Round flanged unit, cast housing with spigot joint Eccentric locking collar type



Shaft dia.  mm inch	Unit number (1)	Nominal dimensions													Bolt size  mm inch
		mm inch													
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>	S		
20  3/4	UELFC204D1W3	100	78	55.2	10	12	5	20.5	25.5	62	41.6	43.7	17.1	M10	
	UELFC204-012D1W3	3 <sup>15</sup> / <sub>16</sub>	3 <sup>5</sup> / <sub>16</sub>	2 <sup>11</sup> / <sub>64</sub>	25 <sup>25</sup> / <sub>64</sub>	15 <sup>15</sup> / <sub>32</sub>	13 <sup>13</sup> / <sub>64</sub>	13 <sup>13</sup> / <sub>16</sub>	1	2.4409	1 <sup>41</sup> / <sub>64</sub>	1.720	0.673	3/8	
25  13/16 7/8 15/16 1	UELFC205D1W3	115	90	63.6	10	12	6	21	27	70	42.95	44.4	17.45	M10	
	UELFC205-013D1W3														
	UELFC205-014D1W3														
	UELFC205-015D1W3	4 <sup>17</sup> / <sub>32</sub>	3 <sup>35</sup> / <sub>64</sub>	2 <sup>1</sup> / <sub>2</sub>	25 <sup>25</sup> / <sub>64</sub>	15 <sup>15</sup> / <sub>32</sub>	15 <sup>15</sup> / <sub>64</sub>	13 <sup>13</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>	2.7559	1 <sup>11</sup> / <sub>16</sub>	1.748	0.687	3/8	
	UELFC205-100D1W3														
30  1 1/16 1 1/8 1 1/16 1 1/4	UELFC206D1W3	125	100	70.7	10	12	8	23	31	80	48.15	48.4	18.25	M10	
	UELFC206-101D1W3														
	UELFC206-102D1W3	4 <sup>29</sup> / <sub>32</sub>	3 <sup>15</sup> / <sub>16</sub>	2 <sup>25</sup> / <sub>32</sub>	25 <sup>25</sup> / <sub>64</sub>	15 <sup>15</sup> / <sub>32</sub>	5 <sup>5</sup> / <sub>16</sub>	29 <sup>29</sup> / <sub>32</sub>	1 <sup>7</sup> / <sub>32</sub>	3.1496	1 <sup>57</sup> / <sub>64</sub>	1.906	0.719	3/8	
	UELFC206-103D1W3														
	UELFC206-104D1W3														
35  1 1/4 1 5/16 1 3/8 1 7/16	UELFC207D1W3	135	110	77.8	11	14	8	26	34	90	51.3	51.1	18.8	M12	
	UELFC207-104D1W3														
	UELFC207-105D1W3	5 <sup>5</sup> / <sub>16</sub>	4 <sup>21</sup> / <sub>64</sub>	3 <sup>1</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>16</sub>	35 <sup>35</sup> / <sub>64</sub>	5 <sup>5</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>32</sub>	1 <sup>11</sup> / <sub>32</sub>	3.5433	2 <sup>1</sup> / <sub>64</sub>	2.012	0.740	7/16	
	UELFC207-106D1W3														
	UELFC207-107D1W3														
40  1 1/2 1 9/16	UELFC208D1W3	145	120	84.9	11	14	10	26	36	100	55.9	56.3	21.4	M12	
	UELFC208-108D1W3	5 <sup>23</sup> / <sub>32</sub>	4 <sup>23</sup> / <sub>32</sub>	3 <sup>11</sup> / <sub>32</sub>	7 <sup>7</sup> / <sub>16</sub>	35 <sup>35</sup> / <sub>64</sub>	25 <sup>25</sup> / <sub>64</sub>	1 <sup>1</sup> / <sub>32</sub>	1 <sup>27</sup> / <sub>64</sub>	3.9370	2 <sup>13</sup> / <sub>64</sub>	2.217	0.843	7/16	
	UELFC208-109D1W3														
45  1 5/8 1 11/16 1 3/4	UELFC209D1W3	160	132	93.3	10	16	12	26	38	105	56.9	56.3	21.4	M14	
	UELFC209-110D1W3														
	UELFC209-111D1W3	6 <sup>5</sup> / <sub>16</sub>	5 <sup>13</sup> / <sub>64</sub>	3 <sup>43</sup> / <sub>64</sub>	25 <sup>25</sup> / <sub>64</sub>	5 <sup>5</sup> / <sub>8</sub>	15 <sup>15</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>2</sub>	4.1339	2 <sup>15</sup> / <sub>64</sub>	2.217	0.843	1/2	
	UELFC209-112D1W3														
50  1 13/16 1 7/8 1 15/16 2	UELFC210D1W3	165	138	97.6	10	16	12	28	40	110	60.1	62.7	24.6	M14	
	UELFC210-113D1W3														
	UELFC210-114D1W3														
	UELFC210-115D1W3	6 <sup>1</sup> / <sub>2</sub>	5 <sup>7</sup> / <sub>16</sub>	3 <sup>27</sup> / <sub>32</sub>	25 <sup>25</sup> / <sub>64</sub>	5 <sup>5</sup> / <sub>8</sub>	15 <sup>15</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>32</sub>	1 <sup>37</sup> / <sub>64</sub>	4.3307	2 <sup>23</sup> / <sub>64</sub>	2.469	0.969	1/2	
	UELFC210-200D1W3														


Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL204D1W3	FC204D1	0.8
UEL204-012D1W3	FC204D1	1.8
UEL205D1W3	FC205D1	1.1
UEL205-013D1W3	FC205D1	
UEL205-014D1W3	FC205D1	2.4
UEL205-015D1W3	FC205D1	
UEL205-100D1W3	FC205D1	
UEL206D1W3	FC206D1	1.4
UEL206-101D1W3	FC206D1	
UEL206-102D1W3	FC206D1	3.1
UEL206-103D1W3	FC206D1	
UEL206-104D1W3	FC206D1	
UEL207D1W3	FC207D1	1.8
UEL207-104D1W3	FC207D1	
UEL207-105D1W3	FC207D1	4.0
UEL207-106D1W3	FC207D1	
UEL207-107D1W3	FC207D1	
UEL208D1W3	FC208D1	2.1
UEL208-108D1W3	FC208D1	4.6
UEL208-109D1W3	FC208D1	
UEL209D1W3	FC209D1	2.8
UEL209-110D1W3	FC209D1	
UEL209-111D1W3	FC209D1	6.2
UEL209-112D1W3	FC209D1	
UEL210D1W3	FC210D1	3.1
UEL210-113D1W3	FC210D1	
UEL210-114D1W3	FC210D1	6.8
UEL210-115D1W3	FC210D1	
UEL210-200D1W3	FC210D1	



## Round flanged unit, cast housing with spigot joint Eccentric locking collar type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions												Bolt size mm inch
		mm inch												
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>	S	
55 2 2 1/16 2 1/8 2 3/16	<b>UELFC211D1W3</b> UELFC211-200D1W3 UELFC211-201D1W3 UELFC211-202D1W3 UELFC211-203D1W3	185	150	106.1	13	19	12	31	43	125	68.65	71.4	27.75	M16
		7 9/32	5 29/32	4 11/64	33/64	3/4	15/32	1 7/32	1 11/16	4.9213	2 45/64	2.811	1.093	5/8
60 2 1/4 2 5/16 2 3/8 2 7/16	<b>UELFC212D1W3</b> UELFC212-204D1W3 UELFC212-205D1W3 UELFC212-206D1W3 UELFC212-207D1W3	195	160	113.1	17	19	12	36	48	135	75.85	77.8	30.95	M16
		7 11/16	6 19/64	4 29/64	43/64	3/4	15/32	1 13/32	1 57/64	5.3150	2 69/64	3.063	1.219	5/8
65 2 1/2 2 9/16	<b>UELFC213D1W3</b> UELFC213-208D1W3 UELFC213-209D1W3	205	170	120.2	16	19	14	36	50	145	81.55	85.7	34.15	M16
		8 1/16	6 11/16	4 47/64	5/8	3/4	35/64	1 13/32	1 31/32	5.7087	3 13/64	3.374	1.344	5/8
70 2 5/8 2 11/16 2 3/4	<b>UELFC214D1W3</b> UELFC214-210D1W3 UELFC214-211D1W3 UELFC214-212D1W3	215	177	125.2	17	19	14	40	54	150	82.55	85.7	34.15	M16
		8 15/32	6 31/32	4 59/64	43/64	3/4	35/64	1 37/64	2 1/8	5.9055	3 1/4	3.374	1.344	5/8
75 2 13/16 2 7/8 2 15/16 3	<b>UELFC215D1W3</b> UELFC215-213D1W3 UELFC215-214D1W3 UELFC215-215D1W3 UELFC215-300D1W3	220	184	130.1	18	19	16	40	56	160	88.7	92	37.3	M16
		8 21/32	7 1/4	5 1/8	45/64	3/4	5/8	1 37/64	2 19/64	6.2992	3 31/64	3.622	1.469	5/8

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL211D1W3	FC211D1	4.3
UEL211-200D1W3	FC211D1	9.5
UEL211-201D1W3	FC211D1	
UEL211-202D1W3	FC211D1	
UEL211-203D1W3	FC211D1	
UEL212D1W3	FC212D1	5.2
UEL212-204D1W3	FC212D1	11
UEL212-205D1W3	FC212D1	
UEL212-206D1W3	FC212D1	
UEL212-207D1W3	FC212D1	
UEL213D1W3	FC213D1	6.5
UEL213-208D1W3	FC213D1	14
UEL213-209D1W3	FC213D1	
UEL214D1W3	FC214D1	7.4
UEL214-210D1W3	FC214D1	16
UEL214-211D1W3	FC214D1	
UEL214-212D1W3	FC214D1	
UEL215D1W3	FC215D1	7.8
UEL215-213D1W3	FC215D1	17
UEL215-214D1W3	FC215D1	
UEL215-215D1W3	FC215D1	
UEL215-300D1W3	FC215D1	

## Rhombus flanged unit, cast housing Eccentric locking collar type




Shaft dia.  mm inch	Unit number (1)	Nominal dimensions											Bolt size  mm inch
		mm inch											
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	S	F <sub>min.</sub>	
20  3/4	UELFL204D1W3	113	90	15	11	25.5	12	60	41.6	43.7	17.1	34	M10
	UELFL204-012D1W3	4 7/16	3 35/64	19/32	7/16	1	1 5/32	2 3/8	1 41/64	1.720	0.673	1.339	3/8
25  1 3/16 7/8 15/16 1	UELFL205D1W3	130	99	16	13	27	16	68	42.95	44.4	17.45	38	M14
	UELFL205-013D1W3												
	UELFL205-014D1W3												
	UELFL205-015D1W3	5 1/8	3 57/64	5/8	1/2	1 1/16	5/8	2 11/16	1 11/16	1.748	0.687	1.496	1/2
	UELFL205-100D1W3												
30  1 1/16 1 1/8 1 3/16 1 1/4	UELFL206D1W3	148	117	18	13	31	16	80	48.15	48.4	18.25	45	M14
	UELFL206-101D1W3												
	UELFL206-102D1W3												
	UELFL206-103D1W3	5 13/16	4 39/64	45/64	1/2	1 7/32	5/8	3 5/32	1 57/64	1.906	0.719	1.772	1/2
	UELFL206-104D1W3												
35  1 1/4 1 5/16 1 3/8 1 7/16	UELFL207D1W3	161	130	19	15	34	16	90	51.3	51.1	18.8	51	M14
	UELFL207-104D1W3												
	UELFL207-105D1W3												
	UELFL207-106D1W3	6 11/32	5 1/8	3/4	19/32	1 11/32	5/8	3 17/32	2 1/64	2.012	0.740	2.008	1/2
	UELFL207-107D1W3												
40  1 1/2 1 9/16	UELFL208D1W3	175	144	21	15	36	16	100	55.9	56.3	21.4	57	M14
	UELFL208-108D1W3												
	UELFL208-109D1W3	6 7/8	5 43/64	53/64	19/32	1 13/32	5/8	3 15/16	2 13/64	2.217	0.843	2.244	1/2
45  1 5/8 1 11/16 1 3/4	UELFL209D1W3	188	148	22	16	38	19	108	56.9	56.3	21.4	62	M16
	UELFL209-110D1W3												
	UELFL209-111D1W3												
	UELFL209-112D1W3	7 13/32	5 53/64	55/64	5/8	1 1/2	3/4	4 1/4	2 15/64	2.217	0.843	2.441	5/8
50  1 13/16 1 7/8 1 15/16 2	UELFL210D1W3	197	157	22	16	40	19	115	60.1	62.7	24.6	67	M16
	UELFL210-113D1W3												
	UELFL210-114D1W3												
	UELFL210-115D1W3	7 3/4	6 3/16	55/64	5/8	1 9/16	3/4	4 17/32	2 23/64	2.469	0.969	2.638	5/8
	UELFL210-200D1W3												

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL204D1W3	FL204D1	0.5
UEL204-012D1W3	FL204D1	1.1
UEL205D1W3	FL205D1	0.7
UEL205-013D1W3	FL205D1	
UEL205-014D1W3	FL205D1	1.5
UEL205-015D1W3	FL205D1	
UEL205-100D1W3	FL205D1	
UEL206D1W3	FL206D1	1.0
UEL206-101D1W3	FL206D1	
UEL206-102D1W3	FL206D1	2.2
UEL206-103D1W3	FL206D1	
UEL206-104D1W3	FL206D1	
UEL207D1W3	FL207D1	1.3
UEL207-104D1W3	FL207D1	
UEL207-105D1W3	FL207D1	2.9
UEL207-106D1W3	FL207D1	
UEL207-107D1W3	FL207D1	
UEL208D1W3	FL208D1	1.6
UEL208-108D1W3	FL208D1	3.5
UEL208-109D1W3	FL208D1	
UEL209D1W3	FL209D1	2.0
UEL209-110D1W3	FL209D1	
UEL209-111D1W3	FL209D1	4.4
UEL209-112D1W3	FL209D1	
UEL210D1W3	FL210D1	2.2
UEL210-113D1W3	FL210D1	
UEL210-114D1W3	FL210D1	4.9
UEL210-115D1W3	FL210D1	
UEL210-200D1W3	FL210D1	

## Rhombus flanged unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	S	F <sub>min.</sub>	
55 2 2 1/16 2 1/8 2 3/16	UELFL211D1W3 UELFL211-200D1W3 UELFL211-201D1W3 UELFL211-202D1W3 UELFL211-203D1W3	224	184	25	18	43	19	130	68.65	71.4	27.75	73	M16 5/8
60 2 1/4 2 5/16 2 3/8 2 7/16	UELFL212D1W3 UELFL212-204D1W3 UELFL212-205D1W3 UELFL212-206D1W3 UELFL212-207D1W3	250	202	29	18	48	23	140	75.85	77.8	30.95	81	M20 3/4
65 2 1/2 2 9/16	UELFL213D1W3 UELFL213-208D1W3 UELFL213-209D1W3	258	210	30	22	50	23	155	81.55	85.7	34.15	87	M20 3/4
70 2 5/8 2 11/16 2 3/4	UELFL214D1W3 UELFL214-210D1W3 UELFL214-211D1W3 UELFL214-212D1W3	265	216	31	22	54	23	160	82.55	85.7	34.15	91	M20 3/4
75 2 13/16 2 7/8 2 15/16 3	UELFL215D1W3 UELFL215-213D1W3 UELFL215-214D1W3 UELFL215-215D1W3 UELFL215-300D1W3	275	225	34	22	56	23	165	88.7	92	37.3	97	M20 3/4

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL211D1W3	FL211D1	3.2
UEL211-200D1W3	FL211D1	7.1
UEL211-201D1W3	FL211D1	
UEL211-202D1W3	FL211D1	
UEL211-203D1W3	FL211D1	
UEL212D1W3	FL212D1	4.1
UEL212-204D1W3	FL212D1	9.0
UEL212-205D1W3	FL212D1	
UEL212-206D1W3	FL212D1	
UEL212-207D1W3	FL212D1	
UEL213D1W3	FL213D1	5.5
UEL213-208D1W3	FL213D1	12
UEL213-209D1W3	FL213D1	
UEL214D1W3	FL214D1	5.8
UEL214-210D1W3	FL214D1	13
UEL214-211D1W3	FL214D1	
UEL214-212D1W3	FL214D1	
UEL215D1W3	FL215D1	6.3
UEL215-213D1W3	FL215D1	14
UEL215-214D1W3	FL215D1	
UEL215-215D1W3	FL215D1	
UEL215-300D1W3	FL215D1	

## Rhombus flanged unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	S	F <sub>min.</sub>	
25 13/16 7/8 15/16 1	UELFL305D1W3 UELFL305-013D1W3 UELFL305-014D1W3 UELFL305-015D1W3 UELFL305-100D1W3	150	113	16	13	29	19	80	46.1	46.8	16.7	41	M16 5/8
30 1 1/16 1 1/8 1 3/16	UELFL306D1W3 UELFL306-101D1W3 UELFL306-102D1W3 UELFL306-103D1W3	180	134	18	15	32	23	90	50.5	50	17.5	49	M20 3/4
35 1 1/4 1 5/16 1 3/8 1 7/16	UELFL307D1W3 UELFL307-104D1W3 UELFL307-105D1W3 UELFL307-106D1W3 UELFL307-107D1W3	185	141	20	16	36	23	100	53.3	51.6	18.3	—	M20 3/4
40 1 1/2 1 9/16	UELFL308D1W3 UELFL308-108D1W3 UELFL308-109D1W3	200	158	23	17	40	23	112	60.3	57.1	19.8	—	M20 3/4
45 1 5/8 1 11/16 1 3/4	UELFL309D1W3 UELFL309-110D1W3 UELFL309-111D1W3 UELFL309-112D1W3	230	177	25	18	44	25	125	63.9	58.7	19.8	—	M22 7/8
50 1 13/16 1 7/8 1 15/16	UELFL310D1W3 UELFL310-113D1W3 UELFL310-114D1W3 UELFL310-115D1W3	240	187	28	19	48	25	140	70	66.6	24.6	—	M22 7/8


Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Inner race face does not protrude from the housing face except UELFL305 and UELFL316.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL305D1W3 UEL305-013D1W3 UEL305-014D1W3 UEL305-015D1W3 UEL305-100D1W3	FL305D1 FL305D1 FL305D1 FL305D1 FL305D1	1.0 2.2
UEL306D1W3 UEL306-101D1W3 UEL306-102D1W3 UEL306-103D1W3	FL306D1 FL306D1 FL306D1 FL306D1	1.6 3.5
UEL307D1W3 UEL307-104D1W3 UEL307-105D1W3 UEL307-106D1W3 UEL307-107D1W3	FL307D1 FL307D1 FL307D1 FL307D1 FL307D1	1.8 4.0
UEL308D1W3 UEL308-108D1W3 UEL308-109D1W3	FL308D1 FL308D1 FL308D1	2.3 5.1
UEL309D1W3 UEL309-110D1W3 UEL309-111D1W3 UEL309-112D1W3	FL309D1 FL309D1 FL309D1 FL309D1	3.1 6.8
UEL310D1W3 UEL310-113D1W3 UEL310-114D1W3 UEL310-115D1W3	FL310D1 FL310D1 FL310D1 FL310D1	4.2 9.3

## Rhombus flanged unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	S	F <sub>min.</sub>	
55 2 2 1/16 2 1/8 2 3/16	UEFL311D1W3 UEFL311-200D1W3 UEFL311-201D1W3 UEFL311-202D1W3 UEFL311-203D1W3	250	198	30	20	52	25	150	75.2	73	27.8	—	M22 7/8
60 2 1/4 2 5/16 2 3/8 2 7/16	UEFL312D1W3 UEFL312-204D1W3 UEFL312-205D1W3 UEFL312-206D1W3 UEFL312-207D1W3	270	212	33	22	56	31	160	81.45	79.4	30.95	—	M27 1
65 2 1/2 2 9/16	UEFL313D1W3 UEFL313-208D1W3 UEFL313-209D1W3	295	240	33	25	58	31	175	86.15	85.7	32.55	93	M27 1
70 2 5/8 2 11/16 2 3/4	UEFL314D1W3 UEFL314-210D1W3 UEFL314-211D1W3 UEFL314-212D1W3	315	250	36	28	61	35	185	93.95	92.1	34.15	—	M30 1 1/8
75 2 13/16 2 7/8 2 15/16 3	UEFL315D1W3 UEFL315-213D1W3 UEFL315-214D1W3 UEFL315-215D1W3 UEFL315-300D1W3	320	260	39	30	66	35	195	101.7	100	37.3	106	M30 1 1/8
80 3 1/16 3 1/8 3 3/16	UEFL316D1W3 UEFL316-301D1W3 UEFL316-302D1W3 UEFL316-303D1W3	355	285	38	32	68	38	210	103.9	106.4	40.5	112	M33 1 1/4


Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Inner race face does not protrude from the housing face except UELFL305 and UELFL316.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL311D1W3 UEL311-200D1W3 UEL311-201D1W3 UEL311-202D1W3 UEL311-203D1W3	FL311D1 FL311D1 FL311D1 FL311D1 FL311D1	4.9 11
UEL312D1W3 UEL312-204D1W3 UEL312-205D1W3 UEL312-206D1W3 UEL312-207D1W3	FL312D1 FL312D1 FL312D1 FL312D1 FL312D1	6.1 13
UEL313D1W3 UEL313-208D1W3 UEL313-209D1W3	FL313D1 FL313D1 FL313D1	8.0 18
UEL314D1W3 UEL314-210D1W3 UEL314-211D1W3 UEL314-212D1W3	FL314D1 FL314D1 FL314D1 FL314D1	9.2 20
UEL315D1W3 UEL315-213D1W3 UEL315-214D1W3 UEL315-215D1W3 UEL315-300D1W3	FL315D1 FL315D1 FL315D1 FL315D1 FL315D1	10 22
UEL316D1W3 UEL316-301D1W3 UEL316-302D1W3 UEL316-303D1W3	FL316D1 FL316D1 FL316D1 FL316D1	14 31

## Rhombus flanged unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions											Bolt size mm inch
		mm inch											
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	S	F <sub>min.</sub>	
85 3 1/4 3 5/16 3 7/16	UELFL317D1W3 UELFL317-304D1W3 UELFL317-305D1W3 UELFL317-306D1W3	370	300	44	32	74	38	220	111.45	109.5	42.05	119	M33
		14 9/16	11 13/16	1 47/64	1 1/4	2 29/32	1 1/2	8 21/32	4 25/64	4.311	1.656	4.685	1 1/4
90 3 7/16 3 1/2	UELFL318D1W3 UELFL318-307D1W3 UELFL318-308D1W3	385	315	44	36	76	38	235	116.25	115.9	43.65	125	M33
		15 5/32	12 13/32	1 47/64	1 13/32	3	1 1/2	9 1/4	4 37/64	4.563	1.719	4.921	1 1/4
95 3 5/8 3 11/16 3 3/4	UELFL319D1W3 UELFL319-310D1W3 UELFL319-311D1W3 UELFL319-312D1W3	405	330	59	40	94	41	250	142.4	122.3	38.9	—	M36
		15 15/16	12 63/64	2 21/64	1 9/16	3 11/16	1 39/64	9 27/32	5 39/64	4.815	1.531	—	1 3/8
100 3 13/16 3 7/8 3 15/16 4	UELFL320D1W3 UELFL320-313D1W3 UELFL320-314D1W3 UELFL320-315D1W3 UELFL320-400D1W3	440	360	59	40	94	44	270	137.6	128.6	50	—	M39
		17 5/16	14 11/64	2 21/64	1 9/16	3 11/16	1 47/64	10 5/8	5 27/64	5.063	1.969	—	1 1/2
105	UELFL321D1W3	440	360	59	40	94	44	270	150.3	139.7	48.4	—	M39
110	UELFL322D1W3	470	390	60	42	96	44	300	152.1	141.3	49.2	—	M39


Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Inner race face does not protrude from the housing face except UELFL305 and UELFL316.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL317D1W3	FL317D1	16
UEL317-304D1W3	FL317D1	35
UEL317-305D1W3	FL317D1	35
UEL317-306D1W3	FL317D1	35
UEL318D1W3	FL318D1	19
UEL318-307D1W3	FL318D1	42
UEL318-308D1W3	FL318D1	42
UEL319D1W3	FL319D1	24
UEL319-310D1W3	FL319D1	53
UEL319-311D1W3	FL319D1	53
UEL319-312D1W3	FL319D1	53
UEL320D1W3	FL320D1	28
UEL320-313D1W3	FL320D1	62
UEL320-314D1W3	FL320D1	62
UEL320-315D1W3	FL320D1	62
UEL320-400D1W3	FL320D1	62
UEL321D1W3	FL321D1	30
UEL322D1W3	FL322D1	36

## Rhombus flanged unit, cast housing Eccentric locking collar type




Shaft dia.  mm inch	Unit number (*)	Nominal dimensions										Bolt size  mm inch
		mm inch										
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	S	
20  3/4	UELFLU204D1W3	113	90	19	15	29.5	11.5	61	45.6	43.7	17.1	M10
	UELFLU204-012D1W3	4 7/16	3 5/8	3/4	19/32	1 5/32	29/64	2 1/32	1 51/64	1.720	0.673	5/16
25  1 3/16 7/8 15/16	UELFLU205D1W3	125	99	19	15	30	11.5	70	45.95	44.4	17.45	M10
	UELFLU205-013D1W3	4 29/32	3 57/64	3/4	19/32	1 3/16	29/64	2 3/4	1 13/16	1.748	0.687	3/8
	UELFLU205-014D1W3											
	UELFLU205-015D1W3											
1	UELFLU205-100D1W3											
30  1 1/16 1 1/8 3/16 1 1/4	UELFLU206D1W3	142	116.5	20	16	33	11.5	83	50.15	48.4	18.25	M10
	UELFLU206-101D1W3	5 19/32	4 19/32	25/32	5/8	1 5/16	29/64	3 3/32	1 31/32	1.906	0.719	3/8
	UELFLU206-102D1W3											
	UELFLU206-103D1W3											
UELFLU206-104D1W3												
35  1 1/4 1 5/16 3/8 1 3/4 1 7/16	UELFLU207D1W3	156	130	21	17	36	14	96	53.3	51.1	18.8	M12
	UELFLU207-104D1W3	6 5/32	5 1/8	53/64	21/32	1 13/32	35/64	3 25/32	2 3/32	2.012	0.740	1/2
	UELFLU207-105D1W3											
	UELFLU207-106D1W3											
UELFLU207-107D1W3												
40  1 1/2 9/16	UELFLU208D1W3	172	143.5	24	17	39	14	105	58.9	56.3	21.4	M12
	UELFLU208-108D1W3	6 25/32	5 21/32	15/16	21/32	1 17/32	35/64	4 1/8	2 5/16	2.217	0.843	1/2
	UELFLU208-109D1W3											
45  1 5/8 1 1/16 1 3/4	UELFLU209D1W3	180	148.5	24	18	40	16	111	58.9	56.3	21.4	M14
	UELFLU209-110D1W3	7 3/32	5 27/32	15/16	23/32	1 9/16	5/8	4 3/8	2 5/16	2.217	0.843	1/2
	UELFLU209-111D1W3											
	UELFLU209-112D1W3											
UELFLU209-113D1W3												
50  1 13/16 1 7/8 1 15/16 2	UELFLU210D1W3	190	157	28	20	46	18	116	66.1	62.7	24.6	M16
	UELFLU210-113D1W3	7 15/32	6 3/16	1 7/64	25/32	1 13/16	45/64	4 9/16	2 39/64	2.469	0.969	5/8
	UELFLU210-114D1W3											
	UELFLU210-115D1W3											
UELFLU210-200D1W3												

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL204D1W3	FLU204D1	0.6
UEL204-012D1W3	FLU204D1	1.3
UEL205D1W3	FLU205D1	0.7
UEL205-013D1W3	FLU205D1	1.5
UEL205-014D1W3	FLU205D1	
UEL205-015D1W3	FLU205D1	
UEL205-100D1W3	FLU205D1	
UEL206D1W3	FLU206D1	1.1
UEL206-101D1W3	FLU206D1	2.4
UEL206-102D1W3	FLU206D1	
UEL206-103D1W3	FLU206D1	
UEL206-104D1W3	FLU206D1	
UEL207D1W3	FLU207D1	1.5
UEL207-104D1W3	FLU207D1	3.3
UEL207-105D1W3	FLU207D1	
UEL207-106D1W3	FLU207D1	
UEL207-107D1W3	FLU207D1	
UEL208D1W3	FLU208D1	1.9
UEL208-108D1W3	FLU208D1	4.2
UEL208-109D1W3	FLU208D1	
UEL209D1W3	FLU209D1	2.3
UEL209-110D1W3	FLU209D1	5.1
UEL209-111D1W3	FLU209D1	
UEL209-112D1W3	FLU209D1	
UEL209-113D1W3	FLU209D1	
UEL210D1W3	FLU210D1	2.9
UEL210-113D1W3	FLU210D1	6.4
UEL210-114D1W3	FLU210D1	
UEL210-115D1W3	FLU210D1	
UEL210-200D1W3	FLU210D1	

## Rhombus flanged unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	S	
55 2 2 1/16 2 1/8 2 3/16	UELFLU211D1W3 UELFLU211-200D1W3 UELFLU211-201D1W3 UELFLU211-202D1W3 UELFLU211-203D1W3	217 8 11/32	184 7 1/4	31 1 7/32	21 1 3/16	49 1 15/16	18 45/64	134 5 9/32	74.65 2 5/16	71.4 2.811	27.75 1.093	M16 5/8
60 2 1/4 2 5/16 2 3/8 2 7/16	UELFLU212D1W3 UELFLU212-204D1W3 UELFLU212-205D1W3 UELFLU212-206D1W3 UELFLU212-207D1W3	235 9 1/4	202 7 61/64	34 1 11/32	21 1 3/16	53 2 3/32	18 45/64	138 5 7/16	80.85 3 3/16	77.8 3.063	30.95 1.219	M16 5/8
65 2 1/2 2 9/16	UELFLU213D1W3 UELFLU213-208D1W3 UELFLU213-209D1W3	248 9 3/4	210 8 17/64	38 1 1/2	22 7/8	59 2 5/16	20.5 1 3/16	152 5 31/32	89.55 3 17/32	85.7 3.374	34.15 1.344	M18 5/8
70 2 5/8 2 11/16 2 3/4	UELFLU214D1W3 UELFLU214-210D1W3 UELFLU214-211D1W3 UELFLU214-212D1W3	257 10 1/8	216 8 1/2	38 1 1/2	22 7/8	62 2 7/16	20.5 1 3/16	159 6 1/4	89.55 3 17/32	85.7 3.374	34.15 1.344	M18 5/8
75 2 13/16 2 7/8 2 15/16 3	UELFLU215D1W3 UELFLU215-213D1W3 UELFLU215-214D1W3 UELFLU215-215D1W3 UELFLU215-300D1W3	266 10 15/32	225 8 55/64	41 1 39/64	22 7/8	65 2 9/16	20.5 1 3/16	165 6 1/2	95.7 3 49/64	92 3.622	37.3 1.469	M18 5/8

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Mass of unit kg lb
UEL211D1W3	FLU211D1	3.6
UEL211-200D1W3	FLU211D1	7.9
UEL211-201D1W3	FLU211D1	
UEL211-202D1W3	FLU211D1	
UEL211-203D1W3	FLU211D1	
UEL212D1W3	FLU212D1	4.0
UEL212-204D1W3	FLU212D1	8.8
UEL212-205D1W3	FLU212D1	
UEL212-206D1W3	FLU212D1	
UEL212-207D1W3	FLU212D1	
UEL213D1W3	FLU213D1	5.6
UEL213-208D1W3	FLU213D1	12
UEL213-209D1W3	FLU213D1	
UEL214D1W3	FLU214D1	6.3
UEL214-210D1W3	FLU214D1	14
UEL214-211D1W3	FLU214D1	
UEL214-212D1W3	FLU214D1	
UEL215D1W3	FLU215D1	6.8
UEL215-213D1W3	FLU215D1	15
UEL215-214D1W3	FLU215D1	
UEL215-215D1W3	FLU215D1	
UEL215-300D1W3	FLU215D1	



## Light rhombus flanged unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number (*)	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	S	
12 1/2	AELFB201W3	81	63.5	9.5	9.5	18	7	56	31.6	28.6	6.5	M6
	AELFB201-008W3	3 3/16	2 1/2	3/8	3/8	23/32	9/32	2 7/32	1 1/4	1.126	0.256	1/4
15 9/16 5/8	AELFB202W3	81	63.5	9.5	9.5	18	7	56	31.6	28.6	6.5	M6
	AELFB202-009W3	3 3/16	2 1/2	3/8	3/8	23/32	9/32	2 7/32	1 1/4	1.126	0.256	1/4
17 1/2	AELFB203W3	81	63.5	9.5	9.5	18	7	56	31.6	28.6	6.5	M6
	AELFB203-011W3	3 3/16	2 1/2	3/8	3/8	23/32	9/32	2 7/32	1 1/4	1.126	0.256	1/4
20 3/4	AELFB204W3	90	71.5	11	11	20	10	61	34.5	31	7.5	M8
	AELFB204-012W3	3 7/32	2 19/16	7/16	7/16	25/32	25/64	2 19/32	1 23/64	1.220	0.295	5/16
25 13/16 7/8 15/16 1	AELFB205W3	95	76	11	11	20	10	64	34.5	31	7.5	M8
	AELFB205-013W3	3 3/4	2 63/64	7/16	7/16	25/32	25/64	2 17/32	1 23/64	1.220	0.295	5/16
	AELFB205-014W3											
	AELFB205-015W3											
30 1 1/16 1 1/8 1 3/16 1 1/4	AELFB206W3	113	90.5	12	12	22.5	12	76	38.7	35.7	9	M10
	AELFB206-101W3	4 7/16	3 9/16	15/32	15/32	7/8	15/32	3	1 17/32	1.406	5415	3/8
	AELFB206-102W3											
	AELFB206-103W3											
35 1 1/4 1 5/16 1 3/8 1 7/16	AELFB207W3	122	100	11	13	24	12	89	40.4	38.9	9.5	M10
	AELFB207-104W3	4 13/16	3 15/16	7/16	1/2	15/16	15/32	3 1/2	1 19/32	1.531	0.374	3/8
	AELFB207-105W3											
	AELFB207-106W3											
	AELFB207-107W3											

Note (\*) If relubricatable type is needed, please order with suffix "D1".

Bearing number	Housing number	Mass of unit kg lb
AEL201W3	FB201	0.3
AEL201-008W3	FB201	0.7
AEL202W3	FB201	0.3
AEL202-009W3	FB201	0.7
AEL202-010W3	FB201	0.7
AEL203W3	FB201	0.3
AEL203-011W3	FB201	0.7
AEL204W3	FB204	0.4
AELB204-012W3	FB204	0.9
AEL205W3	FB205	0.4
AEL205-013W3	FB205	
AEL205-014W3	FB205	0.9
AEL205-015W3	FB205	
AEL205-100W3	FB205	
AEL206W3	FB206	0.6
AEL206-101W3	FB206	
AEL206-102W3	FB206	1.3
AEL206-103W3	FB206	
AEL206-104W3	FB206	
AEL207W3	FB207	0.9
AEL207-104W3	FB207	
AEL207-105W3	FB207	2.0
AEL207-106W3	FB207	
AEL207-107W3	FB207	

## Light rhombus flanged unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions									Bolt size mm inch
		<i>H</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i>	<i>N</i>	<i>L</i>	<i>A</i> <sub>0</sub>	<i>B</i> <sub>1</sub>	<i>S</i>	
12 1/2	AELFD201W3	81	63	8.5	15	7	59	30.6	28.6	6.5	M6
	AELFD201-008W3	3 <sup>3/16</sup>	2 <sup>31/64</sup>	21/64	19/32	9/32	2 <sup>5/16</sup>	1 <sup>13/64</sup>	1.126	0.256	1/4
15 9/16 5/8	AELFD202W3	81	63	8.5	15	7	59	30.6	28.6	6.5	M6
	AELFD202-009W3	3 <sup>3/16</sup>	2 <sup>31/64</sup>	21/64	19/32	9/32	2 <sup>5/16</sup>	1 <sup>13/64</sup>	1.126	0.256	1/4
	AELFD202-010W3										
17 11/16	AELFD203W3	81	63	8.5	15	7	59	30.6	28.6	6.5	M6
	AELFD203-011W3	3 <sup>3/16</sup>	2 <sup>31/64</sup>	21/64	19/32	9/32	2 <sup>5/16</sup>	1 <sup>13/64</sup>	1.126	0.256	1/4
20 3/4	AELFD204W3	90	71	9.5	17	10	67	33	31	7.5	M8
	AELFD204-012W3	3 <sup>17/32</sup>	2 <sup>51/64</sup>	3/8	21/32	25/64	2 <sup>5/8</sup>	1 <sup>13/64</sup>	1.220	0.295	5/16
25 13/16 7/8 15/16 1	AELFD205W3	95	76	9.5	17	10	71	33	31	7.5	M8
	AELFD205-013W3										
	AELFD205-014W3	3 <sup>3/4</sup>	2 <sup>63/64</sup>	3/8	21/32	25/64	2 <sup>25/32</sup>	1 <sup>19/64</sup>	1.220	0.295	5/16
	AELFD205-015W3										
30 1 1/16 1 1/8 1 3/16 1 1/4	AELFD206W3	113	90	12	21	12	84	38.7	35.7	9	M10
	AELFD206-101W3										
	AELFD206-102W3	4 <sup>7/16</sup>	3 <sup>35/64</sup>	15/32	13/16	15/32	3 <sup>5/16</sup>	1 <sup>17/32</sup>	1.406	0.354	3/8
	AELFD206-103W3										
35 1 1/4 1 5/16 1 3/8 1 7/16	AELFD207W3	125	100	12.5	22	12	94	41.9	38.9	9.5	M10
	AELFD207-104W3										
	AELFD207-105W3	4 <sup>29/32</sup>	3 <sup>15/16</sup>	31/64	7/8	15/32	3 <sup>11/16</sup>	1 <sup>21/32</sup>	1.531	0.374	3/8
	AELFD207-106W3										
40 1 1/2 1 9/16	AELFD208W3	148	119	14.5	25	13.5	104	47.2	43.7	11	M12
	AELFD208-108W3	5 <sup>13/16</sup>	4 <sup>11/16</sup>	37/64	31/32	17/32	4 <sup>3/32</sup>	1 <sup>27/32</sup>	1.720	0.433	7/16
	AELFD208-109W3										

Note (1) If relubricatable type is needed, please order with suffix "A-" "D1". Example: A-AELFD201D1W3

Bearing number	Housing number	Mass of unit kg lb
AEL201W3	FD201	0.3
AEL201-008W3	FD201	0.7
AEL202W3	FD201	0.3
AEL202-009W3	FD201	0.7
AEL202-010W3	FD201	0.7
AEL203W3	FD201	0.3
AEL203-011W3	FD201	0.7
AEL204W3	FD204	0.4
AEL204-012W3	FD204	0.9
AEL205W3	FD205	0.5
AEL205-013W3	FD205	
AEL205-014W3	FD205	1.1
AEL205-015W3	FD205	
AEL205-100W3	FD205	
AEL206W3	FD206	0.8
AEL206-101W3	FD206	
AEL206-102W3	FD206	1.8
AEL206-103W3	FD206	
AEL206-104W3	FD206	
AEL207W3	FD207	1.1
AEL207-104W3	FD207	
AEL207-105W3	FD207	2.4
AEL207-106W3	FD207	
AEL207-107W3	FD207	
AEL208W3	FD208	1.5
AEL208-108W3	FD208	3.3
AEL208-109W3	FD208	

## Light rhombus flanged unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number <sup>(1)</sup>	Nominal dimensions									Bolt size mm inch
		<i>H</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i>	<i>N</i>	<i>L</i>	<i>A</i> <sub>0</sub>	<i>B</i> <sub>1</sub>	<i>S</i>	
12 1/2	JELFD201W3	81	63	8.5	15	7	59	30.6	28.6	6.5	M6
	JELFD201-008W3	3 <sup>3/16</sup>	2 <sup>31/64</sup>	21/64	19/32	9/32	2 <sup>5/16</sup>	1 <sup>13/64</sup>	1.126	0.256	1/4
15 9/16 5/8	JELFD202W3	81	63	8.5	15	7	59	30.6	28.6	6.5	M6
	JELFD202-009W3	3 <sup>3/16</sup>	2 <sup>31/64</sup>	21/64	19/32	9/32	2 <sup>5/16</sup>	1 <sup>13/64</sup>	1.126	0.256	1/4
	JELFD202-010W3										
17 11/16	JELFD203W3	81	63	8.5	15	7	59	30.6	28.6	6.5	M6
	JELFD203-011W3	3 <sup>3/16</sup>	2 <sup>31/64</sup>	21/64	19/32	9/32	2 <sup>5/16</sup>	1 <sup>13/64</sup>	1.126	0.256	1/4
20 3/4	JELFD204W3	90	71	9.5	17	10	67	33	31	7.5	M8
	JELFD204-012W3	3 <sup>17/32</sup>	2 <sup>51/64</sup>	3/8	21/32	25/64	2 <sup>5/8</sup>	1 <sup>19/64</sup>	1.220	0.295	5/16
25 13/16 7/8 15/16 1	JELFD205W3	95	76	9.5	17	10	71	33	31	7.5	M8
	JELFD205-013W3										
	JELFD205-014W3	3 <sup>3/4</sup>	2 <sup>63/64</sup>	3/8	21/32	25/64	2 <sup>25/32</sup>	1 <sup>19/64</sup>	1.220	0.295	5/16
	JELFD205-015W3										
JELFD205-100W3											
30 1 1/16 1 1/8 1 3/16 1 1/4	JELFD206W3	113	90	12	21	12	84	38.7	35.7	9	M10
	JELFD206-101W3										
	JELFD206-102W3	4 <sup>7/16</sup>	3 <sup>35/64</sup>	15/32	13/16	15/32	3 <sup>5/16</sup>	1 <sup>17/32</sup>	1.406	0.354	3/8
	JELFD206-103W3										
JELFD206-104W3											
35 1 1/4 1 5/16 1 3/8 1 7/16	JELFD207W3	125	100	12.5	22	12	94	41.9	38.9	9.5	M10
	JELFD207-104W3										
	JELFD207-105W3	4 <sup>29/32</sup>	3 <sup>15/16</sup>	31/64	7/8	15/32	3 <sup>11/16</sup>	1 <sup>21/32</sup>	1.531	0.374	3/8
	JELFD207-106W3										
JELFD207-107W3											
40 1 1/2 1 9/16	JELFD208W3	148	119	14.5	25	13.5	104	47.2	43.7	11	M12
	JELFD208-108W3	5 <sup>13/16</sup>	4 <sup>11/16</sup>	37/64	31/32	17/32	4 <sup>3/32</sup>	1 <sup>27/32</sup>	1.720	0.433	7/16
	JELFD208-109W3										

Note <sup>(1)</sup> If relubricatable type is needed, please order with suffix "A-" "D1". Example:A-JELFD201D1W3

Bearing number	Housing number	Mass of unit kg lb
JEL201W3	FD201	0.3
JEL201-008W3	FD201	0.7
JEL202W3	FD201	0.3
JEL202-009W3	FD201	0.7
JEL202-010W3	FD201	0.7
JEL203W3	FD201	0.3
JEL203-011W3	FD201	0.7
AEL204W3	FD204	0.4
JEL204-012W3	FD204	0.9
JEL205W3	FD205	0.5
JEL205-013W3	FD205	
JEL205-014W3	FD205	1.1
JEL205-015W3	FD205	
JEL205-100W3	FD205	
JEL206W3	FD206	0.8
JEL206-101W3	FD206	
JEL206-102W3	FD206	1.8
JEL206-103W3	FD206	
JEL206-104W3	FD206	
JEL207W3	FD207	1.1
JEL207-104W3	FD207	
JEL207-105W3	FD207	2.4
JEL207-106W3	FD207	
JEL207-107W3	FD207	
JEL208W3	FD208	1.5
JEL208-108W3	FD208	3.3
JEL208-109W3	FD208	

Round flanged unit, pressed steel housing  
Eccentric locking collar type




Shaft dia. mm inch	Unit number	Nominal dimensions									Bolt size mm inch
		H	J	A <sub>1</sub>	mm inch		B <sub>1</sub>	S	H <sub>1</sub> min.		
					M <sup>(1)</sup>	A					
12 1/2	AELPF201W3	81	63.5	4	7.1	14	28.6	6.5	49	M6	
	AELPF201-008W3	3 <sup>3/16</sup>	2 <sup>1/2</sup>	0.157	9/32	9/16	1.126	0.256	1 <sup>15/16</sup>	1/4	
15 9/16 5/8	AELPF202W3	81	63.5	4	7.1	14	28.6	6.5	49	M6	
	AELPF202-009W3 AELPF202-010W3	3 <sup>3/16</sup>	2 <sup>1/2</sup>	0.157	9/32	9/16	1.126	0.256	1 <sup>15/16</sup>	1/4	
17 11/16	AELPF203W3	81	63.5	4	7.1	14	28.6	6.5	49	M6	
	AELPF203-011W3	3 <sup>3/16</sup>	2 <sup>1/2</sup>	0.157	9/32	9/16	1.126	0.256	1 <sup>15/16</sup>	1/4	
20 3/4	AELPF204W3	90	71.5	4	9	16	31	7.5	56	M8	
	AELPF204-012W3	3 <sup>35/64</sup>	2 <sup>13/16</sup>	0.157	23/64	5/8	1.220	0.295	2 <sup>7/32</sup>	5/16	
25 13/16 7/8 15/16 1	AELPF205W3	95	76	4	9	18	31	7.5	60	M8	
	AELPF205-013W3	3 <sup>3/4</sup>	2 <sup>63/64</sup>	0.157	23/64	23/32	1.220	0.295	2 <sup>3/8</sup>	5/16	
	AELPF205-014W3										
	AELPF205-015W3										
AELPF205-100W3											
30 1 1/16 1 1/8 1 3/16 1 1/4	AELPF206W3	113	90.5	5.2	11	18	35.7	9	71	M10	
	AELPF206-101W3	4 <sup>7/16</sup>	3 <sup>9/16</sup>	0.205	7/16	23/32	1.406	0.354	2 <sup>13/16</sup>	3/8	
	AELPF206-102W3										
	AELPF206-103W3										
AELPF206-104W3											
35 1 1/4 1 5/16 1 3/8 1 7/16	AELPF207W3	122	100	5.2	11	20	38.9	9.5	81	M10	
	AELPF207-104W3	4 <sup>13/16</sup>	3 <sup>15/16</sup>	0.205	7/16	25/32	1.531	0.374	3 <sup>3/16</sup>	3/8	
	AELPF207-105W3										
	AELPF207-106W3										
AELPF207-107W3											
40 1 1/2 1 9/16	AELPF208W3	148	119	6.8	13.5	21	43.7	11	91	M12	
	AELPF208-108W3 AELPF208-109W3	5 <sup>13/16</sup>	4 <sup>11/16</sup>	0.268	17/32	13/16	1.720	0.433	3 <sup>19/32</sup>	1/2	

Notes (1) AELPF208 has four bolt holes.

(2) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.

Max. load <sup>(2)</sup> recommended		Bearing number	Housing number	Mass of unit kg lb
N lbf				
radial	axial			
2 700 600	1 350 300	AEL201W3	PF203	0.3
		AEL201-008W3	PF203	0.7
2 700 600	1 350 300	AEL202W3	PF203	0.3
		AEL202-009W3 AEL202-010W3	PF203 PF203	0.7
2 700 600	1 350 300	AEL203W3	PF203	0.3
		AEL203-011W3	PF203	0.7
3 000 660	1 500 330	AEL204W3	PF204	0.3
		AEL204-012W3	PF204	0.7
4 000 880	2 000 440	AEL205W3	PF205	0.4
		AEL205-013W3	PF205	0.9
		AEL205-014W3	PF205	
		AEL205-015W3 AEL205-100W3	PF205 PF205	
5 000 1 100	2 500 550	AEL206W3	PF206	
		AEL206-101W3	PF206	1.3
		AEL206-102W3	PF206	
		AEL206-103W3 AEL206-104W3	PF206 PF206	
6 000 1 300	3 000 650	AEL207W3	PF207	
		AEL207-104W3	PF207	1.8
		AEL207-105W3	PF207	
		AEL207-106W3 AEL207-107W3	PF207 PF207	
7 000 1 500	3 500 750	AEL208W3	PF208	
		AEL208-108W3 AEL208-109W3	PF208 PF208	3.1

## Round flanged unit, pressed steel housing Eccentric locking collar type




Shaft dia. mm inch	Unit number	Nominal dimensions								Bolt size mm inch
		H	J	A <sub>1</sub>	mm inch		B <sub>1</sub>	S	H <sub>1</sub> min.	
					M <sup>(1)</sup>	A				
12 1/2	JELPF201W3	81	63.5	4	7.1	14	28.6	6.5	49	M6
	JELPF201-008W3	3 <sup>3/16</sup>	2 <sup>1/2</sup>	0.157	9/32	9/16	1.126	0.256	1 <sup>15/16</sup>	1/4
15 9/16 5/8	JELPF202W3	81	63.5	4	7.1	14	28.6	6.5	49	M6
	JELPF202-009W3	3 <sup>3/16</sup>	2 <sup>1/2</sup>	0.157	9/32	9/16	1.126	0.256	1 <sup>15/16</sup>	1/4
	JELPF202-010W3									
17 11/16	JELPF203W3	81	63.5	4	7.1	14	28.6	6.5	49	M6
	JELPF203-011W3	3 <sup>3/16</sup>	2 <sup>1/2</sup>	0.157	9/32	9/16	1.126	0.256	1 <sup>15/16</sup>	1/4
20 3/4	JELPF204W3	90	71.5	4	9	16	31	7.5	56	M8
	JELPF204-012W3	3 <sup>35/64</sup>	2 <sup>13/16</sup>	0.157	23/64	5/8	1.220	0.295	2 <sup>7/32</sup>	5/16
25 13/16 7/8 15/16 1	JELPF205W3	95	76	4	9	18	31	7.5	60	M8
	JELPF205-013W3									
	JELPF205-014W3	3 <sup>3/4</sup>	2 <sup>63/64</sup>	0.157	23/64	23/32	1.220	0.295	2 <sup>3/8</sup>	5/16
	JELPF205-015W3									
	JELPF205-100W3									
30 1 1/16 1 1/8 1 3/16 1 1/4	JELPF206W3	113	90.5	5.2	11	18	35.7	9	71	M10
	JELPF206-101W3									
	JELPF206-102W3	4 <sup>7/16</sup>	3 <sup>9/16</sup>	0.205	7/16	23/32	1.406	0.354	2 <sup>13/16</sup>	3/8
	JELPF206-103W3									
	JELPF206-104W3									
35 1 1/4 1 5/16 1 3/8 1 7/16	JELPF207W3	122	100	5.2	11	20	38.9	9.5	81	M10
	JELPF207-104W3									
	JELPF207-105W3	4 <sup>13/16</sup>	3 <sup>15/16</sup>	0.205	7/16	25/32	1.531	0.374	3 <sup>3/16</sup>	3/8
	JELPF207-106W3									
	JELPF207-107W3									
40 1 1/2 1 9/16	JELPF208W3	148	119	6.8	13.5	21	43.7	11.0	91	M12
	JELPF208-108W3	5 <sup>13/16</sup>	4 <sup>11/16</sup>	0.268	17/32	13/16	1.720	0.433	3 <sup>19/32</sup>	1/2
JELPF208-109W3										

Notes (1) JELPF208 has four bolt holes.

(2) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.

Max. load <sup>(2)</sup> recommended		Bearing number	Housing number	Mass of unit kg lb
N lbf				
radial	axial			
2 700 600	1 350 300	JEL201W3	PF203	0.3
		JEL201-008W3	PF203	0.7
2 700 600	1 350 300	JEL202W3	PF203	0.3
		JEL202-009W3	PF203	0.7
		JEL202-010W3	PF203	0.7
2 700 600	1 350 300	JEL203W3	PF203	0.3
		JEL203-011W3	PF203	0.7
3 000 660	1 500 330	JEL204W3	PF204	0.3
		JEL204-012W3	PF204	0.7
4 000 880	2 000 440	JEL205W3	PF205	0.4
		JEL205-013W3	PF205	
		JEL205-014W3	PF205	0.9
		JEL205-015W3	PF205	
		JEL205-100W3	PF205	
5 000 1 100	2 500 550	JEL206W3	PF206	0.6
		JEL206-101W3	PF206	
		JEL206-102W3	PF206	1.3
		JEL206-103W3	PF206	
		JEL206-104W3	PF206	
6 000 1 300	3 000 650	JEL207W3	PF207	0.8
		JEL207-104W3	PF207	
		JEL207-105W3	PF207	1.8
		JEL207-106W3	PF207	
		JEL207-107W3	PF207	
7 000 1 500	3 500 750	JEL208W3	PF208	1.4
		JEL208-108W3	PF208	3.1
JEL208-109W3	PF208			

Round flanged unit, pressed steel housing with rubber ring  
Eccentric locking collar type




Shaft dia.  mm inch	Unit number	Nominal dimensions								Bolt size  mm inch
		H	J	A <sub>1</sub>	mm inch		B <sub>1</sub>	S	H <sub>1</sub> min.	
					N	A				
12 1/2	AELRPF201W3	90	71.5	4	9	16	28.6	6.5	56	M8
	AELRPF201-008W3	3 <sup>35</sup> / <sub>64</sub>	2 <sup>13</sup> / <sub>16</sub>	0.157	23 <sup>3</sup> / <sub>64</sub>	5 <sup>5</sup> / <sub>8</sub>	1.126	0.256	2 <sup>7</sup> / <sub>32</sub>	5 <sup>5</sup> / <sub>16</sub>
15 9 16 5 8	AELRPF202W3	90	71.5	4	9	16	28.6	6.5	56	M8
	AELRPF202-009W3 AELRPF202-010W3	3 <sup>35</sup> / <sub>64</sub>	2 <sup>13</sup> / <sub>16</sub>	0.157	23 <sup>3</sup> / <sub>64</sub>	5 <sup>5</sup> / <sub>8</sub>	1.126	0.256	2 <sup>7</sup> / <sub>32</sub>	5 <sup>5</sup> / <sub>16</sub>
17 11 16	AELRPF203W3	90	71.5	4	9	16	28.6	6.5	56	M8
	AELRPF203-011W3	3 <sup>35</sup> / <sub>64</sub>	2 <sup>13</sup> / <sub>16</sub>	0.157	23 <sup>3</sup> / <sub>64</sub>	5 <sup>5</sup> / <sub>8</sub>	1.126	0.256	2 <sup>7</sup> / <sub>32</sub>	5 <sup>5</sup> / <sub>16</sub>
20 3 4	AELRPF204W3	95	76	4	9	18	31	7.5	60	M8
	AELRPF204-012W3	3 <sup>3</sup> / <sub>4</sub>	2 <sup>63</sup> / <sub>64</sub>	0.157	23 <sup>3</sup> / <sub>64</sub>	23 <sup>3</sup> / <sub>32</sub>	1.220	0.295	2 <sup>3</sup> / <sub>8</sub>	5 <sup>5</sup> / <sub>16</sub>
25 13 16 7 8 15 16 1	AELRPF205W3	113	90.5	5.2	11	18	31	7.5	71	M10
	AELRPF205-013W3	4 <sup>7</sup> / <sub>16</sub>	3 <sup>9</sup> / <sub>16</sub>	0.205	7 <sup>7</sup> / <sub>16</sub>	23 <sup>3</sup> / <sub>32</sub>	1.220	0.295	2 <sup>13</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>8</sub>
	AELRPF205-014W3									
	AELRPF205-015W3									
AELRPF205-100W3										
30 1 1 16 1 8 1 16 1 1 4	AELRPF206W3	122	100	5.2	11	20	35.7	9	81	M10
	AELRPF206-101W3	4 <sup>13</sup> / <sub>16</sub>	3 <sup>15</sup> / <sub>16</sub>	0.205	7 <sup>7</sup> / <sub>16</sub>	25 <sup>3</sup> / <sub>32</sub>	1.406	0.354	3 <sup>3</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>8</sub>
	AELRPF206-102W3									
	AELRPF206-103W3									
AELRPF206-104W3										

Note (1) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.

Remarks When an anti-vibration rubber ring is used, the self alignment capability will be reduce.

Max. load (1) recommended		Bearing number	Housing number		Mass of unit  kg lb
N lbf			rubber ring	steel	
radial	axial				
1 000 220	200 40	AEL201W3	R201	PF204	0.3
		AEL201-008W3	R201	PF204	0.7
1 000 220	200 40	AEL202W3	R201	PF204	0.3
		AEL202-009W3 AEL202-010W3	R201	PF204 PF204	0.7
1 000 220	200 40	AEL203W3	R201	PF204	0.3
		AEL203-011W3	R201	PF204	0.7
1 150 250	200 40	AEL204W3	R204	PF205	0.4
		AEL204-012W3	R204	PF205	0.9
1 300 280	200 40	AEL205W3	R205	PF206	0.5
		AEL205-013W3 AEL205-014W3 AEL205-015W3 AEL205-100W3	R205 R205 R205 R205	PF206 PF206 PF206 PF206	1.1
1 500 330	200 40	AEL206W3	R206	PF207	0.7
		AEL206-101W3 AEL206-102W3 AEL206-103W3 AEL206-104W3	R206 R206 R206 R206	PF207 PF207 PF207 PF207	1.5

## Rhombus flanged unit, pressed steel housing Eccentric locking collar type



Shaft dia.  mm inch	Unit number	Nominal dimensions									Bolt size  mm inch
		mm inch									
		H	J	A <sub>1</sub>	N	A	L	B <sub>1</sub>	S	H <sub>1</sub>	
12 1/2	<b>AELPFL201W3</b> <b>AELPFL201-008W3</b>	81 3 3/16	63.5 2 1/2	4 0.157	7.1 9/32	14 9/16	59 2 5/16	28.6 1.126	6.5 0.256	49 1 15/16	M6 1/4
15 9/16 5/8	<b>AELPFL202W3</b> <b>AELPFL202-009W3</b> <b>AELPFL202-010W3</b>	81 3 3/16	63.5 2 1/2	4 0.157	7.1 9/32	14 9/16	59 2 5/16	28.6 1.126	6.5 0.256	49 1 15/16	M6 1/4
17 11/16	<b>AELPFL203W3</b> <b>AELPFL203-011W3</b>	81 3 3/16	63.5 2 1/2	4 0.157	7.1 9/32	14 9/16	59 2 5/16	28.6 1.126	6.5 0.256	49 1 15/16	M6 1/4
20 3/4	<b>AELPFL204W3</b> <b>AELPFL204-012W3</b>	90 3 5/8	71.5 2 13/16	4 0.157	9 23/64	16 5/8	67 2 5/8	31 1.220	7.5 0.295	56 2 7/32	M8 5/16
25 13/16 7/8 15/16 1	<b>AELPFL205W3</b> <b>AELPFL205-013W3</b> <b>AELPFL205-014W3</b> <b>AELPFL205-015W3</b> <b>AELPFL205-100W3</b>	95 3 3/4	76 2 63/64	4 0.157	9 23/64	18 23/32	71 2 25/32	31 1.220	7.5 0.295	60 2 3/8	M8 5/16
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>AELPFL206W3</b> <b>AELPFL206-101W3</b> <b>AELPFL206-102W3</b> <b>AELPFL206-103W3</b> <b>AELPFL206-104W3</b>	113 4 7/16	90.5 3 3/16	5.2 0.205	11 7/16	18 23/32	84 3 5/16	35.7 1.406	9 0.354	71 2 13/16	M10 3/8
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>AELPFL207W3</b> <b>AELPFL207-104W3</b> <b>AELPFL207-105W3</b> <b>AELPFL207-106W3</b> <b>AELPFL207-107W3</b>	122 4 13/16	100 3 15/16	5.2 0.205	11 7/16	20 25/32	94 3 11/16	38.9 1.531	9.5 0.374	81 3 3/16	M10 3/8
40 1 1/2 1 9/16	<b>AELPFL208W3</b> <b>AELPFL208-108W3</b> <b>AELPFL208-109W3</b>	148 5 13/16	119 4 11/16	6.8 0.268	13.5 17/32	21 13/16	100 3 15/16	43.7 1.720	11 0.433	91 3 19/32	M12 1/2

Note (1) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.

Max. load (1)		Bearing number	Housing number	Mass of unit  kg lb
N lbf				
radial	axial			
2 700 600	1 350 300	<b>AEL201W3</b> <b>AEL201-008W3</b>	<b>PFL203W3</b> <b>PFL203W3</b>	0.3 0.7
2 700 600	1 350 300	<b>AEL202W3</b> <b>AEL202-009W3</b> <b>AEL202-010W3</b>	<b>PFL203W3</b> <b>PFL203W3</b> <b>PFL203W3</b>	0.3 0.7
2 700 600	1 350 300	<b>AEL203W3</b> <b>AEL203-011W3</b>	<b>PFL203W3</b> <b>PFL203W3</b>	0.3 0.7
3 000 660	1 500 330	<b>AEL204W3</b> <b>AEL204-012W3</b>	<b>PFL204W3</b> <b>PFL204W3</b>	0.3 0.7
4 000 880	2 000 440	<b>AEL205W3</b> <b>AEL205-013W3</b> <b>AEL205-014W3</b> <b>AEL205-015W3</b> <b>AEL205-100W3</b>	<b>PFL205W3</b> <b>PFL205W3</b> <b>PFL205W3</b> <b>PFL205W3</b> <b>PFL205W3</b>	0.4 0.9
5 000 1 100	2 500 550	<b>AEL206W3</b> <b>AEL206-101W3</b> <b>AEL206-102W3</b> <b>AEL206-103W3</b> <b>AEL206-104W3</b>	<b>PFL206W3</b> <b>PFL206W3</b> <b>PFL206W3</b> <b>PFL206W3</b> <b>PFL206W3</b>	0.6 1.3
6 000 1 300	3 000 650	<b>AEL207W3</b> <b>AEL207-104W3</b> <b>AEL207-105W3</b> <b>AEL207-106W3</b> <b>AEL207-107W3</b>	<b>PFL207W3</b> <b>PFL207W3</b> <b>PFL207W3</b> <b>PFL207W3</b> <b>PFL207W3</b>	0.9 2.0
6 000 1 300	3 000 650	<b>AEL208W3</b> <b>AEL208-108W3</b> <b>AEL208-109W3</b>	<b>PFL208W3</b> <b>PFL208W3</b> <b>PFL208W3</b>	1.3 2.9

## Rhombus flanged unit, pressed steel housing Eccentric locking collar type




Shaft dia. mm inch	Unit number	Nominal dimensions									Bolt size mm inch
		mm inch									
		<i>H</i>	<i>J</i>	<i>A</i> <sub>1</sub>	<i>N</i>	<i>A</i>	<i>L</i>	<i>B</i> <sub>1</sub>	<i>S</i>	<i>H</i> <sub>1</sub>	
12 1/2	JELPFL201W3 JELPFL201-008W3	81 3 3/16	63 2 31/64	4 0.157	7.1 9/32	14 9/16	59 2 5/16	28.6 1.126	6.5 0.256	49 1 15/16	M6 1/4
15 9/16 5/8	JELPFL202W3 JELPFL202-009W3 JELPFL202-010W3	81 3 3/16	63 2 31/64	4 0.157	7.1 9/32	14 9/16	59 2 5/16	28.6 1.126	6.5 0.256	49 1 15/16	M6 1/4
17 11/16	JELPFL203W3 JELPFL203-011W3	81 3 3/16	63 2 31/64	4 0.157	7.1 9/32	14 9/16	59 2 5/16	28.6 1.126	6.5 0.256	49 1 15/16	M6 1/4
20 3/4	JELPFL204W3 JELPFL204-012W3	90 3 35/64	71 2 51/64	4 0.157	9 23/64	16 5/8	67 2 5/8	31 1.220	7.5 0.295	56 2 7/32	M8 5/16
25 13/16 7/8 15/16 1	JELPFL205W3 JELPFL205-013W3 JELPFL205-014W3 JELPFL205-015W3 JELPFL205-100W3	95 3 3/4	76 2 63/64	4 0.157	9 23/64	18 23/32	71 2 25/32	31 1.220	7.5 0.295	60 2 3/8	M8 5/16
30 1 1/16 1 1/8 1 3/16 1 1/4	JELPFL206W3 JELPFL206-101W3 JELPFL206-102W3 JELPFL206-103W3 JELPFL206-104W3	113 4 7/16	90 3 35/64	5.2 0.205	11 7/16	18 23/32	84 3 5/16	35.7 1.406	9 0.354	71 2 13/16	M10 3/8
35 1 1/4 1 5/16 1 3/8 1 7/16	JELPFL207W3 JELPFL207-104W3 JELPFL207-105W3 JELPFL207-106W3 JELPFL207-107W3	122 4 13/16	100 3 15/16	5.2 0.205	11 7/16	20 25/32	94 3 11/16	38.9 1.531	9.5 0.374	81 3 3/16	M10 3/8
40 1 1/2 1 9/16	JELPFL208W3 JELPFL208-108W3 JELPFL208-109W3	148 5 13/16	119 4 11/16	6.8 0.268	13.5 17/32	21 13/16	100 3 15/16	43.7 1.720	11 0.433	91 3 19/32	M12 1/2

Note (1) The permissible load only applies in applications where the load is stable and the speed is 2400 min<sup>-1</sup> or less.

Max. load (1)		Bearing number	Housing number	Mass of unit
N lbf				
radial	axial			kg lb
2 700 600	1 350 300	JEL201W3 JEL201-008W3	PFL203W3 PFL203W3	0.3 0.7
2 700 600	1 350 300	JEL202W3 JEL202-009W3 JEL202-010W3	PFL203W3 PFL203W3 PFL203W3	0.3 0.7
2 700 600	1 350 300	JEL203W3 JEL203-011W3	PFL203W3 PFL203W3	0.3 0.7
3 000 660	1 500 330	JEL204W3 JEL204-012W3	PFL204W3 PFL204W3	0.3 0.7
4 000 880	2 000 440	JEL205W3 JEL205-013W3 JEL205-014W3 JEL205-015W3 JEL205-100W3	PFL205W3 PFL205W3 PFL205W3 PFL205W3 PFL205W3	0.4 0.9
5 000 1 100	2 500 550	JEL206W3 JEL206-101W3 JEL206-102W3 JEL206-103W3 JEL206-104W3	PFL206W3 PFL206W3 PFL206W3 PFL206W3 PFL206W3	0.6 1.3
6 000 1 300	3 000 650	JEL207W3 JEL207-104W3 JEL207-105W3 JEL207-106W3 JEL207-107W3	PFL207W3 PFL207W3 PFL207W3 PFL207W3 PFL207W3	0.9 2.0
6 000 1 300	3 000 650	JEL208W3 JEL208-108W3 JEL208-109W3	PFL208W3 PFL208W3 PFL208W3	1.3 2.9



## Take-up unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions											
		mm inch											
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$
20 3/4	UEL204D1W3	16	12	51	32	19	51	12	76	89	94	21	32
	UEL204-012D1W3	5/8	15/32	2	1 1/4	3/4	2	0.472	2 63/64	3 1/2	3 11/16	13/16	1 1/4
25 1 3/16 7/8 15/16 1	UEL205D1W3	16	12	51	32	19	51	12	76	89	97	24	32
	UEL205-013D1W3												
	UEL205-014D1W3												
	UEL205-015D1W3	5/8	15/32	2	1 1/4	3/4	2	0.472	2 63/64	3 1/2	3 13/16	15/16	1 1/4
	UEL205-100D1W3												
30 1 1/16 1 1/8 1 1/16 1 1/4	UEL206D1W3	16	12	56	37	22	57	12	89	102	113	28	37
	UEL206-101D1W3												
	UEL206-102D1W3												
	UEL206-103D1W3	5/8	15/32	2 7/32	1 15/32	7/8	2 1/4	0.472	3 1/2	4 1/32	4 7/16	1 3/32	1 15/32
	UEL206-104D1W3												
35 1 1/4 1 5/16 1 3/8 1 7/16	UEL207D1W3	16	15	64	37	22	64	12	89	102	129	30	37
	UEL207-104D1W3												
	UEL207-105D1W3												
	UEL207-106D1W3	5/8	19/32	2 17/32	1 15/32	7/8	2 17/32	0.472	3 1/2	4 1/32	5 3/32	1 3/16	1 15/32
	UEL207-107D1W3												
40 1 1/2 1 5/16	UEL208D1W3	19	18	83	49	29	83	16	102	114	144	33	49
	UEL208-108D1W3												
	UEL208-109D1W3	3/4	23/32	3 9/32	1 15/16	1 5/32	3 9/32	0.630	4 1/64	4 1/2	5 21/32	1 5/16	1 15/16
45 1 5/8 1 11/16 1 3/4	UEL209D1W3	19	18	83	49	29	83	16	102	117	145	35	49
	UEL209-110D1W3												
	UEL209-111D1W3												
	UEL209-112D1W3	3/4	23/32	3 9/32	1 15/16	1 5/32	3 9/32	0.630	4 1/64	4 19/32	5 23/32	1 3/8	1 15/16
50 1 13/16 1 7/8 1 15/16 2	UEL210D1W3	19	18	83	49	29	86	16	102	117	151	37	49
	UEL210-113D1W3												
	UEL210-114D1W3												
	UEL210-115D1W3	3/4	23/32	3 9/32	1 15/16	1 5/32	3 3/8	0.630	4 1/64	4 19/32	5 15/16	1 15/32	1 15/16
	UEL210-200D1W3												

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Nominal dimensions				Bearing number	Housing number	Mass of unit kg lb
mm inch						
$r$	$L_1$	$B_1$	$S$			
33	61	43.7	17.1	UEL204D1W3	T204D1	0.6
1 5/16	2 13/32	1.720	0.673	UEL204-012D1W3	T204D1	1.3
35	62	44.4	17.5	UEL205D1W3	T205D1	0.9
				UEL205-013D1W3	T205D1	
				UEL205-014D1W3	T205D1	
				UEL205-015D1W3	T205D1	2.0
				UEL205-100D1W3	T205D1	
43	70	48.4	18.25	UEL206D1W3	T206D1	1.4
				UEL206-101D1W3	T206D1	
				UEL206-102D1W3	T206D1	
				UEL206-103D1W3	T206D1	3.1
				UEL206-104D1W3	T206D1	
51	78	51.1	18.8	UEL207D1W3	T207D1	1.7
				UEL207-104D1W3	T207D1	
				UEL207-105D1W3	T207D1	
				UEL207-106D1W3	T207D1	3.7
				UEL207-107D1W3	T207D1	
56	88	56.3	21.4	UEL208D1W3	T208D1	2.5
				UEL208-108D1W3	T208D1	
				UEL208-109D1W3	T208D1	5.5
57	88	56.3	21.4	UEL209D1W3	T209D1	2.5
				UEL209-110D1W3	T209D1	
				UEL209-111D1W3	T209D1	
				UEL209-112D1W3	T209D1	5.5
59	92	62.7	24.6	UEL210D1W3	T210D1	2.7
				UEL210-113D1W3	T210D1	
				UEL210-114D1W3	T210D1	
				UEL210-115D1W3	T210D1	6.0
				UEL210-200D1W3	T210D1	

## Take-up unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions											
		mm inch											
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$
55 2 2 1/16 2 1/8 2 3/16	UEL211D1W3 UEL211-200D1W3 UEL211-201D1W3 UEL211-202D1W3 UEL211-203D1W3	25	21	102	64	35	95	22	130	146	171	38	64
		3 1/32	1 3/16	4 1/32	2 17/32	1 3/8	3 3/4	0.866	5 1/8	5 3/4	6 23/32	1 1/2	2 17/32
60 2 1/4 2 5/16 2 3/8 2 7/16	UEL212D1W3 UEL212-204D1W3 UEL212-205D1W3 UEL212-206D1W3 UEL212-207D1W3	32	21	102	64	35	102	22	130	146	194	42	64
		1 1/4	1 3/16	4 1/32	2 17/32	1 3/8	4 1/32	0.866	5 1/8	5 3/4	7 5/8	1 21/32	2 17/32
65 2 1/2 2 9/16	UEL213D1W3 UEL213-208D1W3 UEL213-209D1W3	32	23	111	70	41	121	26	151	167	224	44	70
		1 1/4	2 9/32	4 3/8	2 3/4	1 5/8	4 3/4	1.024	5 15/16	6 9/16	8 13/16	1 29/32	2 3/4
70 2 5/8 2 11/16 2 3/4	UEL214D1W3 UEL214-210D1W3 UEL214-211D1W3 UEL214-212D1W3	32	23	111	70	41	121	26	151	167	224	46	70
		1 1/4	2 9/32	4 3/8	2 3/4	1 5/8	4 3/4	1.024	5 15/16	6 9/16	8 13/16	1 13/16	2 3/4
75 2 13/16 2 7/8 2 15/16 3	UEL215D1W3 UEL215-213D1W3 UEL215-214D1W3 UEL215-215D1W3 UEL215-300D1W3	32	23	111	70	41	121	26	151	167	232	48	70
		1 1/4	2 9/32	4 3/8	2 3/4	1 5/8	4 3/4	1.024	5 15/16	6 9/16	9 1/8	1 7/8	2 3/4

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Nominal dimensions				Bearing number	Housing number	Mass of unit kg lb
mm inch						
$r$	$L_1$	$B_1$	$S$			
65	106	71.4	27.75	UEL211D1W3 UEL211-200D1W3 UEL211-201D1W3 UEL211-202D1W3 UEL211-203D1W3	T211D1 T211D1 T211D1 T211D1 T211D1	4.2 9.3
2 9/16	4 3/16	2.811	1.093			
75	119	77.8	30.95	UEL212D1W3 UEL212-204D1W3 UEL212-205D1W3 UEL212-206D1W3 UEL212-207D1W3	T212D1 T212D1 T212D1 T212D1 T212D1	5.2 11
2 15/16	4 11/16	3.063	1.219			
87	137	85.7	34.15	UEL213D1W3 UEL213-208D1W3 UEL213-209D1W3	T213D1 T213D1 T213D1	7.7 17
3 7/16	5 13/32	3.374	1.344			
87	137	85.7	34.15	UEL214D1W3 UEL214-210D1W3 UEL214-211D1W3 UEL214-212D1W3	T214D1 T214D1 T214D1 T214D1	7.3 16
3 7/16	5 13/32	3.374	1.344			
92	140	92	37.3	UEL215D1W3 UEL215-213D1W3 UEL215-214D1W3 UEL215-215D1W3 UEL215-300D1W3	T215D1 T215D1 T215D1 T215D1 T215D1	7.8 17
3 5/8	5 1/2	3.622	1.469			

## Take-up unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions											
		mm inch											
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$
25 $\frac{13}{16}$ $\frac{7}{8}$ $\frac{15}{16}$ 1	UEL305D1W3	16	14	62	36	26	65	12	80	89	122	26	36
	UEL305-013D1W3												
	UEL305-014D1W3												
	UEL305-015D1W3	$\frac{5}{8}$	$\frac{9}{16}$	$2\frac{7}{16}$	$1\frac{13}{32}$	$1\frac{1}{32}$	$2\frac{9}{16}$	0.472	$3\frac{5}{32}$	$3\frac{1}{2}$	$4\frac{13}{16}$	$1\frac{1}{32}$	$1\frac{13}{32}$
30 $1\frac{1}{16}$ $1\frac{1}{8}$ $1\frac{3}{16}$	UEL306D1W3	18	16	70	41	28	74	16	90	100	137	28	41
	UEL306-101D1W3												
	UEL306-102D1W3												
	UEL306-103D1W3	$\frac{23}{32}$	$\frac{5}{8}$	$2\frac{3}{4}$	$1\frac{5}{8}$	$1\frac{3}{32}$	$2\frac{29}{32}$	0.630	$3\frac{35}{64}$	$3\frac{15}{16}$	$5\frac{13}{32}$	$1\frac{3}{32}$	$1\frac{5}{8}$
35 $1\frac{1}{4}$ $1\frac{5}{16}$ $1\frac{3}{8}$ $1\frac{7}{16}$	UEL307D1W3	20	17	75	45	30	80	16	100	111	150	32	45
	UEL307-104D1W3												
	UEL307-105D1W3												
	UEL307-106D1W3	$\frac{25}{32}$	$\frac{21}{32}$	$2\frac{15}{16}$	$1\frac{25}{32}$	$1\frac{3}{16}$	$3\frac{5}{32}$	0.630	$3\frac{15}{16}$	$4\frac{3}{8}$	$5\frac{29}{32}$	$1\frac{1}{4}$	$1\frac{25}{32}$
40 $1\frac{1}{2}$ $1\frac{9}{16}$	UEL308D1W3	22	19	83	50	32	89	18	112	124	162	34	50
	UEL308-108D1W3												
	UEL308-109D1W3	$\frac{7}{8}$	$\frac{3}{4}$	$3\frac{9}{32}$	$1\frac{31}{32}$	$1\frac{1}{4}$	$3\frac{1}{2}$	0.709	$4\frac{13}{32}$	$4\frac{7}{8}$	$6\frac{3}{8}$	$1\frac{11}{32}$	$1\frac{31}{32}$
45 $1\frac{5}{8}$ $1\frac{11}{16}$ $1\frac{3}{4}$	UEL309D1W3	24	20	90	55	34	97	18	125	138	178	38	55
	UEL309-110D1W3												
	UEL309-111D1W3	$\frac{15}{16}$	$\frac{25}{32}$	$3\frac{17}{32}$	$2\frac{5}{32}$	$1\frac{11}{32}$	$3\frac{13}{16}$	0.709	$4\frac{59}{64}$	$5\frac{7}{16}$	7	$1\frac{1}{2}$	$2\frac{5}{32}$
50 $1\frac{13}{16}$ $1\frac{7}{8}$ $1\frac{15}{16}$	UEL310D1W3	27	22	98	61	37	106	20	140	151	192	40	61
	UEL310-113D1W3												
	UEL310-114D1W3	$1\frac{1}{16}$	$\frac{7}{8}$	$3\frac{27}{32}$	$2\frac{13}{32}$	$1\frac{15}{32}$	$4\frac{3}{16}$	0.787	$5\frac{39}{64}$	$5\frac{15}{16}$	$7\frac{9}{16}$	$1\frac{9}{16}$	$2\frac{13}{32}$
	UEL310-115D1W3												

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Nominal dimensions				Bearing number	Housing number	Mass of unit kg lb
mm inch						
$r$	$L_1$	$B_1$	$S$			
46	76	46.8	16.7	UEL305D1W3	T305D1	1.4
$1\frac{13}{16}$	3	1.843	0.657	UEL305-013D1W3	T305D1	3.1
				UEL305-014D1W3	T305D1	
				UEL305-015D1W3	T305D1	
				UEL305-100D1W3	T305D1	
52	85	50	17.5	UEL306D1W3	T306D1	1.9
$2\frac{1}{16}$	$3\frac{11}{32}$	1.969	0.689	UEL306-101D1W3	T306D1	4.2
				UEL306-102D1W3	T306D1	
				UEL306-103D1W3	T306D1	
56	94	51.6	18.3	UEL307D1W3	T307D1	2.4
$2\frac{7}{32}$	$3\frac{11}{16}$	2.031	0.720	UEL307-104D1W3	T307D1	5.3
				UEL307-105D1W3	T307D1	
				UEL307-106D1W3	T307D1	
				UEL307-107D1W3	T307D1	
62	100	57.1	19.8	UEL308D1W3	T308D1	3.1
$2\frac{7}{16}$	$3\frac{15}{16}$	2.248	0.780	UEL308-108D1W3	T308D1	6.8
				UEL308-109D1W3	T308D1	
68	110	58.7	19.8	UEL309D1W3	T309D1	4.1
$2\frac{11}{16}$	$4\frac{11}{32}$	2.311	0.780	UEL309-110D1W3	T309D1	9.0
				UEL309-111D1W3	T309D1	
				UEL309-112D1W3	T309D1	
74	118	66.6	24.6	UEL310D1W3	T310D1	5.2
$2\frac{29}{32}$	$4\frac{21}{32}$	2.622	0.969	UEL310-113D1W3	T310D1	11
				UEL310-114D1W3	T310D1	
				UEL310-115D1W3	T310D1	

## Take-up unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions																							
		mm inch																							
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$												
55 2 2 1/16 2 1/8 2 3/16	UEL311D1W3 UEL311-200D1W3 UEL311-201D1W3 UEL311-202D1W3 UEL311-203D1W3	29	23	105	66	39	115	22	150	163	207	44	66	1 5/32	29/32	4 1/8	2 19/32	1 17/32	4 17/32	0.866	5 29/32	6 13/32	8 5/32	1 23/32	2 19/32
60 2 1/4 2 5/16 2 3/8 2 7/16	UEL312D1W3 UEL312-204D1W3 UEL312-205D1W3 UEL312-206D1W3 UEL312-207D1W3	31	25	113	71	41	123	22	160	178	220	46	71	1 7/32	3 1/32	4 7/16	2 25/32	1 5/8	4 27/32	0.866	6 19/64	7	8 21/32	1 13/16	2 25/32
65 2 1/2 2 5/16	UEL313D1W3 UEL313-208D1W3 UEL313-209D1W3	32	27	116	70	43	134	26	170	190	238	50	80	1 1/4	1 1/16	4 9/16	2 3/4	1 11/16	5 9/32	1.024	6 11/16	7 15/32	9 3/8	1 31/32	3 5/32
70 2 5/8 2 11/16 2 3/4	UEL314D1W3 UEL314-210D1W3 UEL314-211D1W3 UEL314-212D1W3	36	27	130	85	46	140	26	180	202	252	52	90	1 13/32	1 1/16	5 1/8	3 11/32	1 13/16	5 1/2	1.024	7 3/32	7 15/16	9 29/32	2 1/16	3 17/32
75 2 3/16 2 7/8 2 15/16 3	UEL315D1W3 UEL315-213D1W3 UEL315-214D1W3 UEL315-215D1W3 UEL315-300D1W3	36	27	132	85	46	150	26	192	216	262	55	90	1 13/32	1 1/16	5 3/16	3 11/32	1 13/16	5 29/32	1.024	7 7/16	8 1/2	10 5/16	2 5/32	3 17/32
80 3 1/16 3 1/8 3 3/16	UEL316D1W3 UEL316-301D1W3 UEL316-302D1W3 UEL316-303D1W3	42	30	150	98	53	160	30	204	230	282	60	102	1 21/32	1 3/16	5 29/32	3 27/32	2 3/32	6 5/16	1.181	8 1/32	9 1/16	11 3/32	2 3/8	4 1/32

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.

Nominal dimensions				Bearing number	Housing number	Mass of unit kg lb
mm inch						
$r$	$L_1$	$B_1$	$S$			
80	127	73	27.8	UEL311D1W3 UEL311-200D1W3 UEL311-201D1W3 UEL311-202D1W3 UEL311-203D1W3	T311D1 T311D1 T311D1 T311D1 T311D1	6.6 15
3 5/32	5	2.874	1.094			
85	135	79.4	30.95	UEL312D1W3 UEL312-204D1W3 UEL312-205D1W3 UEL312-206D1W3 UEL312-207D1W3	T312D1 T312D1 T312D1 T312D1 T312D1	7.9 17
3 11/32	5 5/16	3.126	1.219			
92	146	85.7	32.55	UEL313D1W3 UEL313-208D1W3 UEL313-209D1W3	T313D1 T313D1 T313D1	9.8 22
3 5/8	5 3/4	3.374	1.281			
97	155	92.1	34.15	UEL314D1W3 UEL314-210D1W3 UEL314-211D1W3 UEL314-212D1W3	T314D1 T314D1 T314D1 T314D1	11 24
3 13/16	6 3/32	3.626	1.344			
102	160	100	37.3	UEL315D1W3 UEL315-213D1W3 UEL315-214D1W3 UEL315-215D1W3 UEL315-300D1W3	T315D1 T315D1 T315D1 T315D1 T315D1	14 31
4 1/32	6 5/16	3.937	1.469			
108	174	106.4	40.5	UEL316D1W3 UEL316-301D1W3 UEL316-302D1W3 UEL316-303D1W3	T316D1 T316D1 T316D1 T316D1	17 37
4 1/4	6 27/32	4.189	1.594			

## Take-up unit, cast housing Eccentric locking collar type




Shaft dia. mm inch	Unit number (1)	Nominal dimensions											
		mm inch											
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$
85 3 1/4 3 5/16 3 7/16	UEL317D1W3 UEL317-304D1W3 UEL317-305D1W3 UEL317-307D1W3	42	32	152	98	53	170	32	214	240	298	64	102
		1 21/32	1 1/4	5 31/32	3 27/32	2 3/32	6 11/16	1.260	8 27/64	9 7/16	11 23/32	2 17/32	4 1/32
90 3 7/16 3 1/2	UEL318D1W3 UEL318-307D1W3 UEL318-308D1W3	46	32	160	106	57	175	32	228	255	312	66	110
		1 13/16	1 1/4	6 5/16	4 3/16	2 1/4	6 7/8	1.260	8 31/32	10 1/32	12 9/32	2 19/32	4 11/32
95 3 5/8 3 11/16 3 3/4	UEL319D1W3 UEL319-310D1W3 UEL319-311D1W3 UEL319-312D1W3	46	33	165	106	57	180	35	240	270	322	72	110
		1 13/16	1 5/16	6 1/2	4 3/16	2 1/4	7 3/32	1.378	9 29/64	10 5/8	12 11/16	2 27/32	4 11/32
100 3 13/16 3 7/8 3 15/16 4	UEL320D1W3 UEL320-313D1W3 UEL320-314D1W3 UEL320-315D1W3 UEL320-400D1W3	48	34	175	115	59	200	35	260	290	345	75	120
		1 7/8	1 11/32	6 7/8	4 17/32	2 5/16	7 7/8	1.378	10 15/64	11 13/32	13 19/32	2 15/16	4 23/32
105	UEL321D1W3	48	34	175	115	59	200	35	260	290	347	75	120
110	UEL322D1W3	52	40	185	125	65	215	38	285	320	385	80	130

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

Nominal dimensions				Bearing number	Housing number	Mass of unit kg lb
mm inch						
$r$	$L_1$	$B_1$	$S$			
115	183	109.5	42.05	UEL317D1W3 UEL317-304D1W3 UEL317-305D1W3 UEL317-307D1W3	T317D1 T317D1 T317D1 T317D1	20 44
4 17/32	7 7/32	4.311	1.656			
120	192	115.9	43.65	UEL318D1W3 UEL318-307D1W3 UEL318-308D1W3	T318D1 T318D1 T318D1	23 51
4 23/32	7 9/16	4.563	1.719			
125	197	122.3	38.9	UEL319D1W3 UEL319-310D1W3 UEL319-311D1W3 UEL319-312D1W3	T319D1 T319D1 T319D1 T319D1	26 57
4 29/32	7 3/4	4.815	1.531			
135	210	128.6	50	UEL320D1W3 UEL320-313D1W3 UEL320-314D1W3 UEL320-315D1W3 UEL320-400D1W3	T320D1 T320D1 T320D1 T320D1 T320D1	32 71
5 5/16	8 3/32	5.063	1.969			
135	212	139.7	48.4	UEL321D1D1W3	T321D1	33
150	235	141.3	49.2	UEL322D1D1W3	T322D1	42

## Take-up mini stretcher Units™ Eccentric locking collar type




AELPT type

Shaft dia.  mm inch	Unit number	Nominal dimensions			Bolt size  mm inch	Max. load (1) recommended  N lbf
		A	B <sub>1</sub>	S		
12  1/2	AELPT201-10W3	37.1	28.6	6.5	M10	3 430
	AELPT201-008-10W3	1 <sup>29</sup> / <sub>64</sub>	1.126	0.256	3/8	770
15  9/16 5/8	AELPT202-10W3	37.1	28.6	6.5	M10	3 430
	AELPT202-009-10W3 AELPT202-010-10W3	1 <sup>29</sup> / <sub>64</sub>	1.126	0.256	3/8	770
17  11/16	AELPT203-10W3	37.1	28.6	6.5	M10	3 430
	AELPT203-011-10W3	1 <sup>29</sup> / <sub>64</sub>	1.126	0.256	3/8	770
20  3/4	AELPT204-10W3	38.5	31	7.5	M10	3 430
	AELPT204-012-10W3	1 <sup>33</sup> / <sub>64</sub>	1.220	0.295	3/8	770
25  13/16 7/8 15/16 1	AELPT205-10W3	38.5	31	7.5	M10	3 430
	AELPT205-013-10W3					
	AELPT205-014-10W3					
	AELPT205-015-10W3	1 <sup>33</sup> / <sub>64</sub>	1.220	0.295	3/8	770
	AELPT205-100-10W3					

Bearing number	Mass of unit  kg lb
AEL201W3	1.1
AEL201-008W3	2.4
AEL202W3	1.1
AEL202-009W3	2.4
AEL202-010W3	
AEL203W3	1.1
AEL203-011W3	2.4
AEL204W3	1.1
AEL204-012W3	2.4
AEL205W3	1.2
AEL205-013W3	
AEL205-014W3	
AEL205-015W3	2.6
AEL205-100W3	

Note (1) The Stretcher Units is designed to only take a horizontal radial load, in line with the adjustment direction. Axial loads or vertical radial loads can deform or break the housing.

## Take-up mini stretcher Units™ Eccentric locking collar type




Shaft dia.  mm inch	Unit number	Nominal dimensions			Bolt size  mm inch	Max. load (1) recommended  N lbf
		A	B <sub>1</sub>	S		
12  1/2	JELPT201-10W3	37.1	28.6	6.5	M10	3 430
	JELPT201-008-10W3	1 <sup>29</sup> / <sub>64</sub>	1.126	0.256	3/8	770
15  9/16 5/8	JELPT202-10W3	37.1	28.6	6.5	M10	3 430
	JELPT202-009-10W3 JELPT202-010-10W3	1 <sup>29</sup> / <sub>64</sub>	1.126	0.256	3/8	770
17  11/16	JELPT203-10W3	37.1	28.6	6.5	M10	3 430
	JELPT203-011-10W3	1 <sup>29</sup> / <sub>64</sub>	1.126	0.256	3/8	770
20  3/4	JELPT204-10W3	38.5	31	7.5	M10	3 430
	JELPT204-012-10W3	1 <sup>33</sup> / <sub>64</sub>	1.220	0.295	3/8	770
25  13/16 7/8 15/16 1	JELPT205-10W3	38.5	31	7.5	M10	3 430
	JELPT205-013-10W3					
	JELPT205-014-10W3					
	JELPT205-015-10W3	1 <sup>33</sup> / <sub>64</sub>	1.220	0.295	3/8	770
	JELPT205-100-10W3					

Bearing number	Mass of unit kg lb
JEL201W3	1.1
JEL201-008W3	2.4
JEL202W3	1.1
JEL202-009W3	2.4
JEL202-010W3	
JEL203W3	1.1
JEL203-011W3	2.4
JEL204W3	1.1
JEL204-012W3	2.4
JEL205W3	1.2
JEL205-013W3	
JEL205-014W3	
JEL205-015W3	2.6
JEL205-100W3	


**Note (1)** The Stretcher Units is designed to only take a horizontal radial load, in line with the adjustment direction. Axial loads or vertical radial loads can deform or break the housing.

## Cartridge unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number (*)	Nominal dimensions mm inch					Bearing number	Housing number	Mass of unit kg lb
		H	A	r	B <sub>1</sub>	S			
20 3/4	UEL204D1W3	72	20	2	43.7	17.1	UEL204D1W3	C204D1	0.6
	UEL204-012D1W3	2.8346	25/32	0.079	1.720	0.673	UEL204-012D1W3	C204D1	1.3
25 1 1/16 7/8 15/16	UEL205D1W3	80	22	2	44.4	17.45	UEL205D1W3	C205D1	0.7
	UEL205-013D1W3	3.1496	55/64	0.079	1.748	0.687	UEL205-013D1W3	C205D1	1.5
	UEL205-014D1W3						C205D1		
	UEL205-015D1W3						C205D1		
UEL205-100D1W3	C205D1								
30 1 1/16 1 1/8 1 3/16 1 1/4	UEL206D1W3	85	27	2	48.4	18.25	UEL206D1W3	C206D1	0.9
	UEL206-101D1W3	3.3465	1 1/16	0.079	1.906	0.719	UEL206-101D1W3	C206D1	2.0
	UEL206-102D1W3						C206D1		
	UEL206-103D1W3						C206D1		
	UEL206-104D1W3						C206D1		
UEL206-104D1W3	C206D1								
35 1 1/4 1 5/16 1 3/8 1 7/16	UEL207D1W3	90	28	2	51.1	18.8	UEL207D1W3	C207D1	1.0
	UEL207-104D1W3	3.5433	1 7/64	0.079	2.012	0.740	UEL207-104D1W3	C207D1	2.2
	UEL207-105D1W3						C207D1		
	UEL207-106D1W3						C207D1		
	UEL207-106D1W3						C207D1		
UEL207-107D1W3	C207D1								
40 1 1/2 1 9/16	UEL208D1W3	100	30	2.5	56.3	21.4	UEL208D1W3	C208D1	1.4
	UEL208-108D1W3	3.9370	1 3/16	0.098	2.217	0.843	UEL208-108D1W3	C208D1	3.1
	UEL208-109D1W3						C208D1		
UEL208-109D1W3	C208D1								
45 1 5/8 1 7/16 1 3/4	UEL209D1W3	110	31	2.5	56.3	21.4	UEL209D1W3	C209D1	1.6
	UEL209-110D1W3	4.3307	1 7/32	0.098	2.217	0.843	UEL209-110D1W3	C209D1	3.5
	UEL209-111D1W3						C209D1		
	UEL209-111D1W3						C209D1		
UEL209-112D1W3	C209D1								

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.




Shaft dia. mm inch	Unit number (*)	Nominal dimensions mm inch					Bearing number	Housing number	Mass of unit kg lb
		H	A	r	B <sub>1</sub>	S			
50 1 13/16 1 7/8 1 15/16 2	UEL210D1W3	120	33	2.5	62.7	24.6	UEL210D1W3	C210D1	2.1
	UEL210-113D1W3	4.7244	1 19/64	0.098	2.469	0.969	UEL210-113D1W3	C210D1	4.6
	UEL210-114D1W3						C210D1		
	UEL210-115D1W3						C210D1		
	UEL210-200D1W3						C210D1		
UEL210-200D1W3	C210D1								
55 2 2 1/16 2 1/8 2 3/16	UEL211D1W3	125	35	2.5	71.4	27.75	UEL211D1W3	C211D1	2.4
	UEL211-200D1W3	4.9213	1 3/8	0.098	2.811	1.093	UEL211-200D1W3	C211D1	5.3
	UEL211-201D1W3						C211D1		
	UEL211-202D1W3						C211D1		
	UEL211-203D1W3						C211D1		
UEL211-203D1W3	C211D1								
60 2 1/4 2 5/16 2 3/8 2 7/16	UEL212D1W3	130	38	2.5	77.8	30.95	UEL212D1W3	C212D1	2.8
	UEL212-204D1W3	5.1181	1 1/2	0.098	3.063	1.219	UEL212-204D1W3	C212D1	6.2
	UEL212-205D1W3						C212D1		
	UEL212-206D1W3						C212D1		
	UEL212-206D1W3						C212D1		
UEL212-207D1W3	C212D1								

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
Remarks Please refer to page A21 for size of grease fitting.




## Cartridge unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions					Bearing number	Housing number	Mass of unit kg lb
		<i>H</i>	<i>A</i>	<i>r</i>	<i>B</i> <sub>1</sub>	<i>S</i>			
25 $1\frac{3}{16}$ $\frac{7}{8}$ $1\frac{5}{16}$ 1	<b>UELC305D1W3</b>	90	26	2.5	46.8	16.7	UEL305D1W3	C305D1	1.0
	<b>UELC305-013D1W3</b>						UEL305-013D1W3	C305D1	
	<b>UELC305-014D1W3</b>	3.5433	$1\frac{1}{32}$	0.098	1.843	0.657	UEL305-014D1W3	C305D1	2.2
	<b>UELC305-015D1W3</b>						UEL305-015D1W3	C305D1	
	<b>UELC305-100D1W3</b>						UEL305-100D1W3	C305D1	
30 $1\frac{1}{16}$ $1\frac{1}{8}$ $1\frac{3}{16}$	<b>UELC306D1W3</b>	100	28	2.5	50	17.5	UEL306D1W3	C306D1	1.4
	<b>UELC306-101D1W3</b>						UEL306-101D1W3	C306D1	
	<b>UELC306-102D1W3</b>	3.9370	$1\frac{7}{64}$	0.098	1.969	0.689	UEL306-102D1W3	C306D1	3.1
	<b>UELC306-103D1W3</b>						UEL306-103D1W3	C306D1	
35 $1\frac{1}{4}$ $1\frac{5}{16}$ $1\frac{3}{8}$ $1\frac{7}{16}$	<b>UELC307D1W3</b>	110	32	3	51.6	18.3	UEL307D1W3	C307D1	1.8
	<b>UELC307-104D1W3</b>						UEL307-104D1W3	C307D1	
	<b>UELC307-105D1W3</b>	4.3307	$1\frac{17}{64}$	0.118	2.031	0.720	UEL307-105D1W3	C307D1	4.0
	<b>UELC307-106D1W3</b>						UEL307-106D1W3	C307D1	
	<b>UELC307-107D1W3</b>						UEL307-107D1W3	C307D1	
40 $1\frac{1}{2}$ $1\frac{9}{16}$	<b>UELC308D1W3</b>	120	34	3	57.1	19.8	UEL308D1W3	C308D1	2.3
	<b>UELC308-108D1W3</b>	4.7244	$1\frac{11}{32}$	0.118	2.248	0.780	UEL308-108D1W3	C308D1	5.1
	<b>UELC308-109D1W3</b>						UEL308-109D1W3	C308D1	
45 $1\frac{5}{8}$ $1\frac{11}{16}$ $1\frac{3}{4}$	<b>UELC309D1W3</b>	130	38	3.5	58.7	19.8	UEL309D1W3	C309D1	2.9
	<b>UELC309-110D1W3</b>						UEL309-110D1W3	C309D1	
	<b>UELC309-111D1W3</b>	5.1181	$1\frac{1}{2}$	0.138	2.311	0.780	UEL309-111D1W3	C309D1	6.4
	<b>UELC309-112D1W3</b>						UEL309-112D1W3	C309D1	
50 $1\frac{13}{16}$ $1\frac{7}{8}$ $1\frac{15}{16}$	<b>UELC310D1W3</b>	140	40	3.5	66.6	24.6	UEL310D1W3	C310D1	3.5
	<b>UELC310-113D1W3</b>						UEL310-113D1W3	C310D1	
	<b>UELC310-114D1W3</b>	5.5118	$1\frac{37}{64}$	0.138	2.622	0.969	UEL310-114D1W3	C310D1	7.7
	<b>UELC310-115D1W3</b>						UEL310-115D1W3	C310D1	

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.




Shaft dia. mm inch	Unit number (1)	Nominal dimensions					Bearing number	Housing number	Mass of unit kg lb
		<i>H</i>	<i>A</i>	<i>r</i>	<i>B</i> <sub>1</sub>	<i>S</i>			
55 2 $2\frac{1}{16}$ $2\frac{1}{8}$ $2\frac{3}{16}$	<b>UELC311D1W3</b>	150	44	3.5	73	27.8	UEL311D1W3	C311D1	4.3
	<b>UELC311-200D1W3</b>						UEL311-200D1W3	C311D1	
	<b>UELC311-201D1W3</b>	5.9055	$1\frac{47}{64}$	0.138	2.874	1.094	UEL311-201D1W3	C311D1	9.5
	<b>UELC311-202D1W3</b>						UEL311-202D1W3	C311D1	
	<b>UELC311-203D1W3</b>						UEL311-203D1W3	C311D1	
60 $2\frac{1}{4}$ $2\frac{5}{16}$ $2\frac{3}{8}$ $2\frac{7}{16}$	<b>UELC312D1W3</b>	160	46	3.5	79.4	30.95	UEL312D1W3	C312D1	5.1
	<b>UELC312-204D1W3</b>						UEL312-204D1W3	C312D1	
	<b>UELC312-205D1W3</b>	6.2992	$1\frac{19}{16}$	0.138	3.126	1.219	UEL312-205D1W3	C312D1	11
	<b>UELC312-206D1W3</b>						UEL312-206D1W3	C312D1	
	<b>UELC312-207D1W3</b>						UEL312-207D1W3	C312D1	
65 $2\frac{1}{2}$ $2\frac{9}{16}$	<b>UELC313D1W3</b>	170	50	3.5	85.7	32.55	UEL313D1W3	C313D1	6.2
	<b>UELC313-208D1W3</b>	6.6929	$1\frac{31}{32}$	0.138	3.374	1.281	UEL313-208D1W3	C313D1	14
	<b>UELC313-209D1W3</b>						UEL313-209D1W3	C313D1	
70 $2\frac{5}{8}$ $2\frac{11}{16}$ $2\frac{3}{4}$	<b>UELC314D1W3</b>	180	52	4	92.1	34.15	UEL314D1W3	C314D1	7.3
	<b>UELC314-210D1W3</b>						UEL314-210D1W3	C314D1	
	<b>UELC314-211D1W3</b>	7.0866	$2\frac{3}{64}$	0.157	3.626	1.344	UEL314-211D1W3	C314D1	16
	<b>UELC314-212D1W3</b>						UEL314-212D1W3	C314D1	
75 $2\frac{13}{16}$ $2\frac{7}{8}$ $2\frac{15}{16}$ 3	<b>UELC315D1W3</b>	190	55	4	100	37.3	UEL315D1W3	C315D1	8.5
	<b>UELC315-213D1W3</b>						UEL315-213D1W3	C315D1	
	<b>UELC315-214D1W3</b>	7.4803	$2\frac{11}{64}$	0.157	3.937	1.469	UEL315-214D1W3	C315D1	19
	<b>UELC315-215D1W3</b>						UEL315-215D1W3	C315D1	
	<b>UELC315-300D1W3</b>						UEL315-300D1W3	C315D1	
80 $3\frac{1}{16}$ $3\frac{1}{8}$ $3\frac{3}{16}$	<b>UELC316D1W3</b>	200	60	4	106.4	40.5	UEL316D1W3	C316D1	10
	<b>UELC316-301D1W3</b>						UEL316-301D1W3	C316D1	
	<b>UELC316-302D1W3</b>	7.8740	$2\frac{23}{64}$	0.157	4.189	1.594	UEL316-302D1W3	C316D1	22
	<b>UELC316-303D1W3</b>						UEL316-303D1W3	C316D1	

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Remarks Please refer to page A21 for size of grease fitting.

## Cartridge unit, cast housing Eccentric locking collar type



Shaft dia. mm inch	Unit number (1)	Nominal dimensions mm inch					Bearing number	Housing number	Mass of unit kg lb
		H	A	r	B <sub>1</sub>	S			
85 3 1/4	<b>UEL317D1W3</b>	215	64	4	109.5	42.05	UEL317D1W3	C317D1	13
3 5/16	<b>UEL317-304D1W3</b>	8.4646	2 33/64	0.157	4.311	1.656	UEL317-304D1W3	C317D1	29
3 7/16	<b>UEL317-305D1W3</b>						UEL317-305D1W3	C317D1	
	<b>UEL317-307D1W3</b>						UEL317-307D1W3	C317D1	
90 3 7/16	<b>UEL318D1W3</b>	225	66	4	115.9	43.65	UEL318D1W3	C318D1	14
3 1/2	<b>UEL318-307D1W3</b>	8.8583	2 19/32	0.157	4.563	1.719	UEL318-307D1W3	C318D1	31
	<b>UEL318-308D1W3</b>						UEL318-308D1W3	C318D1	
95 3 5/8	<b>UEL319D1W3</b>	240	72	4	122.3	38.9	UEL319D1W3	C319D1	17
3 11/16	<b>UEL319-310D1W3</b>	9.4488	2 53/64	0.157	4.815	1.531	UEL319-310D1W3	C319D1	37
3 3/4	<b>UEL319-311D1W3</b>						UEL319-311D1W3	C319D1	
	<b>UEL319-312D1W3</b>						UEL319-312D1W3	C319D1	
100 3 13/16	<b>UEL320D1W3</b>	260	75	4	128.6	50	UEL320D1W3	C320D1	22
3 7/8	<b>UEL320-313D1W3</b>	10.2362	2 61/64	0.157	5.063	1.969	UEL320-313D1W3	C320D1	49
3 15/16	<b>UEL320-314D1W3</b>						UEL320-314D1W3	C320D1	
	<b>UEL320-315D1W3</b>						UEL320-315D1W3	C320D1	
4	<b>UEL320-400D1W3</b>						UEL320-400D1W3	C320D1	
105	<b>UEL321D1W3</b>	260	75	4	139.7	48.4	UEL321D1W3	C321D1	21
110	<b>UEL322D1W3</b>	300	80	5	141.3	49.2	UEL322D1W3	C322D1	31

**Note** (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

**Remarks** Please refer to page A21 for size of grease fitting.

## Pillow block unit, cast housing Adapter type



**Pressed steel dust cover type**  
Open end **Z-UKP...D1**  
Closed end **ZM-UKP...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup> / <sub>(2)</sub> / <sub>(3)</sub>	Nominal dimensions										Bolt size mm inch	Bearing number
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>		
20 3/4	UKP205D1;H2305X	36.5	140	105	38	13	16	15	71	42	35	M10	UK205D1;H2305X
	UKP205D1;HE2305	1 7/16	5 1/2	4 1/8	1 1/2	1/2	5/8	19/32	2 25/32	1 21/32	1.378	3/8	UK205D1;HE2305
25 7/8 1	UKP206D1;H2306X	42.9	165	121	48	17	20	17	83	54	38	M14	UK206D1;H2306X
	UKP206D1;HS2306	1 11/16	6 1/2	4 3/4	1 7/8	21/32	25/32	21/32	3 9/32	2 1/8	1.496	1/2	UK206D1;HS2306
30 1 1/8	UKP207D1;H2307X	47.6	167	127	48	17	20	18	93	54	43	M14	UK207D1;H2307X
	UKP207D1;HS2307	1 7/8	6 9/16	5	1 7/8	21/32	25/32	23/32	3 21/32	2 1/8	1.693	1/2	UK207D1;HS2307
35 1 1/4 1 3/8	UKP208D1;H2308X	49.2	184	137	54	17	20	18	98	52	46	M14	UK208D1;H2308X
	UKP208D1;HE2308X	1 15/16	7 1/4	5 13/32	2 1/8	21/32	25/32	23/32	3 27/32	2 1/16	1.811	1/2	UK208D1;HE2308X
40 1 7/16 1 1/2 1 5/8	UKP209D1;H2309X	54	190	146	54	17	20	20	106	60	50	M14	UK209D1;H2309X
	UKP209D1;HA2309	2 1/8	7 15/32	5 3/4	2 1/8	21/32	25/32	25/32	4 3/16	2 3/8	1.969	1/2	UK209D1;HA2309
45 1 5/8 1 11/16 1 3/4	UKP210D1;H2310X	57.2	206	159	60	20	23	21	114	65	55	M16	UK210D1;H2310X
	UKP210D1;HA2310	2 1/4	8 1/8	6 1/4	2 3/8	25/32	29/32	13/16	4 1/2	2 9/16	2.165	5/8	UK210D1;HA2310
50 1 7/8 1 15/16 2	UKP211D1;H2311X	63.5	219	171	60	20	23	23	126	65	59	M16	UK211D1;H2311X
	UKP211D1;HA2311	2 1/2	8 5/8	6 23/32	2 3/8	25/32	29/32	29/32	4 31/32	2 9/16	2.323	5/8	UK211D1;HA2311
55 2 1/8	UKP212D1;H2312X	69.8	241	184	70	20	23	25	138	70	62	M16	UK212D1;H2312X
	UKP212D1;HS2312	2 3/4	9 1/2	7 1/4	2 3/4	25/32	29/32	31/32	5 7/16	2 3/4	2.441	5/8	UK212D1;HS2312

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve. In this case the lock washer with the straight inner prong should be used.

<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve. To distinguish it, a suffix "Y" is added.

Remarks Please refer to page A21 for size of grease fitting.



**Cast cover type**  
Open end **C-UKP...D1**  
Closed end **CM-UKP...D1**

Housing number	Unit number pressed steel dust cover type	Unit number cast dust cover type	Nominal dimensions				Mass of unit		
			mm inch				kg lb		
			t max.	A <sub>4</sub>	H <sub>3</sub>	A <sub>5</sub>	UKP	Z(ZM)	C(CM)
P205D1	Z(ZM)-UKP205D1;H2305X	C(CM)-UKP205D1;H2305X	2	48	76	70	0.8	0.9	1.2
	Z(ZM)-UKP205ED1;HE2305	C(CM)-UKP205ED1;HE2305	5/64	1 29/32	3	2 3/4	1.8	2.0	2.6
P206D1	Z(ZM)-UKP206D1;H2306X	C(CM)-UKP206D1;H2306X	2	53	88	75	1.4	1.5	1.8
	Z(ZM)-UKP206SD1;HS2306	C(CM)-UKP206SD1;HS2306	5/64	2 3/32	3 15/32	2 15/16	3.1	3.3	4.0
P207D1	Z(ZM)-UKP207D1;H2307X	C(CM)-UKP207D1;H2307X	3	60	99	80	1.7	1.8	2.1
	Z(ZM)-UKP207SD1;HS2307	C(CM)-UKP207SD1;HS2307	1/8	2 3/8	3 29/32	3 3/32	3.7	4.0	4.6
P208D1	Z(ZM)-UKP208D1;H2308X	C(CM)-UKP208D1;H2308X	3	69	105	90	2.0	2.2	2.8
	Z(ZM)-UKP208ED1;HE2308X	C(CM)-UKP208ED1;HE2308X	1/8	2 23/32	4 1/8	3 11/32	4.4	4.9	6.2
P209D1	Z(ZM)-UKP209D1;H2309X	C(CM)-UKP209D1;H2309X	3	69	113	95	2.3	2.5	3.3
	Z(ZM)-UKP209AD1;HA2309	C(CM)-UKP209AD1;HA2309	1/8	2 23/32	4 7/16	3 3/4	5.1	5.5	7.3
P210D1	Z(ZM)-UKP210D1;H2310X	C(CM)-UKP210D1;H2310X	3	76	119	100	2.9	3.0	3.9
	Z(ZM)-UKP210SD1;HS2310	C(CM)-UKP210SD1;HS2310	1/8	3	4 11/16	3 5/16	6.4	6.6	8.6
P211D1	Z(ZM)-UKP211D1;H2311X	C(CM)-UKP211D1;H2311X	4	77	130	100	3.6	3.7	4.8
	Z(ZM)-UKP211SD1;HS2311	C(CM)-UKP211SD1;HS2311	5/32	3 1/32	5 1/8	3 5/16	7.9	8.2	11
P212D1	Z(ZM)-UKP212D1;H2312X	C(CM)-UKP212D1;H2312X	4	89	143	115	4.7	5.1	6.2
	Z(ZM)-UKP212SD1;HS2312	C(CM)-UKP212SD1;HS2312	5/32	3 1/2	5 5/8	4 7/32	10	11	14

## Pillow block unit, cast housing Adapter type



Pressed steel dust cover type

Open end **Z-UKP...D1**  
Closed end **ZM-UKP...D1**

Shaft dia. mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions										Bolt size mm inch	Bearing number
		mm inch											
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>		
60 2 3/16 2 1/4 2 3/8	<b>UKP213D1;H2313X</b> <b>UKP213D1;HA2313</b> <b>UKP213D1;HE2313X</b> <b>UKP213D1;HS2313X</b>	76.2	265	203	70	25	28	27	151	77	65	M20	UK213D1;H2313X UK213D1;HA2313 UK213D1;HE2313X UK213D1;HS2313X
65 2 7/16 2 1/2	<b>UKP215D1;H2315X</b> <b>UKP215D1;HA2315</b> <b>UKP215D1;HE2315X</b>	82.6	275	217	74	25	28	28	163	80	73	M20	UK215D1;H2315X UK215D1;HA2315 UK215D1;HE2315X
70 2 11/16 2 3/4	<b>UKP216D1;H2316X</b> <b>UKP216D1;HA2316</b> <b>UKP216D1;HE2316X</b>	88.9	292	232	78	25	28	30	175	85	78	M20	UK216D1;H2316X UK216D1;HA2316 UK216D1;HE2316X
75 2 15/16 3	<b>UKP217D1;H2317X</b> <b>UKP217D1;HA2317X</b> <b>UKP217D1;HE2317X</b>	95.2	310	247	83	25	28	32	187	85	82	M20	UK217D1;H2317X UK217D1;HA2317X UK217D1;HE2317X
80 3 3/16	<b>UKP218D1;H2318X</b> <b>UKP218D1;HA2318X</b>	101.6	327	262	88	27	30	33	200	90	86	M22	UK218D1;H2318X UK218D1;HA2318X

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.

Remarks Please refer to page A21 for size of grease fitting.



Cast dust cover type

Open end **C-UKP...D1**  
Closed end **CM-UKP...D1**

Housing number	Unit number pressed steel dust cover type	Unit number cast dust cover type	Nominal dimensions				Mass of unit		
			mm inch				kg lb		
			t max.	A <sub>4</sub>	H <sub>3</sub>	A <sub>5</sub>	UKP	Z(ZM)	C(CM)
P213D1 P213D1 P213D1 P213D1	<b>Z(ZM)-UKP213D1;H2313X</b> <b>Z(ZM)-UKP213AD1;HA2313</b> <b>Z(ZM)-UKP213ED1;HE2313X</b> <b>Z(ZM)-UKP213SD1;HS2313X</b>	<b>C(CM)-UKP213D1;H2313X</b> <b>C(CM)-UKP213AD1;HA2313</b> <b>C(CM)-UKP213ED1;HE2313X</b> <b>C(CM)-UKP213SD1;HS2313X</b>	4 5/32	91 3 19/32	155 6 3/32	120 4 23/32	5.7 13	5.9 13	7.6 17
P215D1 P215D1 P215D1	— — —	<b>C(CM)-UKP215D1;H2315X</b> <b>C(CM)-UKP215AD1;HA2315</b> <b>C(CM)-UKP215ED1;HE2315X</b>	4 5/32	— —	168 6 5/8	135 5 5/16	7.5 17	— —	10 22
P216D1 P216D1 P216D1	— — —	<b>C(CM)-UKP216D1;H2316X</b> <b>C(CM)-UKP216AD1;HA2316</b> <b>C(CM)-UKP216ED1;HE2316X</b>	4 5/32	— —	181 7 1/8	145 5 23/32	9.2 20	— —	12 26
P217D1 P217D1 P217D1	— — —	<b>C(CM)-UKP217D1;H2317X</b> <b>C(CM)-UKP217AD1;HA2317X</b> <b>C(CM)-UKP217ED1;HE2317X</b>	5 13/64	— —	191 7 17/32	155 6 3/32	11 24	— —	14 31
P218D1 P218D1	— —	<b>C(CM)-UKP218D1;H2318X</b> <b>C(CM)-UKP218AD1;HA2318X</b>	5 13/64	— —	204 8 1/32	165 6 1/2	13 29	— —	16 35

## Pillow block unit, cast housing Adapter type



**Cast dust cover type**  
Open end **C-UKP...D1**  
Closed end **CM-UKP...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup> / <sub>(2)</sub> / <sub>(3)</sub>	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	
20 3/4	UKP305D1;H2305X UKP305D1;HE2305	45 1 49/64	175 6 7/8	132 5 3/16	45 1 25/32	17 2 1/32	20 25/32	15 19/32	85 3 11/32	54 2 1/8	35 1.378	M14 1/2
25 7/8 1	UKP306D1;H2306X UKP306D1;HS2306 UKP306D1;HE2306X	50 1 31/32	180 7 3/32	140 5 1/2	50 1 31/32	17 2 1/32	20 25/32	18 23/32	95 3 3/4	54 2 1/8	38 1.496	M14 1/2
30 1 1/8	UKP307D1;H2307X UKP307D1;HS2307	56 2 13/64	210 8 3/32	160 6 5/16	56 2 7/32	17 2 1/32	25 3 1/32	20 25/32	106 4 3/16	60 2 3/8	43 1.693	M14 1/2
35 1 1/4 1 3/8	UKP308D1;H2308X UKP308D1;HE2308X UKP308D1;HS2308X	60 2 23/64	220 8 21/32	170 6 11/16	60 2 3/8	17 2 1/32	27 1 1/16	22 7/8	116 4 9/16	60 2 3/8	46 1.811	M14 1/2
40 1 7/16 1 1/2 1 5/8	UKP309D1;H2309X UKP309D1;HA2309 UKP309D1;HE2309X UKP309D1;HS2309X	67 2 41/64	245 9 21/32	190 7 15/32	67 2 5/8	20 25/32	30 1 3/16	24 15/16	129 5 3/32	65 2 9/16	50 1.969	M16 5/8
45 1 5/8 1 11/16 1 3/4	UKP310D1;H2310X UKP310D1;HS2310 UKP310D1;HA2310 UKP310D1;HE2310X	75 2 61/64	275 10 13/16	212 8 11/32	75 2 15/16	20 25/32	35 1 3/8	27 1 1/16	143 5 5/8	75 2 15/16	55 2.165	M16 5/8
50 1 7/8 1 15/16 2	UKP311D1;H2311X UKP311D1;HS2311 UKP311D1;HA2311 UKP311D1;HE2311XY	80 3 5/32	310 12 7/32	236 9 9/32	80 3 5/32	20 25/32	38 1 1/2	30 1 3/16	154 6 1/16	85 3 11/32	59 2.323	M16 5/8
55 2 1/8	UKP312D1;H2312X UKP312D1;HS2312	85 3 11/32	330 13	250 9 27/32	85 3 11/32	25 3 1/32	38 1 1/2	32 1 1/4	165 6 1/2	95 3 3/4	62 2.441	M20 3/4

**Notes** <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.  
To distinguish it, a suffix "Y" is added.

**Remarks** Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			t max.	H <sub>3</sub>	A <sub>5</sub>	UKP	C(CM)
UK305D1;H2305X UK305D1;HE2305	P305D1 P305D1	C(CM)-UKP305D1;H2305X C(CM)-UKP305ED1;HE2305	2 5/64	91 3 19/32	80 3 5/32	1.4 3.1	1.9 4.2
UK306D1;H2306X UK306D1;HS2306 UK306D1;HE2306X	P306D1 P306D1 P306D1	C(CM)-UKP306D1;H2306X C(CM)-UKP306SD1;HS2306 C(CM)-UKP306ED1;HE2306X	2 5/64	105 4 1/8	85 3 11/32	1.8 4.0	2.6 5.7
UK307D1;H2307X UK307D1;HS2307	P307D1 P307D1	C(CM)-UKP307D1;H2307X C(CM)-UKP307SD1;HS2307	3 1/8	115 4 17/32	95 3 3/4	2.6 5.7	3.3 7.3
UK308D1;H2308X UK308D1;HE2308X UK308D1;HS2308X	P308D1 P308D1 P308D1	C(CM)-UKP308D1;H2308X C(CM)-UKP308ED1;HE2308X C(CM)-UKP308SD1;HS2308X	3 1/8	125 4 29/32	105 4 1/8	3.1 6.8	4.2 9.3
UK309D1;H2309X UK309D1;HA2309 UK309D1;HE2309X UK309D1;HS2309X	P309D1 P309D1 P309D1 P309D1	C(CM)-UKP309D1;H2309X C(CM)-UKP309AD1;HA2309 C(CM)-UKP309ED1;HE2309X C(CM)-UKP309SD1;HS2309X	3 1/8	140 5 1/2	110 4 11/32	4.1 9.0	5.6 12
UK310D1;H2310X UK310D1;HS2310 UK310D1;HA2310 UK310D1;HE2310X	P310D1 P310D1 P310D1 P310D1	C(CM)-UKP310D1;H2310X C(CM)-UKP310SD1;HS2310 C(CM)-UKP310AD1;HA2310 C(CM)-UKP310ED1;HE2310X	3 1/8	156 6 5/32	120 4 23/32	5.6 12	7.2 16
UK311D1;H2311X UK311D1;HS2311 UK311D1;HA2311 UK311D1;HE2311XY	P311D1 P311D1 P311D1 P311D1	C(CM)-UKP311D1;H2311X C(CM)-UKP311SD1;HS2311 C(CM)-UKP311AD1;HA2311 C(CM)-UKP311ED1;HE2311XY	4 5/32	166 6 17/32	125 4 29/32	7.3 16	9.0 20
UK312D1;H2312X UK312D1;HS2312	P312D1 P312D1	C(CM)-UKP312D1;H2312X C(CM)-UKP312SD1;HS2312	4 5/32	179 7 1/16	135 5 5/16	9.3 21	11 24

## Pillow block unit, cast housing Adapter type



**Cast dust cover type**  
Open end **C-UKP...D1**  
Closed end **CM-UKP...D1**

Shaft dia.  mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )	Nominal dimensions										Bolt size  mm inch
		mm inch										
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	
60 2 3/16 2 1/4 2 3/8	UKP313D1;H2313X UKP313D1;HA2313 UKP313D1;HE2313X UKP313D1;HS2313X	90 3 35/64	340 13 3/8	260 10 1/4	90 3 17/32	25 3 1/32	38 1 1/2	33 1 5/16	176 6 15/16	105 4 1/8	65 2.559	M20 3/4
65 2 7/16 2 1/2	UKP315D1;H2315X UKP315D1;HA2315 UKP315D1;HE2315X	100 3 5/16	380 14 31/32	290 11 13/32	100 3 5/16	27 1 1/16	40 1 9/16	35 1 3/8	198 7 25/32	110 4 1 1/2	73 2.874	M22 7/8
70 2 11/16 2 3/4	UKP316D1;H2316X UKP316D1;HA2316 UKP316D1;HE2316X	106 4 1 1/4	400 15 3/4	300 11 13/16	110 4 1 1/2	27 1 1/16	40 1 9/16	40 1 9/16	210 8 9/32	110 4 1 1/2	78 3.071	M22 7/8
75 2 15/16 3	UKP317D1;H2317X UKP317D1;HA2317X UKP317D1;HE2317X	112 4 1 1/2	420 16 1 1/2	320 12 1 1/2	110 4 1 1/2	33 1 5/16	45 1 25/32	40 1 9/16	220 8 2 1/2	120 4 2 1/2	82 3.228	M27 1
80 3 3/16	UKP318D1;H2318X UKP318D1;HA2318X	118 4 4 1/4	430 16 15/16	330 13	110 4 1 1/2	33 1 5/16	45 1 25/32	45 1 25/32	235 9 1/4	120 4 2 1/2	86 3.386	M27 1
85 3 1/4	UKP319D1;H2319X UKP319D1;HE2319X	125 4 5 5/64	470 18 1/2	360 14 3/16	120 4 2 1/2	35 1 1 1/2	50 1 3 1/2	45 1 25/32	250 9 2 1/2	125 4 2 1/2	90 3.543	M30 1 1/8
90 3 7/16 3 1/2	UKP320D1;H2320X UKP320D1;HA2320 UKP320D1;HE2320X	140 5 23/64	490 19 9/32	380 14 3 1/2	120 4 2 1/2	36 1 1 1/2	50 1 3 1/2	50 1 3 1/2	275 10 1 1/2	130 5 1/8	97 3.819	M30 1 1/8
100	UKP322D1;H2322X	150	520	400	140	40	55	55	300	135	105	M33
110	UKP324D1;H2324X	160	570	450	140	40	55	65	320	140	112	M33
115	UKP326D1;H2326	180	600	480	140	40	55	75	355	140	121	M33
125	UKP328D1;H2328	200	620	500	140	40	55	75	390	140	131	M33


Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			t max.	H <sub>3</sub>	A <sub>5</sub>	UKP	C(CM)
UK313D1;H2313X UK313D1;HA2313 UK313D1;HE2313X UK313D1;HS2313X	P313D1 P313D1 P313D1 P313D1	C(CM)-UKP313D1;H2313X C(CM)-UKP313AD1;HA2313 C(CM)-UKP313ED1;HE2313X C(CM)-UKP313SD1;HS2313X	4 5/32	190 7 15/32	140 5 1/2	10 22	12 26
UK315D1;H2315X UK315D1;HA2315 UK315D1;HE2315X	P315D1 P315D1 P315D1	C(CM)-UKP315D1;H2315X C(CM)-UKP315AD1;HA2315 C(CM)-UKP315ED1;HE2315X	4 5/32	210 8 3/32	150 5 29/32	14 31	18 40
UK316D1;H2316X UK316D1;HA2316 UK316D1;HE2316X	P316D1 P316D1 P316D1	C(CM)-UKP316D1;H2316X C(CM)-UKP316AD1;HA2316 C(CM)-UKP316ED1;HE2316X	4 5/32	221 8 1 1/16	155 6 3/32	17 37	21 46
UK317D1;H2317X UK317D1;HA2317X UK317D1;HE2317X	P317D1 P317D1 P317D1	C(CM)-UKP317D1;H2317X C(CM)-UKP317AD1;HA2317X C(CM)-UKP317ED1;HE2317X	5 1 3/64	235 9 1/4	170 6 1 1/16	19 42	24 53
UK318D1;H2318X UK318D1;HA2318X	P318D1 P318D1	C(CM)-UKP318D1;H2318X C(CM)-UKP318AD1;HA2318X	5 1 3/64	246 9 1 1/16	170 6 1 1/16	22 49	28 62
UK319D1;H2319X UK319D1;HE2319X	P319D1 P319D1	C(CM)-UKP319D1;H2319X C(CM)-UKP319ED1;HE2319X	5 1 3/64	258 10 5/32	180 7 3/32	27 60	33 73
UK320D1;H2320X UK320D1;HA2320 UK320D1;HE2320X	P320D1 P320D1 P320D1	C(CM)-UKP320D1;H2320X C(CM)-UKP320AD1;HA2320 C(CM)-UKP320ED1;HE2320X	5 1 3/64	283 11 5/32	190 7 15/32	33 73	40 88
UK322D1;H2322X	P322D1	C(CM)-UKP322D1;H2322X	5	313	200	43	53
UK324D1;H2324X	P324D1	C(CM)-UKP324D1;H2324X	5	335	215	50	67
UK326D1;H2326	P326D1	C(CM)-UKP326D1;H2326	6	375	225	69	86
UK328D1;H2328	P328D1	C(CM)-UKP328D1;H2328	6	407	235	84	101

## Pillow block unit, cast housing Adapter type



**Cast dust cover type**  
Open end **C-UKP...D1**  
Closed end **CM-UKP...D1**


Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )( <sup>3</sup> )	Nominal dimensions										Bolt size mm inch
		mm inch										
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	
20 ¾	<b>UKPX05D1;H2305X</b> <b>UKPX05D1;HE2305</b>	44.4 1¾	159 6¼	119 4 <sup>11</sup> / <sub>16</sub>	51 2	17 2 <sup>1</sup> / <sub>32</sub>	20 2 <sup>5</sup> / <sub>32</sub>	18 2 <sup>9</sup> / <sub>32</sub>	85 3 <sup>1</sup> / <sub>32</sub>	50 1 <sup>31</sup> / <sub>32</sub>	35 1.378	M14 ½
25 7/8 1	<b>UKPX06D1;H2306X</b> <b>UKPX06D1;HS2306</b> <b>UKPX06D1;HE2306X</b>	47.6 1 <sup>7</sup> / <sub>8</sub>	175 6 <sup>7</sup> / <sub>8</sub>	127 5	57 2 <sup>1</sup> / <sub>4</sub>	17 2 <sup>1</sup> / <sub>32</sub>	20 2 <sup>5</sup> / <sub>32</sub>	20 2 <sup>5</sup> / <sub>32</sub>	93 3 <sup>21</sup> / <sub>32</sub>	54 2 <sup>1</sup> / <sub>6</sub>	38 1.496	M14 ½
30 1 <sup>1</sup> / <sub>8</sub>	<b>UKPX07D1;H2307X</b> <b>UKPX07D1;HS2307</b>	54 2 <sup>1</sup> / <sub>8</sub>	203 8	144 5 <sup>21</sup> / <sub>32</sub>	57 2 <sup>1</sup> / <sub>4</sub>	17 2 <sup>1</sup> / <sub>32</sub>	20 2 <sup>5</sup> / <sub>32</sub>	21 1 <sup>9</sup> / <sub>16</sub>	105 4 <sup>1</sup> / <sub>8</sub>	60 2 <sup>3</sup> / <sub>8</sub>	43 1.693	M14 ½
35 1 <sup>1</sup> / <sub>4</sub> 1 <sup>3</sup> / <sub>8</sub>	<b>UKPX08D1;H2308X</b> <b>UKPX08D1;HE2308X</b> <b>UKPX08D1;HS2308X</b>	58.7 2 <sup>5</sup> / <sub>16</sub>	222 8 <sup>3</sup> / <sub>4</sub>	156 6 <sup>5</sup> / <sub>32</sub>	67 2 <sup>5</sup> / <sub>8</sub>	20 2 <sup>5</sup> / <sub>32</sub>	23 2 <sup>9</sup> / <sub>32</sub>	26 1 <sup>1</sup> / <sub>32</sub>	111 4 <sup>3</sup> / <sub>8</sub>	65 2 <sup>9</sup> / <sub>16</sub>	46 1.811	M16 5/8
40 1 <sup>7</sup> / <sub>16</sub> 1 <sup>1</sup> / <sub>2</sub> 1 <sup>5</sup> / <sub>8</sub>	<b>UKPX09D1;H2309X</b> <b>UKPX09D1;HA2309</b> <b>UKPX09D1;HE2309X</b> <b>UKPX09D1;HS2309X</b>	58.7 2 <sup>5</sup> / <sub>16</sub>	222 8 <sup>3</sup> / <sub>4</sub>	156 6 <sup>5</sup> / <sub>32</sub>	67 2 <sup>5</sup> / <sub>8</sub>	20 2 <sup>5</sup> / <sub>32</sub>	23 2 <sup>9</sup> / <sub>32</sub>	26 1 <sup>1</sup> / <sub>32</sub>	116 4 <sup>9</sup> / <sub>16</sub>	65 2 <sup>9</sup> / <sub>16</sub>	50 1.969	M16 5/8
45 1 <sup>5</sup> / <sub>8</sub> 1 <sup>11</sup> / <sub>16</sub> 1 <sup>3</sup> / <sub>4</sub>	<b>UKPX10D1;H2310X</b> <b>UKPX10D1;HS2310</b> <b>UKPX10D1;HA2310</b> <b>UKPX10D1;HE2310X</b>	63.5 2 <sup>1</sup> / <sub>2</sub>	241 9 <sup>1</sup> / <sub>2</sub>	171 6 <sup>29</sup> / <sub>32</sub>	73 2 <sup>7</sup> / <sub>8</sub>	20 2 <sup>5</sup> / <sub>32</sub>	23 2 <sup>9</sup> / <sub>32</sub>	27 1 <sup>1</sup> / <sub>16</sub>	126 4 <sup>31</sup> / <sub>32</sub>	70 2 <sup>3</sup> / <sub>4</sub>	55 2.165	M16 5/8
50 1 <sup>7</sup> / <sub>8</sub> 1 <sup>15</sup> / <sub>16</sub> 2	<b>UKPX11D1;H2311X</b> <b>UKPX11D1;HS2311</b> <b>UKPX11D1;HA2311</b> <b>UKPX11D1;HE2311XY</b>	69.8 2 <sup>3</sup> / <sub>4</sub>	260 10 <sup>1</sup> / <sub>4</sub>	184 7 <sup>1</sup> / <sub>4</sub>	79 3 <sup>1</sup> / <sub>8</sub>	25 3 <sup>1</sup> / <sub>32</sub>	28 1 <sup>3</sup> / <sub>32</sub>	30 1 <sup>3</sup> / <sub>16</sub>	137 5 <sup>15</sup> / <sub>32</sub>	75 2 <sup>15</sup> / <sub>16</sub>	59 2.323	M20 ¾
55 2 <sup>1</sup> / <sub>8</sub>	<b>UKPX12D1;H2312X</b> <b>UKPX12D1;HS2312</b>	76.2 3	286 11 <sup>1</sup> / <sub>4</sub>	203 8	83 3 <sup>3</sup> / <sub>32</sub>	25 3 <sup>1</sup> / <sub>32</sub>	28 1 <sup>3</sup> / <sub>32</sub>	33 1 <sup>5</sup> / <sub>16</sub>	151 5 <sup>15</sup> / <sub>16</sub>	80 3 <sup>5</sup> / <sub>32</sub>	62 2.441	M20 ¾

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.  
To distinguish it, a suffix "Y" is added.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			t max.	H <sub>5</sub>	A <sub>5</sub>	UKP	C(CM)
UKX05D1;H2305X UKX05D1;HE2305	PX05D1 PX05D1	<b>C(CM)-UKPX05D1;H2305X</b> <b>C(CM)-UKPX05ED1;HE2305</b>	2 5/64	89 3 <sup>1</sup> / <sub>2</sub>	75 2 <sup>15</sup> / <sub>16</sub>	1.4 3.1	1.8 4.0
UKX06D1;H2306X UKX06D1;HS2306 UKX06D1;HE2306X	PX06D1 PX06D1 PX06D1	<b>C(CM)-UKPX06D1;H2306X</b> <b>C(CM)-UKPX06SD1;HS2306</b> <b>C(CM)-UKPX06ED1;HE2306X</b>	2 5/64	99 3 <sup>29</sup> / <sub>32</sub>	80 3 <sup>5</sup> / <sub>32</sub>	1.7 3.7	2.2 4.9
UKX07D1;H2307X UKX07D1;HS2307	PX07D1 PX07D1	<b>C(CM)-UKPX07D1;H2307X</b> <b>C(CM)-UKPX07SD1;HS2307</b>	3 1/8	110 4 <sup>11</sup> / <sub>32</sub>	90 3 <sup>17</sup> / <sub>32</sub>	2.5 5.5	3.3 7.3
UKX08D1;H2308X UKX08D1;HE2308X UKX08D1;HS2308X	PX08D1 PX08D1 PX08D1	<b>C(CM)-UKPX08D1;H2308X</b> <b>C(CM)-UKPX08ED1;HE2308X</b> <b>C(CM)-UKPX08SD1;HS2308X</b>	3 1/8	118 4 <sup>41</sup> / <sub>64</sub>	95 3 <sup>3</sup> / <sub>4</sub>	3.2 7.1	4.1 9.0
UKX09D1;H2309X UKX09D1;HA2309 UKX09D1;HE2309X UKX09D1;HS2309X	PX09D1 PX09D1 PX09D1 PX09D1	<b>C(CM)-UKPX09D1;H2309X</b> <b>C(CM)-UKPX09AD1;HA2309</b> <b>C(CM)-UKPX09ED1;HE2309X</b> <b>C(CM)-UKPX09SD1;HS2309X</b>	3 1/8	120 4 <sup>23</sup> / <sub>32</sub>	100 3 <sup>15</sup> / <sub>16</sub>	3.3 7.3	4.3 9.5
UKX10D1;H2310X UKX10D1;HS2310 UKX10D1;HA2310 UKX10D1;HE2310X	PX10D1 PX10D1 PX10D1 PX10D1	<b>C(CM)-UKPX10D1;H2310X</b> <b>C(CM)-UKPX10SD1;HS2310</b> <b>C(CM)-UKPX10AD1;HA2310</b> <b>C(CM)-UKPX10ED1;HE2310X</b>	3 1/8	130 5 <sup>1</sup> / <sub>8</sub>	100 3 <sup>15</sup> / <sub>16</sub>	4.2 9.3	5.4 12
UKX11D1;H2311X UKX11D1;HS2311 UKX11D1;HA2311 UKX11D1;HE2311XY	PX11D1 PX11D1 PX11D1 PX11D1	<b>C(CM)-UKPX11D1;H2311X</b> <b>C(CM)-UKPX11SD1;HS2311</b> <b>C(CM)-UKPX11AD1;HA2311</b> <b>C(CM)-UKPX11ED1;HE2311XY</b>	4 5/32	144 5 <sup>21</sup> / <sub>32</sub>	115 4 <sup>17</sup> / <sub>32</sub>	5.3 12	6.8 15
UKX12D1;H2312X UKX12D1;HS2312	PX12D1 PX12D1	<b>C(CM)-UKPX12D1;H2312X</b> <b>C(CM)-UKPX12SD1;HS2312</b>	4 5/32	155 6 <sup>3</sup> / <sub>32</sub>	120 4 <sup>23</sup> / <sub>32</sub>	6.8 15	8.6 19

## Pillow block unit, cast housing Adapter type



Cast dust cover type  
Open end C-UKP...D1  
Closed end CM-UKP...D1

Shaft dia.  mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions										Bolt size  mm inch
		mm inch										
		H	L	J	A	N	N <sub>1</sub>	H <sub>1</sub>	H <sub>2</sub>	L <sub>1</sub>	B <sub>1</sub>	
60 2 3/16 2 1/4 2 3/8	UKPX13D1;H2313X UKPX13D1;HA2313 UKPX13D1;HE2313X UKPX13D1;HS2313X	76.2	286	203	83	25	28	33	154	80	65	M20
		3	11 1/4	8	3 3/32	3 1/32	1 3/32	1 5/16	6 1/16	3 5/32	2.559	3/4
65 2 7/16 2 1/2	UKPX15D1;H2315X UKPX15D1;HA2315 UKPX15D1;HE2315X	88.9	330	229	89	27	30	35	175	95	73	M22
		3 1/2	13	9 1/32	3 1/2	1 1/16	1 3/16	1 3/8	6 7/8	3 3/4	2.874	7/8
70 2 11/16 2 3/4	UKPX16D1;H2316X UKPX16D1;HA2316 UKPX16D1;HE2316X	101.6	381	283	102	27	30	40	194	110	78	M22
		4	15	11 5/32	4 1/32	1 1/16	1 3/16	1 9/16	7 5/8	4 11/32	3.071	7/8
75 2 15/16 3	UKPX17D1;H2317X UKPX17D1;HA2317X UKPX17D1;HE2317X	101.6	381	283	102	27	30	40	200	110	82	M22
		4	15	11 5/32	4 1/32	1 1/16	1 3/16	1 9/16	7 7/8	4 11/32	3.228	7/8
80 3 3/16	UKPX18D1;H2318X UKPX18D1;HA2318X	101.6	381	283	111	27	30	40	206	110	86	M22
		4	15	11 5/32	4 3/8	1 1/16	1 3/16	1 9/16	8 1/8	4 11/32	3.386	7/8
90	UKPX20D1;H2320X	127	432	337	121	33	36	45	244	125	97	M27

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.


In this case the lock washer with the straight inner prong should be used.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			t max.	H <sub>5</sub>	A <sub>5</sub>	UKP	C(CM)
UKX13D1;H2313X UKX13D1;HA2313 UKX13D1;HE2313X UKX13D1;HS2313X	PX13D1 PX13D1 PX13D1 PX13D1	C(CM)-UKPX13D1;H2313X C(CM)-UKPX13AD1;HA2313 C(CM)-UKPX13ED1;HE2313X C(CM)-UKPX13SD1;HS2313X	4 5/32	159 6 1/4	135 5 5/16	6.9 15	9.2 20
UKX15D1;H2315X UKX15D1;HA2315 UKX15D1;HE2315X	PX15D1 PX15D1 PX15D1	C(CM)-UKPX15D1;H2315X C(CM)-UKPX15AD1;HA2315 C(CM)-UKPX15ED1;HE2315X	4 5/32	181 7 1/8	145 5 23/32	10 22	13 29
UKX16D1;H2316X UKX16D1;HA2316 UKX16D1;HE2316X	PX16D1 PX16D1 PX16D1	C(CM)-UKPX16D1;H2316X C(CM)-UKPX16AD1;HA2316 C(CM)-UKPX16ED1;HE2316X	4 5/32	198 7 25/32	155 6 3/32	14 31	17 37
UKX17D1;H2317X UKX17D1;HA2317X UKX17D1;HE2317X	PX17D1 PX17D1 PX17D1	C(CM)-UKPX17D1;H2317X C(CM)-UKPX17AD1;HA2317X C(CM)-UKPX17ED1;HE2317X	5 13/64	204 8 1/32	165 6 1/2	15 33	18 40
UKX18D1;H2318X UKX18D1;HA2318X	PX18D1 PX18D1	C(CM)-UKPX18D1;H2318X C(CM)-UKPX18AD1;HA2318	5 13/64	208 8 3/16	180 7 3/32	16 35	20 44
UKX20D1;H2320X	PX20D1	C(CM)-UKPX20D1;H2320X	5	244	195	24	28



## Square flanged unit, cast housing Adapter type



Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>(2)</sup> )	Nominal dimensions									Bolt size mm inch	Bearing number
		mm inch										
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B <sub>1</sub>	F min.		
20 3/4	UKF205D1;H2305X	95	70	16	13	27	12	35.5	35	30	M10	UK205D1;H2305X
	UKF205D1;HE2305	3 3/4	2 3/4	5/8	1/2	1 1/16	15/32	1 25/64	1.378	1 3/16	3/8	UK205D1;HE2305
25 7/8 1	UKF206D1;H2306X	108	83	18	13	31	12	39	38	36	M10	UK206D1;H2306X
	UKF206D1;HS2306	4 1/4	3 17/64	45/64	1/2	1 7/32	15/32	1 17/32	1.496	1 13/32	3/8	UK206D1;HS2306
30 1 1/8	UKF207D1;H2307X	117	92	19	15	34	14	42.5	43	40	M12	UK207D1;H2307X
	UKF207D1;HS2307	4 19/32	3 5/8	3/4	19/32	1 11/32	35/64	1 43/64	1.693	1 9/16	7/16	UK207D1;HS2307
35 1 1/4 1 3/8	UKF208D1;H2308X	130	102	21	15	36	16	46.5	46	46	M14	UK208D1;H2308X
	UKF208D1;HE2308X	5 1/8	4 1/64	53/64	19/32	1 13/32	5/8	1 53/64	1.811	1 13/16	1/2	UK208D1;HE2308X
40 1 7/16 1 1/2 1 5/8	UKF209D1;H2309X	137	105	22	16	38	16	48.5	50	52	M14	UK209D1;H2309X
	UKF209D1;HA2309	5 13/32	4 9/64	55/64	5/8	1 1/2	5/8	1 29/32	1.969	2 1/16	1/2	UK209D1;HA2309
45 1 5/8 1 11/16 1 3/4	UKF210D1;H2310X	143	111	22	16	40	16	50	55	57	M14	UK210D1;H2310X
	UKF210D1;HS2310	5 5/8	4 3/8	55/64	5/8	1 9/16	5/8	1 31/32	2.165	2 1/4	1/2	UK210D1;HS2310
50 1 7/8 1 15/16 2	UKF211D1;H2311X	162	130	25	18	43	19	54.5	59	64	M16	UK211D1;H2311X
	UKF211D1;HA2311	6 3/8	5 1/8	63/64	23/32	1 11/16	3/4	2 9/64	2.323	2 7/32	5/8	UK211D1;HA2311
55 2 1/8	UKF212D1;H2312X	175	143	29	18	48	19	61	62	69	M16	UK212D1;H2312X
	UKF212D1;HS2312	6 7/8	5 5/8	1 9/64	23/32	1 7/8	3/4	2 13/32	2.441	2 23/32	5/8	UK212D1;HS2312

- Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
 In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.  
 To distinguish it, a suffix "Y" is added.  
<sup>(4)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
 Example: ZM-UKF205D1;HE2305

Remarks Please refer to page A21 for size of grease fitting.

B260

## Pressed steel dust cover type

Open end Z-UKF...D1  
 Closed end ZM-UKF...D1

## Cast dust cover type

Open end C-UKF...D1  
 Closed end CM-UKF...D1

Housing number	Unit number <sup>(4)</sup> pressed steel dust cover type	Unit number <sup>(4)</sup> cast dust cover type	Nominal dimensions			Mass of unit		
			mm inch			kg lb		
			t max.	A <sub>4</sub>	A <sub>5</sub>	UKF	Z(ZM)	C(CM)
F205D1	Z(ZM)-UKF205D1;H2305X	C(CM)-UKF205D1;H2305X	2	40	51	0.8	0.8	1.0
	Z(ZM)-UKF205ED1;HE2305	C(CM)-UKF205ED1;HE2305	5/64	1 19/32	2	1.8	1.8	2.2
F206D1	Z(ZM)-UKF206D1;H2306X	C(CM)-UKF206D1;H2306X	2	45	56	1.1	1.1	1.3
	Z(ZM)-UKF206SD1;HS2306	C(CM)-UKF206SD1;HS2306	5/64	1 3/4	2 7/32	2.4	2.4	2.9
F207D1	Z(ZM)-UKF207D1;H2307X	C(CM)-UKF207D1;H2307X	3	49	59	1.6	1.6	1.9
	Z(ZM)-UKF207SD1;HS2307	C(CM)-UKF207SD1;HS2307	1/8	1 15/16	2 5/16	3.5	3.5	4.2
F208D1	Z(ZM)-UKF208D1;H2308X	C(CM)-UKF208D1;H2308X	3	56	66	1.8	1.9	2.4
	Z(ZM)-UKF208ED1;HE2308X	C(CM)-UKF208ED1;HE2308X	1/8	2 3/16	2 19/32	4.0	4.2	5.3
F209D1	Z(ZM)-UKF209D1;H2309X	C(CM)-UKF209D1;H2309X	3	57	70	2.3	2.3	2.8
	Z(ZM)-UKF209AD1;HA2309	C(CM)-UKF209AD1;HA2309	1/8	2 1/4	2 3/4	5.1	5.1	6.2
F210D1	Z(ZM)-UKF210D1;H2310X	C(CM)-UKF210D1;H2310X	3	60	72	2.6	2.7	3.2
	Z(ZM)-UKF210SD1;HS2310	C(CM)-UKF210SD1;HS2310	1/8	2 3/8	2 27/32	5.7	6.0	7.1
F211D1	Z(ZM)-UKF211D1;H2311X	C(CM)-UKF211D1;H2311X	4	64	75	3.5	3.6	4.3
	Z(ZM)-UKF211SD1;HS2311	C(CM)-UKF211SD1;HS2311	5/32	2 1/2	2 15/16	7.7	7.9	9.5
F212D1	Z(ZM)-UKF212D1;H2312X	C(CM)-UKF212D1;H2312X	4	74	86	4.0	4.2	5.0
	Z(ZM)-UKF212SD1;HS2312	C(CM)-UKF212SD1;HS2312	5/32	2 29/32	3 3/8	8.8	9.3	11

B261

## Square flanged unit, cast housing Adapter type



Shaft dia.  mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )	Nominal dimensions									Bolt size  mm inch	Bearing number
		mm inch										
		L	J	A <sub>2</sub>	A <sub>1</sub>	A	N	A <sub>0</sub>	B <sub>1</sub>	F min.		
60 2 3/16 2 1/4 2 3/8	UKF213D1;H2313X UKF213D1;HA2313 UKF213D1;HE2313X UKF213D1;HS2313X	187 7 3/8	149 5 5/64	30 1 3/16	22 7/8	50 1 31/32	19 3/4	64 2 33/64	65 2.559	74 2 29/32	M16 5/8	UK213D1;H2313X UK213D1;HA2313 UK213D1;HE2313X UK213D1;HS2313X
65 2 7/16 2 1/2	UKF215D1;H2315X UKF215D1;HA2315 UKF215D1;HE2315X	200 7 7/8	159 6 17/64	34 1 11/32	22 7/8	56 2 7/32	19 3/4	71 2 51/64	73 2.874	84 3 5/16	M16 5/8	UK215D1;H2315X UK215D1;HA2315 UK215D1;HE2315X
70 2 11/16 2 3/4	UKF216D1;H2316X UKF216D1;HA2316 UKF216D1;HE2316X	208 8 3/16	165 6 1/2	34 1 11/32	22 7/8	58 2 9/32	23 29/32	73.5 2 57/64	78 3.071	90 3 17/32	M20 3/4	UK216D1;H2316X UK216D1;HA2316 UK216D1;HE2316X
75 2 15/16 3	UKF217D1;H2317X UKF217D1;HA2317X UKF217D1;HE2317X	220 8 21/32	175 6 57/64	36 1 27/64	24 1 5/16	63 2 15/32	23 29/32	77 3 1/32	82 3.228	95 3 3/4	M20 3/4	UK217D1;H2317X UK217D1;HA2317X UK217D1;HE2317X
80 3 3/16	UKF218D1;H2318X UKF218D1;HA2318X	235 9 1/4	187 7 23/64	40 1 37/64	24 1 5/16	68 2 11/16	23 29/32	81.5 3 13/64	86 3.386	102 4 1/32	M20 3/4	UK218D1;H2318X UK218D1;HA2318X

**Notes** <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
 In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
 Example: ZM-UKF205D1;HE2305

**Remarks** Please refer to page A21 for size of grease fitting.



## Pressed steel dust cover type


Open end **Z-UKF...D1**  
 Closed end **ZM-UKF...D1**

## Cast dust cover type

Open end **C-UKF...D1**  
 Closed end **CM-UKF...D1**

Housing number	Unit number <sup>(2)</sup> pressed steel dust cover type	Unit number <sup>(2)</sup> cast dust cover type	Nominal dimensions			Mass of unit		
			mm inch			kg lb		
			t max.	A <sub>4</sub>	A <sub>5</sub>	UKF	Z(ZM)	C(CM)
F213D1 F213D1 F213D1 F213D1	Z(ZM)-UKF213D1;H2313X Z(ZM)-UKF213AD1;HA2313 Z(ZM)-UKF213ED1;HE2313X Z(ZM)-UKF213SD1;HS2313X	C(CM)-UKF213D1;H2313X C(CM)-UKF213AD1;HA2313 C(CM)-UKF213ED1;HE2313X C(CM)-UKF213SD1;HS2313X	4 5/32	76 3	90 3 17/32	5.6 12	5.8 13	6.7 15
F215D1 F215D1 F215D1	— — —	C(CM)-UKF215D1;H2315X C(CM)-UKF215AD1;HA2315 C(CM)-UKF215ED1;HE2315X	4 5/32	— —	102 4 1/32	6.8 15	— —	8.3 18
F216D1 F216D1 F216D1	— — —	C(CM)-UKF216D1;H2316X C(CM)-UKF216AD1;HA2316 C(CM)-UKF216ED1;HE2316X	4 5/32	— —	106 4 3/16	8.3 18	— —	10 22
F217D1 F217D1 F217D1	— — —	C(CM)-UKF217D1;H2317X C(CM)-UKF217AD1;HA2317X C(CM)-UKF217ED1;HE2317X	5 13/64	— —	114 4 1/2	10 22	— —	13 29
F218D1 F218D1	— —	C(CM)-UKF218D1;H2318X C(CM)-UKF218AD1;HA2318X	5 13/64	— —	122 4 13/16	12 26	— —	14 31

## Square flanged unit, cast housing Adapter type



**Cast dust cover type**  
Open end **C-UKF...D1**  
Closed end **CM-UKF...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup> / <sub>(2)</sub> / <sub>(3)</sub>	Nominal dimensions								Bolt size mm inch
		mm inch								
		<i>L</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>1</sub>	<i>A</i>	<i>N</i>	<i>A</i> <sub>0</sub>	<i>B</i> <sub>1</sub>	
20 3/4	UKF305D1;H2305X UKF305D1;HE2305	110 4 11/32	80 3 5/32	16 5/8	13 1/2	29 1 5/32	16 5/8	37 1 29/64	35 1.378	M14 1/2
25 7/8 1	UKF306D1;H2306X UKF306D1;HS2306 UKF306D1;HE2306X	125 4 29/32	95 3 47/64	18 45/64	15 19/32	32 1 1/4	16 5/8	40.5 1 19/32	38 1.496	M14 1/2
30 1 1/8	UKF307D1;H2307X UKF307D1;HS2307	135 5 5/16	100 3 15/16	20 25/32	16 5/8	36 1 13/32	19 3/4	45.5 1 51/64	43 1.693	M16 5/8
35 1 1/4 1 3/8	UKF308D1;H2308X UKF308D1;HE2308X UKF308D1;HS2308X	150 5 29/32	112 4 13/32	23 29/32	17 21/32	40 1 9/16	19 3/4	50 1 31/32	46 1.811	M16 5/8
40 1 7/16 1 1/2 1 5/8	UKF309D1;H2309X UKF309D1;HA2309 UKF309D1;HE2309X UKF309D1;HS2309X	160 6 5/16	125 4 59/64	25 63/64	18 23/32	44 1 23/32	19 3/4	54.5 2 9/64	50 1.969	M16 5/8
45 1 5/8 1 11/16 1 3/4	UKF310D1;H2310X UKF310D1;HS2310 UKF310D1;HA2310 UKF310D1;HE2310X	175 6 7/8	132 5 13/64	28 1 7/64	19 3/4	48 1 7/8	23 29/32	60.5 2 3/8	55 2.165	M20 3/4
50 1 7/8 1 15/16 2	UKF311D1;H2311X UKF311D1;HS2311 UKF311D1;HA2311 UKF311D1;HE2311XY	185 7 9/32	140 5 33/64	30 1 3/16	20 25/32	52 2 1/16	23 29/32	64 2 33/64	59 2.323	M20 3/4
55 2 1/8	UKF312D1;H2312X UKF312D1;HS2312	195 7 11/16	150 5 29/32	33 1 19/64	22 7/8	56 2 7/32	23 29/32	69.5 2 47/64	62 2.441	M20 3/4

- Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
 In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.  
 To distinguish it, a suffix "Y" is added.  
<sup>(4)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
 Example: CM-UKF305D1;HE2305


Remarks Please refer to page A21 for size of grease fitting.

B264

Bearing number	Housing number	Unit number <sup>(4)</sup> cast dust cover type	Nominal dimensions		Mass of unit	
			mm inch		kg lb	
			<i>t</i> max.	<i>A</i> <sub>5</sub>	UKF	C(CM)
UK305D1;H2305X UK305D1;HE2305	F305D1 F305D1	C(CM)-UKF305D1;H2305X C(CM)-UKF305ED1;HE2305	2 5/64	56 2 7/32	1.1 2.4	1.5 3.3
UK306D1;H2306X UK306D1;HS2306 UK306D1;HE2306X	F306D1 F306D1 F306D1	C(CM)-UKF306D1;H2306X C(CM)-UKF306SD1;HS2306 C(CM)-UKF306ED1;HE2306X	2 5/64	60 2 3/8	1.7 3.7	2.1 4.6
UK307D1;H2307X UK307D1;HS2307	F307D1 F307D1	C(CM)-UKF307D1;H2307X C(CM)-UKF307SD1;HS2307	3 1/8	68 2 11/16	2.1 4.6	2.7 6.0
UK308D1;H2308X UK308D1;HE2308X UK308D1;HS2308X	F308D1 F308D1 F308D1	C(CM)-UKF308D1;H2308X C(CM)-UKF308ED1;HE2308X C(CM)-UKF308SD1;HS2308X	3 1/8	76 3	2.8 6.2	3.5 7.7
UK309D1;H2309X UK309D1;HA2309 UK309D1;HE2309X UK309D1;HS2309X	F309D1 F309D1 F309D1 F309D1	C(CM)-UKF309D1;H2309X C(CM)-UKF309AD1;HA2309 C(CM)-UKF309ED1;HE2309X C(CM)-UKF309SD1;HS2309X	3 1/8	80 3 5/32	3.4 7.5	4.4 9.7
UK310D1;H2310X UK310D1;HS2310 UK310D1;HA2310 UK310D1;HE2310X	F310D1 F310D1 F310D1 F310D1	C(CM)-UKF310D1;H2310X C(CM)-UKF310SD1;HS2310 C(CM)-UKF310AD1;HA2310 C(CM)-UKF310ED1;HE2310X	3 1/8	88 3 15/32	4.5 9.9	5.9 13
UK311D1;H2311X UK311D1;HS2311 UK311D1;HA2311 UK311D1;HE2311XY	F311D1 F311D1 F311D1 F311D1	C(CM)-UKF311D1;H2311X C(CM)-UKF311SD1;HS2311 C(CM)-UKF311AD1;HA2311 C(CM)-UKF311ED1;HE2311XY	4 5/32	92 3 5/8	5.3 12	6.8 15
UK312D1;H2312X UK312D1;HS2312	F312D1 F312D1	C(CM)-UKF312D1;H2312X C(CM)-UKF312SD1;HS2312	4 5/32	100 3 15/16	6.3 14	7.9 17

B265

## Squire flanged unit, cast housing Adapter type



Cast dust cover type  
Open end **C-UKF...D1**  
Closed end **CM-UKF...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )	Nominal dimensions								Bolt size mm inch
		mm inch								
		<i>L</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>1</sub>	<i>A</i>	<i>N</i>	<i>A</i> <sub>0</sub>	<i>B</i> <sub>1</sub>	
60 2 3/16 2 1/4 2 3/8	<b>UKF313D1;H2313X</b> <b>UKF313D1;HA2313</b> <b>UKF313D1;HE2313X</b> <b>UKF313D1;HS2313X</b>	208 8 3/16	166 6 17/32	33 1 19/64	22 7/8	58 2 9/32	23 29/32	71.5 2 13/16	65 2.559	M20 3/4
65 2 7/16 2 1/2	<b>UKF315D1;H2315X</b> <b>UKF315D1;HA2315</b> <b>UKF315D1;HE2315X</b>	236 9 9/32	184 7 1/4	39 1 17/32	25 3 1/32	66 2 19/32	25 69/64	81.5 3 13/64	73 2.874	M22 7/8
70 2 11/16 2 3/4	<b>UKF316D1;H2316X</b> <b>UKF316D1;HA2316</b> <b>UKF316D1;HE2316X</b>	250 9 27/32	196 7 23/32	38 1 1/2	27 1 1/16	68 2 11/16	31 1 7/32	84 3 5/16	78 3.071	M27 1
75 2 15/16 3	<b>UKF317D1;H2317X</b> <b>UKF317D1;HA2317X</b> <b>UKF317D1;HE2317X</b>	260 10 1/4	204 8 1/32	44 1 47/64	27 1 1/16	74 2 29/32	31 1 7/32	92 3 5/8	82 3.228	M27 1
80 3 13/16	<b>UKF318D1;H2318X</b> <b>UKF318D1;HA2318X</b>	280 11 1/32	216 8 1/2	44 1 47/64	30 1 3/16	76 3	35 1 3/8	94 3 45/64	86 3.386	M30 1 1/8
85 3 1/4	<b>UKF319D1;H2319X</b> <b>UKF319D1;HE2319X</b>	290 11 13/32	228 8 21/32	59 2 21/64	30 1 3/16	94 3 11/16	35 1 3/8	111.5 4 25/64	90 3.543	M30 1 1/8
90 3 7/16 3 1/2	<b>UKF320D1;H2320X</b> <b>UKF320D1;HA2320</b> <b>UKF320D1;HE2320X</b>	310 12 7/32	242 9 17/32	59 2 21/64	32 1 1/4	94 3 11/16	38 1 1/2	115.5 4 35/64	97 3.819	M33 1 1/4
100	<b>UKF322D1;H2322X</b>	340	266	60	35	96	41	121	105	M36
110	<b>UKF324D1;H2324</b>	370	290	65	40	110	41	130	112	M36
115	<b>UKF326D1;H2326</b>	410	320	65	45	115	41	133	121	M36
125	<b>UKF328D1;H2328</b>	450	350	75	55	125	41	146.5	131	M36

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".



<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.

<sup>(3)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
Example: CM-UKF305D1;HE2305

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number <sup>(3)</sup> cast dust cover type	Nominal dimensions		Mass of unit	
			<i>t</i> max.	<i>A</i> <sub>5</sub>	UKF	C(CM)
			mm	inch	kg	lb
UK313D1;H2313X UK313D1;HA2313 UK313D1;HE2313X UK313D1;HS2313X	F313D1 F313D1 F313D1 F313D1	<b>C(CM)-UKF313D1;H2313X</b> <b>C(CM)-UKF313AD1;HA2313</b> <b>C(CM)-UKF313ED1;HE2313X</b> <b>C(CM)-UKF313SD1;HS2313X</b>	4 5/32	103 4 1/16	7.8 17	9.6 21
UK315D1;H2315X UK315D1;HA2315 UK315D1;HE2315X	F315D1 F315D1 F315D1	<b>C(CM)-UKF315D1;H2315X</b> <b>C(CM)-UKF315AD1;HA2315</b> <b>C(CM)-UKF315ED1;HE2315X</b>	4 5/32	114 4 1/2	11 24	13 29
UK316D1;H2316X UK316D1;HA2316 UK316D1;HE2316X	F316D1 F316D1 F316D1	<b>C(CM)-UKF316D1;H2316X</b> <b>C(CM)-UKF316AD1;HA2316</b> <b>C(CM)-UKF316ED1;HE2316X</b>	4 5/32	116 4 9/16	14 31	16 35
UK317D1;H2317X UK317D1;HA2317X UK317D1;HE2317X	F317D1 F317D1 F317D1	<b>C(CM)-UKF317D1;H2317X</b> <b>C(CM)-UKF317AD1;HA2317X</b> <b>C(CM)-UKF317ED1;HE2317X</b>	5 13/64	129 5 3/32	15 33	19 42
UK318D1;H2318X UK318D1;HA2318X	F318D1 F318D1	<b>C(CM)-UKF318D1;H2318X</b> <b>C(CM)-UKF318AD1;HA2318X</b>	5 13/64	129 5 3/32	19 42	23 51
UK319D1;H2319X UK319D1;HE2319X	F319D1 F319D1	<b>C(CM)-UKF319D1;H2319X</b> <b>C(CM)-UKF319ED1;HE2319X</b>	5 13/64	149 5 7/8	22 49	26 57
UK320D1;H2320X UK320D1;HA2320 UK320D1;HE2320X	F320D1 F320D1 F320D1	<b>C(CM)-UKF320D1;H2320X</b> <b>C(CM)-UKF320AD1;HA2320</b> <b>C(CM)-UKF320ED1;HE2320X</b>	5 13/64	154 6 1/16	27 60	32 71
UK322D1;H2322X	F322D1	<b>C(CM)-UKF322D1;H2322X</b>	5	160	35	41
UK324D1;H2324	F324D1	<b>C(CM)-UKF324D1;H2324</b>	5	172	48	56
UK326D1;H2326	F326D1	<b>C(CM)-UKF326D1;H2326</b>	6	178	63	75
UK328D1;H2328	F328D1	<b>C(CM)-UKF328D1;H2328</b>	6	192	90	101

## Square flanged unit, cast housing Adapter type



**Cast dust cover type**  
Open end **C-UKF...D1**  
Closed end **CM-UKF...D1**


Shaft dia. mm inch	Unit number <sup>(1)</sup> / <sub>(2)</sub> / <sub>(3)</sub>	Nominal dimensions									Bolt size mm inch
		<i>L</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>1</sub>	<i>A</i>	<i>N</i>	<i>A</i> <sub>0</sub>	<i>B</i> <sub>1</sub>	<i>F</i> min.	
20 3/4	UKFX05D1;H2305X	108	83	18	13	30	12	39	35	-	M10
	UKFX05D1;HE2305	4 1/4	3 17/64	45/64	1/2	1 3/16	15/32	1 17/32	1.378	-	3/8
25 7/8 1	UKFX06D1;H2306X	117	92	19	14	34	16	41.5	38	-	M14
	UKFX06D1;HS2306 UKFX06D1;HE2306X	4 19/32	3 5/8	3/4	9/16	1 11/32	5/8	1 41/64	1.496	-	1/2
30 1 1/8	UKFX07D1;H2307X	130	102	21	14	38	16	45.5	43	-	M14
	UKFX07D1;HS2307	5 1/8	4 1/4	53/64	9/16	1 1/2	5/8	1 51/64	1.693	-	1/2
35 1 1/4 1 3/8	UKFX08D1;H2308X	137	105	22	14	40	19	47.5	46	46	M16
	UKFX08D1;HE2308X UKFX08D1;HS2308X	5 13/32	4 9/64	55/64	9/16	1 9/16	3/4	1 7/8	1.811	1 19/16	5/8
40 1 7/16 1 1/2 1 5/8	UKFX09D1;H2309X	143	111	23	14	40	19	50	50	52	M16
	UKFX09D1;HA2309 UKFX09D1;HE2309X UKFX09D1;HS2309X	5 5/8	4 3/8	29/32	9/16	1 9/16	3/4	1 31/32	1.969	2 1/16	5/8
45 1 5/8 1 11/16 1 3/4	UKFX10D1;H2310X	162	130	26	20	44	19	55.5	55	57	M16
	UKFX10D1;HS2310 UKFX10D1;HA2310 UKFX10D1;HE2310X	6 3/8	5 1/8	1 1/32	25/32	1 23/32	3/4	2 3/16	2.165	2 1/4	5/8
50 1 7/8 1 15/16 2	UKFX11D1;H2311X	175	143	29	20	49	19	60	59	64	M16
	UKFX11D1;HS2311 UKFX11D1;HA2311 UKFX11D1;HE2311XY	6 7/8	5 5/8	1 9/64	25/32	1 15/16	3/4	2 23/64	2.323	2 17/32	5/8
55 2 1/8	UKFX12D1;H2312X	187	149	34	21	59	19	67	62	-	M16
	UKFX12D1;HS2312	7 3/8	5 55/64	1 11/32	19/16	2 5/16	3/4	2 21/64	2.441	-	5/8

- Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve. In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve. To distinguish it, a suffix "Y" is added.  
<sup>(4)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included. Example: CM-UKFX05D1;HE2305

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number <sup>(4)</sup> cast dust cover type	Nominal dimensions		Mass of unit	
			<i>t</i> max.	<i>A</i> <sub>5</sub>	UKF	C(CM)
UKX05D1;H2305X UKX05D1;HE2305	FX05D1 FX05D1	C(CM)-UKFX05D1;H2305X	2	56	1.1	1.3
		C(CM)-UKFX05ED1;HE2305	5/64	2 7/32	2.4	2.9
UKX06D1;H2306X UKX06D1;HS2306 UKX06D1;HE2306X	FX06D1 FX06D1 FX06D1	C(CM)-UKFX06D1;H2306X	2	59	1.6	1.8
		C(CM)-UKFX06SD1;HS2306 C(CM)-UKFX06ED1;HE2306X	5/64	2 5/16	3.5	4.0
UKX07D1;H2307X UKX07D1;HS2307	FX07D1 FX07D1	C(CM)-UKFX07D1;H2307X	3	66	2.1	2.5
		C(CM)-UKFX07SD1;HS2307	1/8	2 19/32	4.6	5.5
UKX08D1;H2308X UKX08D1;HE2308X UKX08D1;HS2308X	FX08D1 FX08D1 FX08D1	C(CM)-UKFX08D1;H2308X	3	70	2.5	2.9
		C(CM)-UKFX08ED1;HE2308X C(CM)-UKFX08SD1;HS2308X	1/8	2 3/4	5.5	6.4
UKX09D1;H2309X UKX09D1;HA2309 UKX09D1;HE2309X UKX09D1;HS2309X	FX09D1 FX09D1 FX09D1 FX09D1	C(CM)-UKFX09D1;H2309X	3	73	2.5	3.0
		C(CM)-UKFX09AD1;HA2309 C(CM)-UKFX09ED1;HE2309X C(CM)-UKFX09SD1;HS2309X	1/8	2 7/8	5.5	6.6
UKX10D1;H2310X UKX10D1;HS2310 UKX10D1;HA2310 UKX10D1;HE2310X	FX10D1 FX10D1 FX10D1 FX10D1	C(CM)-UKFX10D1;H2310X	3	76	3.8	4.4
		C(CM)-UKFX10SD1;HS2310 C(CM)-UKFX10AD1;HA2310 C(CM)-UKFX10ED1;HE2310X	1/8	3	8.4	9.7
UKX11D1;H2311X UKX11D1;HS2311 UKX11D1;HA2311 UKX11D1;HE2311XY	FX11D1 FX11D1 FX11D1 FX11D1	C(CM)-UKFX11D1;H2311X	4	86	4.7	5.4
		C(CM)-UKFX11SD1;HS2311 C(CM)-UKFX11AD1;HA2311 C(CM)-UKFX11ED1;HE2311XY	5/32	3 3/8	10	12
UKX12D1;H2312X UKX12D1;HS2312	FX12D1 FX12D1	C(CM)-UKFX12D1;H2312X	4	94	6.4	7.2
		C(CM)-UKFX12SD1;HS2312	5/32	3 31/32	14	16

## Square flanged unit, cast housing Adapter type



**Cast dust cover type**  
Open end **C-UKF...D1**  
Closed end **CM-UKF...D1**


Shaft dia. mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions									Bolt size mm inch
		<i>L</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>1</sub>	<i>A</i>	<i>N</i>	<i>A</i> <sub>0</sub>	<i>B</i> <sub>1</sub>	<i>F</i> min.	
60 2 3/16 2 1/4 2 3/8	UKFX13D1;H2313X UKFX13D1;HA2313 UKFX13D1;HE2313X UKFX13D1;HS2313X	187 7 3/8	149 5 55/64	34 1 11/32	21 1 3/16	59 2 5/16	19 3/4	69 2 23/32	65 2.559	-	M16 5/8
65 2 7/16 2 1/2	UKFX15D1;H2315X UKFX15D1;HA2315 UKFX15D1;HE2315X	197 7 3/4	152 5 63/64	40 1 37/64	24 1 5/16	68 2 11/16	23 29/32	77.5 3 3/64	73 2.874	-	M20 3/4
70 2 11/16 2 3/4	UKFX16D1;H2316X UKFX16D1;HA2316 UKFX16D1;HE2316X	214 8 7/16	171 6 47/64	40 1 37/64	24 1 5/16	70 2 3/4	23 29/32	80 3 5/32	78 3.071	90 3 17/32	M20 3/4
75 2 15/16 3	UKFX17D1;H2317X UKFX17D1;HA2317X UKFX17D1;HE2317X	214 8 7/16	171 6 47/64	40 1 37/64	24 1 5/16	70 2 3/4	23 29/32	81.5 3 13/64	82 3.228	95 3 3/4	M20 3/4
80 3 3/16	UKFX18D1;H2318X UKFX18D1;HA2318X	214 8 7/16	171 6 47/64	45 1 49/64	24 1 5/16	76 3	23 29/32	87.5 3 7/16	86 3.386	102 4 1/32	M20 3/4
90	UKFX20D1;H2320X	268	211	59	31	97	31	107.5	97	-	M27

- Notes** <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve. In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included. Example: CM-UKFX05D1;HE2305

**Remarks** Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number <sup>(3)</sup> cast dust cover type	Nominal dimensions		Mass of unit	
			<i>t</i> max.	<i>A</i> <sub>5</sub>	UKF	C(CM)
UKX13D1;H2313X UKX13D1;HA2313 UKX13D1;HE2313X UKX13D1;HS2313X	FX13D1 FX13D1 FX13D1 FX13D1	C(CM)-UKFX13D1;H2313X C(CM)-UKFX13AD1;HA2313 C(CM)-UKFX13ED1;HE2313X C(CM)-UKFX13SD1;HS2313X	4 5/32	101 3 31/32	6.4 14	7.6 17
UKX15D1;H2315X UKX15D1;HA2315 UKX15D1;HE2315X	FX15D1 FX15D1 FX15D1	C(CM)-UKFX15D1;H2315X C(CM)-UKFX15AD1;HA2315 C(CM)-UKFX15ED1;HE2315X	4 5/32	112 4 13/32	8.7 19	10 22
UKX16D1;H2316X UKX16D1;HA2316 UKX16D1;HE2316X	FX16D1 FX16D1 FX16D1	C(CM)-UKFX16D1;H2316X C(CM)-UKFX16AD1;HA2316 C(CM)-UKFX16ED1;HE2316X	4 5/32	118 4 21/32	11 24	12 26
UKX17D1;H2317X UKX17D1;HA2317X UKX17D1;HE2317X	FX17D1 FX17D1 FX17D1	C(CM)-UKFX17D1;H2317X C(CM)-UKFX17AD1;HA2317X C(CM)-UKFX17ED1;HE2317X	5 13/64	122 4 13/16	12 26	14 31
UKX18D1;H2318X UKX18D1;HA2318X	FX18D1 FX18D1	C(CM)-UKFX18D1;H2318X C(CM)-UKFX18AD1;HA2318	5 13/64	135 5 5/16	12 26	14 31
UKX20D1;H2320X	FX20D1	C(CM)-UKFX20D1;H2320X	5	146.5	20	22

## Square flanged unit, cast housing with spigot joint Adapter type



**Cast dust cover type**  
Open end **C-UKFS...D1**  
Closed end **CM-UKFS...D1**


Shaft dia.  mm inch	Unit number <sup>(1)</sup> / <sub>(2)</sub> / <sub>(3)</sub>	Nominal dimensions											Bolt size  mm inch
		mm inch											
		L	J	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>		
20 3/4	UKFS305D1;H2305X UKFS305D1;HE2305	110 4 11/32	80 3 5/32	9 23/64	16 5/8	7 9/32	13 1/2	29 1 9/64	80 3.1496	37 1 29/64	35 1.378	M14 1/2	
25 7/8 1	UKFS306D1;H2306X UKFS306D1;HS2306 UKFS306D1;HE2306X	125 4 29/32	95 3 47/64	10 25/64	16 5/8	8 5/16	15 19/32	32 1 17/64	90 3.5433	40.5 1 19/32	38 1.496	M14 1/2	
30 1 1/8	UKFS307D1;H2307X UKFS307D1;HS2307	135 5 5/16	100 3 15/16	11 7/16	19 3/4	9 23/64	16 5/8	36 1 13/32	100 3.9370	45.5 1 51/64	43 1.693	M16 5/8	
35 1 1/4 1 3/8	UKFS308D1;H2308X UKFS308D1;HE2308X UKFS308D1;HS2308X	150 5 29/32	112 4 13/32	13 33/64	19 3/4	10 25/64	17 21/32	40 1 9/16	115 4.5276	50 1 31/32	46 1.811	M16 5/8	
40 1 7/16 1 1/2 1 5/8	UKFS309D1;H2309X UKFS309D1;HA2309 UKFS309D1;HE2309X UKFS309D1;HS2309X	160 6 5/16	125 4 59/64	14 35/64	19 3/4	11 7/16	18 23/32	44 1 47/64	125 4.9213	54.5 2 9/64	50 1.969	M16 5/8	
45 1 5/8 1 11/16 1 3/4	UKFS310D1;H2310X UKFS310D1;HS2310 UKFS310D1;HA2310 UKFS310D1;HE2310X	175 6 7/8	132 5 13/64	16 5/8	23 29/32	12 15/32	19 3/4	48 1 57/64	140 5.5118	60.5 2 3/8	55 2.165	M20 3/4	
50 1 7/8 1 15/16 2	UKFS311D1;H2311X UKFS311D1;HS2311 UKFS311D1;HA2311 UKFS311D1;HE2311XY	185 7 9/32	140 5 33/64	17 43/64	23 29/32	13 33/64	20 25/32	52 2 3/64	150 5.9055	64 2 33/64	59 2.323	M20 3/4	
55 2 1/8	UKFS312D1;H2312X UKFS312D1;HS2312	195 7 11/16	150 5 29/32	19 3/4	23 29/32	14 35/64	22 7/8	56 2 13/64	160 6.2992	69.5 2 47/64	62 2.441	M20 3/4	

- Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
 In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.  
 To distinguish it, a suffix "Y" is added.  
<sup>(4)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
 Example: CM-UKFS305D1;HE2305

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number <sup>(1)</sup> cast dust cover type	Nominal dimensions		Mass of unit	
			mm inch		kg lb	
			t max.	A <sub>5</sub>	UKFS	C(CM)
UK305D1;H2305X UK305D1;HE2305	FS305D1 FS305D1	C(CM)-UKFS305D1;H2305X C(CM)-UKFS305ED1;HE2305	2 5/64	56 2 13/64	1.2 2.6	1.5 3.3
UK306D1;H2306X UK306D1;HS2306 UK306D1;HE2306X	FS306D1 FS306D1 FS306D1	C(CM)-UKFS306D1;H2306X C(CM)-UKFS306SD1;HS2306 C(CM)-UKFS306ED1;HE2306X	2 5/64	60 2 23/64	1.8 4.0	2.2 4.9
UK307D1;H2307X UK307D1;HS2307	FS307D1 FS307D1	C(CM)-UKFS307D1;H2307X C(CM)-UKFS307SD1;HS2307	3 1/8	67 2 11/64	2.3 5.1	2.9 6.4
UK308D1;H2308X UK308D1;HE2308X UK308D1;HS2308X	FS308D1 FS308D1 FS308D1	C(CM)-UKFS308D1;H2308X C(CM)-UKFS308ED1;HE2308X C(CM)-UKFS308SD1;HS2308X	3 1/8	76 2 63/64	3.2 7.1	3.7 8.2
UK309D1;H2309X UK309D1;HA2309 UK309D1;HE2309X UK309D1;HS2309X	FS309D1 FS309D1 FS309D1 FS309D1	C(CM)-UKFS309D1;H2309X C(CM)-UKFS309AD1;HA2309 C(CM)-UKFS309ED1;HE2309X C(CM)-UKFS309SD1;HS2309X	3 1/8	80 3 5/32	3.8 8.4	4.7 10
UK310D1;H2310X UK310D1;HS2310 UK310D1;HA2310 UK310D1;HE2310X	FS310D1 FS310D1 FS310D1 FS310D1	C(CM)-UKFS310D1;H2310X C(CM)-UKFS310SD1;HS2310 C(CM)-UKFS310AD1;HA2310 C(CM)-UKFS310ED1;HE2310X	3 1/8	88 3 15/32	5.1 11	6.3 14
UK311D1;H2311X UK311D1;HS2311 UK311D1;HA2311 UK311D1;HE2311XY	FS311D1 FS311D1 FS311D1 FS311D1	C(CM)-UKFS311D1;H2311X C(CM)-UKFS311SD1;HS2311 C(CM)-UKFS311AD1;HA2311 C(CM)-UKFS311ED1;HE2311XY	4 5/32	93 3 21/32	5.9 13	7.3 16
UK312D1;H2312X UK312D1;HS2312	FS312D1 FS312D1	C(CM)-UKFS312D1;H2312X C(CM)-UKFS312SD1;HS2312	4 5/32	100 3 15/16	7.0 15	8.4 19

## Square flanged unit, cast housing with spigot Adapter type



Cast dust cover type  
Open end **C-UKFS...D1**  
Closed end **CM-UKFS...D1**

Shaft dia.  mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )	Nominal dimensions										Bolt size  mm inch
		mm inch										
		L	J	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>	
60 2 3/16 2 1/4 2 3/8	UKFS313D1;H2313X UKFS313D1;HA2313 UKFS313D1;HE2313X UKFS313D1;HS2313X	208 8 3/16	166 6 17/32	15 19/32	33 29/32	18 45/64	22 7/8	58 2 9/32	175 6.8898	71.5 2 19/16	65 2.559	M20 3/4
65 2 7/16 2 1/2	UKFS315D1;H2315X UKFS315D1;HA2315 UKFS315D1;HE2315X	236 9 9/32	184 7 1/4	21 53/64	25 63/64	18 45/64	25 31/32	66 2 19/32	200 7.8740	81.5 3 13/64	73 2.874	M22 7/8
70 2 11/16 2 3/4	UKFS316D1;H2316X UKFS316D1;HA2316 UKFS316D1;HE2316X	250 9 27/32	196 7 23/32	18 45/64	31 1 7/32	20 25/32	27 1 1/16	68 2 43/64	210 8.2677	84 3 5/16	78 3.071	M27 1
75 2 15/16 3	UKFS317D1;H2317X UKFS317D1;HA2317X UKFS317D1;HE2317X	260 10 1/4	204 8 1/2	24 15/16	31 1 7/32	20 25/32	27 1 1/16	74 2 29/32	220 8.6614	92 3 5/8	82 3.228	M27 1
80 3 3/16	UKFS318D1;H2318X UKFS318D1;HA2318X	280 11 1/32	216 8 1/2	24 15/16	35 1 3/8	20 25/32	30 1 3/16	76 2 63/64	240 9.4488	94 3 45/64	86 3.386	M30 1 1/8
85 3 1/4	UKFS319D1;H2319X UKFS319D1;HE2319X	290 11 13/32	228 8 31/32	39 1 17/32	35 1 3/8	20 25/32	30 1 3/16	94 3 45/64	250 9.8425	111.5 4 25/64	90 3.543	M30 1 1/8
90 3 7/16 3 1/2	UKFS320D1;H2320X UKFS320D1;HA2320 UKFS320D1;HE2320X	310 12 7/32	242 9 17/32	39 1 17/32	38 1 1/2	20 25/32	32 1 1/4	94 3 45/64	260 10.2362	115.5 4 35/64	97 3.819	M33 1 1/4
100	UKFS322D1;H2322X	340	266	35	41	25	35	96	300	121	105	M36
110	UKFS324D1;H2324	370	290	35	41	30	40	110	330	130	112	M36
115	UKFS326D1;H2326	410	320	35	41	30	45	115	360	133	121	M36
125	UKFS328D1;H2328	450	350	45	41	30	55	125	400	146.5	131	M36


Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
Example: CM-UKFS305D1;HE2305

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number <sup>(2)</sup> cast dust cover type	Nominal dimensions		Mass of unit	
			mm inch		kg lb	
			t max.	A <sub>5</sub>	UKFS	C(CM)
UK313D1;H2313X UK313D1;HA2313 UK313D1;HE2313X UK313D1;HS2313X	FS313D1 FS313D1 FS313D1 FS313D1	C(CM)-UKFS313D1;H2313X C(CM)-UKFS313AD1;HA2313 C(CM)-UKFS313ED1;HE2313X C(CM)-UKFS313SD1;HS2313X	4 5/32	103 4 1/16	8.4 19	18 22
UK315D1;H2315X UK315D1;HA2315 UK315D1;HE2315X	FS315D1 FS315D1 FS315D1	C(CM)-UKFS315D1;H2315X C(CM)-UKFS315AD1;HA2315 C(CM)-UKFS315ED1;HE2315X	4 5/32	114 4 3/64	12 26	14 31
UK316D1;H2316X UK316D1;HA2316 UK316D1;HE2316X	FS316D1 FS316D1 FS316D1	C(CM)-UKFS316D1;H2316X C(CM)-UKFS316AD1;HA2316 C(CM)-UKFS316ED1;HE2316X	4 5/32	116 4 9/16	15 33	17 37
UK317D1;H2317X UK317D1;HA2317X UK317D1;HE2317X	FS317D1 FS317D1 FS317D1	C(CM)-UKFS317D1;H2317X C(CM)-UKFS317AD1;HA2317X C(CM)-UKFS317ED1;HE2317X	5 13/64	129 5 5/64	17 37	20 44
UK318D1;H2318X UK318D1;HA2318X	FS318D1 FS318D1	C(CM)-UKFS318D1;H2318X C(CM)-UKFS318AD1;HA2318X	5 13/64	129 5 5/64	21 46	24 53
UK319D1;H2319X UK319D1;HE2319X	FS319D1 FS319D1	C(CM)-UKFS319D1;H2319X C(CM)-UKFS319ED1;HE2319X	5 13/64	149 5 55/64	24 53	29 64
UK320D1;H2320X UK320D1;HA2320 UK320D1;HE2320X	FS320D1 FS320D1 FS320D1	C(CM)-UKFS320D1;H2320X C(CM)-UKFS320AD1;HA2320 C(CM)-UKFS320ED1;HE2320X	5 13/64	154 6 1/16	29 64	34 75
UK322D1;H2322X	FS322D1	C(CM)-UKFS322D1;H2322X	5	160	38	46
UK324D1;H2324	FS324D1	C(CM)-UKFS324D1;H2324	5	172	51	59
UK326D1;H2326	FS326D1	C(CM)-UKFS326D1;H2326	6	178	69	79
UK328D1;H2328	FS328D1	C(CM)-UKFS328D1;H2328	6	192	98	110



## Round flanged unit, cast housing with spigot joint Adapter type



Shaft dia. mm inch	Unit number <sup>(1)(2)(3)</sup>	Nominal dimensions													Bolt size mm inch	Bearing number
		mm inch														
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>	F	mm min.		
20 3/4	UKFC205D1;H2305X UKFC205D1;HE2305	115 4 17/32	90 3 35/64	63.6 2 1/2	10 25/64	12 15/32	6 15/64	21 13/16	27 1 1/16	70 2.7559	35.5 1 25/64	35 1.378	30 1 3/16	M10 3/8	UK205D1;H2305X UK205D1;HE2305	
25 7/8 1	UKFC206D1;H2306X UKFC206D1;HS2306 UKFC206D1;HE2306X	125 4 29/32	100 3 15/16	70.7 2 25/32	10 25/64	12 15/32	8 5/16	23 29/32	31 1 7/32	80 3.1496	39 1 17/32	38 1.496	36 1 13/32	M10 3/8	UK206D1;H2306X UK206D1;HS2306 UK206D1;HE2306X	
30 1 1/8	UKFC207D1;H2307X UKFC207D1;HS2307	135 5 5/16	110 4 21/64	77.8 3 1/16	11 7/16	14 35/64	8 5/16	26 1 1/32	34 1 11/32	90 3.5433	42.5 1 43/64	43 1.693	40 1 9/16	M12 7/16	UK207D1;H2307X UK207D1;HS2307	
35 1 1/4 1 3/8	UKFC208D1;H2308X UKFC208D1;HE2308X UKFC208D1;HS2308X	145 5 23/32	120 4 23/32	84.9 3 11/32	11 7/16	14 35/64	10 25/64	26 1 1/32	36 1 27/64	100 3.9370	46.5 1 59/64	46 1.811	46 1 13/16	M12 7/16	UK208D1;H2308X UK208D1;HE2308X UK208D1;HS2308X	
40 1 7/16 1 1/2 1 5/8	UKFC209D1;H2309X UKFC209D1;HA2309 UKFC209D1;HE2309X UKFC209D1;HS2309X	160 6 5/16	132 5 13/64	93.3 3 49/64	10 25/64	16 5/8	12 15/32	26 1 1/32	38 1 1/2	105 4.1339	48.5 1 29/32	50 1.969	52 2 1/16	M14 1/2	UK209D1;H2309X UK209D1;HA2309 UK209D1;HE2309X UK209D1;HS2309X	
45 1 5/8 1 11/16 1 3/4	UKFC210D1;H2310X UKFC210D1;HS2310 UKFC210D1;HA2310 UKFC210D1;HE2310X	165 6 1/2	138 5 7/16	97.6 3 27/32	10 25/64	16 5/8	12 15/32	28 1 3/32	40 1 37/64	110 4.3307	50 1 31/32	55 2.165	57 2 1/4	M14 1/2	UK210D1;H2310X UK210D1;HS2310 UK210D1;HA2310 UK210D1;HE2310X	
50 1 7/8 1 15/16 2	UKFC211D1;H2311X UKFC211D1;HS2311 UKFC211D1;HA2311 UKFC211D1;HE2311XY	185 7 9/32	150 5 29/32	106.1 4 11/64	13 33/64	19 3/4	12 15/32	31 1 7/32	43 1 11/16	125 4.9213	54.5 2 9/64	59 2.323	64 2 17/32	M16 5/8	UK211D1;H2311X UK211D1;HS2311 UK211D1;HA2311 UK211D1;HE2311XY	
55 2 1/8	UKFC212D1;H2312X UKFC212D1;HS2312	195 7 11/16	160 6 19/64	113.1 4 29/64	17 43/64	19 3/4	12 15/32	36 1 13/32	48 1 57/64	135 5.3150	61 2 13/32	62 2.441	69 2 23/32	M16 5/8	UK212D1;H2312X UK212D1;HS2312	

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve. In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve. To distinguish it, a suffix "Y" is added.  
<sup>(4)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included. Example: ZM-UKFC205D1;HE2305


Remarks Please refer to page A21 for size of grease fitting.

Pressed steel dust cover type  
 Open end Z-UKFC...D1  
 Closed end ZM-UKFC...D1

Cast dust cover type  
 Open end C-UKFC...D1  
 Closed end CM-UKFC...D1

Housing number	Unit number <sup>(4)</sup> pressed steel dust cover type	Unit number <sup>(4)</sup> cast dust cover type	Nominal dimensions				Mass of unit		
			mm inch				kg lb		
			t max.	A <sub>4</sub>	A <sub>1c</sub>	A <sub>5</sub>	UKFC	Z(M)	C(M)
FC205D1 FC205D1	Z(ZM)-UKFC205D1;H2305X Z(ZM)-UKFC205ED1;HE2305	C(CM)-UKFC205D1;H2305X C(CM)-UKFC205ED1;HE2305	2 5/64	40 1 19/32	22 7/8	51 2	1.0 2.2	1.1 2.4	1.2 2.6
FC206D1 FC206D1	Z(ZM)-UKFC206D1;H2306X Z(ZM)-UKFC206SD1;HS2306 Z(ZM)-UKFC206ED1;HE2306X	C(CM)-UKFC206D1;H2306X C(CM)-UKFC206SD1;HS2306 C(CM)-UKFC206ED1;HE2306X	2 5/64	45 1 3/4	24.5 31/32	56 2 19/64	1.3 2.9	1.4 3.1	1.7 3.7
FC207D1 FC207D1	Z(ZM)-UKFC207D1;H2307X Z(ZM)-UKFC207SD1;HS2307	C(CM)-UKFC207D1;H2307X C(CM)-UKFC207SD1;HS2307	3 1/8	49 1 15/16	26 1 1/32	59 2 21/64	1.7 3.7	1.8 4.0	2.0 4.4
FC208D1 FC208D1	Z(ZM)-UKFC208D1;H2308X Z(ZM)-UKFC208ED1;HE2308X Z(ZM)-UKFC208SD1;HS2308X	C(CM)-UKFC208D1;H2308X C(CM)-UKFC208ED1;HE2308X C(CM)-UKFC208SD1;HS2308X	3 1/8	56 2 3/16	27.5 1 5/64	66 2 19/32	2.1 4.6	2.2 4.9	2.6 5.7
FC209D1 FC209D1	Z(ZM)-UKFC209D1;H2309X Z(ZM)-UKFC209AD1;HA2309 Z(ZM)-UKFC209ED1;HE2309X Z(ZM)-UKFC209SD1;HS2309X	C(CM)-UKFC209D1;H2309X C(CM)-UKFC209AD1;HA2309 C(CM)-UKFC209ED1;HE2309X C(CM)-UKFC209SD1;HS2309X	3 1/8	57 2 1/4	28 1 7/64	70 2 3/4	2.8 6.2	2.9 6.4	3.4 7.5
FC210D1 FC210D1	Z(ZM)-UKFC210D1;H2310X Z(ZM)-UKFC210SD1;HS2310 Z(ZM)-UKFC210AD1;HA2310 Z(ZM)-UKFC210ED1;HE2310X	C(CM)-UKFC210D1;H2310X C(CM)-UKFC210SD1;HS2310 C(CM)-UKFC210AD1;HA2310 C(CM)-UKFC210ED1;HE2310X	3 1/8	60 2 3/8	29 3 3/8	72 2 59/64	3.1 6.8	3.3 7.3	4.8 11
FC211D1 FC211D1	Z(ZM)-UKFC211D1;H2311X Z(ZM)-UKFC211SD1;HS2311 Z(ZM)-UKFC211AD1;HA2311 Z(ZM)-UKFC211ED1;HE2311XY	C(CM)-UKFC211D1;H2311X C(CM)-UKFC211SD1;HS2311 C(CM)-UKFC211AD1;HA2311 C(CM)-UKFC211ED1;HE2311XY	4 5/32	64 2 1/2	32.5 3 3/8	75 2 61/64	4.2 9.3	4.4 9.7	5.1 11
FC212D1 FC212D1	Z(ZM)-UKFC212D1;H2312X Z(ZM)-UKFC212SD1;HS2312	C(CM)-UKFC212D1;H2312X C(CM)-UKFC212SD1;HS2312	4 5/32	74 2 29/32	38 3 3/8	86 3 25/64	5.0 11	5.2 11	6.1 13

## Round flanged unit, cast housing with spigot joint Adapter type



Shaft dia. mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions													Bolt size mm inch	Bearing number
		mm inch														
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>	F	mm min.		
60 2 3/16 2 1/4 2 3/8	UKFC213D1;H2313X UKFC213D1;HA2313 UKFC213D1;HE2313X UKFC213D1;HS2313X	205	170	120.2	16	19	14	36	50	145	64	65	74	M16	UK213D1;H2313X UK213D1;HA2313 UK213D1;HE2313X UK213D1;HS2313X	
65 2 7/16 2 1/2	UKFC215D1;H2315X UKFC215D1;HA2315 UKFC215D1;HE2315X	220	184	130.1	18	19	16	40	56	160	71	73	84	M16	UK215D1;H2315X UK215D1;HA2315 UK215D1;HE2315X	
70 2 11/16 2 3/4	UKFC216D1;H2316X UKFC216D1;HA2316 UKFC216D1;HE2316X	240	200	141.4	18	23	16	42	58	170	73.5	78	90	M20	UK216D1;H2316X UK216D1;HA2316 UK216D1;HE2316X	
75 2 15/16 3	UKFC217D1;H2317X UKFC217D1;HA2317X UKFC217D1;HE2317X	250	208	147.1	18	23	18	45	63	180	77	82	95	M20	UK217D1;H2317X UK217D1;HA2317X UK217D1;HE2317X	
80 3 3/16	UKFC218D1;H2318X UKFC218D1;HA2318X	265	220	155.6	22	23	18	50	68	190	81.5	86	102	M20	UK218D1;H2318X UK218D1;HA2318X	

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
 In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
 Example: ZM-UKFC205D1;HE2305

Remarks Please refer to page A21 for size of grease fitting.

Pressed steel dust cover type  
 Open end Z-UKFC...D1  
 Closed end ZM-UKFC...D1

Cast dust cover type  
 Open end C-UKFC...D1  
 Closed end CM-UKFC...D1

Housing number	Unit number <sup>(2)</sup> pressed steel dust cover type	Unit number <sup>(2)</sup> cast dust cover type	Nominal dimensions				Mass of unit		
			mm inch				kg lb		
			t max.	A <sub>4</sub>	A <sub>1c</sub>	A <sub>5</sub>	UKFC	Z(M)	C(CM)
FC213D1	Z(ZM)-UKFC213D1;H2313X	C(CM)-UKFC213D1;H2313X	4	76	38	89.5	6.0	6.1	7.1
FC213D1	Z(ZM)-UKFC213AD1;HA2313	C(CM)-UKFC213AD1;HA2313	5/32	3	3 3/8	3 17/32	13	13	16
FC213D1	Z(ZM)-UKFC213ED1;HE2313X	C(CM)-UKFC213ED1;HE2313X	5/32	3	3 3/8	3 17/32	13	13	16
FC213D1	Z(ZM)-UKFC213SD1;HS2313X	C(CM)-UKFC213SD1;HS2313X	5/32	3	3 3/8	3 17/32	13	13	16
FC215D1	—	C(CM)-UKFC215D1;H2315X	4	—	43	102	7.7	—	9.3
FC215D1	—	C(CM)-UKFC215AD1;HA2315	5/32	—	1 11/16	4 1/4	17	—	21
FC215D1	—	C(CM)-UKFC215ED1;HE2315X	5/32	—	1 11/16	4 1/4	17	—	21
FC216D1	—	C(CM)-UKFC216D1;H2316X	4	—	43	106	9.5	—	11
FC216D1	—	C(CM)-UKFC216AD1;HA2316	5/32	—	1 11/16	4 11/64	21	—	24
FC216D1	—	C(CM)-UKFC216ED1;HE2316X	5/32	—	1 11/16	4 11/64	21	—	24
FC217D1	—	C(CM)-UKFC217D1;H2317X	5	—	45.5	114	11	—	13
FC217D1	—	C(CM)-UKFC217AD1;HA2317X	1 3/6	—	1 51/64	4 31/64	24	—	29
FC217D1	—	C(CM)-UKFC217ED1;HE2317X	1 3/6	—	1 51/64	4 31/64	24	—	29
FC218D1	—	C(CM)-UKFC218D1;H2318X	5	—	50	122	13	—	15
FC218D1	—	C(CM)-UKFC218AD1;HA2318X	1 3/6	—	1 31/32	4 51/64	29	—	33

## Round flanged unit, cast housing with spigot joint Adapter type



Shaft dia.  mm inch	Unit number <sup>(1)(2)(3)</sup>	Nominal dimensions												
		mm inch												
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>	F min.	
20 3/4	<b>UKFCX05D1;H2305X</b> <b>UKFCX05D1;HE2305</b>	111 4 3/8	92 3 5/8	65.1 2 9/16	10 25/64	9.5 3/8	6 1/4	24 15/16	30 1 3/16	76 2.9921	37 1 29/64	35 1.378	30 1 3/16	
25 7/8 1	<b>UKFCX06D1;H2306X</b> <b>UKFCX06D1;HS2306</b> <b>UKFCX06D1;HE2306X</b>	127 5	105 4 9/64	74.2 2 59/64	8 5/16	12 15/32	9.5 3/8	22.5 7/8	32 1 17/64	85 3.3465	40 1 37/64	38 1.496	36 1 13/32	
30 1 1/8	<b>UKFCX07D1;H2307X</b> <b>UKFCX07D1;HS2307</b>	133 5 1/4	111 4 3/8	78.5 3 3/32	9 23/64	12 15/32	11 7/16	26 1 1/32	37 1 29/64	92 3.6220	44.5 1 3/4	43 1.693	40 1 9/16	
35 1 1/4 1 3/8	<b>UKFCX08D1;H2308X</b> <b>UKFCX08D1;HE2308X</b> <b>UKFCX08D1;HS2308X</b>	133 5 1/4	111 4 3/8	78.5 3 3/32	9 23/64	12 15/32	11 7/16	26 1 1/32	37 1 29/64	92 3.6220	45.5 1 51/64	46 1.811	46 1 13/16	
40 1 7/16 1 1/2 1 5/8	<b>UKFCX09D1;H2309X</b> <b>UKFCX09D1;HA2309</b> <b>UKFCX09D1;HE2309X</b> <b>UKFCX09D1;HS2309X</b>	155 6 3/32	130 5 1/8	91.9 3 5/8	8 5/16	14 35/64	12 15/32	25 31/32	37 1 29/64	108 4.2520	47 1 27/32	50 1.969	52 2 1/16	
45 1 5/8 1 11/16 1 3/4	<b>UKFCX10D1;H2310X</b> <b>UKFCX10D1;HS2310</b> <b>UKFCX10D1;HA2310</b> <b>UKFCX10D1;HE2310X</b>	162 6 3/8	136 5 23/64	96.2 3 25/32	7 9/32	14 35/64	16 5/8	25 31/32	41 1 39/64	118 4.6457	52.5 2 1/16	55 2.165	57 2 1/4	
50 1 7/8 1 15/16 2	<b>UKFCX11D1;H2311X</b> <b>UKFCX11D1;HS2311</b> <b>UKFCX11D1;HA2311</b> <b>UKFCX11D1;HE2311XY</b>	180 7 9/32	152 5 63/64	107.5 4 15/64	4 5/32	16 5/8	22 55/64	26 1 1/32	48 1 57/64	127 5.0000	57 2 1/4	59 2.323	64 2 17/32	
55 2 1/8	<b>UKFCX12D1;H2312X</b> <b>UKFCX12D1;HS2312</b>	194 7 5/8	165 6 1/2	116.7 4 19/32	11 7/16	16 5/8	20 25/32	33 1 5/16	53 2 5/64	140 5.5118	64 2 33/64	62 2.441	69 2 23/32	

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.

In this case the lock washer with the straight inner prong should be used.

<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.

To distinguish it, a suffix "Y" is added.

Remarks Please refer to page A21 for size of grease fitting.

Bolt size  mm inch	Bearing number	Housing number	Mass of unit  kg lb
M8 5/16	UKX05D1;H2305X UKX05D1;HE2305	FCX05D1 FCX05D1	1.2 2.6
M10 5/8	UKX06D1;H2306X UKX06D1;HS2306 UKX06D1;HE2306X	FCX06D1 FCX06D1 FCX06D1	1.5 3.3
M10 3/8	UKX07D1;H2307X UKX07D1;HS2307	FCX07D1 FCX07D1	1.9 4.2
M10 3/8	UKX08D1;H2308X UKX08D1;HE2308X UKX08D1;HS2308X	FCX08D1 FCX08D1 FCX08D1	2.2 4.9
M12 7/16	UKX09D1;H2309X UKX09D1;HA2309 UKX09D1;HE2309X UKX09D1;HS2309X	FCX09D1 FCX09D1 FCX09D1 FCX09D1	2.7 6.0
M12 7/16	UKX10D1;H2310X UKX10D1;HS2310 UKX10D1;HA2310 UKX10D1;HE2310X	FCX10D1 FCX10D1 FCX10D1 FCX10D1	3.1 6.8
M14 1/2	UKX11D1;H2311X UKX11D1;HS2311 UKX11D1;HA2311 UKX11D1;HE2311XY	FCX11D1 FCX11D1 FCX11D1 FCX11D1	4.2 9.3
M14 1/2	UKX12D1;H2312X UKX12D1;HS2312	FCX12D1 FCX12D1	5.5 12

## Round flanged unit, cast housing with spigot joint Adapter type



Shaft dia.  mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )	Nominal dimensions											
		mm inch											
		L	J	(J <sub>1</sub> )	A <sub>2</sub>	N	A <sub>3</sub>	A <sub>1</sub>	A	H <sub>3</sub>	A <sub>0</sub>	B <sub>1</sub>	F min.
60 2 3/16 2 1/4 2 3/8	<b>UKFCX13D1;H2313X</b> <b>UKFCX13D1;HA2313</b> <b>UKFCX13D1;HE2313X</b> <b>UKFCX13D1;HS2313X</b>	194	165	116.7	11	16	20	33	53	140	66	65	74
		7 5/8	6 1/2	4 19/32	7/16	5/8	25/32	1 5/16	2 5/64	5.5118	2 19/32	2.559	2 29/32
65 2 7/16 2 1/2	<b>UKFCX15D1;H2315X</b> <b>UKFCX15D1;HA2315</b> <b>UKFCX15D1;HE2315X</b>	222	190	134.4	12	19	22	35	57	164	71.5	73	84
		8 3/4	7 31/64	5 9/32	15/32	3/4	55/64	1 3/8	2 1/4	6.4567	2 13/16	2.874	3 5/16
70 2 11/16 2 3/4	<b>UKFCX16D1;H2316X</b> <b>UKFCX16D1;HA2316</b> <b>UKFCX16D1;HE2316X</b>	260	219	154.9	10	23	25	36	61	186	75	78	90
		10 1/4	8 5/8	6 3/32	25/64	29/32	63/64	1 13/32	2 13/32	7.3228	2 61/64	3.071	3 17/32
75 2 15/16 3	<b>UKFCX17D1;H2317X</b> <b>UKFCX17D1;HA2317X</b> <b>UKFCX17D1;HE2317X</b>	260	219	154.9	10	23	25	36	61	186	76.5	82	95
		10 1/4	8 5/8	6 3/32	25/64	29/32	63/64	1 13/32	2 13/32	7.3228	3 1/64	3.228	3 3/4
80 3 3/16	<b>UKFCX18D1;H2318X</b> <b>UKFCX18D1;HA2318X</b>	260	219	154.9	12	23	28	43	71	186	82.5	86	102
		10 1/4	8 5/8	6 3/32	15/32	29/32	1 7/64	1 1/16	2 51/64	7.3228	3 1/4	3.386	4 1/32
90	<b>UKFCX20D1;H2320X</b>	276	238	168.3	22	23	28	66	94	206	98.5	97	112

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.

In this case the lock washer with the straight inner prong should be used.

Remarks Please refer to page A21 for size of grease fitting.

Bolt size  mm inch	Bearing number	Housing number	Mass of unit  kg lb
M14  1/2	<b>UKX13D1;H2313X</b> <b>UKX13D1;HA2313</b> <b>UKX13D1;HE2313X</b> <b>UKX15D1;HS2313X</b>	<b>FCX13D1</b> <b>FCX13D1</b> <b>FCX13D1</b> <b>FCX13D1</b>	5.4  12
M16  5/8	<b>UKX15D1;H2315X</b> <b>UKX15D1;HA2315</b> <b>UKX15D1;HE2315X</b>	<b>FCX15D1</b> <b>FCX15D1</b> <b>FCX15D1</b>	8.2  18
M20  3/4	<b>UKX16D1;H2316X</b> <b>UKX16D1;HA2316</b> <b>UKX16D1;HE2316X</b>	<b>FCX16D1</b> <b>FCX16D1</b> <b>FCX16D1</b>	12  26
M20  3/4	<b>UKX17D1;H2317X</b> <b>UKX17D1;HA2317X</b> <b>UKX17D1;HE2317X</b>	<b>FCX17D1</b> <b>FCX17D1</b> <b>FCX17D1</b>	12  26
M20  3/4	<b>UKX18D1;H2318X</b> <b>UKX18D1;HA2318X</b>	<b>FCX18D1</b> <b>FCX18D1</b>	12  26
M20	<b>UKX20D1;H2320X</b>	<b>FCX20D1</b>	18

## Rhombus flanged unit, cast housing Adapter type




**Pressed steel dust cover type**  
Open end **Z-UKFL...D1**  
Closed end **ZM-UKFL...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )( <sup>3</sup> )	Nominal dimensions										Bolt size mm inch	Bearing number
		mm inch											
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	F min.		
20 3/4	UKFL205D1;H2305X UKFL205D1;HE2305	130 5 1/8	99 3 57/64	16 5/8	13 1/2	27 1 1/16	16 5/8	68 2 11/16	35.5 1 25/64	35 1.378	30 1 3/16	M14 1/2	UK205D1;H2305X UK205D1;HE2305
25 7/8 1	UKFL206D1;H2306X UKFL206D1;HS2306 UKFL206D1;HE2306X	148 5 15/16	117 4 39/64	18 45/64	13 1/2	31 1 7/32	16 5/8	80 3 5/32	39 1 17/32	38 1.496	36 1 13/32	M14 1/2	UK206D1;H2306X UK206D1;HS2306 UK206D1;HE2306X
30 1 1/8	UKFL207D1;H2307X UKFL207D1;HS2307	161 6 11/32	130 5 1/8	19 3/4	15 19/32	34 1 11/32	16 5/8	90 3 17/32	42.5 1 43/64	43 1.693	40 1 9/16	M14 1/2	UK207D1;H2307X UK207D1;HS2307
35 1 1/4 1 3/8	UKFL208D1;H2308X UKFL208D1;HE2308X UKFL208D1;HS2308X	175 6 7/8	144 5 43/64	21 53/64	15 19/32	36 1 13/32	16 5/8	100 3 15/16	46.5 1 53/64	46 1.811	46 1 13/16	M14 1/2	UK208D1;H2308X UK208D1;HE2308X UK208D1;HS2308X
40 1 7/16 1 1/2 1 5/8	UKFL209D1;H2309X UKFL209D1;HA2309 UKFL209D1;HE2309X UKFL209D1;HS2309X	188 7 13/32	148 5 53/64	22 55/64	16 5/8	38 1 1/2	19 3/4	108 4 1/4	48.5 1 29/32	50 1.969	52 2 1/16	M16 5/8	UK209D1;H2309X UK209D1;HA2309 UK209D1;HE2309X UK209D1;HS2309X
45 1 5/8 1 11/16 1 3/4	UKFL210D1;H2310X UKFL210D1;HS2310 UKFL210D1;HA2310 UKFL210D1;HE2310X	197 7 3/4	157 6 3/16	22 55/64	16 5/8	40 1 9/16	19 3/4	115 4 17/32	50 1 31/32	55 2.165	57 2 1/4	M16 5/8	UK210D1;H2310X UK210D1;HS2310 UK210D1;HA2310 UK210D1;HE2310X
50 1 7/8 1 15/16 2	UKFL211D1;H2311X UKFL211D1;HS2311 UKFL211D1;HA2311 UKFL211D1;HE2311XY	224 8 13/16	184 7 1/4	25 63/64	18 23/32	43 1 11/16	19 3/4	130 5 1/8	54.5 2 9/64	59 2.323	64 2 17/32	M16 5/8	UK211D1;H2311X UK211D1;HS2311 UK211D1;HA2311 UK211D1;HE2311XY
55 2 1/8	UKFL212D1;H2312X UKFL212D1;HS2312	250 9 27/32	202 7 61/64	29 1 9/64	18 23/32	48 1 7/8	23 29/32	140 5 1/2	61 2 13/32	62 2.441	69 2 23/32	M20 3/4	UK212D1;H2312X UK212D1;HS2312

- Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve. In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve. To distinguish it, a suffix "Y" is added.  
<sup>(4)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included. Example: ZM-UKFL205D1;HE2305

Remarks Please refer to page A21 for size of grease fitting.



**Cast dust cover type**  
Open end **C-UKFL...D1**  
Closed end **CM-UKFL...D1**

Housing number	Unit number <sup>(4)</sup> pressed steel dust cover type	Unit number <sup>(4)</sup> cast dust cover type	Nominal dimensions					Mass of unit		
			mm inch					kg lb		
			t max.	A <sub>4</sub>	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UKFL	Z(ZM)	C(CM)
FL205D1 FL205D1	Z(ZM)-UKFL205D1;H2305X Z(ZM)-UKFL205ED1;HE2305	C(CM)-UKFL205D1;H2305X C(CM)-UKFL205ED1;HE2305	2 5/64	40 1 19/32	51 2	74 2 29/32	34 1 11/32	0.6 1.3	0.7 1.5	0.8 1.8
FL206D1 FL206D1 FL206D1	Z(ZM)-UKFL206D1;H2306X Z(ZM)-UKFL206SD1;HS2306 Z(ZM)-UKFL206ED1;HE2306X	C(CM)-UKFL206D1;H2306X C(CM)-UKFL206SD1;HS2306 C(CM)-UKFL206ED1;HE2306X	2 5/64	45 1 3/4	56 2 7/32	85 3 11/32	40 1 9/16	0.9 2.0	1.0 2.2	1.2 2.9
FL207D1 FL207D1	Z(ZM)-UKFL207D1;H2307X Z(ZM)-UKFL207SD1;HS2307	C(CM)-UKFL207D1;H2307X C(CM)-UKFL207SD1;HS2307	3 1/8	49 1 15/16	59 2 5/16	97 3 13/16	45 1 25/32	1.3 2.9	1.3 2.9	1.6 3.5
FL208D1 FL208D1 FL208D1	Z(ZM)-UKFL208D1;H2308X Z(ZM)-UKFL208ED1;HE2308X Z(ZM)-UKFL208SD1;HS2308X	C(CM)-UKFL208D1;H2308X C(CM)-UKFL208ED1;HE2308X C(CM)-UKFL208SD1;HS2308X	3 1/8	56 2 3/16	66 2 19/32	106 4 3/16	50 1 31/32	1.6 3.5	1.7 3.7	2.1 4.6
FL209D1 FL209D1 FL209D1 FL209D1	Z(ZM)-UKFL209D1;H2309X Z(ZM)-UKFL209AD1;HA2309 Z(ZM)-UKFL209ED1;HE2309X Z(ZM)-UKFL209SD1;HS2309X	C(CM)-UKFL209D1;H2309X C(CM)-UKFL209AD1;HA2309 C(CM)-UKFL209ED1;HE2309X C(CM)-UKFL209SD1;HS2309X	3 1/8	57 2 1/4	70 2 3/4	113 4 7/16	54 2 1/8	2.0 4.4	2.1 4.6	2.5 5.7
FL210D1 FL210D1 FL210D1 FL210D1	Z(ZM)-UKFL210D1;H2310X Z(ZM)-UKFL210SD1;HS2310 Z(ZM)-UKFL210AD1;HA2310 Z(ZM)-UKFL210ED1;HE2310X	C(CM)-UKFL210D1;H2310X C(CM)-UKFL210SD1;HS2310 C(CM)-UKFL210AD1;HA2310 C(CM)-UKFL210ED1;HE2310X	3 1/8	60 2 3/8	72 2 27/32	120 4 23/32	58 2 9/32	2.2 4.9	2.4 5.3	2.9 6.4
FL211D1 FL211D1 FL211D1 FL211D1	Z(ZM)-UKFL211D1;H2311X Z(ZM)-UKFL211SD1;HS2311 Z(ZM)-UKFL211AD1;HA2311 Z(ZM)-UKFL211ED1;HE2311XY	C(CM)-UKFL211D1;H2311X C(CM)-UKFL211SD1;HS2311 C(CM)-UKFL211AD1;HA2311 C(CM)-UKFL211ED1;HE2311XY	4 5/32	64 2 1/2	75 2 15/16	133 5 1/4	65 2 9/16	3.1 6.8	3.4 7.5	3.7 8.2
FL212D1 FL212D1	Z(ZM)-UKFL212D1;H2312X Z(ZM)-UKFL212SD1;HS2312	C(CM)-UKFL212D1;H2312X C(CM)-UKFL212SD1;HS2312	4 5/32	74 2 29/32	86 3 3/8	144 5 21/32	70 2 3/4	3.9 8.6	4.2 9.3	4.7 10

## Rhombus flanged unit, cast housing Adapter type




**Pressed steel dust cover type**  
Open end **Z-UKFL...D1**  
Closed end **ZM-UKFL...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )	Nominal dimensions											Bolt size mm inch	Bearing number
		mm inch												
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	F	min.		
60 2 3/16 2 1/4 2 3/8	UKFL213D1;H2313X UKFL213D1;HA2313 UKFL213D1;HE2313X UKFL213D1;HS2313X	258	210	30	22	50	23	155	64	65	74	M20	UK213D1;H2313X UK213D1;HA2313 UK213D1;HE2313X UK213D1;HS2313X	
		10 5/32	8 17/64	1 3/16	7/8	1 31/32	29/32	6 3/32	2 33/64	2.559	2 29/32	3/4		
65 2 7/16 2 1/2	UKFL215D1;H2315X UKFL215D1;HA2315 UKFL215D1;HE2315X	275	225	34	22	56	23	165	71	73	84	M20	UK215D1;H2315X UK215D1;HA2315 UK215D1;HE2315X	
		10 13/16	8 55/64	1 11/32	7/8	2 7/32	29/32	6 1/2	2 51/64	2.874	3 5/16	3/4		
70 2 11/16 2 3/4	UKFL216D1;H2316X UKFL216D1;HA2316 UKFL216D1;HE2316X	290	233	34	22	58	25	180	73.5	78	90	M22	UK216D1;H2316X UK216D1;HA2316 UK216D1;HE2316X	
		11 13/32	9 11/64	1 11/32	7/8	2 9/32	63/64	7 3/32	2 57/64	3.071	3 17/32	7/8		
75 2 15/16 3	UKFL217D1;H2317X UKFL217D1;HA2317X UKFL217D1;HE2317X	305	248	36	24	63	25	190	77	82	95	M22	UK217D1;H2317X UK217D1;HA2317X UK217D1;HE2317X	
		12	9 49/64	1 27/64	15/16	2 15/32	63/64	7 15/32	3 1/32	3.228	3 3/4	7/8		
80 3 3/16	UKFL218D1;H2318X UKFL218D1;HA2318X	320	265	40	24	68	25	205	81.5	86	102	M22	UK218D1;H2318X UK218D1;HA2318X	
		12 19/32	10 7/16	1 37/64	15/16	2 11/16	63/64	8 1/16	3 13/64	3.386	4 1/32	7/8		

**Notes** <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
Example: ZM-UKFL205D1;HE2305


**Remarks** Please refer to page A21 for size of grease fitting.



**Cast dust cover type**  
Open end **C-UKFL...D1**  
Closed end **CM-UKFL...D1**

Housing number	Unit number <sup>(2)</sup> pressed steel dust cover type	Unit number <sup>(2)</sup> cast dust cover type	Nominal dimensions					Mass of unit		
			mm inch					kg lb		
			t max.	A <sub>4</sub>	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UKFL	Z(ZM)	C(CM)
FL213D1 FL213D1 FL213D1 FL213D1	Z(ZM)-UKFL213D1;H2313X Z(ZM)-UKFL213AD1;HA2313 Z(ZM)-UKFL213ED1;HE2313X Z(ZM)-UKFL213SD1;HS2313X	C(CM)-UKFL213D1;H2313X C(CM)-UKFL213AD1;HA2313 C(CM)-UKFL213ED1;HE2313X C(CM)-UKFL213SD1;HS2313X	4 5/32	76 3	90 3 17/32	157 6 3/16	78 3 1/16	5.0 11	5.4 12	6.0 13
FL215D1 FL215D1 FL215D1	— — —	C(CM)-UKFL215D1;H2315X C(CM)-UKFL215AD1;HA2315 C(CM)-UKFL215ED1;HE2315X	4 5/32	— 4 1/32	102 6 21/32	169 6 3/32	82 3 7/32	6.2 14	— —	7.6 17
FL216D1 FL216D1 FL216D1	— — —	C(CM)-UKFL216D1;H2316X C(CM)-UKFL216AD1;HA2316 C(CM)-UKFL216ED1;HE2316X	4 5/32	— 4 3/16	106 7 7/32	183 7 7/32	90 3 17/32	7.9 17	— —	9.3 21
FL217D1 FL217D1 FL217D1	— — —	C(CM)-UKFL217D1;H2317X C(CM)-UKFL217AD1;HA2317X C(CM)-UKFL217ED1;HE2317X	5 13/64	— 4 1/2	114 7 7/16	192 7 3/4	95 3 3/4	9.2 20	— —	11 24
FL218D1 FL218D1	— —	C(CM)-UKFL218D1;H2318X C(CM)-UKFL218AD1;HA2318X	5 13/64	— 4 13/16	122 8 1/16	205 8 1/16	102 4 1/32	11 24	— —	13 29

## Rhombus flanged unit, cast housing Adapter type



Cast dust cover type  
Open end **C-UKFL...D1**  
Closed end **CM-UKFL...D1**


Shaft dia. mm inch	Unit number <sup>(1)(2)(3)</sup>	Nominal dimensions									Bolt size mm inch
		mm inch									
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	
20 3/4	UKFL305D1;H2305X UKFL305D1;HE2305	150 5 <sup>29</sup> / <sub>32</sub>	113 4 <sup>29</sup> / <sub>64</sub>	16 5/8	13 1/2	29 1 <sup>5</sup> / <sub>32</sub>	19 3/4	80 3 <sup>5</sup> / <sub>32</sub>	37 1 <sup>29</sup> / <sub>64</sub>	35 1.378	M16 5/8
25 7/8 1	UKFL306D1;H2306X UKFL306D1;HS2306 UKFL306D1;HE2306X	180 7 <sup>3</sup> / <sub>32</sub>	134 5 <sup>9</sup> / <sub>32</sub>	18 45/64	15 19/32	32 1 <sup>1</sup> / <sub>4</sub>	23 29/32	90 3 <sup>17</sup> / <sub>32</sub>	40.5 1 <sup>19</sup> / <sub>32</sub>	38 1.496	M20 3/4
30 1 1/8	UKFL307D1;H2307X UKFL307D1;HS2307	185 7 <sup>3</sup> / <sub>32</sub>	141 5 <sup>35</sup> / <sub>64</sub>	20 25/32	16 5/8	36 1 <sup>13</sup> / <sub>32</sub>	23 29/32	100 3 <sup>15</sup> / <sub>16</sub>	45.5 1 <sup>51</sup> / <sub>64</sub>	43 1.693	M20 3/4
35 1 1/4 1 3/8	UKFL308D1;H2308X UKFL308D1;HE2308X UKFL308D1;HS2308X	200 7 <sup>7</sup> / <sub>8</sub>	158 6 <sup>7</sup> / <sub>32</sub>	23 29/32	17 21/32	40 1 <sup>9</sup> / <sub>16</sub>	23 29/32	112 4 <sup>13</sup> / <sub>32</sub>	50 1 <sup>31</sup> / <sub>32</sub>	46 1.811	M20 3/4
40 1 7/16 1 1/2 1 5/8	UKFL309D1;H2309X UKFL309D1;HA2309 UKFL309D1;HE2309X UKFL309D1;HS2309X	230 9 <sup>1</sup> / <sub>16</sub>	177 6 <sup>31</sup> / <sub>32</sub>	25 63/64	18 23/32	44 1 <sup>23</sup> / <sub>32</sub>	25 63/64	125 4 <sup>29</sup> / <sub>32</sub>	54.5 2 <sup>9</sup> / <sub>64</sub>	50 1.969	M22 7/8
45 1 5/8 1 11/16 1 3/4	UKFL310D1;H2310X UKFL310D1;HS2310 UKFL310D1;HA2310 UKFL310D1;HE2310X	240 9 <sup>7</sup> / <sub>16</sub>	187 7 <sup>23</sup> / <sub>64</sub>	28 1 <sup>7</sup> / <sub>64</sub>	19 3/4	48 1 <sup>7</sup> / <sub>8</sub>	25 63/64	140 5 <sup>1</sup> / <sub>2</sub>	60.5 2 <sup>3</sup> / <sub>8</sub>	55 2.165	M22 7/8
50 1 7/8 1 15/16 2	UKFL311D1;H2311X UKFL311D1;HS2311 UKFL311D1;HA2311 UKFL311D1;HE2311XY	250 9 <sup>27</sup> / <sub>32</sub>	198 7 <sup>51</sup> / <sub>64</sub>	30 1 <sup>3</sup> / <sub>16</sub>	20 25/32	52 2 <sup>1</sup> / <sub>16</sub>	25 63/64	150 5 <sup>29</sup> / <sub>32</sub>	64 2 <sup>33</sup> / <sub>64</sub>	59 2.323	M22 7/8
55 2 1/8	UKFL312D1;H2312X UKFL312D1;HS2312	270 10 <sup>5</sup> / <sub>8</sub>	212 8 <sup>11</sup> / <sub>32</sub>	33 1 <sup>19</sup> / <sub>64</sub>	22 7/8	56 2 <sup>7</sup> / <sub>32</sub>	31 1 <sup>7</sup> / <sub>32</sub>	160 6 <sup>5</sup> / <sub>16</sub>	69.5 2 <sup>47</sup> / <sub>64</sub>	62 2.441	M27 1

- Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
 In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.  
 To distinguish it, a suffix "Y" is added.  
<sup>(4)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
 Example: CM-UKFL305D1;HE2305

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number <sup>(4)</sup> cast dust cover type	Nominal dimensions				Mass of unit	
			t max.	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UKFL	C(CM)
			mm inch				kg lb	
UK305D1;H2305X UK305D1;HE2305	FL305D1 FL305D1	C(CM)-UKFL305D1;H2305X C(CM)-UKFL305ED1;HE2305	2 5/64	56 2 <sup>7</sup> / <sub>32</sub>	86 3 <sup>3</sup> / <sub>8</sub>	40 1 <sup>9</sup> / <sub>16</sub>	1.0 2.2	1.3 2.9
UK306D1;H2306X UK306D1;HS2306 UK306D1;HE2306X	FL306D1 FL306D1 FL306D1	C(CM)-UKFL306D1;H2306X C(CM)-UKFL306SD1;HS2306 C(CM)-UKFL306ED1;HE2306X	2 5/64	60 2 <sup>3</sup> / <sub>8</sub>	101 3 <sup>31</sup> / <sub>32</sub>	45 1 <sup>25</sup> / <sub>32</sub>	1.5 3.3	1.8 4.0
UK307D1;H2307X UK307D1;HS2307	FL307D1 FL307D1	C(CM)-UKFL307D1;H2307X C(CM)-UKFL307SD1;HS2307	3 1/8	68 2 <sup>11</sup> / <sub>16</sub>	110 4 <sup>11</sup> / <sub>32</sub>	50 1 <sup>31</sup> / <sub>32</sub>	1.8 4.0	2.2 4.9
UK308D1;H2308X UK308D1;HE2308X UK308D1;HS2308X	FL308D1 FL308D1 FL308D1	C(CM)-UKFL308D1;H2308X C(CM)-UKFL308ED1;HE2308X C(CM)-UKFL308SD1;HS2308X	3 1/8	76 3	122 4 <sup>13</sup> / <sub>16</sub>	56 2 <sup>7</sup> / <sub>32</sub>	2.2 4.9	3.0 6.6
UK309D1;H2309X UK309D1;HA2309 UK309D1;HE2309X UK309D1;HS2309X	FL309D1 FL309D1 FL309D1 FL309D1	C(CM)-UKFL309D1;H2309X C(CM)-UKFL309AD1;HA2309 C(CM)-UKFL309ED1;HE2309X C(CM)-UKFL309SD1;HS2309X	3 1/8	80 3 <sup>5</sup> / <sub>32</sub>	135 5 <sup>5</sup> / <sub>16</sub>	62 2 <sup>7</sup> / <sub>16</sub>	3.0 6.6	3.9 8.6
UK310D1;H2310X UK310D1;HS2310 UK310D1;HA2310 UK310D1;HE2310X	FL310D1 FL310D1 FL310D1 FL310D1	C(CM)-UKFL310D1;H2310X C(CM)-UKFL310SD1;HS2310 C(CM)-UKFL310AD1;HA2310 C(CM)-UKFL310ED1;HE2310X	3 1/8	88 3 <sup>15</sup> / <sub>32</sub>	152 5 <sup>31</sup> / <sub>32</sub>	70 2 <sup>3</sup> / <sub>4</sub>	4.1 9.0	5.1 11
UK311D1;H2311X UK311D1;HS2311 UK311D1;HA2311 UK311D1;HE2311XY	FL311D1 FL311D1 FL311D1 FL311D1	C(CM)-UKFL311D1;H2311X C(CM)-UKFL311SD1;HS2311 C(CM)-UKFL311AD1;HA2311 C(CM)-UKFL311ED1;HE2311XY	4 5/32	92 3 <sup>5</sup> / <sub>8</sub>	162 6 <sup>3</sup> / <sub>8</sub>	75 2 <sup>15</sup> / <sub>16</sub>	4.6 10	6.0 13
UK312D1;H2312X UK312D1;HS2312	FL312D1 FL312D1	C(CM)-UKFL312D1;H2312X C(CM)-UKFL312SD1;HS2312	4 5/32	100 3 <sup>15</sup> / <sub>16</sub>	175 6 <sup>7</sup> / <sub>8</sub>	80 3 <sup>5</sup> / <sub>32</sub>	5.7 13	7.7 17

## Rhombus flanged unit, cast housing Adapter type



Cast dust cover type  
Open end **C-UKFL...D1**  
Closed end **CM-UKFL...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )	Nominal dimensions									Bolt size mm inch
		mm inch									
		H	J	A <sub>2</sub>	A <sub>1</sub>	A	N	L	A <sub>0</sub>	B <sub>1</sub>	
60 2 3/16 2 1/4 2 3/8	<b>UKFL313D1;H2313X</b> <b>UKFL313D1;HA2313</b> <b>UKFL313D1;HE2313X</b> <b>UKFL313D1;HS2313X</b>	295 11 5/8	240 9 29/64	33 1 19/64	25 31/32	58 2 9/32	31 1 7/32	175 6 7/8	71.5 2 13/16	65 2.559	M27 1
65 2 7/16 2 1/2	<b>UKFL315D1;H2315X</b> <b>UKFL315D1;HA2315</b> <b>UKFL315D1;HE2315X</b>	320 12 19/32	260 10 15/64	39 1 17/32	30 1 3/16	66 2 19/32	35 1 3/8	195 7 11/16	81.5 3 13/64	73 2.874	M30 1 1/8
70 2 11/16 2 3/4	<b>UKFL316D1;H2316X</b> <b>UKFL316D1;HA2316</b> <b>UKFL316D1;HE2316X</b>	355 13 31/32	285 11 7/32	38 1 1/2	32 1 1/4	68 2 11/16	38 1 1/2	210 8 9/32	84 3 5/16	78 3.071	M33 1 1/4
75 2 15/16 3	<b>UKFL317D1;H2317X</b> <b>UKFL317D1;HA2317X</b> <b>UKFL317D1;HE2317X</b>	370 14 9/16	300 11 13/16	44 1 47/64	32 1 1/4	74 2 29/32	38 1 1/2	220 8 21/32	92 3 5/8	82 3.228	M33 1 1/4
80 3 3/16	<b>UKFL318D1;H2318X</b> <b>UKFL318D1;HA2318X</b>	385 15 5/32	315 12 13/32	44 1 47/64	36 1 13/32	76 3	38 1 1/2	235 9 1/4	94 3 45/64	86 3.386	M33 1 1/4
85 3 1/4	<b>UKFL319D1;H2319X</b> <b>UKFL319D1;HE2319X</b>	405 15 15/16	330 12 63/64	59 2 21/64	40 1 9/16	94 3 11/16	41 1 39/64	250 9 27/32	111.5 4 25/64	90 3.543	M36 1 3/8
90 3 7/16 3 1/2	<b>UKFL320D1;H2320X</b> <b>UKFL320D1;HA2320</b> <b>UKFL320D1;HE2320X</b>	440 17 5/16	360 14 11/64	59 2 21/64	40 1 9/16	94 3 11/16	44 1 47/64	270 10 5/8	115.5 4 35/64	97 3.819	M39 1 1/2
100	<b>UKFL322D1;H2322X</b>	470	390	60	42	96	44	300	121	105	M39
110	<b>UKFL324D1;H2324</b>	520	430	65	48	110	47	330	130	112	M42
115	<b>UKFL326D1;H2326</b>	550	460	65	50	115	47	360	133	121	M42
125	<b>UKFL328D1;H2328</b>	600	500	75	60	125	51	400	146.5	131	M45



Notes <sup>(1)</sup> These numbers indicate lubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
Example: CM-UKFL305D1;HE2305

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number <sup>(3)</sup> cast dust cover type	Nominal dimensions				Mass of unit	
			t max.	A <sub>5</sub>	L <sub>1</sub>	L <sub>2</sub>	UKFL	C(CM)
			mm inch				kg lb	
UK313D1;H2313X UK313D1;HA2313 UK313D1;HE2313X UK313D1;HS2313X	FL313D1 FL313D1 FL313D1 FL313D1	<b>C(CM)-UKFL313D1;H2313X</b> <b>C(CM)-UKFL313AD1;HA2313</b> <b>C(CM)-UKFL313ED1;HE2313X</b> <b>C(CM)-UKFL313SD1;HS2313X</b>	4 5/32	103 4 1/16	189 7 7/16	88 3 15/32	7.4 16	9.8 22
UK315D1;H2315X UK315D1;HA2315 UK315D1;HE2315X	FL315D1 FL315D1 FL315D1	<b>C(CM)-UKFL315D1;H2315X</b> <b>C(CM)-UKFL315AD1;HA2315</b> <b>C(CM)-UKFL315ED1;HE2315X</b>	4 5/32	114 4 1/2	210 8 9/32	98 3 27/32	9.9 22	13 29
UK316D1;H2316X UK316D1;HA2316 UK316D1;HE2316X	FL316D1 FL316D1 FL316D1	<b>C(CM)-UKFL316D1;H2316X</b> <b>C(CM)-UKFL316AD1;HA2316</b> <b>C(CM)-UKFL316ED1;HE2316X</b>	4 5/32	116 4 9/16	222 8 3/4	105 4 1/8	13 29	17 37
UK317D1;H2317X UK317D1;HA2317X UK317D1;HE2317X	FL317D1 FL317D1 FL317D1	<b>C(CM)-UKFL317D1;H2317X</b> <b>C(CM)-UKFL317AD1;HA2317X</b> <b>C(CM)-UKFL317ED1;HE2317X</b>	5 13/64	127 5	234 9 7/32	110 4 11/32	15 33	18 40
UK318D1;H2318X UK318D1;HA2318X	FL318D1 FL318D1	<b>C(CM)-UKFL318D1;H2318X</b> <b>C(CM)-UKFL318AD1;HA2318X</b>	5 13/64	129 5 3/32	247 9 23/32	118 4 21/32	18 40	22 49
UK319D1;H2319X UK319D1;HE2319X	FL319D1 FL319D1	<b>C(CM)-UKFL319D1;H2319X</b> <b>C(CM)-UKFL319ED1;HE2319X</b>	5 13/64	149 5 7/8	260 10 1/4	125 4 29/32	22 49	27 60
UK320D1;H2320X UK320D1;HA2320 UK320D1;HE2320X	FL320D1 FL320D1 FL320D1	<b>C(CM)-UKFL320D1;H2320X</b> <b>C(CM)-UKFL320AD1;HA2320</b> <b>C(CM)-UKFL320ED1;HE2320X</b>	5 13/64	154 6 1/16	280 11 1/32	135 5 5/16	26 57	32 71
UK322D1;H2322X	FL322D1	<b>C(CM)-UKFL322D1;H2322X</b>	5	160	315	150	34	41
UK324D1;H2324	FL324D1	<b>C(CM)-UKFL324D1;H2324</b>	5	172	342	165	47	52
UK326D1;H2326	FL326D1	<b>C(CM)-UKFL326D1;H2326</b>	6	178	376	180	58	65
UK328D1;H2328	FL328D1	<b>C(CM)-UKFL328D1;H2328</b>	6	192	410	200	82	90



## Rhombus flanged unit, cast housing Adapter type



**Cast dust cover type**  
Open end **C-UKFL...D1**  
Closed end **CM-UKFL...D1**

Shaft dia.  mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions									
		mm inch									
		<i>H</i>	<i>J</i>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>1</sub>	<i>A</i>	<i>N</i>	<i>L</i>	<i>A</i> <sub>0</sub>	<i>B</i> <sub>1</sub>	<i>F</i> min.
20 3/4	<b>UKFLX05D1;H2305X</b> <b>UKFLX05D1;HE2305</b>	141 5 9/16	117 4 39/64	18 45/64	13 1/2	30 1 3/16	12 15/32	83 3 9/32	39 1 17/32	35 1.378	-
25 7/8 1	<b>UKFLX06D1;H2306X</b> <b>UKFLX06D1;HS2306</b> <b>UKFLX06D1;HE2306X</b>	156 6 5/32	130 5 1/8	19 3/4	15 19/32	34 1 11/32	16 5/8	95 3 3/4	41.5 1 41/64	38 1.496	-
30 1 1/8	<b>UKFLX07D1;H2307X</b> <b>UKFLX07D1;HS2307</b>	171 6 23/32	144 5 43/64	21 53/64	16 5/8	38 1 1/2	16 5/8	105 4 1/8	45.5 1 51/64	43 1.693	-
35 1 1/4 1 3/8	<b>UKFLX08D1;H2308X</b> <b>UKFLX08D1;HE2308X</b> <b>UKFLX08D1;HS2308X</b>	179 7 1/16	148 5 59/64	22 55/64	16 5/8	40 1 9/16	16 5/8	111 4 3/8	47.5 1 7/8	46 1.811	46 1 13/16
40 1 7/16 1 1/2 1 5/8	<b>UKFLX09D1;H2309X</b> <b>UKFLX09D1;HA2309</b> <b>UKFLX09D1;HE2309X</b> <b>UKFLX09D1;HS2309X</b>	189 7 7/16	157 6 3/16	23 29/32	16 5/8	40 1 9/16	16 5/8	116 4 9/16	50 1 31/32	50 1.969	52 2 1/16
45 1 5/8 1 11/16 1 3/4	<b>UKFLX10D1;H2310X</b> <b>UKFLX10D1;HS2310</b> <b>UKFLX10D1;HA2310</b> <b>UKFLX10D1;HE2310X</b>	216 8 1/2	184 7 1/4	26 1 1/32	18 23/32	44 1 23/32	19 3/4	133 5 1/4	55.5 2 3/16	55 2.165	57 2 3/4

- Notes** <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve. In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> If the inch series housing units with dust cover are ordered with a closed end, the suffixes E, S or A are not included.  
Example: CM-UKFLX05D1;HE2305

**Remarks** Please refer to page A21 for size of grease fitting.

Bolt size  mm inch	Bearing number	Housing number	Unit number <sup>(2)</sup> cast dust cover type	Nominal dimensions				Mass of unit	
				mm inch				kg lb	
				<i>t</i> max.	<i>A</i> <sub>5</sub>	<i>L</i> <sub>1</sub>	<i>L</i> <sub>2</sub>	UKF	C(CM)
M10 3/8	UKX05D1;H2305X UKX05D1;HE2305	FLX05D1 FLX05D1	<b>C(CM)-UKFLX05D1;H2305X</b> <b>C(CM)-UKFLX05ED1;HE2305</b>	2 5/64	56 2 7/32	86 3 3/8	41.5 1 5/8	1.0 2.2	1.2 2.7
M14 1/2	UKX06D1;H2306X UKX06D1;HS2306 UKX06D1;HE2306X	FLX06D1 FLX06D1 FLX06D1	<b>C(CM)-UKFLX06D1;H2306X</b> <b>C(CM)-UKFLX06SD1;HS2306</b> <b>C(CM)-UKFLX06ED1;HE2306X</b>	2 5/64	59 2 5/16	98.5 3 7/8	47.5 1 7/8	1.4 3.1	1.6 3.5
M14 1/2	UKX07D1;H2307X UKX07D1;HS2307	FLX07D1 FLX07D1	<b>C(CM)-UKFLX07D1;H2307X</b> <b>C(CM)-UKFLX07SD1;HS2307</b>	3 1/8	66 2 19/32	108.5 4 9/32	52.5 2 1/16	1.8 4.0	2.2 4.9
M14 1/2	UKX08D1;H2308X UKX08D1;HE2308X UKX08D1;HS2308X	FLX08D1 FLX08D1 FLX08D1	<b>C(CM)-UKFLX08D1;H2308X</b> <b>C(CM)-UKFLX08ED1;HE2308X</b> <b>C(CM)-UKFLX08SD1;HS2308X</b>	3 1/8	70 2 3/4	114.5 4 1/4	55.5 2 3/16	2.2 4.9	2.6 5.7
M14 1/2	UKX09D1;H2309X UKX09D1;HA2309 UKX09D1;HE2309X UKX09D1;HS2309X	FLX09D1 FLX09D1 FLX09D1 FLX09D1	<b>C(CM)-UKFLX09D1;H2309X</b> <b>C(CM)-UKFLX09AD1;HA2309</b> <b>C(CM)-UKFLX09ED1;HE2309X</b> <b>C(CM)-UKFLX09SD1;HS2309X</b>	3 1/8	73 2 7/8	119.5 4 23/32	58 2 9/32	2.2 4.9	2.7 6.0
M16 5/8	UKX10D1;H2310X UKX10D1;HS2310 UKX10D1;HA2310 UKX10D1;HE2310X	FLX10D1 FLX10D1 FLX10D1 FLX10D1	<b>C(CM)-UKFLX10D1;H2310X</b> <b>C(CM)-UKFLX10SD1;HS2310</b> <b>C(CM)-UKFLX10AD1;HA2310</b> <b>C(CM)-UKFLX10ED1;HE2310X</b>	3 1/8	76 3	133.5 5 1/4	66.5 2 5/8	3.1 6.8	3.6 7.9

## Take-up unit, cast housing Adapter type



**Pressed steel dust cover type**  
Open end **Z-UKT...D1**  
Closed end **ZM-UKT...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )( <sup>3</sup> )	Nominal dimensions															Bearing number
		mm inch															
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B_1$	
20 3/4	UKT205D1;H2305X UKT205D1;HE2305	16	12	51	32	19	51	12	76	89	97	24	32	35	62	35	UK205D1;H2305X UK205D1;HE2305
25 7/8	UKT206D1;H2306X UKT206D1;HS2306 UKT206D1;HE2306X	16	12	56	37	22	57	12	89	102	113	28	37	43	70	38	UK206D1;H2306X UK206D1;HS2306 UK206D1;HE2306X
30 1 1/8	UKT207D1;H2307X UKT207D1;HS2307	16	15	64	37	22	64	12	89	102	129	30	37	51	78	43	UK207D1;H2307X UK207D1;HS2307
35 1 1/4 1 3/8	UKT208D1;H2308X UKT208D1;HE2308X UKT208D1;HS2308X	19	18	83	49	29	83	16	102	114	144	33	49	56	88	46	UK208D1;H2308X UK208D1;HE2308X UK208D1;HS2308X
40 1 7/16 1 1/2 1 5/8	UKT209D1;H2309X UKT209D1;HA2309 UKT209D1;HE2309X UKT209D1;HS2309X	19	18	83	49	29	83	16	102	117	145	35	49	57	88	50	UK209D1;H2309X UK209D1;HA2309 UK209D1;HE2309X UK209D1;HS2309X
45 1 5/8 1 11/16 1 3/4	UKT210D1;H2310X UKT210D1;HS2310 UKT210D1;HA2310 UKT210D1;HE2310X	19	18	83	49	29	86	16	102	117	151	37	49	59	92	55	UK210D1;H2310X UK210D1;HS2310 UK210D1;HA2310 UK210D1;HE2310X
50 1 7/8 1 15/16 2	UKT211D1;H2311X UKT211D1;HS2311 UKT211D1;HA2311 UKT211D1;HE2311XY	25	21	102	64	35	95	22	130	146	171	38	64	65	106	59	UK211D1;H2311X UK211D1;HS2311 UK211D1;HA2311 UK211D1;HE2311XY
55 2 1/8	UKT212D1;H2312X UKT212D1;HS2312	32	21	102	64	35	102	22	130	146	194	42	64	75	119	62	UK212D1;H2312X UK212D1;HS2312

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.  
To distinguish it, a suffix "Y" is added.

Remarks Please refer to page A21 for size of grease fitting.



**Cast dust cover type**  
Open end **C-UKT...D1**  
Closed end **CM-UKT...D1**

Housing number	Unit number pressed steel dust cover type	Unit number cast dust cover type	Nominal dimensions				Mass of unit		
			mm inch				kg lb		
			$t$ max.	$A_4$	$L_4$	$A_5$	UKT	Z(ZM)	C(CM)
T205D1 T205D1	Z(ZM)-UKT205D1;H2305X Z(ZM)-UKT205ED1;HE2305	C(CM)-UKT205D1;H2305X C(CM)-UKT205ED1;HE2305	2 5/8	48 1 29/32	100.5 3 31/32	70 2 3/4	0.9 2.0	0.9 2.0	1.2 2.6
T206D1 T206D1 T206D1	Z(ZM)-UKT206D1;H2306X Z(ZM)-UKT206SD1;HS2306 Z(ZM)-UKT206ED1;HE2306X	C(CM)-UKT206D1;H2306X C(CM)-UKT206SD1;HS2306 C(CM)-UKT206ED1;HE2306X	2 5/64	53 2 3/32	113.5 4 15/32	75 2 15/16	1.3 2.9	1.4 3.1	1.8 4.0
T207D1 T207D1	Z(ZM)-UKT207D1;H2307X Z(ZM)-UKT207SD1;HS2307	C(CM)-UKT207D1;H2307X C(CM)-UKT207SD1;HS2307	3 1/8	60 2 11/32	129 5 3/32	80 3 3/32	1.7 3.7	1.8 4.0	2.2 4.9
T208D1 T208D1 T208D1	Z(ZM)-UKT208D1;H2308X Z(ZM)-UKT208ED1;HE2308X Z(ZM)-UKT208SD1;HS2308X	C(CM)-UKT208D1;H2308X C(CM)-UKT208ED1;HE2308X C(CM)-UKT208SD1;HS2308X	3 1/8	69 2 23/32	144 5 21/32	90 3 17/32	2.5 5.5	2.6 5.7	3.3 7.3
T209D1 T209D1 T209D1 T209D1	Z(ZM)-UKT209D1;H2309X Z(ZM)-UKT209AD1;HA2309 Z(ZM)-UKT209ED1;HE2309X Z(ZM)-UKT209SD1;HS2309X	C(CM)-UKT209D1;H2309X C(CM)-UKT209AD1;HA2309 C(CM)-UKT209ED1;HE2309X C(CM)-UKT209SD1;HS2309X	3 1/8	69 2 23/32	145.5 5 29/32	95 3 3/4	2.5 5.5	2.6 5.7	3.5 7.7
T210D1 T210D1 T210D1 T210D1	Z(ZM)-UKT210D1;H2310X Z(ZM)-UKT210SD1;HS2310 Z(ZM)-UKT210AD1;HA2310 Z(ZM)-UKT210ED1;HE2310X	C(CM)-UKT210D1;H2310X C(CM)-UKT210SD1;HS2310 C(CM)-UKT210AD1;HA2310 C(CM)-UKT210ED1;HE2310X	3 1/8	76 3	152 5 31/32	100 3 15/16	2.7 6.0	2.8 6.2	3.8 8.4
T211D1 T211D1 T211D1 T211D1	Z(ZM)-UKT211D1;H2311X Z(ZM)-UKT211SD1;HS2311 Z(ZM)-UKT211AD1;HA2311 Z(ZM)-UKT211ED1;HE2311XY	C(CM)-UKT211D1;H2311X C(CM)-UKT211SD1;HS2311 C(CM)-UKT211AD1;HA2311 C(CM)-UKT211ED1;HE2311XY	4 5/32	77 3 3/32	171.5 6 3/4	100 3 15/16	4.1 9.0	4.3 9.5	5.3 12
T212D1 T212D1	Z(ZM)-UKT212D1;H2312X Z(ZM)-UKT212SD1;HS2312	C(CM)-UKT212D1;H2312X C(CM)-UKT212SD1;HS2312	4 5/32	89 3 1/2	194 7 5/8	115 4 17/32	4.9 11	5.2 11	6.3 14

## Take-up unit, cast housing Adapter type



**Pressed steel dust cover type**  
Open end **Z-UKT...D1**  
Closed end **ZM-UKT...D1**

Shaft dia. mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions														Bearing number	
		mm inch															
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$		$B_1$
60 2 3/16 2 1/4 2 3/8	UKT213D1;H2313X UKT213D1;HA2313 UKT213D1;HE2313X UKT213D1;HS2313X	32	23	111	70	41	121	26	151	167	224	44	70	87	137	65	UK213D1;H2313X UK213D1;HA2313 UK213D1;HE2313X UK213D1;HS2313X
65 2 7/16 2 1/2	UKT215D1;H2315X UKT215D1;HA2315 UKT215D1;HE2315X	32	23	111	70	41	121	26	151	167	232	48	70	92	140	73	UK215D1;H2315X UK215D1;HA2315 UK215D1;HE2315X
70 2 11/16 2 3/4	UKT216D1;H2316X UKT216D1;HA2316 UKT216D1;HE2316X	32	23	111	70	41	121	26	165	184	235	51	70	95	140	78	UK216D1;H2316X UK216D1;HA2316 UK216D1;HE2316X
75 2 15/16 3	UKT217D1;H2317X UKT217D1;HA2317X UKT217D1;HE2317X	38	31	124	73	48	157	30	173	198	260	54	73	98	162	82	UK217D1;H2317X UK217D1;HA2317X UK217D1;HE2317X

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.


Remarks Please refer to page A21 for size of grease fitting.



**Cast dust cover type**  
Open end **C-UKT...D1**  
Closed end **CM-UKT...D1**

Housing number	Unit number pressed steel dust cover type	Unit number cast dust cover type	Nominal dimensions				Mass of unit		
			mm inch				kg lb		
			$t$ max.	$A_4$	$L_4$	$A_5$	UKT	Z(ZM)	C(CM)
T213D1	Z(ZM)-UKT213D1;H2313X	C(CM)-UKT213D1;H2313X	4	91	224	120	7.1	7.4	8.8
T213D1	Z(ZM)-UKT213AD1;HA2313	C(CM)-UKT213AD1;HA2313	5/32	3 19/32	8 13/16	4 23/32	16	16	19
T213D1	Z(ZM)-UKT213ED1;HE2313X	C(CM)-UKT213ED1;HE2313X	5/32	3 19/32	8 13/16	4 23/32	16	16	19
T213D1	Z(ZM)-UKT213SD1;HS2313X	C(CM)-UKT213SD1;HS2313X	5/32	3 19/32	8 13/16	4 23/32	16	16	19
T215D1	—	C(CM)-UKT215D1;H2315X	4	—	232	135	7.7	—	10
T215D1	—	C(CM)-UKT215AD1;HA2315	5/32	—	9 1/8	5 5/16	17	—	22
T215D1	—	C(CM)-UKT215ED1;HE2315X	5/32	—	9 1/8	5 5/16	17	—	22
T216D1	—	C(CM)-UKT216D1;H2316X	4	—	235	145	8.7	—	12
T216D1	—	C(CM)-UKT216AD1;HA2316	5/32	—	9 1/4	5 23/32	19	—	26
T216D1	—	C(CM)-UKT216ED1;HE2316X	5/32	—	9 1/4	5 23/32	19	—	26
T217D1	—	C(CM)-UKT217D1;H2317X	5	—	260	155	11	—	15
T217D1	—	C(CM)-UKT217AD1;HA2317X	13/64	—	10 1/4	6 3/32	24	—	33
T217D1	—	C(CM)-UKT217ED1;HE2317X	13/64	—	10 1/4	6 3/32	24	—	33

## Take-up unit, cast housing Adapter type



Cast dust cover type  
Open end C-UKT...D1  
Closed end CM-UKT...D1

Shaft dia.  mm inch	Unit number <sup>(1)</sup> ( <sup>(2)</sup> ) <sup>(3)</sup>	Nominal dimensions														
		mm inch														
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B_1$
20 3/4	UKT305D1;H2305X UKT305D1;HE2305	16 5/8	14 9/16	62 2 7/16	36 1 13/32	26 1 1/2	65 2 9/16	12 0.472	80 2 5/32	89 3 1/2	122 4 13/16	26 1 1/2	36 1 13/32	46 1 13/16	76 3	35 1.378
25 7/8 1	UKT306D1;H2306X UKT306D1;HS2306 UKT306D1;HE2306X	18 23/32	16 5/8	70 2 3/4	41 1 5/8	28 1 3/32	74 2 29/32	16 0.630	90 3 35/64	100 3 15/16	137 5 13/32	28 1 3/32	41 1 5/8	52 2 1/16	85 3 11/32	38 1.496
30 1 1/8	UKT307D1;H2307X UKT307D1;HS2307	20 25/32	17 21/32	75 2 15/16	45 1 25/32	30 1 1/16	80 3 5/32	16 0.630	100 3 15/16	111 4 3/8	150 5 29/32	32 1 1/4	45 1 25/32	56 2 7/16	94 3 11/16	43 1.693
35 1 1/4 1 3/8	UKT308D1;H2308X UKT308D1;HE2308X UKT308D1;HS2308X	22 7/8	19 3/4	83 3 9/32	50 1 31/32	32 1 1/4	89 3 1/2	18 0.709	112 4 13/32	124 4 7/8	162 6 3/8	34 1 11/32	50 1 31/32	62 2 7/16	100 3 15/16	46 1.811
40 1 7/16 1 1/2 1 5/8	UKT309D1;H2309X UKT309D1;HA2309 UKT309D1;HE2309X UKT309D1;HS2309X	24 15/16	20 25/32	90 3 17/32	55 2 5/32	34 1 11/32	97 3 13/16	18 0.709	125 4 59/64	138 5 7/16	178 7	38 1 1/2	55 2 5/32	68 2 11/16	110 4 11/32	50 1.969
45 1 5/8 1 11/16 1 3/4	UKT310D1;H2310X UKT310D1;HS2310 UKT310D1;HA2310 UKT310D1;HE2310X	27 1 1/16	22 7/8	98 3 27/32	61 2 13/32	37 1 15/32	106 4 3/16	20 0.787	140 5 33/64	151 5 15/16	192 7 9/16	40 1 9/16	61 2 13/32	74 2 29/32	118 4 21/32	55 2.165
50 1 7/8 1 15/16 2	UKT311D1;H2311X UKT311D1;HS2311 UKT311D1;HA2311 UKT311D1;HE2311XY	29 1 5/32	23 29/32	105 4 1/8	66 2 19/32	39 1 17/32	115 4 17/32	22 0.866	150 5 29/32	163 6 13/32	207 8 5/32	44 1 23/32	66 2 19/32	80 3 5/32	127 5	59 2.323
55 2 1/8	UKT312D1;H2312X UKT312D1;HS2312	31 1 1/32	25 31/32	113 4 7/16	71 2 25/32	41 1 5/8	123 4 27/32	22 0.866	160 6 19/64	178 7	220 8 21/32	46 1 13/16	71 2 25/32	85 3 11/32	135 5 5/16	62 2.441

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.

In this case the lock washer with the straight inner prong should be used.

<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.

To distinguish it, a suffix "Y" is added.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			$t$ max.	$L_4$	$A_5$	UKT	C(CM)
UK305D1;H2305X UK305D1;HE2305	T305D1 T305D1	C(CM)-UKT305D1;H2305X C(CM)-UKT305ED1;HE2305	2 5/64	122 4 13/16	80 3 5/32	1.4 3.1	1.9 4.2
UK306D1;H2306X UK306D1;HS2306 UK306D1;HE2306X	T306D1 T306D1 T306D1	C(CM)-UKT306D1;H2306X C(CM)-UKT306SD1;HS2306 C(CM)-UKT306ED1;HE2306X	2 5/64	139 5 31/32	85 3 11/32	1.8 4.0	2.5 5.5
UK307D1;H2307X UK307D1;HS2307	T307D1 T307D1	C(CM)-UKT307D1;H2307X C(CM)-UKT307SD1;HS2307	3 1/8	152 5 31/32	95 3 3/4	2.4 5.3	3.3 7.3
UK308D1;H2308X UK308D1;HE2308X UK308D1;HS2308X	T308D1 T308D1 T308D1	C(CM)-UKT308D1;H2308X C(CM)-UKT308ED1;HE2308X C(CM)-UKT308SD1;HS2308X	3 1/8	164 6 15/32	105 4 1/8	3.0 6.6	4.3 9.5
UK309D1;H2309X UK309D1;HA2309 UK309D1;HE2309X UK309D1;HS2309X	T309D1 T309D1 T309D1 T309D1	C(CM)-UKT309D1;H2309X C(CM)-UKT309AD1;HA2309 C(CM)-UKT309ED1;HE2309X C(CM)-UKT309SD1;HS2309X	3 1/8	181 7 1/8	110 4 11/32	4.0 8.8	5.6 12
UK310D1;H2310X UK310D1;HS2310 UK310D1;HA2310 UK310D1;HE2310X	T310D1 T310D1 T310D1 T310D1	C(CM)-UKT310D1;H2310X C(CM)-UKT310SD1;HS2310 C(CM)-UKT310AD1;HA2310 C(CM)-UKT310ED1;HE2310X	3 1/8	197 7 3/4	120 4 23/32	5.1 11	7.1 16
UK311D1;H2311X UK311D1;HS2311 UK311D1;HA2311 UK311D1;HE2311XY	T311D1 T311D1 T311D1 T311D1	C(CM)-UKT311D1;H2311X C(CM)-UKT311SD1;HS2311 C(CM)-UKT311AD1;HA2311 C(CM)-UKT311ED1;HE2311XY	4 5/32	211 8 5/16	125 4 29/32	6.3 14	8.6 19
UK312D1;H2312X UK312D1;HS2312	T312D1 T312D1	C(CM)-UKT312D1;H2312X C(CM)-UKT312SD1;HS2312	4 5/32	227 8 15/16	135 5 5/16	7.6 17	10 22

## Take-up unit, cast housing Adapter type




Cast dust cover type  
Open end C-UKT...D1  
Closed end CM-UKT...D1

Shaft dia. mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions														
		mm inch														
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B_1$
60 2 3/16 2 1/4 2 3/8	UKT313D1;H2313X UKT313D1;HA2313 UKT313D1;HE2313X UKT313D1;HS2313X	32	27	116	70	43	134	26	170	190	238	50	80	92	146	65
65 2 7/16 2 1/2	UKT315D1;H2315X UKT315D1;HA2315 UKT315D1;HE2315X	36	27	132	85	46	150	26	192	216	262	55	90	102	160	73
70 2 11/16 2 3/4	UKT316D1;H2316X UKT316D1;HA2316 UKT316D1;HE2316X	42	30	150	98	53	160	30	204	230	282	60	102	108	174	78
75 2 15/16 3	UKT317D1;H2317X UKT317D1;HA2317X UKT317D1;HE2317X	42	32	152	98	53	170	32	214	240	298	64	102	115	183	82
80 3 3/16	UKT318D1;H2318X UKT318D1;HA2318X	46	32	160	106	57	175	32	228	255	312	66	110	120	192	86
85 3 1/4	UKT319D1;H2319X UKT319D1;HE2319X	46	33	165	106	57	180	35	240	270	322	72	110	125	197	90
90 3 7/16 3 1/2	UKT320D1;H2320X UKT320D1;HA2320 UKT320D1;HE2320X	48	34	175	115	59	200	35	260	290	345	75	120	135	210	97
100	UKT322D1;H2322X	52	40	185	125	65	215	38	285	320	385	80	130	150	235	105
110	UKT324D1;H2324	60	44	210	140	70	230	45	320	355	432	90	140	165	267	112
115	UKT326D1;H2326	65	47	220	150	75	240	50	350	385	465	100	150	180	285	121
125	UKT328D1;H2328	70	52	230	160	80	255	50	380	415	515	100	155	200	315	131

Notes <sup>(1)</sup> These numbers indicate lubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.  
Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			$t$ max.	$L_4$	$A_5$	UKT	C(CM)
UK313D1;H2313X UK313D1;HA2313 UK313D1;HE2313X UK313D1;HS2313X	T313D1 T313D1 T313D1 T313D1	C(CM)-UKT313D1;H2313X C(CM)-UKT313AD1;HA2313 C(CM)-UKT313ED1;HE2313X C(CM)-UKT313SD1;HS2313X	4 5/32	244 9 9/32	140 5 1/2	9.2 20	12 26
UK315D1;H2315X UK315D1;HA2315 UK315D1;HE2315X	T315D1 T315D1 T315D1	C(CM)-UKT315D1;H2315X C(CM)-UKT315AD1;HA2315 C(CM)-UKT315ED1;HE2315X	4 5/32	268 10 9/16	150 5 29/32	13 29	17 37
UK316D1;H2316X UK316D1;HA2316 UK316D1;HE2316X	T316D1 T316D1 T316D1	C(CM)-UKT316D1;H2316X C(CM)-UKT316AD1;HA2316 C(CM)-UKT316ED1;HE2316X	4 5/32	287 11 5/16	155 6 3/32	16 35	21 46
UK317D1;H2317X UK317D1;HA2317X UK317D1;HE2317X	T317D1 T317D1 T317D1	C(CM)-UKT317D1;H2317X C(CM)-UKT317AD1;HA2317X C(CM)-UKT317ED1;HE2317X	5 13/64	303 11 15/16	170 6 11/16	19 42	25 55
UK318D1;H2318X UK318D1;HA2318X	T318D1 T318D1	C(CM)-UKT318D1;H2318X C(CM)-UKT318AD1;HA2318X	5 13/64	317 12 15/32	170 6 11/16	21 46	28 62
UK319D1;H2319X UK319D1;HE2319X	T319D1 T319D1	C(CM)-UKT319D1;H2319X C(CM)-UKT319ED1;HE2319X	5 13/64	327 12 7/8	180 7 3/32	25 55	32 71
UK320D1;H2320X UK320D1;HA2320 UK320D1;HE2320X	T320D1 T320D1 T320D1	C(CM)-UKT320D1;H2320X C(CM)-UKT320AD1;HA2320 C(CM)-UKT320ED1;HE2320X	5 13/64	350 13 25/32	190 7 15/32	30 66	39 86
UK322D1;H2322X	T322D1	C(CM)-UKT322D1;H2322X	5	395	200	40	51
UK324D1;H2324	T324D1	C(CM)-UKT324D1;H2324	5	439	215	43	69
UK326D1;H2326	T326D1	C(CM)-UKT326D1;H2326	6	476	225	69	85
UK328D1;H2328	T328D1	C(CM)-UKT328D1;H2328	6	519	235	88	107

## Take-up unit, cast housing Adapter type



**Cast dust cover type**  
Open end **C-UKT...D1**  
Closed end **CM-UKT...D1**

Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>(2)</sup> ) <sup>(3)</sup>	Nominal dimensions														
		mm inch														
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B_1$
20 3/4	UKTX05D1;H2305X UKTX05D1;HE2305	16 5/8	12 15/32	56 2 1/32	37 1 15/32	22 7/8	57 2 1/4	12 0.472	89 3 1/2	102 4 1/32	113 4 7/16	28 1 3/32	37 1 15/32	43 1 11/16	70 2 3/4	35 1.378
25 7/8 1	UKTX06D1;H2306X UKTX06D1;HS2306 UKTX06D1;HE2306X	16 5/8	15 19/32	64 2 17/32	37 1 15/32	22 7/8	64 2 17/32	12 0.472	89 3 1/2	102 4 1/32	129 5 3/32	30 1 3/16	37 1 15/32	51 2	78 3 1/16	38 1.496
30 1 1/8	UKTX07D1;H2307X UKTX07D1;HS2307	19 3/4	17 2 1/32	83 3 9/32	49 1 15/16	29 1 5/32	83 3 9/32	16 0.630	102 4 1/64	114 4 1/2	144 5 21/32	36 1 13/32	49 1 15/16	56 2 7/32	88 3 15/32	43 1.693
35 1 1/4 1 3/8	UKTX08D1;H2308X UKTX08D1;HE2308X UKTX08D1;HS2308X	19 3/4	17 2 1/32	83 3 9/32	49 1 15/16	29 1 5/32	83 3 9/32	16 0.630	102 4 1/64	117 4 19/32	144 5 21/32	36 1 13/32	49 1 15/16	57 2 1/4	87 3 7/16	46 1.811
40 1 7/16 1 1/2 1 5/8	UKTX09D1;H2309X UKTX09D1;HA2309 UKTX09D1;HE2309X UKTX09D1;HS2309X	19 3/4	18 23/32	83 3 9/32	49 1 15/16	29 1 5/32	86 3 3/8	16 0.630	102 4 1/64	117 4 19/32	151 5 15/16	38 1 1/2	49 1 15/16	59 2 5/16	92 3 5/8	50 1.969
45 1 5/8 1 11/16 1 3/4	UKTX10D1;H2310X UKTX10D1;HS2310 UKTX10D1;HA2310 UKTX10D1;HE2310X	25 3 1/32	21 13/16	102 4 1/32	64 2 17/32	35 1 3/8	95 3 3/4	22 0.866	130 5 1/8	146 5 3/4	171 6 23/32	42 1 21/32	64 2 17/32	65 2 9/16	106 4 3/16	55 2.165
50 1 7/8 1 15/16 2	UKTX11D1;H2311X UKTX11D1;HS2311 UKTX11D1;HA2311 UKTX11D1;HE2311XY	32 1 1/4	21 13/16	102 4 1/32	64 2 17/32	35 1 3/8	102 4 1/32	22 0.866	130 5 1/8	146 5 3/4	194 7 5/8	44 1 23/32	64 2 17/32	75 2 15/16	119 4 11/16	59 2.323
55 2 1/8	UKTX12D1;H2312X UKTX12D1;HS2312	32 1 1/4	23 29/32	111 4 3/8	70 2 3/4	41 1 5/8	121 4 3/4	26 1.024	151 5 15/16	167 6 9/16	224 8 13/16	48 1 7/8	70 2 3/4	87 3 7/16	137 5 13/32	62 2.441

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.


In this case the lock washer with the straight inner prong should be used.

<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve. To distinguish it, a suffix "Y" is added.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			$t$ max.	$L_4$	$A_5$	UKT	C(CM)
UKX05D1;H2305X UKX05D1;HE2305	TX05D1 TX05D1	C(CM)-UKTX05D1;H2305X C(CM)-UKTX05ED1;HE2305	2 5/64	113.5 4 15/32	75 2 15/16	1.3 2.9	1.8 4.0
UKX06D1;H2306X UKX06D1;HS2306 UKX06D1;HE2306X	TX06D1 TX06D1 TX06D1	C(CM)-UKTX06D1;H2306X C(CM)-UKTX06SD1;HS2306 C(CM)-UKTX06ED1;HE2306X	2 5/64	129 5 3/32	80 3 5/32	1.7 3.7	2.2 4.9
UKX07D1;H2307X UKX07D1;HS2307	TX07D1 TX07D1	C(CM)-UKTX07D1;H2307X C(CM)-UKTX07SD1;HS2307	3 1/8	144 5 21/32	90 3 17/32	2.7 6.0	3.5 7.7
UKX08D1;H2308X UKX08D1;HE2308X UKX08D1;HS2308X	TX08D1 TX08D1 TX08D1	C(CM)-UKTX08D1;H2308X C(CM)-UKTX08ED1;HE2308X C(CM)-UKTX08SD1;HS2308X	3 1/8	144.5 5 11/16	95 3 3/4	2.8 6.2	3.7 8.2
UKX09D1;H2309X UKX09D1;HA2309 UKX09D1;HE2309X UKX09D1;HS2309X	TX09D1 TX09D1 TX09D1 TX09D1	C(CM)-UKTX09D1;H2309X C(CM)-UKTX09AD1;HA2309 C(CM)-UKTX09ED1;HE2309X C(CM)-UKTX09SD1;HS2309X	3 1/8	152 5 31/32	100 3 15/16	2.7 6.0	3.8 8.4
UKX10D1;H2310X UKX10D1;HS2310 UKX10D1;HA2310 UKX10D1;HE2310X	TX10D1 TX10D1 TX10D1 TX10D1	C(CM)-UKTX10D1;H2310X C(CM)-UKTX10SD1;HS2310 C(CM)-UKTX10AD1;HA2310 C(CM)-UKTX10ED1;HE2310X	3 1/8	171.5 6 3/4	100 3 15/16	4.3 9.5	5.5 12
UKX11D1;H2311X UKX11D1;HS2311 UKX11D1;HA2311 UKX11D1;HE2311XY	TX11D1 TX11D1 TX11D1 TX11D1	C(CM)-UKTX11D1;H2311X C(CM)-UKTX11SD1;HS2311 C(CM)-UKTX11AD1;HA2311 C(CM)-UKTX11ED1;HE2311XY	4 5/32	194 7 5/8	115 4 17/32	5.1 11	6.6 15
UKX12D1;H2312X UKX12D1;HS2312	TX12D1 TX12D1	C(CM)-UKTX12D1;H2312X C(CM)-UKTX12SD1;HS2312	4 5/32	224 8 13/16	120 4 23/32	7.2 16	9.0 20

## Take-up unit, cast housing Adapter type



**Cast dust cover type**  
Open end **C-UKT...D1**  
Closed end **CM-UKT...D1**

Shaft dia.  mm inch	Unit number <sup>(1)(2)</sup>	Nominal dimensions														
		mm inch														
		$N_1$	$L_2$	$H_2$	$N_2$	$N$	$L_3$	$A_1$	$H_1$	$H$	$L$	$A_2$	$A$	$r$	$L_1$	$B_1$
60 2 3/16 2 1/4 2 3/8	<b>UKTX13D1;H2313X</b> <b>UKTX13D1;HA2313</b> <b>UKTX13D1;HE2313X</b> <b>UKTX13D1;HS2313X</b>	32	23	111	70	41	121	26	151	167	224	48	70	87	137	65
		1 1/4	29/32	4 3/8	2 3/4	1 5/8	4 3/4	1.024	5 15/16	6 9/16	8 13/16	1 7/8	2 3/4	3 7/16	5 13/32	2.559
65 2 7/16 2 1/2	<b>UKTX15D1;H2315X</b> <b>UKTX15D1;HA2315</b> <b>UKTX15D1;HE2315X</b>	32	23	111	70	41	121	28	165	184	235	48	70	95	140	73
		1 1/4	29/32	4 3/8	2 3/4	1 5/8	4 3/4	1.102	6 1/2	7 1/4	9 1/4	1 7/8	2 3/4	3 3/4	5 1/2	2.874
70 2 11/16 2 3/4	<b>UKTX16D1;H2316X</b> <b>UKTX16D1;HA2316</b> <b>UKTX16D1;HE2316X</b>	38	30	124	73	48	157	28	173	198	260	54	73	98	162	78
		1 1/2	1 3/16	4 7/8	2 7/8	1 7/8	6 3/16	1.102	6 13/16	7 25/32	10 1/4	2 1/8	2 7/8	3 27/32	6 3/8	3.071
75 2 15/16 3	<b>UKTX17D1;H2317X</b> <b>UKTX17D1;HA2317X</b> <b>UKTX17D1;HE2317X</b>	38	30	124	73	48	157	28	173	198	260	54	73	98	162	82
		1 1/2	1 3/16	4 7/8	2 7/8	1 7/8	6 3/16	1.102	6 13/16	7 25/32	10 1/4	2 1/8	2 7/8	3 27/32	6 3/8	3.228


Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.

Remarks Please refer to page A21 for size of grease fitting.

Bearing number	Housing number	Unit number cast dust cover type	Nominal dimensions			Mass of unit	
			mm inch			kg lb	
			$t$ max.	$L_4$	$A_5$	UKT	C(CM)
UKX13D1;H2313X UKX13D1;HA2313 UKX13D1;HE2313X UKX13D1;HS2313X	TX13D1 TX13D1 TX13D1 TX13D1	<b>C(CM)-UKTX13D1;H2313X</b> <b>C(CM)-UKTX13AD1;HA2313</b> <b>C(CM)-UKTX13ED1;HE2313X</b> <b>C(CM)-UKTX13SD1;HS2313X</b>	4 5/32	224 8 13/16	135 5 5/16	7.2 16	9.5 21
UKX15D1;H2315X UKX15D1;HA2315 UKX15D1;HE2315X	TX15D1 TX15D1 TX15D1	<b>C(CM)-UKTX15D1;H2315X</b> <b>C(CM)-UKTX15AD1;HA2315</b> <b>C(CM)-UKTX15ED1;HE2315X</b>	4 5/32	235 9 1/4	145 5 23/32	8.5 19	11 24
UKX16D1;H2316X UKX16D1;HA2316 UKX16D1;HE2316X	TX16D1 TX16D1 TX16D1	<b>C(CM)-UKTX16D1;H2316X</b> <b>C(CM)-UKTX16AD1;HA2316</b> <b>C(CM)-UKTX16ED1;HE2316X</b>	4 5/32	260 10 1/4	155 6 3/32	11 24	14 31
UKX17D1;H2317X UKX17D1;HA2317X UKX17D1;HE2317X	TX17D1 TX17D1 TX17D1	<b>C(CM)-UKTX17D1;H2317X</b> <b>C(CM)-UKTX17AD1;HA2317X</b> <b>C(CM)-UKTX17ED1;HE2317X</b>	5 13/64	262 10 5/16	165 6 1/2	11 24	15 33

## Cartridge unit, cast housing Adapter type



Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )( <sup>3</sup> )	Nominal dimensions				Bearing number	Housing number	Mass of unit kg lb
		<i>H</i>	<i>A</i>	<i>r</i>	<i>B</i> <sub>1</sub>			
20 $\frac{3}{4}$	UKC205D1;H2305X	80	22	2	35	UK205D1;H2305X	C205D1	0.7
	UKC205D1;HE2305	3.1496	$\frac{55}{64}$	0.079	1.378	UK205D1;HE2305	C205D1	1.5
25 $\frac{7}{8}$ 1	UKC206D1;H2306X	85	27	2	38	UK206D1;H2306X	C206D1	0.9
	UKC206D1;HS2306	3.3465	$1\frac{1}{16}$	0.079	1.496	UK206D1;HS2306	C206D1	2.0
	UKC206D1;HE2306X					UK206D1;HE2306X	C206D1	
30 $1\frac{1}{8}$	UKC207D1;H2307X	90	28	2	43	UK207D1;H2307X	C207D1	1.0
	UKC207D1;HS2307	3.5433	$1\frac{7}{64}$	0.079	1.693	UK207D1;HS2307	C207D1	2.2
35 $1\frac{1}{4}$ $1\frac{3}{8}$	UKC208D1;H2308X	100	30	2.5	46	UK208D1;H2308X	C208D1	1.3
	UKC208D1;HE2308X	3.9370	$1\frac{3}{16}$	0.098	1.811	UK208D1;HE2308X	C208D1	2.9
	UKC208D1;HS2308X					UK208D1;HS2308X	C208D1	
40 $1\frac{7}{16}$ $1\frac{1}{2}$ $1\frac{5}{8}$	UKC209D1;H2309X	110	31	2.5	50	UK209D1;H2309X	C209D1	1.6
	UKC209D1;HA2309	4.3307	$1\frac{7}{32}$	0.098	1.969	UK209D1;HA2309	C209D1	3.5
	UKC209D1;HE2309X					UK209D1;HE2309X	C209D1	
	UKC209D1;HS2309X					UK209D1;HS2309X	C209D1	
UKC209D1;HS2309X	UK209D1;HS2309X					C209D1		
45 $1\frac{5}{8}$ $1\frac{11}{16}$ $1\frac{3}{4}$	UKC210D1;H2310X	120	33	2.5	55	UK210D1;H2310X	C210D1	2.1
	UKC210D1;HS2310	4.7244	$1\frac{19}{64}$	0.098	2.165	UK210D1;HS2310	C210D1	4.6
	UKC210D1;HA2310					UK210D1;HA2310	C210D1	
	UKC210D1;HE2310X					UK210D1;HE2310X	C210D1	
UKC210D1;HE2310X	UK210D1;HE2310X					C210D1		
50 $1\frac{7}{8}$ $1\frac{15}{16}$ 2	UKC211D1;H2311X	125	35	2.5	59	UK211D1;H2311X	C211D1	2.3
	UKC211D1;HS2311	4.9213	$1\frac{3}{8}$	0.098	2.323	UK211D1;HS2311	C211D1	5.1
	UKC211D1;HA2311					UK211D1;HA2311	C211D1	
	UKC211D1;HE2311XY					UK211D1;HE2311XY	C211D1	
UKC211D1;HE2311XY	UK211D1;HE2311XY					C211D1		
55 $2\frac{1}{8}$	UKC212D1;H2312X	130	38	2.5	62	UK212D1;H2312X	C212D1	2.6
	UKC212D1;HS2312	5.1181	$1\frac{1}{2}$	0.098	2.441	UK212D1;HS2312	C212D1	5.7
60 $2\frac{3}{16}$ $2\frac{1}{4}$ $2\frac{3}{8}$	UKC213D1;H2313X	140	40	3	65	UK213D1;H2313X	C213D1	3.2
	UKC213D1;HA2313	5.5118	$1\frac{37}{64}$	0.118	2.559	UK213D1;HA2313	C213D1	7.1
	UKC213D1;HE2313X					UK213D1;HE2313X	C213D1	
	UKC213D1;HS2313X					UK213D1;HS2313X	C213D1	
UKC213D1;HS2313X	UK213D1;HS2313X					C213D1		

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.

In this case the lock washer with the straight inner prong should be used.


<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.

To distinguish it, a suffix "Y" is added.

Remarks Please refer to page A21 for size of grease fitting.



## Cartridge unit, cast housing Adapter type



Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> ) <sup>(3)</sup>	Nominal dimensions mm inch				Bearing number	Housing number	Mass of unit kg lb
		H	A	r	B <sub>1</sub>			
20 3/4	UKC305D1;H2305X	90	26	2.5	35	UK305D1;H2305X	C305D1	1.0
	UKC305D1;HE2305	3.5433	1 1/32	0.098	1.378	UK305D1;HE2305	C305D1	2.2
25 7/8 1	UKC306D1;H2306X	100	28	2.5	38	UK306D1;H2306X	C306D1	1.3
	UKC306D1;HS2306	3.9370	1 7/64	0.098	1.496	UK306D1;HS2306	C306D1	2.9
30 1 1/8	UKC307D1;H2307X	110	32	3	43	UK307D1;H2307X	C307D1	1.8
	UKC307D1;HS2307	4.3307	1 17/64	0.118	1.693	UK307D1;HS2307	C307D1	4.0
35 1 1/4 1 3/8	UKC308D1;H2308X	120	34	3	46	UK308D1;H2308X	C308D1	2.2
	UKC308D1;HE2308X	4.7244	1 11/32	0.118	1.811	UK308D1;HE2308X	C308D1	4.9
40 1 7/16 1 1/2 1 5/8	UKC309D1;H2309X	130	38	3.5	50	UK309D1;H2309X	C309D1	2.7
	UKC309D1;HA2309	5.1181	1 1/2	0.138	1.969	UK309D1;HA2309	C309D1	6.0
45 1 5/8 1 11/16 1 3/4	UKC310D1;H2310X	140	40	3.5	55	UK310D1;H2310X	C310D1	3.4
	UKC310D1;HS2310	5.5118	1 37/64	0.138	2.165	UK310D1;HS2310	C310D1	7.5
50 1 7/8 1 15/16 2	UKC311D1;H2311X	150	44	3.5	59	UK311D1;H2311X	C311D1	4.0
	UKC311D1;HS2311	5.9055	1 47/64	0.138	2.323	UK311D1;HS2311	C311D1	8.8
55 2 1/8	UKC312D1;H2312X	160	46	3.5	62	UK312D1;H2312X	C312D1	4.8
	UKC312D1;HS2312	6.2992	1 19/16	0.138	2.441	UK312D1;HS2312	C312D1	11
60 2 3/16 2 1/4 2 3/8	UKC313D1;H2313X	170	50	3.5	65	UK313D1;H2313X	C313D1	5.6
	UKC313D1;HA2313	6.6929	1 31/32	0.138	2.559	UK313D1;HA2313	C313D1	12
	UKC313D1;HE2313X					UK313D1;HE2313X	C313D1	
	UKC313D1;HS2313X					UK313D1;HS2313X	C313D1	

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".


<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.

In this case the lock washer with the straight inner prong should be used.

<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.

To distinguish it, a suffix "Y" is added.

Remarks Please refer to page A21 for size of grease fitting.



Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>2</sup> )	Nominal dimensions mm inch				Bearing number	Housing number	Mass of unit kg lb
		H	A	r	B <sub>1</sub>			
65 2 7/16 2 1/2	UKC315D1;H2315X	190	55	4	73	UK315D1;H2315X	C315D1	7.9
	UKC315D1;HA2315	7.4803	2 11/64	0.157	2.874	UK315D1;HA2315	C315D1	17
70 2 11/16 2 3/4	UKC316D1;H2316X	200	60	4	78	UK316D1;H2316X	C316D1	9.4
	UKC316D1;HA2316	7.8740	2 23/64	0.157	3.071	UK316D1;HA2316	C316D1	21
75 2 5/16 3	UKC317D1;H2317X	215	64	4	82	UK317D1;H2317X	C317D1	11
	UKC317D1;HA2317X	8.4646	2 33/64	0.157	3.228	UK317D1;HA2317X	C317D1	24
80 3 3/16	UKC318D1;H2318X	225	66	4	86	UK318D1;H2318X	C318D1	13
	UKC318D1;HA2318X	8.8583	2 19/32	0.157	3.386	UK318D1;HA2318X	C318D1	29
85 3 1/4	UKC319D1;H2319X	240	72	4	90	UK319D1;H2319X	C319D1	16
	UKC319D1;HE2319X	9.4488	2 53/64	0.157	3.543	UK319D1;HE2319X	C319D1	35
90 3 7/16 3 1/2	UKC320D1;H2320X	260	75	4	97	UK320D1;H2320X	C320D1	20
	UKC320D1;HA2320	10.2362	2 61/64	0.157	3.819	UK320D1;HA2320	C320D1	44
100	UKC322D1;H2322X	300	80	5	105	UK322D1;H2322X	C322D1	29
	UKC324D1;H2324	320	90	5	112	UK324D1;H2324	C324D1	35
110	UKC326D1;H2326	340	100	5	121	UK326D1;H2326	C326D1	43
115	UKC328D1;H2328	360	100	5	131	UK328D1;H2328	C328D1	50


Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.

In this case the lock washer with the straight inner prong should be used.

Remarks Please refer to page A21 for size of grease fitting.

## Cartridge unit, cast housing Adapter type



Shaft dia. mm inch	Unit number <sup>(1)</sup> ( <sup>(2)</sup> )	Nominal dimensions				Bearing number	Housing number	Mass of unit kg lb
		<i>H</i>	<i>A</i>	<i>r</i>	<i>B</i> <sub>1</sub>			
20 $\frac{3}{4}$	UKCX05D1;H2305X	90	27	2	35	UKX05D1;H2305X	CX05D1	1.1
	UKCX05D1;HE2305	3.5433	$1\frac{1}{16}$	0.079	1.378	UKX05D1;HE2305	CX05D1	2.4
25 $\frac{7}{8}$ 1	UKCX06D1;H2306X	100	30	2.5	38	UKX06D1;H2306X	CX06D1	1.4
	UKCX06D1;HS2306	3.9370	$1\frac{3}{16}$	0.098	1.496	UKX06D1;HS2306	CX06D1	3.1
	UKCX06D1;HE2306X					UKX06D1;HE2306X	CX06D1	
30 $1\frac{1}{8}$	UKCX07D1;H2307X	110	34	2.5	43	UKX07D1;H2307X	CX07D1	1.8
	UKCX07D1;HS2307	4.3307	$1\frac{11}{32}$	0.098	1.693	UKX07D1;HS2307	CX07D1	4.0
35 $1\frac{1}{4}$ $1\frac{3}{8}$	UKCX08D1;H2308X	120	38	2.5	46	UKX08D1;H2308X	CX08D1	2.5
	UKCX08D1;HE2308X	4.7244	$1\frac{1}{2}$	0.098	1.811	UKX08D1;HE2308X	CX08D1	5.5
	UKCX08D1;HS2308X					UKX08D1;HS2308X	CX08D1	
40 $1\frac{7}{16}$ $1\frac{1}{2}$ $1\frac{5}{8}$	UKCX09D1;H2309X	120	38	2.5	50	UKX09D1;H2309X	CX09D1	2.2
	UKCX09D1;HA2309	4.7244	$1\frac{1}{2}$	0.098	1.969	UKX09D1;HA2309	CX09D1	4.9
	UKCX09D1;HE2309X					UKX09D1;HE2309X	CX09D1	
45 $1\frac{5}{8}$ $1\frac{11}{16}$ $1\frac{3}{4}$	UKCX10D1;H2310X	130	40	2.5	55	UKX10D1;H2310X	CX10D1	2.7
	UKCX10D1;HS2310	5.1181	$1\frac{37}{64}$	0.098	2.165	UKX10D1;HS2310	CX10D1	6.0
	UKCX10D1;HA2310					UKX10D1;HA2310	CX10D1	
50 $1\frac{7}{8}$ $1\frac{15}{16}$ 2	UKCX11D1;H2311X	150	42	3	59	UKX11D1;H2311X	CX11D1	4.0
	UKCX11D1;HS2311	5.9055	$1\frac{21}{32}$	0.118	2.323	UKX11D1;HS2311	CX11D1	8.8
	UKCX11D1;HA2311					UKX11D1;HA2311	CX11D1	
55 $2\frac{1}{8}$	UKCX12D1;H2312X	160	44	3	62	UKX12D1;H2312X	CX12D1	3.9
	UKCX12D1;HS2312	6.2992	$1\frac{47}{64}$	0.118	2.441	UKX12D1;HS2312	CX12D1	8.6

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve. In this case the lock washer with the straight inner prong should be used.

<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve. To distinguish it, a suffix "Y" is added.

Remarks Please refer to page A21 for size of grease fitting.

## Ball bearings Set screw type



Shaft dia. mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i> min.	mm		<i>G</i>	<i>d<sub>s</sub></i>	<i>d<sub>4</sub></i>	<i>F</i>
							<i>S</i>	<i>S<sub>1</sub></i>				
12 1/2	<b>UC201D1</b> <b>UC201-008D1</b>	12 0.5000	47 1.8504	31 1.2205	17 0.6693	0.6 0.024	12.7 0.500	18.3 0.720	4.5 0.177	M5×0.8 No.10-32UNF	29.6 1.1654	4.7 0.185
15 9/16 7/8	<b>UC202D1</b> <b>UC202-009D1</b> <b>UC202-010D1</b>	15 0.5625 0.6250	47 1.8504	31 1.2205	17 0.6693	0.6 0.024	12.7 0.500	18.3 0.720	4.5 0.177	M5×0.8 No.10-32UNF	29.6 1.1654	4.7 0.185
17 11/16	<b>UC203D1</b> <b>UC203-011D1</b>	17 0.6875	47 1.8504	31 1.2205	17 0.6693	0.6 0.024	12.7 0.500	18.3 0.720	4.5 0.177	M5×0.8 No.10-32UNF	29.6 1.1654	4.7 0.185
20 3/4	<b>UC204D1</b> <b>UC204-012D1</b>	20 0.7500	47 1.8504	31 1.2205	17 0.6693	1 0.039	12.7 0.500	18.3 0.720	4.5 0.177	M5×0.8 No.10-32UNF	29.6 1.1654	4.7 0.185
25 13/16 7/8 15/16	<b>UC205D1</b> <b>UC205-013D1</b> <b>UC205-014D1</b> <b>UC205-015D1</b> <b>UC205-100D1</b>	25 0.8125 0.8750 0.9375 1.0000	52 2.0472	34.1 1.3425	17 0.6693	1 0.039	14.3 0.563	19.8 0.780	5 0.197	M5×0.8 No.10-32UNF	33.9 1.3346	4.5 0.177
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>UC206D1</b> <b>UC206-101D1</b> <b>UC206-102D1</b> <b>UC206-103D1</b> <b>UC206-104D1</b>	30 1.0625 1.1250 1.1875 1.2500	62 2.4409	38.1 1.5000	19 0.7480	1 0.039	15.9 0.626	22.2 0.874	5 0.197	M6×0.75 1/4-28UNF	40.8 1.6063	4.6 0.181
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>UC207D1</b> <b>UC207-104D1</b> <b>UC207-105D1</b> <b>UC207-106D1</b> <b>UC207-107D1</b>	35 1.2500 1.3125 1.3750 1.4375	72 2.8346	42.9 1.6890	20 0.7874	1.5 0.059	17.5 0.689	25.4 1.000	6 0.236	M6×0.75 1/4-28UNF	46.8 1.8425	4.6 0.181
40 1 1/2 1 9/16	<b>UC208D1</b> <b>UC208-108D1</b> <b>UC208-109D1</b>	40 1.5000 1.5625	80 3.1496	49.2 1.9370	21 0.8268	1.5 0.059	19 0.748	30.2 1.189	8 0.315	M8×1 5/16-24UNF	53 2.0866	4.5 0.177
45 1 5/8 1 11/16 1 3/4	<b>UC209D1</b> <b>UC209-110D1</b> <b>UC209-111D1</b> <b>UC209-112D1</b>	45 1.6250 1.6875 1.7500	85 3.3465	49.2 1.9370	22 0.8661	1.5 0.059	19 0.748	30.2 1.189	8 0.315	M8×1 5/16-24UNF	57.5 2.2638	4.9 0.193

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Basic load ratings		Mass kg lb
N dynamic <i>C<sub>r</sub></i>	lbf static <i>C<sub>0r</sub></i>	
12 800 2 890	6 650 1 500	0.21 0.46
12 800 2 890	6 650 1 500	0.20 0.44 0.42
12 800 2 890	6 650 1 500	0.18 0.39
12 800 2 890	6 650 1 500	0.17 0.39
14 000 3 150	7 850 1 770	0.20 0.53 0.51 0.46 0.44
19 500 4 400	11 300 2 540	0.32 0.82 0.77 0.73 0.66
25 700 5 750	15 300 3 450	0.46 1.21 1.15 1.08 1.01
29 100 6 550	17 800 4 000	0.64 1.52 1.46
32 500 7 350	20 400 4 600	0.68 1.76 1.68 1.57

## Ball bearings Set screw type



Shaft dia. mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i> min.	<i>S</i> mm	<i>S</i> <sub>1</sub> inch	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>4</sub>	<i>F</i>
50 1 13/16 1 7/8 1 15/16 2	<b>UC210D1</b>	50	90	51.6	24	1.5	19	32.6	9	M8×1	62.4	5.9
	<b>UC210-113D1</b>	1.8125										
	<b>UC210-114D1</b>	1.8750	3.5433	2.0315	0.9449	0.059	0.748	1.283	0.354	5/16-24UNF	2.4567	0.232
	<b>UC210-115D1</b>	1.9375										
	<b>UC210-200D1</b>	2.0000										
55 2 2 1/16 2 1/8 2 3/8	<b>UC211D1</b>	55	100	55.6	25	2	22.2	33.4	9	M8×1	69	6.0
	<b>UC211-200D1</b>	2.0000										
	<b>UC211-201D1</b>	2.0625	3.9370	2.1890	0.9843	0.079	0.874	1.315	0.354	5/16-24UNF	2.7165	0.236
	<b>UC211-202D1</b>	2.1250										
	<b>UC211-203D1</b>	2.1875										
60 2 1/4 2 5/8 2 3/4 2 7/8	<b>UC212D1</b>	60	110	65.1	27	2	25.4	39.7	10	M10×1.25	77	6.2
	<b>UC212-204D1</b>	2.2500										
	<b>UC212-205D1</b>	2.3125	4.3307	2.5630	1.0630	0.079	1.000	1.563	0.394	3/8-24UNF	3.0315	0.244
	<b>UC212-206D1</b>	2.3750										
	<b>UC212-207D1</b>	2.4375										
65 2 1/2 2 9/16	<b>UC213D1</b>	65	120	65.1	32	2	25.4	39.7	10	M10×1.25	82.5	8.7
	<b>UC213-208D1</b>	2.5000	4.7244	2.5630	1.2598	0.079	1.000	1.563	0.394	3/8-24UNF	3.2480	0.343
	<b>UC213-209D1</b>	2.5625										
70 2 5/8 2 11/16 2 3/4	<b>UC214D1</b>	70	125	74.6	33	2	30.2	44.4	12	M10×1.25	87	8.8
	<b>UC214-210D1</b>	2.6250										
	<b>UC214-211D1</b>	2.6875	4.9213	2.9370	1.2992	0.079	1.189	1.748	0.472	3/8-24UNF	3.4252	0.346
	<b>UC214-212D1</b>	2.7500										
75 2 13/16 2 7/8 2 15/16 3	<b>UC215D1</b>	75	130	77.8	34	2	33.3	44.5	12	M10×1.25	93	9.0
	<b>UC215-213D1</b>	2.8125										
	<b>UC215-214D1</b>	2.8750	5.1181	3.0630	1.3386	0.079	1.311	1.752	0.472	3/8-24UNF	3.6614	0.354
	<b>UC215-215D1</b>	2.9375										
	<b>UC215-300D1</b>	3.0000										
80 3 1/16 3 1/8 3 3/16	<b>UC216D1</b>	80	140	82.6	35	2.5	33.3	49.3	12	M10×1.25	98.1	9.5
	<b>UC216-301D1</b>	3.0625										
	<b>UC216-302D1</b>	3.1250	5.5118	3.2520	1.3780	0.098	1.311	1.941	0.472	3/8-24UNF	3.8622	0.374
	<b>UC216-303D1</b>	3.1875										

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Basic load ratings		Mass
N lbf		kg lb
dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>0r</sub>	
35 000	23 200	0.78 2.03
7 900	5 200	1.92 1.81 1.69
43 500	29 200	1.04 2.71
9 750	6 550	2.60 2.46 2.34
52 500	36 000	1.46 3.66
11 800	8 150	3.50 3.33 3.17
57 500	40 000	1.86 4.26
12 900	9 000	4.09
62 000	44 000	2.10 5.09
14 000	9 900	4.87 4.65
66 000	49 500	2.34 5.73
14 900	11 100	5.49 5.25 4.98
72 500	53 000	2.78 6.57
16 300	11 900	6.28 6.00

## Ball bearings Set screw type



Shaft dia.  mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i> min.	<i>S</i> mm	<i>S</i> inch	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>4</sub>
85	<b>UC217D1</b>	85	150	85.7	36	2.5	34.1	51.6	12	M12×1.5	106.4	10.1
3 1/4	<b>UC217-304D1</b>	3.2500										
3 5/16	<b>UC217-305D1</b>	3.3125	5.9055	3.3740	1.4173	0.098	1.343	2.031	0.472	1/2-20UNF	4.1890	0.398
3 7/16	<b>UC217-307D1</b>	3.4375										
90	<b>UC218D1</b>	90	160	96	37	2.5	39.7	56.3	12	M12×1.5	111.6	9.8
3 1/2	<b>UC218-308D1</b>	3.5000	6.2992	3.7795	1.4567	0.098	1.563	2.217	0.472	1/2-20UNF	4.3937	0.386

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Basic load ratings		Mass
dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>0r</sub>	kg lb
83 500	64 000	3.54 7.92
18 700	14 300	7.60 6.97
96 000	71 500	4.40 9.88
21 600	16 100	

Ball bearings  
Set screw type



Shaft dia. mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i> min.	mm inch		<i>G</i>	<i>d<sub>s</sub></i>	<i>d<sub>4</sub></i>	<i>F</i>
25 1 3/16 7/8 1 1/16 1	UC305D1	25	62	38	20	1.5	15	23	6	M6×0.75	36.8	5.0
	UC305-013D1	0.8125										
	UC305-014D1	0.8750	2.4409	1.4961	0.7874	0.059	0.591	0.906	0.236	1/4-28UNF	1.4488	0.197
	UC305-015D1	0.9375										
UC305-100D1	1.0000											
30 1 1/16 1 1/8 1 3/16	UC306D1	30	72	43	23	1.5	17	26	6	M6×0.75	44.9	5.9
	UC306-101D1	1.0625										
	UC306-102D1	1.1250	2.8346	1.6929	0.9055	0.059	0.669	1.024	0.236	1/4-28UNF	1.7677	0.232
UC306-103D1	1.1875											
35 1 1/4 1 5/16 1 3/8 1 7/16	UC307D1	35	80	48	25	2	19	29	8	M8×1	49.4	6.8
	UC307-104D1	1.2500										
	UC307-105D1	1.3125	3.1496	1.8898	0.9843	0.079	0.748	1.142	0.315	5/16-24UNF	1.9449	0.268
	UC307-106D1	1.3750										
UC307-107D1	1.4375											
40 1 1/2 1 9/16	UC308D1	40	90	52	27	2	19	33	10	M10×1.25	56	7.4
	UC308-108D1	1.5000	3.5433	2.0472	1.0630	0.079	0.748	1.299	0.394	3/8-24UNF	2.2047	0.291
	UC308-109D1	1.5625										
45 1 5/8 1 11/16 1 3/4	UC309D1	45	100	57	29	2	22	35	10	M10×1.25	63.5	7.4
	UC309-110D1	1.6250										
	UC309-111D1	1.6875	3.9370	2.2441	1.1417	0.079	0.866	1.378	0.394	3/8-24UNF	2.5000	0.291
UC309-112D1	1.7500											
50 1 13/16 1 7/8 1 15/16	UC310D1	50	110	61	32	2.5	22	39	12	M12×1.5	70.6	8.1
	UC310-113D1	1.8125										
	UC310-114D1	1.8750	4.3307	2.4016	1.2598	0.098	0.866	1.535	0.472	1/2-20UNF	2.7795	0.319
	UC310-115D1	1.9375										

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Basic load ratings		Mass
N lbf		kg lb
dynamic <i>C<sub>r</sub></i>	static <i>C<sub>0r</sub></i>	
21 200	10 900	0.35 0.88
4 750	2 460	0.84 0.79 0.77
26 700	15 000	0.56 1.34
6 000	3 400	1.28 1.23
33 500	19 100	0.70 1.70
7 500	4 300	1.63 1.57 1.50
40 500	24 000	0.96 2.23
9 150	5 400	2.14 1.28
53 000	32 000	1.28 3.06
11 900	7 200	2.98 2.87
62 000	38 500	1.68 3.95
13 900	8 600	3.84 3.70

Ball bearings  
Set screw type



Shaft dia.  mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i> min.	mm inch		<i>G</i>	<i>d<sub>s</sub></i>	<i>d<sub>4</sub></i>	<i>F</i>
							<i>S</i>	<i>S<sub>1</sub></i>				
<b>55</b>	<b>UC311D1</b>	55	120	66	34	2.5	25	41	12	M12×1.5	76.6	8.5
<b>2</b>	<b>UC311-200D1</b>	2.0000										
<b>2 1/16</b>	<b>UC311-201D1</b>	2.0625										
<b>2 1/8</b>	<b>UC311-202D1</b>	2.1250	4.7244	2.5984	1.3386	0.098	0.984	1.614	0.472	1/2-20UNF	3.0157	0.335
<b>2 3/16</b>	<b>UC311-203D1</b>	2.1875										
<b>60</b>	<b>UC312D1</b>	60	130	71	36	2.5	26	45	12	M12×1.5	82.7	9.0
<b>2 1/4</b>	<b>UC312-204D1</b>	2.2500										
<b>2 5/16</b>	<b>UC312-205D1</b>	2.3125										
<b>2 3/8</b>	<b>UC312-206D1</b>	2.3750	5.1181	2.7953	1.4173	0.098	1.024	1.772	0.472	1/2-20UNF	3.2559	0.354
<b>2 7/16</b>	<b>UC312-207D1</b>	2.4375										
<b>65</b>	<b>UC313D1</b>	65	140	75	39	2.5	30	45	12	M12×1.5	88.2	10.1
<b>2 1/2</b>	<b>UC313-208D1</b>	2.5000										
<b>2 9/16</b>	<b>UC313-209D1</b>	2.5625	5.5118	2.9528	1.5354	0.098	1.181	1.772	0.472	1/2-20UNF	3.4724	0.398
<b>70</b>	<b>UC314D1</b>	70	150	78	41	2.5	33	45	12	M12×1.5	94.8	10.5
<b>2 5/8</b>	<b>UC314-210D1</b>	2.6250										
<b>2 11/16</b>	<b>UC314-211D1</b>	2.6875	5.9055	3.0709	1.6142	0.098	1.299	1.772	0.472	1/2-20UNF	3.7323	0.413
<b>2 3/4</b>	<b>UC314-212D1</b>	2.7500										
<b>75</b>	<b>UC315D1</b>	75	160	82	43	2.5	32	50	14	M14×1.5	101.3	11.0
<b>2 13/16</b>	<b>UC315-213D1</b>	2.8125										
<b>2 7/8</b>	<b>UC315-214D1</b>	2.8750										
<b>2 15/16</b>	<b>UC315-215D1</b>	2.9375	6.2992	3.2283	1.6929	0.098	1.260	1.969	0.551	9/16-18UNF	3.9882	0.433
<b>3</b>	<b>UC315-300D1</b>	3.0000										
<b>80</b>	<b>UC316D1</b>	80	170	86	45	2.5	34	52	14	M14×1.5	107.9	11.4
<b>3 1/16</b>	<b>UC316-301D1</b>	3.0625										
<b>3 1/8</b>	<b>UC316-302D1</b>	3.1250	6.6929	3.3858	1.7717	0.098	1.339	2.047	0.551	9/16-18UNF	4.2480	0.449
<b>3 3/16</b>	<b>UC316-303D1</b>	3.1875										

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Basic load ratings		Mass
N lbf		kg lb
dynamic <i>C<sub>r</sub></i>	static <i>C<sub>0r</sub></i>	
71 500	45 000	2.08
		4.96
16 100	10 100	4.81
		4.67
		4.50
82 000	52 000	2.60
		6.06
18 400	11 700	5.89
		5.68
		5.51
92 500	60 000	3.25
		7.36
20 800	13 400	7.14
104 000	68 000	3.86
		9.06
23 400	15 300	8.82
		8.60
113 000	77 000	4.70
		11.0
25 500	17 400	10.7
		10.5
		10.2
123 000	86 500	5.60
		12.6
27 600	19 500	12.3
		12.1

Ball bearings  
Set screw type

Shaft dia.  mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i> min.	mm inch		<i>G</i>	<i>d<sub>s</sub></i>	<i>d<sub>4</sub></i>	<i>F</i>
							<i>S</i>	<i>S<sub>1</sub></i>				
85 3 1/4 3 5/16 3 7/16	<b>UC317D1</b> <b>UC317-304D1</b> <b>UC317-305D1</b> <b>UC317-307D1</b>	85 3.2500 3.3125 3.4375	180 7.0866	96 3.7795	47 1.8504	3 0.118	40 1.575	56 2.205	16 0.630	M16×1.5 5/8-18UNF	114.4 4.5039	12.0 0.472
90 3 7/16 3 1/2	<b>UC318D1</b> <b>UC318-307D1</b> <b>UC318-308D1</b>	90 3.4375 3.5000	190 7.4803	96 3.7795	49 1.9291	3 0.118	40 1.575	56 2.205	16 0.630	M16×1.5 5/8-18UNF	120.9 4.7598	12.3 0.484
95 3 5/8 3 11/16 3 3/4	<b>UC319D1</b> <b>UC319-310D1</b> <b>UC319-311D1</b> <b>UC319-312D1</b>	95 3.6250 3.6875 3.7500	200 7.8740	103 4.0551	51 2.0079	3 0.118	41 1.614	62 2.441	16 0.630	M16×1.5 5/8-18UNF	127.5 5.0197	12.8 0.504
100 3 13/16 3 7/8 3 15/16 4	<b>UC320D1</b> <b>UC320-313D1</b> <b>UC320-314D1</b> <b>UC320-315D1</b> <b>UC320-400D1</b>	100 3.8125 3.8750 3.9375 4.0000	215 8.4646	108 4.2520	55 2.1654	3 0.118	42 1.654	66 2.598	18 0.709	M18×1.5 5/8-18UNF	135.6 5.3386	13.5 0.531
105	<b>UC321D1</b>	105	225	112	57	3	44	68	18	M18×1.5	142.1	13.9
110	<b>UC322D1</b>	110	240	117	59	3	46	71	18	M18×1.5	151.7	13.9
120	<b>UC324D1</b>	120	260	126	63	3	51	75	18	M18×1.5	165.2	16.0
130	<b>UC326D1</b>	130	280	135	67	4	54	81	20	M20×1.5	178.3	16.9
140	<b>UC328D1</b>	140	300	145	71	4	59	86	20	M20×1.5	190.4	17.7

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Basic load ratings		Mass
dynamic <i>C<sub>r</sub></i>	N lbf static <i>C<sub>0r</sub></i>	kg lb
	133 000	97 000
29 800	21 800	14.9 14.2
143 000	107 000	7.60 17.3
32 000	24 100	16.9
153 000	119 000	8.70 19.9
34 500	26 600	19.5 19.1
173 000	141 000	10.8 24.7
39 000	31 500	24.2 23.8 23.4
184 000	153 000	12.2
205 000	179 000	14.3
207 000	185 000	18.5
229 000	214 000	23.0
253 000	246 000	28.5



## Ball bearings Set screw type



Shaft dia.  mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i> min.	mm inch		<i>G</i>	<i>d<sub>s</sub></i>	<i>d<sub>4</sub></i>	<i>F</i>
							<i>S</i>	<i>S<sub>1</sub></i>				
<b>25</b>	<b>UCX05D1</b>	25	62	38.1	19	1	15.9	22.2	5	M6×0.75	40.8	4.6
$\frac{13}{16}$	<b>UCX05-013D1</b>	0.8125										
$\frac{7}{8}$	<b>UCX05-014D1</b>	0.8750	2.4409	1.5000	0.7480	0.039	0.626	0.874	0.197	$\frac{1}{4}$ -28UNF	1.6063	0.181
$\frac{15}{16}$	<b>UCX05-015D1</b>	0.9375										
<b>1</b>	<b>UCX05-100D1</b>	1.0000										
<b>30</b>	<b>UCX06D1</b>	30	72	42.9	20	1	17.5	25.4	6	M8×1	46.8	4.6
$1\frac{1}{16}$	<b>UCX06-101D1</b>	1.0625										
$1\frac{1}{8}$	<b>UCX06-102D1</b>	1.1250	2.8346	1.6890	0.7874	0.039	0.689	1.000	0.236	$\frac{5}{16}$ -24UNF	1.8425	0.181
$1\frac{3}{16}$	<b>UCX06-103D1</b>	1.1875										
<b>35</b>	<b>UCX07D1</b>	35	80	49.2	21	1.5	19	30.2	8	M8×1	53	4.5
$1\frac{5}{16}$	<b>UCX07-105D1</b>	1.3125										
$1\frac{3}{8}$	<b>UCX07-106D1</b>	1.3750	3.1496	1.9370	0.8268	0.059	0.748	1.189	0.315	$\frac{5}{16}$ -24UNF	2.0866	0.177
$1\frac{7}{16}$	<b>UCX07-107D1</b>	1.4375										
<b>40</b>	<b>UCX08D1</b>	40	85	49.2	22	1.5	19	30.2	8	M8×1	57.5	4.9
$1\frac{1}{2}$	<b>UCX08-108D1</b>	1.5000										
$1\frac{9}{16}$	<b>UCX08-109D1</b>	1.5625	3.3465	1.9370	0.8661	0.059	0.748	1.189	0.315	$\frac{5}{16}$ -24UNF	2.2638	0.193
<b>45</b>	<b>UCX09D1</b>	45	90	51.6	24	1.5	19	32.6	9	M10×1.25	62.4	5.9
$1\frac{5}{8}$	<b>UCX09-110D1</b>	1.6250										
$1\frac{11}{16}$	<b>UCX09-111D1</b>	1.6875	3.5433	2.0315	0.9449	0.059	0.748	1.283	0.354	$\frac{3}{8}$ -24UNF	2.4567	0.232
$1\frac{3}{4}$	<b>UCX09-112D1</b>	1.7500										
<b>50</b>	<b>UCX10D1</b>	50	100	55.6	25	1.5	22.2	33.4	9	M10×1.25	69	6.0
$1\frac{7}{8}$	<b>UCX10-114D1</b>	1.8750										
$1\frac{15}{16}$	<b>UCX10-115D1</b>	1.9375	3.9370	2.1890	0.9843	0.059	0.874	1.315	0.354	$\frac{3}{8}$ -24UNF	2.7165	0.236
<b>55</b>	<b>UCX11D1</b>	55	110	65.1	27	2	25.4	39.7	10	M10×1.25	77	6.2
$2\frac{1}{16}$	<b>UCX11-201D1</b>	2.0625										
$2\frac{1}{8}$	<b>UCX11-202D1</b>	2.1250	4.3307	2.5630	1.0630	0.079	1.000	1.563	0.394	$\frac{3}{8}$ -24UNF	3.0315	0.244
$2\frac{3}{16}$	<b>UCX11-203D1</b>	2.1875										
<b>60</b>	<b>UCX12D1</b>	60	120	65.1	32	2	25.4	39.7	10	M10×1.25	82.5	8.7
$2\frac{3}{8}$	<b>UCX12-206D1</b>	2.3750										
$2\frac{1}{4}$	<b>UCX12-207D1</b>	2.4375	4.7244	2.5630	1.2598	0.079	1.000	1.563	0.394	$\frac{3}{8}$ -24UNF	3.2480	0.343

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Basic load ratings		Mass
N lbf		kg lb
dynamic <i>C<sub>r</sub></i>	static <i>C<sub>0r</sub></i>	
19 500	11 300	0.39 0.97
4 400	2 540	0.93 0.88 0.84
25 700	15 300	0.68 1.61
5 750	3 450	1.54 1.50
29 100	17 800	0.74 1.87
6 550	4 000	1.81 1.74
32 500	20 400	0.80 2.16 2.07
7 350	4 600	
35 000	23 200	0.94 2.43
7 900	5 200	2.34 2.25
43 500	29 200	1.22 3.15 3.04
9 750	6 550	
52 500	36 000	1.72 4.43
11 800	8 150	4.30 4.12
57 500	40 000	2.10 4.96
12 900	9 000	4.81

## Ball bearings Set screw type



Shaft dia.  mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i> min.	mm inch		<i>G</i>	<i>d<sub>s</sub></i>	<i>d<sub>4</sub></i>	<i>F</i>
							<i>S</i>	<i>S<sub>1</sub></i>				
65 2 1/2 2 9/16	<b>UCX13D1</b> <b>UCX13-208D1</b> <b>UCX13-209D1</b>	65 2.5000 2.5625	125 4.9213	74.6 2.9370	33 1.2992	2 0.079	30.2 1.189	44.4 1.748	12 0.472	M12×1.5 1/2-20UNF	87 3.4252	8.8 0.346
70 2 5/8 2 11/16 2 3/4	<b>UCX14D1</b> <b>UCX14-210D1</b> <b>UCX14-211D1</b> <b>UCX14-212D1</b>	70 2.6250 2.6875 2.7500	130 5.1181	77.8 3.0630	34 1.3386	2 0.079	33.3 1.311	44.5 1.752	12 0.472	M12×1.5 1/2-20UNF	93 3.6614	9.0 0.354
75 2 13/16 2 7/8 2 15/16 3	<b>UCX15D1</b> <b>UCX15-213D1</b> <b>UCX15-214D1</b> <b>UCX15-215D1</b> <b>UCX15-300D1</b>	75 2.8125 2.8750 2.9375 3.0000	140 5.5118	82.6 3.2520	35 1.3780	2 0.079	33.3 1.311	49.3 1.941	12 0.472	M12×1.5 1/2-20UNF	98.1 3.8622	9.5 0.374
80 3 1/16 3 1/8 3 3/16	<b>UCX16D1</b> <b>UCX16-301D1</b> <b>UCX16-302D1</b> <b>UCX16-303D1</b>	80 3.0625 3.1250 3.1875	150 5.9055	85.7 3.3740	36 1.4173	2.5 0.098	34.1 1.343	51.6 2.031	12 0.472	M12×1.5 1/2-20UNF	106.4 4.1890	10.1 0.398
85 3 5/16 3 7/16	<b>UCX17D1</b> <b>UCX17-305D1</b> <b>UCX17-307D1</b>	85 3.3125 3.4375	160 6.2992	96 3.7795	37 1.4567	2.5 0.098	39.7 1.563	56.3 2.217	12 0.472	M12×1.5 1/2-20UNF	111.6 4.3937	9.8 0.386
90 3 7/16 3 1/2	<b>UCX18D1</b> <b>UCX18-307D1</b> <b>UCX18-308D1</b>	90 3.4375 3.5000	170 6.6929	104 4.0945	39 1.5354	2.5 0.098	42.9 1.689	61.1 2.406	14 0.551	M14×1.5 5/16-18UNF	118.2 4.6535	10.5 0.413
100 3 13/16 3 7/8 3 15/16 4	<b>UCX20D1</b> <b>UCX20-313D1</b> <b>UCX20-314D1</b> <b>UCX20-315D1</b> <b>UCX20-400D1</b>	100 3.8125 3.8750 3.9375 4.0000	190 7.4803	117.5 4.6260	44 1.7323	2.5 0.098	49.2 1.937	68.3 2.689	16 0.630	M16×1.5 5/8-18UNF	131.3 5.1693	11.3 0.445

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Basic load ratings		Mass kg lb
N lbf		
dynamic <i>C<sub>r</sub></i>	static <i>C<sub>0r</sub></i>	
62 000	44 000	2.45
14 000	9 900	5.60 5.38
66 000	49 500	2.47
14 900	11 100	5.93 5.69
72 500	53 000	5.47
16 300	11 900	3.11
83 500	64 000	7.43
18 700	14 300	7.19
96 000	71 500	6.92
21 600	16 100	6.66
109 000	82 000	3.96
24 500	18 400	8.75
133 000	105 000	8.47
29 900	23 500	8.18
		4.72
		10.8
		10.1
		5.50
		13.3
		12.4
		8.06
		18.8
		18.4
		19.7
		19.2

## Ball bearings Set screw type



Shaft dia. mm inch	Bearing (1) number	Nominal dimensions									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i> mm min.	<i>S</i> mm inch	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>4</sub>
12 1/2	<b>AS201</b> <b>AS201-008</b>	12 0.5000	40 1.5748	22 0.8661	12 0.4724	0.6 0.024	6 0.236	16 0.630	4.2 0.165	M5×0.8 No.10-32UNF	24.3 0.957
15 9/16 5/8	<b>AS202</b> <b>AS202-009</b> <b>AS202-010</b>	15 0.5625 0.6250	40 1.5748	22 0.8661	12 0.4724	0.6 0.024	6 0.236	16 0.630	4.2 0.165	M5×0.8 No.10-32UNF	24.3 0.957
17 11/16	<b>AS203</b> <b>AS203-011</b>	17 0.6875	40 1.5748	22 0.8661	12 0.4724	0.6 0.024	6 0.236	16 0.630	4.2 0.165	M5×0.8 No.10-32UNF	24.3 0.957
20 3/4	<b>AS204</b> <b>AS204-012</b>	20 0.7500	47 1.8504	25 0.9843	14 0.5512	1 0.039	7 0.276	18 0.709	4.2 0.165	M5×0.8 No.10-32UNF	29.6 1.165
25 13/16 7/8 15/16 1	<b>AS205</b> <b>AS205-013</b> <b>AS205-014</b> <b>AS205-015</b> <b>AS205-100</b>	25 0.8125 0.8750 0.9375 1.0000	52 2.0472	27 1.0630	15 0.5906	1 0.039	7.5 0.295	19.5 0.768	5 0.197	M5×0.8 No.10-32UNF	33.9 1.335
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>AS206</b> <b>AS206-101</b> <b>AS206-102</b> <b>AS206-103</b> <b>AS206-104</b>	30 1.0625 1.1250 1.1875 1.2500	62 2.4409	29 1.1417	16 0.6299	1 0.039	8 0.315	21 0.827	5 0.197	M6×0.75 1/4-28UNF	40.8 1.606
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>AS207</b> <b>AS207-104</b> <b>AS207-105</b> <b>AS207-106</b> <b>AS207-107</b>	35 1.2500 1.3125 1.3750 1.4375	72 2.8346	34 1.3386	17 0.6693	1.5 0.059	8.5 0.335	25.5 1.004	6 0.236	M6×0.75 1/4-28UNF	46.8 1.843
40 1 1/2 1 9/16	<b>AS208</b> <b>AS208-108</b> <b>AS208-109</b>	40 1.5000 1.5625	80 3.1496	38 1.4961	18 0.7087	1.5 0.059	9 0.354	29 1.142	8 0.315	M8×1 5/16-24UNF	53 2.087

Note (1) If relubricatable type is needed, please order with suffix "D1".

Basic load ratings		Mass
N lbf	kg lb	
dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>0r</sub>	
9 600 2 160	4 600 1 030	0.10 0.22
9 600 2 160	4 600 1 030	0.09 0.21 0.20
9 600 2 160	4 600 1 030	0.08 0.18
12 800 2 890	6 650 1 500	0.13 0.29
14 000 3 150	7 850 1 770	0.16 0.42 0.40 0.38 0.35
19 500 4 400	11 300 2 540	0.25 0.61 0.59 0.57 0.55
25 700 5 750	15 300 3 450	0.38 1.06 0.93 0.81 0.69
29 100 6 550	17 800 4 000	0.51 1.15 1.06

## Ball bearings Set screw type




Shaft dia.  mm inch	Bearing (1) number	Nominal dimensions									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i> min.	<i>S</i> mm	<i>S</i> inch	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>
45	<b>AS209</b>	45	85	40	19	1.5	9.5	30.5	8	M8×1	57.5
1 5/8	<b>AS209-110</b>	1.6250									
1 11/16	<b>AS209-111</b>	1.6875	3.3465	1.5748	0.7480	0.059	0.374	1.201	0.315	5/16-24UNF	2.2638
1 3/4	<b>AS209-112</b>	1.7500									
50	<b>AS210</b>	50	90	42	20	1.5	10	32	9	M8×1	62.4
1 13/16	<b>AS210-113</b>	1.8125									
1 7/8	<b>AS210-114</b>	1.8750	3.5433	1.6535	0.7874	0.059	0.394	1.260	0.354	5/16-24UNF	2.4567
1 15/16	<b>AS210-115</b>	1.9375									
2	<b>AS210-200</b>	2.0000									

Note (1) If relubricatable type is needed, please order with "D1".

Basic load ratings		Mass
dynamic	static	kg
<i>C</i> <sub>r</sub>	<i>C</i> <sub>0r</sub>	lb
32 500	20 400	0.55
		1.39
7 350	4 600	1.32
		1.23
35 000	23 200	0.65
		1.65
7 900	5 200	1.57
		1.48
		1.39

## Ball bearings Set screw type




Shaft dia. mm inch	Bearing (1) number	Nominal dimensions									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	mm		inch		<i>d<sub>s</sub></i>	<i>d<sub>4</sub></i>
						<i>r</i>	<i>S</i>	<i>S<sub>1</sub></i>	<i>G</i>		
12	AR201	12	40	22.5	13	0.6	6.5	16	5	M6×0.75	24.4
1/2	AR201-008	0.5000	1.5748	0.8858	0.5118	0.024	0.256	0.630	0.197	1/4-28UNF	0.9606
15	AR202	15	40	22.5	13	0.6	6.5	16	5	M6×0.75	24.4
9/16	AR202-009	0.5625	1.5748	0.8858	0.5118	0.024	0.256	0.630	0.197	1/4-28UNF	0.9606
5/8	AR202-010	0.6250									
17	AR203	17	40	22.5	13	0.6	6.5	16	5	M6×0.75	24.4
11/16	AR203-011	0.6875	1.5748	0.8858	0.5118	0.024	0.256	0.630	0.197	1/4-28UNF	0.9606
20	AR204	20	47	25.5	15	1	7.5	18	5	M6×0.75	29.6
3/4	AR204-012	0.7500	1.8504	1.0039	0.5906	0.039	0.295	0.709	0.197	1/4-28UNF	1.1654
25	AR205	25	52	27	15	1	7.5	19.5	5	M6×0.75	33.9
19/16	AR205-013	0.8125	2.0472	1.0630	0.5906	0.039	0.295	0.768	0.197	1/4-28UNF	1.3346
7/8	AR205-014	0.8750									
15/16	AR205-015	0.9375									
1	AR205-100	1.0000									
30	AR206	30	62	30	18	1	9	21	5	M6×0.75	40.8
1 1/16	AR206-101	1.0625	2.4409	1.1811	0.7087	0.039	0.354	0.827	0.197	1/4-28UNF	1.6063
1 1/8	AR206-102	1.1250									
1 3/16	AR206-103	1.1875									
1 1/4	AR206-104	1.2500									
35	AR207	35	72	35	19	1.5	9.5	25.5	6	M6×0.75	46.8
1 1/4	AR207-104	1.2500	2.8346	1.3780	0.7480	0.059	0.374	1.004	0.236	1/4-28UNF	1.8425
1 5/16	AR207-105	1.3125									
1 3/8	AR207-106	1.3750									
1 7/16	AR207-107	1.4375									
40	AR208	40	80	40	22	1.5	11.0	29	8	M8×1	53
1 1/2	AR208-108	1.5000	3.1496	1.5748	0.8661	0.059	0.433	1.142	0.315	5/16-24UNF	2.0866
1 5/16	AR208-109	1.5625									

Note (1) If relubricatable type is needed, please order with suffix "D1".

Basic load ratings		Mass
N lbf		kg lb
dynamic <i>C<sub>r</sub></i>	static <i>C<sub>or</sub></i>	
9 600	4 600	0.11
2 160	1 030	0.24
9 600	4 600	0.10
2 160	1 030	0.23
9 600	4 600	0.09
2 160	1 030	0.20
12 800	6 650	0.14
2 890	1 500	0.31
14 000	7 850	0.17
		0.44
3 150	1 770	0.42
		0.40
		0.37
19 500	11 300	0.26
		0.63
4 400	2 540	0.61
		0.59
		0.57
25 700	15 300	0.39
		1.10
5 750	3 450	0.97
		0.85
		0.73
29 100	17 800	0.54
6 550	4 000	1.24
		1.15

# AR2

## Ball bearings Set screw type




Shaft dia.	Bearing (*) number	Nominal dimensions									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>r</i>	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>4</sub>
mm inch		mm inch									
		min.									
45	AR209	45	85	41.5	22	1.5	11	30.5	8	M8×1	57.5
1 5/8	AR209-110	1.6250									
1 1/16	AR209-111	1.6875	3.3465	1.6339	0.8661	0.059	0.433	1.201	0.315	5/16-24UNF	2.2638
1 3/4	AR209-112	1.7500									
50	AR210	80	90	43	22	1.5	11	32	9	M8×1	62.4
1 3/16	AR210-113	1.8125									
1 7/8	AR210-114	1.8750	3.5433	1.6929	0.8661	0.059	0.433	1.260	0.354	5/16-24UNF	2.4567
1 5/16	AR210-115	1.9375									
2	AR210-200	2.0000									

Note (\*) If relubricatable type is needed, please order with "D1".

Basic load ratings		Mass
N lbf		kg lb
dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>0r</sub>	
32 500	20 400	0.61
		1.54
7 350	4 600	1.46
		1.39
35 000	23 200	0.70
		1.76
7 900	5 200	1.68
		1.59
		1.50

## Ball bearings Eccentric locking collar type




Shaft dia. mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	mm inch		<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>
							<i>r</i>	<i>S</i>				
20 ¾	<b>UEL204D1W3</b> <b>UEL204-012D1W3</b>	20 0.7500	47 1.8504	43.7 1.720	34.2 1.3465	17 0.6693	1 0.039	17.1 0.673	26.6 1.047	4.8 0.189	M6×0.75 ¼-28UNF	33 1.299
25 1⅜ 7/8 15/16	<b>UEL205D1W3</b> <b>UEL205-013D1W3</b> <b>UEL205-014D1W3</b> <b>UEL205-015D1W3</b>	25 0.8125 0.8750 0.9375	52 2.0472	44.4 1.748	34.9 1.3740	17 0.6693	1 0.039	17.45 0.687	26.9 1.059	4.8 0.189	M6×0.75 ¼-28UNF	38 1.496
1	<b>UEL205-100D1W3</b>	1.0000										
30 1⅛ 1⅝ 1¾	<b>UEL206D1W3</b> <b>UEL206-101D1W3</b> <b>UEL206-102D1W3</b> <b>UEL206-103D1W3</b> <b>UEL206-104D1W3</b>	30 1.0625 1.1250 1.1875 1.2500	62 2.4409	48.4 1.906	36.5 1.4370	19 0.7480	1 0.039	18.25 0.719	30.1 1.185	6 0.236	M8×1 ⅝-24UNF	44.5 1.752
35 1¼ 1⅝ 1⅝ 1⅞	<b>UEL207D1W3</b> <b>UEL207-104D1W3</b> <b>UEL207-105D1W3</b> <b>UEL207-106D1W3</b> <b>UEL207-107D1W3</b>	35 1.2500 1.3125 1.3750 1.4375	72 2.8346	51.1 2.012	37.6 1.4803	20 0.7874	1.5 0.059	18.8 0.740	32.3 1.272	6.8 0.268	M10×1.25 ⅝-24UNF	55.5 2.185
40 1½ 1⅞	<b>UEL208D1W3</b> <b>UEL208-108D1W3</b> <b>UEL208-109D1W3</b>	40 1.5000 1.5625	80 3.1496	56.3 2.217	42.8 1.6850	21 0.8268	1.5 0.059	21.4 0.843	34.9 1.374	6.8 0.268	M10×1.25 ⅝-24UNF	60 2.362
45 1⅝ 1⅞ 1¾	<b>UEL209D1W3</b> <b>UEL209-110D1W3</b> <b>UEL209-111D1W3</b> <b>UEL209-112D1W3</b>	45 1.6250 1.6875 1.7500	85 3.3465	56.3 2.217	42.8 1.6850	22 0.8661	1.5 0.059	21.4 0.843	34.9 1.374	6.8 0.268	M10×1.25 ⅝-24UNF	63.5 2.500

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions mm inch		Basic load ratings N lbf		Mass kg lb
<i>B</i> <sub>5</sub>	<i>F</i>	dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
13.5	4.7	12 800	6 650	0.23
0.531	0.185	2 890	1 500	0.45
13.5	4.5	14 000	7 850	0.27
				0.61
0.531	0.177	3 150	1 770	0.58
				0.55
				0.51
15.9	4.6	19 500	11 300	0.45
				0.94
0.626	0.181	4 400	2 540	0.89
				0.84
				0.80
17.5	4.6	25 700	15 300	0.60
				1.45
0.689	0.181	5 750	3 450	1.40
				1.35
				1.28
18.3	4.5	29 100	17 800	0.78
				1.90
0.720	0.177	6 550	4 000	1.82
				1.82
18.3	4.9	32 500	20 400	0.80
				2.05
0.720	0.193	7 350	4 600	1.97
				1.88

## Ball bearings Eccentric locking collar type




Shaft dia. mm inch	Bearing (*) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	<i>r</i> mm inch min.	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>
50 1 3/16	UEL210D1W3	50	90	62.7	49.2	24	1.5	24.6	38.1	6.8	M10x1.25	69.5
	UEL210-113D1W3	1.8125										
	UEL210-114D1W3	1.8750										
1 7/8	UEL210-115D1W3	1.9375	3.5433	2.469	1.9370	0.9449	0.059	0.969	1.500	0.268	3/8-24UNF	2.736
1 9/16	UEL210-115D1W3	1.9375										
2	UEL210-200D1W3	2.0000										
55 2	UEL211D1W3	55	100	71.4	55.5	25	2	27.75	43.6	8	M10x1.25	76
	UEL211-200D1W3	2.0000										
	UEL211-201D1W3	2.0625										
2 1/16	UEL211-201D1W3	2.0625	3.9370	2.811	2.1850	0.9843	0.079	1.093	1.717	0.315	3/8-24UNF	2.992
2 1/8	UEL211-202D1W3	2.1250										
2 3/16	UEL211-203D1W3	2.1875										
60 2 1/4	UEL212D1W3	60	110	77.8	61.9	27	2	30.95	46.8	8	M10x1.25	84
	UEL212-204D1W3	2.2500										
	UEL212-205D1W3	2.3125										
2 5/16	UEL212-205D1W3	2.3125	4.3307	3.063	2.4370	1.0630	0.079	1.219	1.843	0.315	3/8-24UNF	3.307
2 3/8	UEL212-206D1W3	2.3750										
2 7/16	UEL212-207D1W3	2.4375										
65 2 1/2	UEL213D1W3	65	120	85.7	68.3	32	2	34.15	51.55	8.7	M10x1.25	97
	UEL213-208D1W3	2.5000										
	UEL213-209D1W3	2.5625										
2 9/16	UEL213-209D1W3	2.5625	4.7244	3.374	2.6890	1.2598	0.079	1.344	2.030	0.343	3/8-24UNF	3.819
70 2 5/8	UEL214D1W3	70	125	85.7	68.3	33	2	34.15	51.55	8.7	M10x1.25	97
	UEL214-210D1W3	2.6250										
	UEL214-211D1W3	2.6875										
2 11/16	UEL214-211D1W3	2.6875	4.9213	3.374	2.6890	1.2992	0.079	1.344	2.030	0.343	3/8-24UNF	3.819
2 3/4	UEL214-212D1W3	2.7500										
75 2 9/16	UEL215D1W3	75	130	92	74.6	34	2	37.3	54.7	8.7	M10x1.25	102
	UEL215-213D1W3	2.8125										
	UEL215-214D1W3	2.8750										
2 7/8	UEL215-214D1W3	2.8750	5.1181	3.622	2.9370	1.3386	0.079	1.469	2.154	0.343	3/8-24UNF	4.016
2 15/16	UEL215-215D1W3	2.9375										
3	UEL215-300D1W3	3.0000										

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions mm inch		Basic load ratings N lbf		Mass kg lb
<i>B</i> <sub>5</sub>	<i>F</i>	dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
18.3	5.9	35 000	23 200	0.96 2.46
0.720	0.232	7 900	5 200	2.36 2.25 2.09
20.7	6.0	43 500	29 200	1.32 3.28
0.815	0.236	9 750	6 550	3.12 3.02 2.90
22.3	6.2	52 500	36 000	1.79 4.38
0.878	0.244	11 800	8 150	4.22 4.05 3.88
23.8	8.7	57 500	40 000	2.54 5.47
0.937	0.343	12 900	9 000	5.30 5.18
23.8	8.8	62 000	44 000	2.47 5.67
0.937	0.346	14 000	9 900	5.45 5.18
23.8	9.0	66 000	49 500	2.68 6.39
0.937	0.354	14 900	11 100	6.15 5.91 5.60



## Ball bearings Eccentric locking collar type




Shaft dia. mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	<i>r</i> mm inch min.	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>
25 1 3/8	UEL305D1W3	25	62	46.8	34.9	20	1.5	16.7	30.1	6	M8×1	42.8
	UEL305-013D1W3	0.8125										
	UEL305-014D1W3	0.8750	2.4409	1.843	1.3740	0.7874	0.059	0.657	1.185	0.236	5/16-24UNF	1.685
	UEL305-015D1W3	0.9375										
1	UEL305-100D1W3	1.0000										
30 1 1/8	UEL306D1W3	30	72	50	36.5	23	1.5	17.5	32.5	6.7	M8×1	50
	UEL306-101D1W3	1.0625										
	UEL306-102D1W3	1.1250	2.8346	1.969	1.4370	0.9055	0.059	0.689	1.280	0.264	5/16-24UNF	1.969
	UEL306-103D1W3	1.1875										
35 1 1/4	UEL307D1W3	35	80	51.6	38.1	25	2	18.3	33.3	6.7	M8×1	55
	UEL307-104D1W3	1.2500										
	UEL307-105D1W3	1.3125	3.1496	2.031	1.5000	0.9843	0.079	0.720	1.311	0.264	5/16-24UNF	2.165
	UEL307-106D1W3	1.3750										
	UEL307-107D1W3	1.4375										
40 1 1/2	UEL308D1W3	40	90	57.1	41.3	27	2	19.8	37.3	8	M10×1.25	63.5
	UEL308-108D1W3	1.5000	3.5433	2.248	1.6260	1.0630	0.079	0.780	1.469	0.315	3/8-24UNF	2.500
	UEL308-109D1W3	1.5625										
45 1 5/8	UEL309D1W3	45	100	58.7	42.9	29	2	19.8	38.9	8	M10×1.25	70
	UEL309-110D1W3	1.6250										
	UEL309-111D1W3	1.6875	3.9370	2.311	1.6890	1.1417	0.079	0.780	1.531	0.315	3/8-24UNF	2.756
	UEL309-112D1W3	1.7500										
50 1 3/4	UEL310D1W3	50	110	66.6	49.2	32	2.5	24.6	42	8.7	M10×1.25	76.2
	UEL310-113D1W3	1.8125										
	UEL310-114D1W3	1.8750	4.3307	2.622	1.9370	1.2598	0.098	0.969	1.654	0.343	3/8-24UNF	3.000
	UEL310-115D1W3	1.9375										

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions mm inch		Basic load ratings N lbf		Mass kg lb
<i>B</i> <sub>5</sub>	<i>F</i>	dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
15.9	5.0	21 200	10 900	0.43
				1.09
0.626	0.197	4 750	2 460	1.05
				1.01
				0.96
17.5	5.9	26 700	15 000	0.69
				1.57
0.689	0.232	6 000	3 400	1.51
				1.45
17.5	6.8	33 500	19 100	0.78
				1.92
0.689	0.268	7 500	4 300	1.84
				1.77
				1.69
20.6	7.4	40 500	24 000	1.08
				2.58
0.811	0.291	9 150	5 400	2.49
20.6	7.4	53 000	32 000	1.40
				3.36
0.811	0.291	11 900	7 200	3.26
				3.15
22.2	8.1	62 000	38 500	1.84
				4.40
0.874	0.319	13 900	8 600	4.29
				4.15

## Ball bearings Eccentric locking collar type




Shaft dia. mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	<i>r</i> mm inch min.	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>
55	UEL311D1W3	55	120	73	55.6	34	2.5	27.8	45.2	8.7	M10x1.25	83
2	UEL311-200D1W3	2.0000										
2 1/16	UEL311-201D1W3	2.0625	4.7244	2.874	2.1890	1.3386	0.098	1.094	1.780	0.343	3/8-24UNF	3.268
2 1/8	UEL311-202D1W3	2.1250										
2 3/16	UEL311-203D1W3	2.1875										
60	UEL312D1W3	60	130	79.4	61.9	36	2.5	30.95	48.45	8.7	M10x1.25	89
2 1/4	UEL312-204D1W3	2.2500										
2 5/16	UEL312-205D1W3	2.3125	5.1181	3.126	2.4370	1.1473	0.098	1.219	1.907	0.343	3/8-24UNF	3.504
2 3/8	UEL312-206D1W3	2.3750										
2 7/16	UEL312-207D1W3	2.4375										
65	UEL313D1W3	65	140	85.7	65.1	39	2.5	32.55	53.15	10.3	M12x1.5	97
2 1/2	UEL313-208D1W3	2.5000	5.5118	3.374	2.5630	1.5354	0.098	1.281	2.093	0.406	1/2-20UNF	3.819
2 9/16	UEL313-209D1W3	2.5625										
70	UEL314D1W3	70	150	92.1	68.3	41	2.5	34.15	57.95	10.3	M12x1.5	102
2 5/8	UEL314-210D1W3	2.6250										
2 11/16	UEL314-211D1W3	2.6875	5.9055	3.626	2.6890	1.6142	0.098	1.344	2.281	0.406	1/2-20UNF	4.016
2 3/4	UEL314-212D1W3	2.7500										
75	UEL315D1W3	75	160	100	74.6	43	2.5	37.3	62.7	12.7	M16x1.5	113
2 3/16	UEL315-213D1W3	2.8125										
2 7/8	UEL315-214D1W3	2.8750	6.2992	3.937	2.9370	1.6929	0.098	1.469	2.469	0.500	5/8-18UNF	4.449
2 5/16	UEL315-215D1W3	2.9375										
3	UEL315-300D1W3	3.0000										
80	UEL316D1W3	80	170	106.4	81	45	2.5	40.5	65.9	12.7	M16x1.5	119
3 1/16	UEL316-301D1W3	3.0625										
3 1/8	UEL316-302D1W3	3.1250	6.6929	4.189	3.1890	1.7717	0.098	1.594	2.594	0.500	5/8-18UNF	4.685
3 3/16	UEL316-303D1W3	3.1875										

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions mm inch		Basic load ratings N lbf		Mass kg lb
<i>B</i> <sub>5</sub>	<i>F</i>	dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
22.2	8.5	71 500	45 000	2.36
				5.58
0.874	0.335	16 100	10 100	5.39
				5.25
				5.08
23.9	9.0	82 000	52 000	2.94
				6.80
0.941	0.354	18 400	11 700	6.65
				6.48
				6.19
27	10.1	92 500	60 000	3.67
				8.49
1.063	0.398	20 800	13 400	8.27
30.2	10.5	104 000	68 000	4.40
				10.4
1.189	0.413	23 400	15 300	10.2
				9.96
31.8	11.0	113 000	77 000	5.34
				13.2
1.252	0.433	25 500	17 400	12.9
				12.7
				12.5
31.8	11.4	123 000	86 500	6.70
				14.9
1.252	0.449	27 600	19 500	14.8
				14.6

## Ball bearings Eccentric locking collar type




Shaft dia. mm inch	Bearing (*) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	<i>r</i> mm inch min.	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>
85 3 3/4	<b>UEL317D1W3</b> <b>UEL317-304D1W3</b>	85	180	109.5	84.1	47	3	42.05	67.45	12.7	M16×1.5	127
3 5/16	<b>UEL317-305D1W3</b>	3.3125	7.0866	4.311	3.3110	1.8504	0.118	1.656	2.656	0.500	5/8-18UNF	5.000
3 7/16	<b>UEL317-307D1W3</b>	3.4375										
90 3 7/16	<b>UEL318D1W3</b> <b>UEL318-307D1W3</b>	90	190	115.9	87.3	49	3	43.65	72.25	14.3	M20×1.5	133
3 1/2	<b>UEL318-308D1W3</b>	3.4375	7.4803	4.563	3.4370	1.9291	0.118	1.719	2.844	0.563	3/4-16UNF	5.236
95 3 5/8	<b>UEL319D1W3</b> <b>UEL319-310D1W3</b>	95	200	122.3	93.7	51	3	38.9	83.4	14.3	M20×1.5	140
3 11/16	<b>UEL319-311D1W3</b>	3.6250										
3 3/4	<b>UEL319-312D1W3</b>	3.6875	7.8740	4.815	3.6890	2.0079	0.118	1.531	3.283	0.563	3/4-16UNF	5.512
100 3 3/8	<b>UEL320D1W3</b> <b>UEL320-313D1W3</b>	100	215	128.6	100	55	3	50	78.6	14.3	M20×1.5	146
3 7/8	<b>UEL320-314D1W3</b>	3.8125										
3 15/16	<b>UEL320-315D1W3</b>	3.8750	8.4646	5.063	3.9370	2.1654	0.118	1.969	3.094	0.563	3/4-16UNF	5.748
4	<b>UEL320-400D1W3</b>	3.9375										
105	<b>UEL321D1W3</b>	4.0000										
110	<b>UEL322D1W3</b>	105	225	139.7	104.8	57	3	48.4	91.3	17.5	M20×1.5	157
		110	240	141.3	106.4	59	3	49.2	92.1	17.5	M20×1.5	168

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions mm inch		Basic load ratings N lbf		Mass kg lb
<i>B</i> <sub>5</sub>	<i>F</i>	dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
31.8	12.0	133 000	97 000	8.00 18.0
1.252	0.472	29 800	21 800	17.7 17.0
36.5	12.3	143 000	107 000	9.10 20.7
1.437	0.484	32 000	24 100	20.2 20.2
36.5	12.8	153 000	119 000	10.4 23.4
1.437	0.504	34 500	26 600	23.0 22.6
36.5	13.5	173 000	141 000	13.0 28.5
1.437	0.531	39 000	31 500	28.0 27.6
42.8	13.9	184 000	153 000	14.6 27.0
42.8	13.9	205 000	179 000	17.2

## Ball bearings Eccentric locking collar type



Shaft dia. mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	<i>r</i> mm inch min.	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>
12	AEL201W3	12	40	28.6	19	12	0.6	6.5	22.1	4.8	M6×0.75	29
1/2	AEL201-008W3	0.5000	1.5748	1.126	0.7480	0.4724	0.024	0.256	0.870	0.189	1/4-28UNF	1.142
15	AEL202W3	15	40	28.6	19	12	0.6	6.5	22.1	4.8	M6×0.75	29
9/16	AEL202-009W3	0.5625	1.5748	1.126	0.7480	0.4724	0.024	0.256	0.870	0.189	1/4-28UNF	1.142
5/8	AEL202-010W3	0.6250										
17	AEL203W3	17	40	28.6	19	12	0.6	6.5	22.1	4.8	M6×0.75	29
11/16	AEL203-011W3	0.6875	1.5748	1.126	0.7480	0.4724	0.024	0.256	0.870	0.189	1/4-28UNF	1.142
20	AEL204W3	20	47	31	21.5	14	1	7.5	23.5	4.8	M6×0.75	33
3/4	AEL204-012W3	0.7500	1.8504	1.220	0.8465	0.5512	0.039	0.295	0.925	0.189	1/4-28UNF	1.299
25	AEL205W3	25	52	31	21.5	15	1	7.5	23.5	4.8	M6×0.75	38
19/16	AEL205-013W3	0.8125										
7/8	AEL205-014W3	0.8750	2.0472	1.220	0.8465	0.5906	0.039	0.295	0.925	0.189	1/4-28UNF	1.496
15/16	AEL205-015W3	0.9375										
1	AEL205-100W3	1.0000										
30	AEL206W3	30	62	35.7	23.8	16	1	9	26.7	6	M8×1	44.5
1 1/16	AEL206-101W3	1.0625										
1 1/8	AEL206-102W3	1.1250	2.4409	1.406	0.9370	0.6299	0.039	0.354	1.051	0.236	5/16-24UNF	1.752
1 3/16	AEL206-103W3	1.1875										
1 1/4	AEL206-104W3	1.2500										
35	AEL207W3	35	72	38.9	25.4	17	1.5	9.5	29.4	6.8	M10×1.25	55.5
1 1/4	AEL207-104W3	1.2500										
1 5/16	AEL207-105W3	1.3125	2.8346	1.531	1.0000	0.6693	0.059	0.374	1.157	0.268	3/8-24UNF	2.185
1 3/8	AEL207-106W3	1.3750										
1 7/16	AEL207-107W3	1.4375										
40	AEL208W3	40	80	43.7	30.2	18	1.5	11	32.7	6.8	M10×1.25	60
1 1/2	AEL208-108W3	1.5000	3.1496	1.720	1.1890	0.7087	0.059	0.433	1.287	0.268	3/8-24UNF	2.362
1 9/16	AEL208-109W3	1.5625										

Note (1) If relubricatable type is needed, please order with suffix "D1".

Nominal dimensions mm inch <i>B</i> <sub>5</sub>	Basic load ratings		Mass kg lb
	N dynamic <i>C</i> <sub>r</sub>	lbf static <i>C</i> <sub>or</sub>	
13.6	9 600	4 600	0.12
0.535	2 160	1 030	0.26
13.6	9 600	4 600	0.11
0.535	2 160	1 030	0.26
13.6	9 600	4 600	0.10
0.535	2 160	1 030	0.23
13.5	12 800	6 650	0.17
0.531	2 890	1 500	0.35
13.5	14 000	7 850	0.22
			0.51
			0.48
0.531	3 150	1 770	0.45
			0.42
15.9	19 500	11 300	0.31
			0.74
			0.73
0.626	4 400	2 540	0.66
			0.61
17.5	25 700	15 300	0.50
			1.15
			1.10
0.689	5 750	3 450	1.04
			0.98
18.3	29 100	17 800	0.66
			1.41
0.720	6 550	4 000	1.34

## Ball bearings Eccentric locking collar type




Shaft dia. mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	<i>r</i> mm inch min.	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>
12 ½	JEL201W3	12	40	28.6	19	13	0.6	6.5	22.1	4.8	M6×0.75	29
	JEL201-008W3	0.5000	1.5748	1.126	0.7480	0.5118	0.024	0.256	0.870	0.189	¼-28UNF	1.142
15 9/16 5/8	JEL202W3	15	40	28.6	19	13	0.6	6.5	22.1	4.8	M6×0.75	29
	JEL202-009W3	0.5625	1.5748	1.126	0.7480	0.5118	0.024	0.256	0.870	0.189	¼-28UNF	1.142
	JEL202-010W3	0.6250										
17 11/16	JEL203W3	17	40	28.6	19	13	0.6	6.5	22.1	4.8	M6×0.75	29
	JEL203-011W3	0.6875	1.5748	1.126	0.7480	0.5118	0.024	0.256	0.870	0.189	¼-28UNF	1.142
20 ¾	JEL204W3	20	47	31	21.5	15	1	7.5	23.5	4.8	M6×0.75	33
	JEL204-012W3	0.7500	1.8504	1.220	0.8465	0.5906	0.039	0.295	0.925	0.189	¼-28UNF	1.299
25 19/16 7/8 15/16	JEL205W3	25	52	31	21.5	15	1	7.5	23.5	4.8	M6×0.75	38
	JEL205-013W3	0.8125										
	JEL205-014W3	0.8750	2.0472	1.220	0.8465	0.5906	0.039	0.295	0.925	0.189	¼-28UNF	1.496
	JEL205-015W3	0.9375										
1	JEL205-100W3	1.0000										
30 1 1/16 1 1/8 1 3/16 1 1/4	JEL206W3	30	62	35.7	23.8	18	1	9	26.7	6	M8×1	44.5
	JEL206-101W3	1.0625										
	JEL206-102W3	1.1250	2.4409	1.406	0.9370	0.7087	0.039	0.354	1.051	0.236	5/16-24UNF	1.752
	JEL206-103W3	1.1875										
1 1/4	JEL206-104W3	1.2500										
35 1 1/4 1 5/16 1 3/8 1 7/16	JEL207W3	35	72	38.9	25.4	19	1.5	9.5	29.4	6.8	M10×1.25	55.5
	JEL207-104W3	1.2500										
	JEL207-105W3	1.3125	2.8346	1.531	1.0000	0.7480	0.059	0.374	1.157	0.268	3/8-24UNF	2.185
	JEL207-106W3	1.3750										
	JEL207-107W3	1.4375										
40 1 1/2 1 9/16	JEL208W3	40	80	43.7	30.2	22	1.5	11	32.7	6.8	M10×1.25	60
	JEL208-108W3	1.5000	3.1496	1.720	1.1890	0.8661	0.059	0.433	1.287	0.268	3/8-24UNF	2.362
	JEL208-109W3	1.5625										

Note (1) If relubricatable type is needed, please order with suffix "D1".

Nominal dimensions mm inch <i>B</i> <sub>5</sub>	Basic load ratings		Mass kg lb
	dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
13.6	9 600	4 600	0.12
0.535	2 160	1 030	0.25
13.6	9 600	4 600	0.10
0.535	2 160	1 030	0.24
			0.22
13.6	9 600	4 600	0.09
0.535	2 160	1 030	0.20
13.5	12 800	6 650	0.16
0.531	2 890	1 500	0.37
13.5	14 000	7 850	0.19
			0.50
			0.47
0.531	3 150	1 770	0.44
			0.41
15.9	19 500	11 300	0.33
			0.78
			0.73
0.626	4 400	2 540	0.69
			0.64
17.5	25 700	15 300	0.50
			1.22
			1.16
0.689	5 750	3 450	1.11
			1.05
18.3	29 100	17 800	0.65
			1.53
0.720	6 550	4 000	1.46

## Ball bearings Eccentric locking collar type




Shaft dia. mm inch	Bearing (1) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	<i>r</i> mm inch min.	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>
20 ¾	REL204W3	20	47	43.7	34.2	15	1	17.1	26.6	4.8	M6×0.75	33.0
	REL204-012W3	0.7500	1.8504	1.720	1.3465	0.5906	0.039	0.673	1.047	0.189	¼-28UNF	1.299
25 13/16 7/8 15/16	REL205W3	25	52	44.4	34.9	15	1	17.45	26.9	4.8	M6×0.75	38.0
	REL205-013W3	0.8125										
	REL205-014W3	0.8750	2.0472	1.748	1.3740	0.5906	0.039	0.687	1.059	0.189	¼-28UNF	1.496
	REL205-015W3	0.9375										
1	REL205-100W3	1.0000										
30 1 1/16 1 1/8 1 3/16 1 1/4	REL206W3	30	62	48.4	36.5	18	1	18.25	30.1	6	M8×1	44.5
	REL206-101W3	1.0625										
	REL206-102W3	1.1250	2.4409	1.906	1.4370	0.7087	0.039	0.719	1.185	0.236	5/16-24UNF	1.752
	REL206-103W3	1.1875										
1 1/4	REL206-104W3	1.2500										
35 1 1/4 1 5/16 1 3/8 1 7/16	REL207W3	35	72	51.1	37.6	19	1.5	18.8	32.3	6.8	M10×1.25	55.5
	REL207-104W3	1.2500										
	REL207-105W3	1.3125	2.8346	2.012	1.4803	0.7480	0.059	0.740	1.272	0.268	3/8-24UNF	2.185
	REL207-106W3	1.3750										
1 7/16	REL207-107W3	1.4375										
40 1 1/2 1 9/16	REL208W3	40	80	56.3	42.8	22	1.5	21.4	34.9	6.8	M10×1.25	60.0
	REL208-108W3	1.5000	3.1496	2.217	1.6850	0.8661	0.059	0.843	1.374	0.268	3/8-24UNF	2.362
	REL208-109W3	1.5625										
45 1 5/8 1 11/16 1 3/4	REL209W3	45	85	56.3	42.8	22	1.5	21.4	34.9	6.8	M10×1.25	63.5
	REL209-110W3	1.6250										
	REL209-111W3	1.6875	3.3465	2.217	1.6850	0.8661	0.059	0.843	1.374	0.268	3/8-24UNF	2.500
	REL209-112W3	1.7500										

Note (1) If relubricatable type is needed, please order with suffix "D1".

Nominal dimensions mm inch <i>B</i> <sub>5</sub>	Basic load ratings		Mass kg lb
	N dynamic <i>C</i> <sub>r</sub>	lbf static <i>C</i> <sub>or</sub>	
13.5 0.531	12 800	6 650	0.22
	2 890	1 500	0.43
13.5 0.531	14 000	7 850	0.26
	3 150	1 770	0.59
15.9 0.626	19 500	11 300	0.39
	4 400	2 540	0.87
17.5 0.689	25 700	15 300	0.59
	5 750	3 450	1.36
18.3 0.720	29 100	17 800	0.76
	6 550	4 000	1.88
18.3 0.720	32 500	20 400	0.78
	7 350	4 600	2.01
18.3 0.720	32 500	20 400	0.78
	7 350	4 600	1.93
18.3 0.720	32 500	20 400	0.78
	7 350	4 600	1.84

## Ball bearings Eccentric locking collar type




Shaft dia. mm inch	Bearing (*) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	<i>r</i> mm inch min.	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>
50 1 3/16	REL210W3	50	90	62.7	49.2	22	1.5	24.6	38.1	6.8	M10x1.25	69.5
	REL210-113W3	1.8125										
	REL210-114W3	1.8750	3.5433	2.469	1.9370	0.8661	0.059	0.969	1.500	0.268	3/8-24UNF	2.736
	REL210-115W3	1.9375										
	REL210-200W3	2.0000										
55 2	REL211W3	55	100	71.4	55.5	24	2	27.75	43.6	8	M10x1.25	76
	REL211-200W3	2.0000										
	REL211-201W3	2.0625	3.9370	2.811	2.1850	0.9449	0.079	1.093	1.717	0.315	3/8-24UNF	2.992
	REL211-202W3	2.1250										
	REL211-203W3	2.1875										
60 2 1/4	REL212W3	60	110	77.8	61.9	27	2	30.95	46.8	8	M10x1.25	84
	REL212-204W3	2.2500										
	REL212-205W3	2.3125	4.3307	3.063	2.4370	1.0630	0.079	1.219	1.843	0.315	3/8-24UNF	3.307
	REL212-206W3	2.3750										
	REL212-207W3	2.4375										

Note (\*) If relubricatable type is needed, please order with suffix "D1".

Nominal dimensions mm inch <i>B</i> <sub>5</sub>	Basic load ratings		Mass kg lb
	N dynamic <i>C</i> <sub>r</sub>	lbf static <i>C</i> <sub>or</sub>	
18.3	35 000	23 200	0.96 2.42
0.720	7 900	5 200	2.32 2.21 2.05
20.7	43 500	29 200	1.28 3.21
0.815	9 750	6 550	3.05 2.95 2.83
22.3	52 500	36 000	1.83 4.29
0.878	11 800	8 150	4.13 3.96 3.79

## Ball bearings Adapter type



UK2...D1;H, HA, HE, HS

UK2...D1


Shaft dia. mm inch	Bearing <sup>(1)</sup> ( <sup>2</sup> )( <sup>3</sup> ) number	Nominal dimensions									
		mm inch									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>d</i> <sub>4</sub>	<i>d</i> <sub>1</sub>	<i>B</i> <sub>1</sub>	<i>B</i> <sub>2</sub>	<i>d</i> <sub>2</sub>	<i>F</i>
20 ¾	UK205D1;H2305X UK205D1;HE2305	25 0.9843	52 2.0472	23 0.9055	17 0.6693	33.9 1.335	20 ¾	35 1.378	8 0.315	38 1.496	4.5 0.177
25 ⅞	UK206D1;H2306X UK206D1;HS2306	30 1.1811	62 2.4409	26 1.0236	19 0.7480	40.8 1.606	25 ⅞	38 1.496	8 0.315	45 1.772	4.6 0.181
1	UK206D1;HE2306X						1				
30 1 ⅛	UK207D1;H2307X UK207D1;HS2307	35 1.3780	72 2.8346	29 1.1417	20 0.7874	46.8 1.843	30 1 ⅛	43 1.693	9 0.354	52 2.047	4.6 0.181
35 1 ¼	UK208D1;H2308X UK208D1;HE2308X	40 1.5748	80 3.1496	31 1.2205	21 0.8268	53 2.087	35 1 ¼	46 1.811	10 0.394	58 2.283	4.5 0.177
1 ⅜	UK208D1;HS2308X						1 ⅜				
40 1 ⅞	UK209D1;H2309X UK209D1;HA2309	45 1.7717	85 3.3465	31 1.2205	22 0.8661	57.5 2.264	40 1 ⅞	50 1.969	11 0.433	65 2.559	4.9 0.193
1 ½	UK209D1;HE2309X						1 ½				
1 ⅝	UK209D1;HS2309X						1 ⅝				
45 1 ⅝	UK210D1;H2310X UK210D1;HS2310	50 1.9685	90 3.5433	32 1.2598	24 0.9449	62.4 2.457	45 1 ⅝	55 2.165	12 0.472	70 2.756	5.9 0.232
1 ⅞	UK210D1;HA2310						1 ⅞				
1 ¾	UK210D1;HE2310X						1 ¾				
50 1 ⅞	UK211D1;H2311X UK211D1;HS2311	55 2.1654	100 3.9370	35 1.3780	25 0.9843	69 2.717	50 1 ⅞	59 2.323	12 0.472	75 2.953	6.0 0.236
1 ⅝	UK211D1;HA2311						1 ⅝				
2	UK211D1;HE2311XY						2				
55 2 ⅞	UK212D1;H2312X UK212D1;HS2312	60 2.3622	110 4.3307	38 1.4961	27 1.0630	77 3.031	55 2 ⅞	62 2.441	13 0.512	80 3.150	6.2 0.244

Basic load ratings		Mass kg lb
N lbf		
dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
14 000	7 850	0.23
3 150	1 770	0.57
19 500	11 300	0.36
4 400	2 540	0.86
25 700	15 300	0.78
5 750	3 450	1.30
29 100	17 800	0.74
6 550	4 000	1.77
32 500	20 400	1.63
		2.01
7 350	4 600	1.93
		1.76
35 000	23 200	0.94
		2.38
7 900	5 200	2.28
		2.18
43 500	29 200	1.22
		2.96
9 750	6 550	2.84
		2.70
52 500	36 000	1.54
11 800	8 150	3.60

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
 In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.  
 To distinguish it, a suffix "Y" is added.



## Ball bearings Adapter type



UK2...D1;H, HA, HE, HS

UK2...D1


Shaft dia. mm inch	Bearing <sup>(1)(2)</sup> number	Nominal dimensions									
		mm inch									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>d</i> <sub>4</sub>	<i>d</i> <sub>1</sub>	<i>B</i> <sub>1</sub>	<i>B</i> <sub>2</sub>	<i>d</i> <sub>2</sub>	<i>F</i>
60 2 3/16 2 1/4 2 3/8	UK213D1;H2313X UK213D1;HA2313 UK213D1;HE2313X UK213D1;HS2313X	65 2.5591	120 4.7244	40 1.5748	32 1.2598	82.5 3.248	60 2 3/16 2 1/4 2 3/8	65 2.559	14 0.551	85 3.346	8.7 0.343
65 2 7/16 2 1/2	UK215D1;H2315X UK215D1;HA2315 UK215D1;HE2315X	75 2.9528	130 5.1181	44 1.7323	34 1.3386	93 3.661	65 2 7/16 2 1/2	73 2.874	15 0.591	98 3.858	9.0 0.354
70 2 11/16 2 3/4	UK216D1;H2316X UK216D1;HA2316 UK216D1;HE2316X	80 3.1496	140 5.5118	45 1.7717	35 1.3780	98.1 3.862	70 2 11/16 2 3/4	78 3.071	17 0.669	105 4.134	9.5 0.374
75 2 5/8 3	UK217D1;H2317X UK217D1;HA2317X UK217D1;HE2317X	85 3.3465	150 5.9055	46 1.8110	36 1.4173	106.4 4.189	75 2 5/8 3	82 3.228	18 0.709	110 4.331	10.1 0.398
80 3 1/16	UK218D1;H2318X UK218D1;HA2318X	90 3.5433	160 6.2992	47 1.8504	37 1.4567	111.6 4.394	80 3 1/16	86 3.386	18 0.709	120 4.724	9.8 0.386

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.

Basic load ratings		Mass kg lb
N lbf		
dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
57 500	40 000	2.00 4.86
12 900	9 000	4.70 4.38
66 000	49 500	2.56 6.04
14 900	11 100	5.84
72 500	53 000	3.23 7.38
16 300	11 900	7.14
83 500	64 000	3.93 8.73
18 700	14 300	8.46
96 000	71 500	4.51
21 600	16 100	11.0

## Ball bearings Adapter type



UK3...D1;H, HA, HE, HS


UK3...D1

Shaft dia. mm inch	Bearing <sup>(1)</sup> ( <sup>2</sup> )( <sup>3</sup> ) number	Nominal dimensions									
		mm inch									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>d</i> <sub>4</sub>	<i>d</i> <sub>1</sub>	<i>B</i> <sub>1</sub>	<i>B</i> <sub>2</sub>	<i>d</i> <sub>2</sub>	<i>F</i>
20 3/4	UK305D1;H2305X UK305D1;HE2305	25 0.9843	62 2.4409	26 1.0236	20 0.7874	36.8 1.449	20 3/4	35 1.378	8 0.315	38 1.496	5.0 0.197
25 7/8 1	UK306D1;H2306X UK306D1;HS2306 UK306D1;HE2306X	30 1.1811	72 2.8346	29 1.1417	23 0.9055	44.9 1.768	25 7/8 1	38 1.496	8 0.315	45 1.772	5.9 0.232
30 1 1/8	UK307D1;H2307X UK307D1;HS2307	35 1.3780	80 3.1496	33 1.2992	25 0.9843	49.4 1.945	30 1 1/8	43 1.693	9 0.354	52 2.047	6.8 0.268
35 1 1/4 1 3/8	UK308D1;H2308X UK308D1;HE2308X UK308D1;HS2308X	40 1.5748	90 3.5433	34 1.3386	27 1.0630	56 2.205	35 1 1/4 1 3/8	46 1.811	10 0.394	58 2.283	7.4 0.291
40 1 7/16 1 1/2 1 5/8	UK309D1;H2309X UK309D1;HA2309 UK309D1;HE2309X UK309D1;HS2309X	45 1.7717	100 3.9370	37 1.4567	29 1.1417	63.5 2.500	40 1 7/16 1 1/2 1 5/8	50 1.969	11 0.433	65 2.559	7.4 0.291
45 1 5/8 1 11/16 1 3/4	UK310D1;H2310X UK310D1;HS2310 UK310D1;HA2310 UK310D1;HE2310X	50 1.9685	110 4.3307	41 1.6142	32 1.2598	70.6 2.780	45 1 5/8 1 11/16 1 3/4	55 2.165	12 0.472	70 2.756	8.1 0.319
50 1 7/8 1 15/16 2	UK311D1;H2311X UK311D1;HS2311 UK311D1;HA2311 UK311D1;HE2311XY	55 2.1654	120 4.7244	44 1.7323	34 1.3386	76.6 3.016	50 1 7/8 1 15/16 2	59 2.323	12 0.472	75 2.953	8.5 0.335
55 2 1/8	UK312D1;H2312X UK312D1;HS2312	60 2.3622	130 5.1181	47 1.8504	36 1.4173	82.7 3.256	55 2 1/8	62 2.441	13 0.512	80 3.150	9.0 0.354

Basic load ratings		Mass kg lb
N lbf		
dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
21 200	10 900	0.36
4 750	2 460	0.81
26 700	15 000	0.59
6 000	3 400	1.37
		1.29
33 500	19 100	0.75
7 500	4 300	1.70
40 500	24 000	1.00
9 150	5 400	2.38
		2.25
53 000	32 000	1.28
		3.22
11 900	7 200	3.14
		2.97
62 000	38 500	1.72
		3.95
13 900	8 600	3.85
		3.74
71 500	45 000	2.06
		4.73
16 100	10 100	4.60
		4.46
82 000	52 000	2.58
18 400	11 700	5.67

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
 In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.  
 To distinguish it, a suffix "Y" is added.

## Ball bearings Adapter type



UK3...D1;H, HA, HE, HS

UK3...D1


Shaft dia. mm inch	Bearing <sup>(1)(2)</sup> number	Nominal dimensions									
		mm inch									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>d</i> <sub>4</sub>	<i>d</i> <sub>1</sub>	<i>B</i> <sub>1</sub>	<i>B</i> <sub>2</sub>	<i>d</i> <sub>2</sub>	<i>F</i>
60 2 3/16 2 1/4 2 3/8	UK313D1;H2313X UK313D1;HA2313 UK313D1;HE2313X UK313D1;HS2313X	65 2.5591	140 5.5118	49 1.9291	39 1.5354	88.2 3.472	60 2 3/16 2 1/4 2 3/8	65 2.559	14 0.551	85 3.346	10.1 0.398
65 2 7/16 2 1/2	UK315D1;H2315X UK315D1;HA2315 UK315D1;HE2315X	75 2.9528	160 6.2992	55 2.1654	43 1.6929	101.3 3.988	65 2 7/16 2 1/2	73 2.874	15 0.591	98 3.858	11.0 0.433
70 2 11/16 2 3/4	UK316D1;H2316X UK316D1;HA2316 UK316D1;HE2316X	80 3.1496	170 6.6929	58 2.2835	45 1.7717	107.9 4.248	70 2 11/16 2 3/4	78 3.071	17 0.669	105 4.134	11.4 0.449
75 2 5/8 3	UK317D1;H2317X UK317D1;HA2317X UK317D1;HE2317X	85 3.3465	180 7.0866	60 2.3622	47 1.8504	114.4 4.504	75 2 5/8 3	82 3.228	18 0.709	110 4.331	12.0 0.472
80 3 1/16	UK318D1;H2318X UK318D1;HA2318X	90 3.5433	190 7.4803	64 2.5197	49 1.9291	120.9 4.760	80 3 1/16	86 3.386	18 0.709	120 4.724	12.3 0.484
85 3 1/4	UK319D1;H2319X UK319D1;HE2319X	95 3.7402	200 7.8740	67 2.6378	51 2.0079	127.5 5.020	85 3 1/4	90 3.543	19 0.748	125 4.921	12.8 0.504
90 3 7/16 3 1/2	UK320D1;H2320X UK320D1;HA2320 UK320D1;HE2320X	100 3.9370	215 8.4646	73 2.8740	55 2.1654	135.6 5.339	90 3 7/16 3 1/2	97 3.819	20 0.787	130 5.118	13.5 0.531
100	UK322D1;H2322X	110	240	80	59	151.7	100	105	21	145	13.9
110	UK324D1;H2324	120	260	86	63	165.2	110	112	22	155	16.0
115	UK326D1;H2326	130	280	90	67	178.3	115	121	23	165	16.9
125	UK328D1;H2328	140	300	95	71	190.4	125	131	24	180	17.7

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.

Basic load ratings		Mass
N lbf		kg lb
dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
92 500	60 000	3.08 7.24
20 800	13 400	7.08 6.76
113 000	77 000	4.75 11.1
25 500	17 400	10.9 5.75
123 000	86 500	12.9 12.7
27 600	19 500	14.6 6.72
133 000	97 000	14.9 14.6
29 800	21 800	17.2 7.75
143 000	107 000	17.2 9.02
32 000	24 100	20.4 11.0
153 000	119 000	24.7 25.1
34 500	26 600	25.1 14.9
173 000	141 000	18.0 23.3
39 000	31 500	23.3 28.6
205 000	179 000	28.6 18.0
207 000	185 000	23.3 28.6
229 000	214 000	28.6 18.0
253 000	246 000	18.0 28.6

## Ball bearings Adapter type



UKX...D1;H, HA, HE, HS


UKX...D1

Shaft dia. mm inch	Bearing <sup>(1)</sup> <sup>(2)</sup> <sup>(3)</sup> number	Nominal dimensions									
		mm inch									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>d</i> <sub>4</sub>	<i>d</i> <sub>1</sub>	<i>B</i> <sub>1</sub>	<i>B</i> <sub>2</sub>	<i>d</i> <sub>2</sub>	<i>F</i>
20 3/4	UKX05D1;H2305X UKX05D1;HE2305	25 0.9843	62 2.4409	26 1.0236	19 0.7480	40.8 1.606	20 3/4	35 1.378	8 0.315	38 1.496	4.6 0.181
25 7/8 1	UKX06D1;H2306X UKX06D1;HS2306 UKX06D1;HE2306X	30 1.1811	72 2.8346	29 1.1417	20 0.7874	46.8 1.843	25 7/8 1	38 1.496	8 0.315	45 1.772	4.6 0.181
30 1 1/8	UKX07D1;H2307X UKX07D1;HS2307	35 1.3780	80 3.1496	31 1.2205	21 0.8268	53 2.087	30 1 1/8	43 1.693	9 0.354	52 2.047	4.5 0.177
35 1 1/4 1 3/8	UKX08D1;H2308X UKX08D1;HE2308X UKX08D1;HS2308X	40 1.5748	85 3.3465	31 1.2205	22 0.8661	57.5 2.264	35 1 1/4 1 3/8	46 1.811	10 0.394	58 2.283	4.9 0.193
40 1 7/16 1 1/2 1 5/8	UKX09D1;H2309X UKX09D1;HA2309 UKX09D1;HE2309X UKX09D1;HS2309X	45 1.7717	90 3.5433	32 1.2598	24 0.9449	62.4 2.457	40 1 7/16 1 1/2 1 5/8	50 1.969	11 0.433	65 2.559	5.9 0.232
45 1 5/8 1 11/16 1 3/4	UKX10D1;H2310X UKX10D1;HS2310 UKX10D1;HA2310 UKX10D1;HE2310X	50 1.9685	100 3.9370	35 1.3780	25 0.9843	69 2.717	45 1 5/8 1 11/16 1 3/4	55 2.165	12 0.472	70 2.756	6.0 0.236
50 1 7/8 1 15/16 2	UKX11D1;H2311X UKX11D1;HS2311 UKX11D1;HA2311 UKX11D1;HE2311XY	55 2.1654	110 4.3307	38 1.4961	27 1.0630	77 3.031	50 1 7/8 1 15/16 2	59 2.323	12 0.472	75 2.953	6.2 0.244
55 2 1/8	UKX12D1;H2312X UKX12D1;HS2312	60 2.3622	120 4.7244	40 1.5748	32 1.2598	82.5 3.248	55 2 1/8	62 2.441	13 0.512	80 3.150	8.7 0.343

Basic load ratings		Mass kg lb
N dynamic <i>C</i> <sub>r</sub>	lbf static <i>C</i> <sub>0r</sub>	
19 500 4 400	11 300 2 540	0.38 0.85
25 700 5 750	15 300 3 450	0.53 1.24 1.16
29 100 6 550	17 800 4 000	0.75 1.70
32 500 7 350	20 400 4 600	0.85 2.01 1.88
35 000 7 900	23 200 5 200	0.97 2.32 2.24 2.07
43 500 9 750	29 200 6 550	1.26 3.09 2.99 2.88
52 500 11 800	36 000 8 150	1.62 3.84 3.72 3.58
57 500 12 900	40 000 9 000	2.07 4.66

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".  
<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
 In this case the lock washer with the straight inner prong should be used.  
<sup>(3)</sup> For HE2311XY, screw thread pitch different from the standard is applied, because of the thin thread section of sleeve.  
 To distinguish it, a suffix "Y" is added.

## Ball bearings Adapter type



UKX...D1;H, HA, HE, HS

UKX...D1


Shaft dia. mm inch	Bearing <sup>(1)(2)</sup> number	Nominal dimensions									
		mm inch									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	<i>d</i> <sub>4</sub>	<i>d</i> <sub>1</sub>	<i>B</i> <sub>1</sub>	<i>B</i> <sub>2</sub>	<i>d</i> <sub>2</sub>	<i>F</i>
60 2 3/16 2 1/4 2 3/8	UKX13D1;H2313X UKX13D1;HA2313 UKX13D1;HE2313X UKX13D1;HS2313X	65 2.5591	125 4.9213	42 1.6535	33 1.2992	87 3.425	60 2 3/16 2 1/4 2 3/8	65 2.559	14 0.551	85 3.346	8.8 0.346
65 2 7/16 2 1/2	UKX15D1;H2315X UKX15D1;HA2315 UKX15D1;HE2315X	75 2.9528	140 5.5118	45 1.7717	35 1.3780	98.1 3.862	65 2 7/16 2 1/2	73 2.874	15 0.591	98 3.858	9.5 0.374
70 2 11/16 2 3/4	UKX16D1;H2316X UKX16D1;HA2316 UKX16D1;HE2316X	80 3.1496	150 5.9055	46 1.8110	36 1.4173	106.4 4.189	70 2 11/16 2 3/4	78 3.071	17 0.669	105 4.134	10.1 0.398
75 2 5/8 3	UKX17D1;H2317X UKX17D1;HA2317X UKX17D1;HE2317X	85 3.3465	160 6.2992	47 1.8504	37 1.4567	111.6 4.394	75 2 5/8 3	82 3.228	18 0.709	110 4.331	9.8 0.386
80 3 3/16	UKX18D1;H2318X UKX18D1;HA2318X	90 3.5433	170 6.6929	49 1.9291	39 1.5354	118.2 4.654	80 3 3/16	86 3.386	18 0.709	120 4.724	10.5 0.413
90	UKX20D1;H2320X	100	190	57	44	131.3	90	97	20	130	11.3

Notes <sup>(1)</sup> These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

<sup>(2)</sup> Adapter number with suffix "X" means a narrow slot type adapter sleeve.  
In this case the lock washer with the straight inner prong should be used.

Basic load ratings		Mass
N lbf		kg lb
dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
62 000	44 000	2.19 5.28
14 000	9 900	5.12 4.79
72 500	53 000	3.25 7.47
16 300	11 900	7.27
83 500	64 000	3.87 8.79
18 700	14 300	8.56
96 000	71 500	4.53 10.6
21 600	16 100	10.3
109 000	82 000	5.17
24 500	18 400	11.2
133 000	105 000	7.39

## Ball bearings Set screw type




Shaft dia. mm inch	Bearing (1) number	Nominal dimensions									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	mm inch		<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>
						<i>r</i> min.	<i>r</i> <sub>1</sub> min.				
12 1/2	UCS201LD1N	12	47	31	17	0.6	0.6	12.7	18.3	4.5	M5×0.8
	UCS201-008LD1N	0.5000	1.8504	1.2205	0.6693	0.024	0.024	0.500	0.720	0.177	No.10-32UNNF
15 9/16 5/8	UCS202LD1N	15	47	31	17	0.6	0.6	12.7	18.3	4.5	M5×0.8
	UCS202-009LD1N	0.5625	1.8504	1.2205	0.6693	0.024	0.024	0.500	0.720	0.177	No.10-32UNNF
17 11/16	UCS203LD1N	17	47	31	17	0.6	0.6	12.7	18.3	4.5	M5×0.8
	UCS203-011LD1N	0.6875	1.8504	1.2205	0.6693	0.024	0.024	0.500	0.720	0.177	No.10-32UNNF
20 3/4	UCS204LD1N	20	47	31	17	1	0.6	12.7	18.3	4.5	M5×0.8
	UCS204-012LD1N	0.7500	1.8504	1.2205	0.6693	0.039	0.024	0.500	0.720	0.177	No.10-32UNNF
25 13/16 7/8 15/16	UCS205LD1N	25	52	34.1	17	1	0.6	14.3	19.8	5	M5×0.8
	UCS205-013LD1N	0.8125									
	UCS205-014LD1N	0.8750	2.0472	1.3425	0.6693	0.039	0.024	0.563	0.780	0.197	No.10-32UNNF
	UCS205-015LD1N	0.9375									
1 1	UCS205-100LD1N	1.0000									
30 1 1/16 1 1/8 1 3/16 1 1/4	UCS206LD1N	30	62	38.1	19	1	1	15.9	22.2	5	M6×0.75
	UCS206-101LD1N	1.0625									
	UCS206-102LD1N	1.1250	2.4409	1.5000	0.7480	0.039	0.039	0.626	0.874	0.197	1/4-28UNF
	UCS206-103LD1N	1.1875									
1 3/4	UCS206-104LD1N	1.2500									
35 1 1/4 1 5/16 1 3/8 1 7/16	UCS207LD1N	35	72	42.9	20	1.5	1.5	17.5	25.4	6	M6×0.75
	UCS207-104LD1N	1.2500									
	UCS207-105LD1N	1.3125	2.8346	1.6890	0.7874	0.059	0.059	0.689	1.000	0.236	1/4-28UNF
	UCS207-106LD1N	1.3750									
1 7/16	UCS207-107LD1N	1.4375									
40 1 1/2 1 9/16	UCS208LD1N	40	80	49.2	21	1.5	1.5	19	30.2	8	M8×1
	UCS208-108LD1N	1.5000	3.1496	1.9370	0.8268	0.059	0.059	0.748	1.189	0.315	5/16-24UNF
	UCS208-109LD1N	1.5625									
45 1 5/8 1 11/16 1 3/4	UCS209LD1N	45	85	49.2	22	1.5	1.5	19	30.2	8	M8×1
	UCS209-110LD1N	1.6250									
	UCS209-111LD1N	1.6875	3.3465	1.9370	0.8661	0.059	0.059	0.748	1.189	0.315	5/16-24UNF
	UCS209-112LD1N	1.7500									

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions					Basic load ratings		Mass
<i>d</i> <sub>4</sub>	<i>D</i> <sub>1</sub>	mm inch		<i>F</i>	N lbf		kg lb
		<i>a</i>	<i>b</i>		dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
29.6	44.6	3.1	1.5	4	12 800	6 650	0.21
1.1654	1.756	0.122	0.059	0.157	2 890	1 500	0.46
29.6	44.6	3.1	1.5	4	12 800	6 650	0.20
1.1654	1.756	0.122	0.059	0.157	2 890	1 500	0.44
29.6	44.6	3.1	1.5	4	12 800	6 650	0.18
1.1654	1.756	0.122	0.059	0.157	2 890	1 500	0.39
29.6	44.6	3.1	1.5	4	12 800	6 650	0.17
1.1654	1.756	0.122	0.059	0.157	2 890	1 500	0.39
33.9	49.73	3.2	1.5	4.1	14 000	7 850	0.20
							0.53
1.3346	1.958	0.126	0.059	0.161	3 150	1 770	0.51
							0.46
							0.44
40.8	59.61	3.2	2.05	4.2	19 500	11 300	0.34
							0.82
1.6063	2.347	0.126	0.081	0.165	4 400	2 540	0.77
							0.73
							0.66
46.8	68.81	3.3	2.05	5	25 700	15 300	0.48
							1.21
1.8425	2.709	0.130	0.081	0.197	5 750	3 450	1.15
							1.08
							1.01
53	76.81	3.4	2.05	5	29 100	17 800	0.65
							1.52
2.0866	3.024	0.134	0.081	0.197	6 550	4 000	1.46
							0.70
57.5	81.81	3.5	2.05	5.1	32 500	20 400	0.70
							1.76
2.2638	3.221	0.138	0.081	0.201	7 350	4 600	1.68
							1.57

## Ball bearings Set screw type



UCS...D1N


UCS...D1

Shaft dia. mm inch	Bearing (*) number	Nominal dimensions									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	mm inch		<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>
						<i>r</i> min.	<i>r</i> <sub>1</sub> min.				
50	UCS210LD1N	50	90	51.6	24	1.5	1.5	19	32.6	9	M8x1
1 3/16	UCS210-113LD1N	1.8125									
1 7/8	UCS210-114LD1N	1.8750	3.5433	2.0315	0.9449	0.059	0.059	0.748	1.283	0.354	5/16-24UNF
1 5/16	UCS210-115LD1N	1.9375									
2	UCS210-200LD1N	2.0000									
55	UCS211LD1N	55	100	55.6	25	2	2	22.2	33.4	9	M8x1
2	UCS211-200LD1N	2.0000									
2 1/16	UCS211-201LD1N	2.0625	3.9370	2.1890	0.9843	0.079	0.079	0.874	1.315	0.354	5/16-24UNF
2 7/8	UCS211-202LD1N	2.1250									
2 3/16	UCS211-203LD1N	2.1875									
60	UCS212LD1N	60	110	65.1	27	2	2	25.4	39.7	10	M10x1.25
2 1/4	UCS212-204LD1N	2.2500									
2 5/16	UCS212-205LD1N	2.3125	4.3307	2.5630	1.0630	0.079	0.079	1.000	1.563	0.394	3/8-24UNF
2 3/8	UCS212-206LD1N	2.3750									
2 7/16	UCS212-207LD1N	2.4375									
65	UCS213D1	65	120	65.1	32	2	2	25.4	39.7	10	M10x1.25
2 1/2	UCS213-208D1	2.5000	4.7244	2.5630	1.2598	0.079	0.079	1.000	1.563	0.394	3/8-24UNF
2 9/16	UCS213-209D1	2.5625									
70	UCS214D1	70	125	74.6	33	2	2	30.2	44.4	12	M10x1.25
75	UCS215D1	75	130	77.8	34	2	2	33.3	44.5	12	M10x1.25
80	UCS216D1	80	140	82.6	35	2.5	2.5	33.3	49.3	12	M10x1.25
85	UCS217D1	85	150	85.7	36	2.5	2.5	34.1	51.6	12	M12x1.5
90	UCS218D1	90	160	96	37	2.5	2.5	39.7	56.3	12	M12x1.5

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions					Basic load ratings		Mass
<i>d</i> <sub>4</sub>	<i>D</i> <sub>1</sub>	mm inch		<i>F</i>	N lbf		kg lb
		<i>a</i>	<i>b</i>		dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>0r</sub>	
62.4	86.79	3.7	2.85	5.6	35 000	23 200	0.78
2.4567	3.417	0.146	0.112	0.220	7 900	5 200	2.03
							1.92
							1.81
							1.69
69	96.80	4.4	2.85	5.9	43 500	29 200	1.06
2.7165	3.811	0.173	0.112	0.232	9 750	6 550	2.71
							2.60
							2.46
							2.34
77	106.81	4.4	2.85	6	52 500	36 000	1.48
3.0315	4.205	0.173	0.112	0.236	11 800	8 150	3.78
							3.62
							3.45
							3.29
82.5	—	—	—	6.8	57 500	40 000	1.88
3.2480	—	—	—	0.268	12 900	9 000	4.41
							4.24
87	—	—	—	7	62 000	44 000	2.17
93	—	—	—	7	66 000	49 500	2.43
98.1	—	—	—	7.5	72 500	53 000	2.89
106.4	—	—	—	7.5	83 500	64 000	3.47
111.6	—	—	—	7	96 000	71 500	4.24

## Ball bearings Set screw type



Shaft dia. mm inch	Bearing (1) number	Nominal dimensions									
		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>	mm inch		<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>
						<i>r</i> min.	<i>r</i> <sub>1</sub> min.				
25 1 3/16	<b>UCS305D1</b>	25	62	38	20	1.5	0.6	15	23	6	M6×0.75
	<b>UCS305-013D1</b>	0.8125									
	<b>UCS305-014D1</b>	0.8750	2.4409	1.4961	0.7874	0.059	0.024	0.591	0.906	0.236	1/4-28UNF
	<b>UCS305-015D1</b>	0.9375									
1	<b>UCS305-100D1</b>	1.0000									
30 1 1/16	<b>UCS306D1</b>	30	72	43	23	1.5	1	17	26	6	M6×0.75
	<b>UCS306-101D1</b>	1.0625									
	<b>UCS306-102D1</b>	1.1250	2.8346	1.6929	0.9055	0.059	0.039	0.669	1.024	0.236	1/4-28UNF
	<b>UCS306-103D1</b>	1.1875									
35 1 1/4	<b>UCS307D1</b>	35	80	48	25	2	1	19	29	8	M8×1
	<b>UCS307-104D1</b>	1.2500									
	<b>UCS307-105D1</b>	1.3125	3.1496	1.8898	0.9843	0.079	0.039	0.748	1.142	0.315	5/16-24UNF
	<b>UCS307-106D1</b>	1.3750									
	<b>UCS307-107D1</b>	1.4375									
40 1 1/2	<b>UCS308D1</b>	40	90	52	27	2	1	19	33	10	M10×1.25
	<b>UCS308-108D1</b>	1.5000	3.5433	2.0472	1.0630	0.079	0.039	0.748	1.299	0.394	3/8-24UNF
	<b>UCS308-109D1</b>	1.5625									
45 1 5/8	<b>UCS309D1</b>	45	100	57	29	2	1	22	35	10	M10×1.25
	<b>UCS309-110D1</b>	1.6250									
	<b>UCS309-111D1</b>	1.6875	3.9370	2.2441	1.1417	0.079	0.039	0.866	1.378	0.394	3/8-24UNF
	<b>UCS309-112D1</b>	1.7500									
50 1 3/8	<b>UCS310D1</b>	50	110	61	32	2.5	1.5	22	39	12	M12×1.5
	<b>UCS310-113D1</b>	1.8125									
	<b>UCS310-114D1</b>	1.8750	4.3307	2.4016	1.2598	0.098	0.059	0.866	1.535	0.472	1/2-20UNF
	<b>UCS310-115D1</b>	1.9375									
55 2	<b>UCS311D1</b>	55	120	66	34	2.5	1.5	25	41	12	M12×1.5
	<b>UCS311-200D1</b>	2.0000									
	<b>UCS311-201D1</b>	2.0625	4.7244	2.5984	1.3386	0.098	0.059	0.984	1.614	0.472	1/2-20UNF
	<b>UCS311-202D1</b>	2.1250									
	<b>UCS311-203D1</b>	2.1875									

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions mm inch		Basic load ratings N lbf		Mass kg lb
<i>d</i> <sub>4</sub>	<i>F</i>	dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
36.8	4.3	21 200	10 900	0.37 0.94
1.4488	0.169	4 750	2 460	0.90 0.83
				0.81
44.9	5.1	26 700	15 000	0.58 1.39
1.7677	0.201	6 000	3 400	1.33 1.28
49.4	5.3	33 500	19 100	0.74 1.77
1.9449	0.209	7 500	4 300	1.70 1.64
				1.57
56	5.6	40 500	24 000	1.00 2.32
2.2047	0.220	9 150	5 400	2.23 1.33
63.5	5.8	53 000	32 000	1.33 3.17
2.5000	0.228	11 900	7 200	3.09 2.98
70.6	6.3	62 000	38 500	1.72 4.10
2.7795	0.248	13 900	8 600	3.99 3.85
76.6	6.5	71 500	45 000	2.15 5.14
3.0157	0.256	16 100	10 100	4.99 4.85
				4.68



## Ball bearings Set screw type



Shaft dia. mm inch	Bearing (1) number	Nominal dimensions									
		d	D	B	C	mm inch		S	S <sub>1</sub>	G	d <sub>s</sub>
						r min.	r <sub>1</sub> min.				
60 2 1/4 2 9/16 2 3/8 2 7/16	<b>UCS312D1</b> <b>UCS312-204D1</b> <b>UCS312-205D1</b> <b>UCS312-206D1</b> <b>UCS312-207D1</b>	60 2.2500 2.3125 2.3750 2.4375	130	71	36	2.5	1.5	26	45	12	M12×1.5
65 2 1/2 2 9/16	<b>UCS313D1</b> <b>UCS313-208D1</b> <b>UCS313-209D1</b>	65 2.5000 2.5625	140	75	39	2.5	2	30	45	12	M12×1.5
70 2 5/8 2 11/16 2 3/4	<b>UCS314D1</b> <b>UCS314-210D1</b> <b>UCS314-211D1</b> <b>UCS314-212D1</b>	70 2.6250 2.6875 2.7500	150	78	41	2.5	2	33	45	12	M12×1.5
75 2 13/16 2 7/8 2 15/16 3	<b>UCS315D1</b> <b>UCS315-213D1</b> <b>UCS315-214D1</b> <b>UCS315-215D1</b> <b>UCS315-300D1</b>	75 2.8125 2.8750 2.9375 3.0000	160	82	43	2.5	2	32	50	14	M14×1.5
80 3 1/16 3 1/8 3 3/16	<b>UCS316D1</b> <b>UCS316-301D1</b> <b>UCS316-302D1</b> <b>UCS316-303D1</b>	80 3.0625 3.1250 3.1875	170	86	45	2.5	2	34	52	14	M14×1.5
85 3 1/4 3 5/16 3 7/16	<b>UCS317D1</b> <b>UCS317-304D1</b> <b>UCS317-305D1</b> <b>UCS317-307D1</b>	85 3.2500 3.3125 3.4375	180	96	47	3	2.5	40	56	16	M16×1.5
90 3 7/16 3 1/2	<b>UCS318D1</b> <b>UCS318-307D1</b> <b>UCS318-308D1</b>	90 3.4375 3.5000	190	96	49	3	2.5	40	56	16	M16×1.5

Note (1) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions mm inch		Basic load ratings N lbf		Mass kg lb
d <sub>4</sub>	F	dynamic C <sub>r</sub>	static C <sub>or</sub>	
82.7	6.7	82 000	52 000	2.70 6.27
3.2559	0.264	18 400	11 700	6.10 5.89 5.72
88.2	7.5	92 500	60 000	3.37 7.63
3.4724	0.295	20 800	13 400	7.41
94.8	7.5	104 000	68 000	4.03 9.37
3.7323	0.295	23 400	15 300	9.13 8.91
101.3	7.7	113 000	77 000	4.88 11.4
3.9882	0.303	25 500	17 400	11.1 10.9 10.6
107.9	7.8	123 000	86 500	5.74 13.0
4.2480	0.307	27 600	19 500	12.7 12.5
114.4	8.2	133 000	97 000	6.88 15.7
4.5039	0.323	29 800	21 800	15.4 14.7
120.9	8.5	143 000	107 000	7.80 17.8
4.7598	0.335	32 000	24 100	17.4

## Ball bearings Set screw type



Shaft dia. mm inch	Bearing number	Nominal dimensions												
		d	D	B	C	mm inch							ds	d4
						r	r1	S	S1	G	S	S1		
12 1/2	<b>ASS201N</b> <b>ASS201-008N</b>	12 0.5000	40 1.5748	22 0.8661	12 0.4724	0.6 0.024	0.6 0.024	6 0.236	16 0.630	4.2 0.165	M5×0.8 No.10-32UNF	24.3 0.957		
15 9/16 5/8	<b>ASS202N</b> <b>ASS202-009N</b> <b>ASS202-010N</b>	15 0.5625 0.6250	40 1.5748	22 0.8661	12 0.4724	0.6 0.024	0.6 0.024	6 0.236	16 0.630	4.2 0.165	M5×0.8 No.10-32UNF	24.3 0.957		
17 11/16	<b>ASS203N</b> <b>ASS203-011N</b>	17 0.6875	40 1.5748	22 0.8661	12 0.4724	0.6 0.024	0.6 0.024	6 0.236	16 0.630	4.2 0.165	M5×0.8 No.10-32UNF	24.3 0.957		
20 3/4	<b>ASS204N</b> <b>ASS204-012N</b>	20 0.7500	47 1.8504	25 0.9843	14 0.5512	1 0.039	0.6 0.024	7 0.276	18 0.709	4.2 0.165	M5×0.8 No.10-32UNF	29.6 1.165		
25 13/16 7/8 15/16 1	<b>ASS205N</b> <b>ASS205-013N</b> <b>ASS205-014N</b> <b>ASS205-015N</b> <b>ASS205-100N</b>	25 0.8125 0.8750 0.9375 1.0000	52 2.0472	27 1.0630	15 0.5906	1 0.039	0.6 0.024	7.5 0.295	19.5 0.768	5 0.197	M5×0.8 No.10-32UNF	33.9 1.335		
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>ASS206N</b> <b>ASS206-101N</b> <b>ASS206-102N</b> <b>ASS206-103N</b> <b>ASS206-104N</b>	30 1.0625 1.1250 1.1875 1.2500	62 2.4409	29 1.1417	16 0.6299	1 0.039	0.6 0.024	8 0.315	21 0.827	5 0.197	M6×0.75 1/4"-28UNF	40.8 1.606		
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>ASS207N</b> <b>ASS207-104N</b> <b>ASS207-105N</b> <b>ASS207-106N</b> <b>ASS207-107N</b>	35 1.2500 1.3125 1.3750 1.4375	72 2.8346	34 1.3386	17 0.6693	1.5 0.059	0.6 0.024	8.5 0.335	25.5 1.004	6 0.236	M6×0.75 1/4"-28UNF	46.8 1.843		
40 1 1/2 1 9/16	<b>ASS208N</b> <b>ASS208-108N</b> <b>ASS208-109N</b>	40 1.5000 1.5625	80 3.1496	38 1.4961	18 0.7087	1.5 0.059	0.6 0.024	9 0.354	29 1.142	8 0.315	M8×1 5/16"-24UNF	53 2.087		

Nominal dimensions			Basic load ratings		Mass
D1	mm inch		N lbf		kg lb
	a	b	dynamic Cr	static Cor	
38.1 1.500	1.98 0.078	1.5 0.059	9 600 2 160	4 600 1 030	0.12 0.24
38.1 1.500	1.98 0.078	1.5 0.059	9 600 2 160	4 600 1 030	0.11 0.23 0.22
38.1 1.500	1.98 0.078	1.5 0.059	9 600 2 160	4 600 1 030	0.10 0.20
44.6 1.756	2.38 0.094	1.5 0.059	12 800 2 890	6 650 1 500	0.17 0.33
49.73	2.38	1.5	14 000	7 850	0.20 0.46 0.44 0.42 0.39
59.61	3.18	2.05	19 500	11 300	0.31 0.67 0.65 0.63 0.61
68.81	3.18	2.05	25 700	15 300	0.49 1.18 1.05 0.93 0.81
76.81	3.18	2.05	29 100	17 800	0.50 1.15 1.06
3.024	0.125	0.081	6 550	4 000	

## Ball bearings Eccentric locking collar type



UELS...D1N

UELS...D1

Shaft dia.  mm inch	Bearing (°) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	mm inch		<i>r</i> min.	<i>r</i> <sub>1</sub> min.	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>
						<i>C</i>	<i>r</i>					
20 3/4	UELS204LD1NW3 UELS204-012LD1NW3	20 0.7500	47 1.8504	43.7 1.720	34.2 1.3465	17 0.6693	1 0.039	0.6 0.024	17.1 0.673	26.6 1.047	4.8 0.189	
25 13/16 7/8 15/16	UELS205LD1NW3 UELS205-013LD1NW3 UELS205-014LD1NW3 UELS205-015LD1NW3	25 0.8125 0.8750 0.9375	52 2.0472	44.4 1.748	34.9 1.3740	17 0.6693	1 0.039	0.6 0.024	17.45 0.687	26.9 1.059	4.8 0.189	
1	UELS205-100LD1NW3	1.0000										
30 1 1/16 1 1/8 1 3/16 1 1/4	UELS206LD1NW3 UELS206-101LD1NW3 UELS206-102LD1NW3 UELS206-103LD1NW3 UELS206-104LD1NW3	30 1.0625 1.1250 1.1875 1.2500	62 2.4409	48.4 1.906	36.5 1.4370	19 0.7480	1 0.039	1 0.039	18.25 0.719	30.1 1.185	6 0.236	
35 1 1/4 1 1/16 1 3/8 1 7/16	UELS207LD1NW3 UELS207-104LD1NW3 UELS207-105LD1NW3 UELS207-106LD1NW3 UELS207-107LD1NW3	35 1.2500 1.3125 1.3750 1.4375	72 2.8346	51.1 2.012	37.6 1.4803	20 0.7874	1.5 0.059	1.5 0.059	18.8 0.740	32.3 1.272	6.8 0.268	
40 1 1/2 1 9/16	UELS208LD1NW3 UELS208-108LD1NW3 UELS208-109LD1NW3	40 1.5000 1.5625	80 3.1496	56.3 2.217	42.8 1.6850	21 0.8268	1.5 0.059	1.5 0.059	21.4 0.843	34.9 1.374	6.8 0.268	
45 1 5/8 1 11/16 1 3/4	UELS209LD1NW3 UELS209-110LD1NW3 UELS209-111LD1NW3 UELS209-112LD1NW3	45 1.6250 1.6875 1.7500	85 3.3465	56.3 2.217	42.8 1.6850	22 0.8661	1.5 0.059	1.5 0.059	21.4 0.843	34.9 1.374	6.8 0.268	
50 1 13/16 1 7/8 1 15/16 2	UCS210LD1NW3 UCS210-113LD1NW3 UCS210-114LD1NW3 UCS210-115LD1NW3 UCS210-200LD1NW3	50 1.8125 1.8750 1.9375 2.0000	90 3.5433	62.7 2.469	49.2 1.9370	24 0.9449	1.5 0.059	1.5 0.059	24.6 0.969	38.1 1.500	6.8 0.268	

Note (°) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions							Basic load ratings		Mass
<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>	mm inch		<i>a</i>	<i>b</i>	<i>F</i>	N lbf		kg lb
		<i>B</i> <sub>5</sub>	<i>D</i> <sub>1</sub>				dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
M6×0.75 1/4-28UNF	33 1.299	13.5 0.531	44.6 1.756	3.1 0.122	1.5 0.059	4 0.157	12 800 2 890	6 650 1 500	0.23 0.45
M6×0.75 1/4-28UNF	38 1.496	13.5 0.531	49.73 1.958	3.2 0.126	1.5 0.059	4.1 0.161	14 000 3 150	7 850 1 770	0.27 0.61 0.58 0.55 0.51
M8×1 5/16-24UNF	44.5 1.752	15.9 0.626	59.61 2.347	3.2 0.126	2.05 0.081	4.2 0.165	19 500 4 400	11 300 2 540	0.41 0.94 0.89 0.84 0.80
M10×1.25 3/8-24UNF	55.5 2.185	17.5 0.689	68.81 2.709	3.3 0.130	2.05 0.081	5 0.197	25 700 5 750	15 300 3 450	0.60 1.45 1.40 1.35 1.28
M10×1.25 3/8-24UNF	60 2.362	18.3 0.720	76.81 3.024	3.4 0.134	2.05 0.081	5 0.197	29 100 6 550	17 800 4 000	0.79 1.90 1.82
M10×1.25 3/8-24UNF	63.5 2.500	18.3 0.720	81.81 3.221	3.5 0.138	2.05 0.081	5.1 0.201	32 500 7 350	20 400 4 600	0.85 2.05 1.97 1.88
M10×1.25 3/8-24UNF	69.5 2.736	18.3 0.720	86.79 3.417	3.7 0.146	2.85 0.112	5.6 0.220	35 000 7 900	23 200 5 200	0.98 2.46 2.36 2.25 2.09

## Ball bearings Eccentric locking collar type



UELS...D1N

UELS...D1

Shaft dia.  mm inch	Bearing (*) number	Nominal dimensions									
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>		<i>r</i> <sub>1</sub>	<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>
						mm	inch				
55	<b>UELS211LD1NW3</b>	55	100	71.4	55.5	25	2	2	27.75	43.6	8
2	<b>UELS211-200LD1NW3</b>	2.0000									
2 1/16	<b>UELS211-201LD1NW3</b>	2.0625	3.9370	2.811	2.1850	0.9843	0.079	0.079	1.093	1.717	0.315
2 1/8	<b>UELS211-202LD1NW3</b>	2.1250									
2 3/16	<b>UELS211-203LD1NW3</b>	2.1875									
60	<b>UELS212LD1NW3</b>	60	110	77.8	61.9	27	2	2	30.95	46.8	8
2 1/4	<b>UELS212-204LD1W3</b>	2.2500									
2 5/16	<b>UELS212-205LD1W3</b>	2.3125	4.3307	3.063	2.4370	1.0630	0.079	0.079	1.219	1.843	0.315
2 3/8	<b>UELS212-206LD1W3</b>	2.3750									
2 7/16	<b>UELS212-207LD1W3</b>	2.4375									

Note (\*) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions							Basic load ratings		Mass	
<i>d</i> <sub>s</sub>	<i>d</i> <sub>3</sub>	<i>B</i> <sub>5</sub>		<i>D</i> <sub>1</sub>	<i>a</i>	<i>b</i>	<i>F</i>	N lbf		kg lb
		mm	inch					dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
M10×1.25	76	20.7	96.80	4.4	2.85	5.9	43 500	29 200	1.32	
3/8-24UNF	2.992	0.815	3.811	0.173	0.112	0.232	9 750	6 550	3.28	
									3.12	
									3.02	
									2.90	
M10×1.25	84	22.3	106.81	4.4	2.85	6	52 500	36 000	1.93	
3/8-24UNF	3.307	0.878	4.205	0.173	0.112	0.236	11 800	8 150	4.50	
									4.34	
									4.17	
									4.00	

## Ball bearings Eccentric locking collar type



Shaft dia.  mm inch	Bearing (°) number	Nominal dimensions												
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	mm		inch		<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>
							<i>r</i> min.	<i>r</i> <sub>1</sub> min.	<i>r</i> min.	<i>r</i> <sub>1</sub> min.				
25  1 3/16 7/8 15/16 1	<b>UELS305D1W3</b>	25	62	46.8	34.9	20	1.5	0.6	16.7	30.1	6	M8×1		
	<b>UELS305-013D1W3</b>	0.8125												
	<b>UELS305-014D1W3</b>	0.8750	2.4409	1.843	1.3740	0.7874	0.059	0.024	0.657	1.185	0.236	5/16-24UNF		
	<b>UELS305-015D1W3</b>	0.9375												
	<b>UELS305-100D1W3</b>	1.0000												
30  1 1/16 1 1/8 1 3/16	<b>UELS306D1W3</b>	30	72	50	36.5	23	1.5	1	17.5	32.5	6.7	M8×1		
	<b>UELS306-101D1W3</b>	1.0625												
	<b>UELS306-102D1W3</b>	1.1250	2.8346	1.969	1.4370	0.9055	0.059	0.039	0.689	1.280	0.264	5/16-24UNF		
	<b>UELS306-103D1W3</b>	1.1875												
35  1 1/4 1 5/16 1 3/8 1 7/16	<b>UELS307D1W3</b>	35	80	51.6	38.1	25	2	1	18.3	33.3	6.7	M8×1		
	<b>UELS307-104D1W3</b>	1.2500												
	<b>UELS307-105D1W3</b>	1.3125	3.1496	2.031	1.5000	0.9843	0.079	0.039	0.720	1.311	0.264	5/16-24UNF		
	<b>UELS307-106D1W3</b>	1.3750												
	<b>UELS307-107D1W3</b>	1.4375												
40  1 1/2 1 9/16	<b>UELS308D1W3</b>	40	90	57.1	41.3	27	2	1	19.8	37.3	8	M10×1.25		
	<b>UELS308-108D1W3</b>	1.5000	3.5433	2.248	1.6260	1.0630	0.079	0.039	0.780	1.469	0.315	3/8-24UNF		
	<b>UELS308-109D1W3</b>	1.5625												
45  1 5/8 1 11/16 1 3/4	<b>UELS309D1W3</b>	45	100	58.7	42.9	29	2	1	19.8	38.9	8	M10×1.25		
	<b>UELS309-110D1W3</b>	1.6250												
	<b>UELS309-111D1W3</b>	1.6875	3.9370	2.311	1.6890	1.1417	0.079	0.039	0.780	1.531	0.315	3/8-24UNF		
	<b>UELS309-112D1W3</b>	1.7500												
50  1 13/16 1 7/8 1 15/16	<b>UCS210D1W3</b>	50	110	66.6	49.2	32	2.5	1.5	24.6	42	8.7	M10×1.25		
	<b>UCS210-113D1W3</b>	1.8125												
	<b>UCS210-114D1W3</b>	1.8750	4.3307	2.622	1.9370	1.2598	0.098	0.059	0.969	1.654	0.343	3/8-24UNF		
	<b>UCS210-115D1W3</b>	1.9375												
55  2 2 1/16 2 1/8 2 3/16	<b>UELS311D1W3</b>	55	120	73	55.6	34	2.5	1.5	27.8	45.2	8.7	M10×1.25		
	<b>UELS311-200D1W3</b>	2.0000												
	<b>UELS311-201D1W3</b>	2.0625	4.7244	2.874	2.1890	1.3386	0.098	0.059	1.094	1.780	0.343	3/8-24UNF		
	<b>UELS311-202D1W3</b>	2.1250												
	<b>UELS311-203D1W3</b>	2.1875												

Note (°) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions			Basic load ratings		Mass
mm inch			N lbf		kg lb
<i>d</i> <sub>3</sub>	<i>B</i> <sub>5</sub>	<i>F</i>	dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>0r</sub>	
42.8	15.9	4.3	21 200	10 900	0.45 1.13 1.09 1.05 1.00
1.685	0.626	0.169	4 750	2 460	
50	17.5	5.1	26 700	15 000	0.71 1.62 1.56 1.50
1.969	0.689	0.201	6 000	3 400	
55	17.5	5.3	33 500	19 100	0.83 1.99 1.91 1.84 1.76
2.165	0.689	0.209	7 500	4 300	
63.5	20.6	5.6	40 500	24 000	1.12 2.67 2.58
2.500	0.811	0.220	9 150	5 400	
70	20.6	5.8	53 000	32 000	1.50 3.26 3.37 3.26
2.756	0.811	0.228	11 900	7 200	
76.2	22.2	6.3	62 000	38 500	1.93 4.55 4.44 4.30
3.000	0.874	0.248	13 900	8 600	
83	22.2	6.5	71 500	45 000	2.42 5.76 5.57 5.43 5.26
3.268	0.874	0.256	16 100	10 100	

## Ball bearings Eccentric locking collar type




Shaft dia.  mm inch	Bearing (°) number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	mm inch		<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>
							<i>r</i> min.	<i>r</i> <sub>1</sub> min.				
60	<b>UELS312D1W3</b>	60	130	79.4	61.9	36	2.5	1.5	30.95	48.45	8.7	M10×1.25
2 1/4	<b>UELS312-204D1W3</b>	2.2500										
2 9/16	<b>UELS312-205D1W3</b>	2.3125										
2 3/8	<b>UELS312-206D1W3</b>	2.3750	5.1181	3.126	2.4370	1.4173	0.098	0.059	1.219	1.907	0.343	3/8-24UNF
2 7/16	<b>UELS312-207D1W3</b>	2.4375										
65	<b>UELS313D1W3</b>	65	140	85.7	65.1	39	2.5	2	32.55	53.15	10.3	M12×1.5
2 1/2	<b>UELS313-208D1W3</b>	2.5000										
2 9/16	<b>UELS313-209D1W3</b>	2.5625	5.5118	3.374	2.5630	1.5354	0.098	0.079	1.281	2.093	0.406	1/2-20UNF
70	<b>UELS314D1W3</b>	70	150	92.1	68.3	41	2.5	2	34.15	57.95	10.3	M12×1.5
2 5/8	<b>UELS314-210D1W3</b>	2.6250										
2 11/16	<b>UELS314-211D1W3</b>	2.6875	5.9055	3.626	2.6890	1.6142	0.098	0.079	1.344	2.281	0.406	1/2-20UNF
2 3/4	<b>UELS314-212D1W3</b>	2.7500										
75	<b>UELS315D1W3</b>	75	160	100	74.6	43	2.5	2	37.3	62.7	12.7	M16×1.5
2 13/16	<b>UELS315-213D1W3</b>	2.8125										
2 7/8	<b>UELS315-214D1W3</b>	2.8750										
2 15/16	<b>UELS315-215D1W3</b>	2.9375	6.2992	3.937	2.9370	1.6929	0.098	0.079	1.469	2.469	0.500	5/8-18UNF
3	<b>UELS315-300D1W3</b>	3.0000										
80	<b>UELS316D1W3</b>	80	170	106.4	81	45	2.5	2	40.5	65.9	12.7	M16×1.5
3 1/16	<b>UELS316-301D1W3</b>	3.0625										
3 1/8	<b>UELS316-302D1W3</b>	3.1250	6.6929	4.189	3.1890	1.7717	0.098	0.079	1.594	2.594	0.500	5/8-18UNF
3 3/16	<b>UELS316-303D1W3</b>	3.1875										
85	<b>UELS317D1W3</b>	85	180	109.5	84.1	47	3	2.5	42.05	67.45	12.7	M16×1.5
3 1/4	<b>UELS317-304D1W3</b>	3.2500										
3 5/16	<b>UELS317-305D1W3</b>	3.3125	7.0866	4.311	3.3110	1.8504	0.118	0.098	1.656	2.656	0.500	5/8-18UNF
3 7/16	<b>UELS317-307D1W3</b>	3.4375										
90	<b>UELS318D1W3</b>	90	190	115.9	87.3	49	3	2.5	43.65	72.25	14.3	M20×1.5
3 7/16	<b>UELS318-307D1W3</b>	3.4375										
3 1/2	<b>UELS318-308D1W3</b>	3.5000	7.4803	4.563	3.4370	1.9291	0.118	0.098	1.719	2.844	0.563	3/4-16UNF

Note (°) These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "D1".

Nominal dimensions			Basic load ratings		Mass
mm inch			N lbf		kg lb
<i>d</i> <sub>3</sub>	<i>B</i> <sub>5</sub>	<i>F</i>	dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
89	23.9	6.7	82 000	52 000	3.04
3.504	0.941	0.264	18 400	11 700	7.01
					6.86
					6.69
					6.40
97	27	7.5	92 500	60 000	3.79
3.819	1.063	0.295	20 800	13 400	8.76
					8.55
102	30.2	7.5	104 000	68 000	4.54
4.016	1.189	0.295	23 400	15 300	10.7
					10.5
					10.2
113	31.8	7.7	113 000	77 000	5.50
4.449	1.252	0.303	25 500	17 400	13.5
					13.2
					13.0
					12.9
119	31.8	7.8	123 000	86 500	6.89
4.685	1.252	0.307	27 600	19 500	15.3
					15.0
					15.3
127	31.8	8.2	133 000	97 000	8.21
5.000	1.252	0.323	29 800	21 800	18.2
					17.9
					17.2
133	36.5	8.5	143 000	107 000	9.34
5.236	1.437	0.335	32 000	24 100	21.2
					20.7

## Ball bearings Eccentric locking collar type



Shaft dia. mm inch	Bearing number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	mm inch		<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>
							<i>r</i> min.	<i>r</i> <sub>1</sub> min.				
12 1/2	<b>AELS201NW3</b> <b>AELS201-008NW3</b>	12 0.5000	40 1.5748	28.6 1.126	19 0.7480	12 0.4724	0.6 0.024	0.6 0.024	6.5 0.256	22.1 0.870	4.8 0.189	M6×0.75 1/4"-28UNF
15 9/16 5/8	<b>AELS202NW3</b> <b>AELS202-009NW3</b> <b>AELS202-010NW3</b>	15 0.5625 0.6250	40 1.5748	28.6 1.126	19 0.7480	12 0.4724	0.6 0.024	0.6 0.024	6.5 0.256	22.1 0.870	4.8 0.189	M6×0.75 1/4"-28UNF
17 11/16	<b>AELS203NW3</b> <b>AELS203-011NW3</b>	17 0.6875	40 1.5748	28.6 1.126	19 0.7480	12 0.4724	0.6 0.024	0.6 0.024	6.5 0.256	22.1 0.870	4.8 0.189	M6×0.75 1/4"-28UNF
20 3/4	<b>AELS204NW3</b> <b>AELS204-012NW3</b>	20 0.7500	47 1.8504	31 1.220	21.5 0.8465	14 0.5512	1 0.039	0.6 0.024	7.5 0.295	23.5 0.925	4.8 0.189	M6×0.75 1/4"-28UNF
25 13/16 7/8 15/16 1	<b>AELS205NW3</b> <b>AELS205-013NW3</b> <b>AELS205-014NW3</b> <b>AELS205-015NW3</b> <b>AELS205-100NW3</b>	25 0.8125 0.8750 0.9375 1.0000	52 2.0472	31 1.220	21.5 0.8465	15 0.5906	1 0.039	0.6 0.024	7.5 0.295	23.5 0.925	4.8 0.189	M6×0.75 1/4"-28UNF
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>AELS206NW3</b> <b>AELS206-101NW3</b> <b>AELS206-102NW3</b> <b>AELS206-103NW3</b> <b>AELS206-104NW3</b>	30 1.0625 1.1250 1.1875 1.2500	62 2.4409	35.7 1.406	23.8 0.9370	16 0.6299	1 0.039	0.6 0.024	9 0.354	26.7 1.051	6 0.236	M8×1 5/16"-24UNF
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>AELS207NW3</b> <b>AELS207-104NW3</b> <b>AELS207-105NW3</b> <b>AELS207-106NW3</b> <b>AELS207-107NW3</b>	35 1.2500 1.3125 1.3750 1.4375	72 2.8346	38.9 1.531	25.4 1.0000	17 0.6693	1.5 0.059	0.6 0.024	9.5 0.374	29.4 1.157	6.8 0.268	M10×1.25 3/8"-24UNF
40 1 1/2 1 9/16	<b>AELS208NW3</b> <b>AELS208-108NW3</b> <b>AELS208-109NW3</b>	40 1.5000 1.5625	80 3.1496	43.7 1.720	30.2 1.1890	18 0.7087	1.5 0.059	0.6 0.024	11 0.433	32.7 1.287	6.8 0.268	M10×1.25 3/8"-24UNF

Nominal dimensions					Basic load ratings		Mass
<i>d</i> <sub>3</sub>	<i>D</i> <sub>1</sub>	mm inch		<i>B</i> <sub>5</sub>	N lbf		kg lb
		<i>a</i>	<i>b</i>		dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
29 1.142	38.1 1.500	1.98 0.078	1.5 0.059	13.6 0.535	9 600 2 160	4 600 1 030	0.12 0.26
29 1.142	38.1 1.500	1.98 0.078	1.5 0.059	13.6 0.535	9 600 2 160	4 600 1 030	0.11 0.26 0.24
29 1.142	38.1 1.500	1.98 0.078	1.5 0.059	13.6 0.535	9 600 2 160	4 600 1 030	0.10 0.23
29 1.142	38.1 1.500	1.98 0.078	1.5 0.059	13.6 0.535	9 600 2 160	4 600 1 030	0.17 0.35
33 1.299	44.6 1.756	2.38 0.094	1.5 0.059	13.5 0.531	12 800 2 890	6 650 1 500	0.17 0.35
38 1.496	49.73 1.958	2.38 0.094	1.5 0.059	13.5 0.531	14 000 3 150	7 850 1 770	0.20 0.51 0.48 0.45 0.42
44.5 1.752	59.61 2.347	3.18 0.125	2.05 0.081	15.9 0.626	19 500 4 400	11 300 2 540	0.31 0.74 0.73 0.66 0.61
55.5 2.185	68.81 2.709	3.18 0.125	2.05 0.081	17.5 0.689	25 700 5 750	15 300 3 450	0.49 1.15 1.10 1.04 0.98
60 2.362	76.81 3.024	3.18 0.125	2.05 0.081	18.3 0.720	29 100 6 550	17 800 4 000	0.66 1.41 1.34

## Ball bearings Eccentric locking collar type



Shaft dia. mm inch	Bearing number	Nominal dimensions										
		<i>d</i>	<i>D</i>	<i>B</i> <sub>1</sub>	<i>B</i>	<i>C</i>	mm inch		<i>S</i>	<i>S</i> <sub>1</sub>	<i>G</i>	<i>d</i> <sub>s</sub>
							<i>r</i> min.	<i>r</i> <sub>1</sub> min.				
12 1/2	<b>JELS201W3</b> <b>JELS201-008W3</b>	12 0.5000	40 1.5748	28.6 1.126	19 0.7480	13 0.5118	0.6 0.024	0.4 0.016	6.5 0.256	22.1 0.870	4.8 0.189	M6×0.75 1/4"-28UNF
15 9/16 5/8	<b>JELS202W3</b> <b>JELS202-009W3</b> <b>JELS202-010W3</b>	15 0.5625 0.6250	40 1.5748	28.6 1.126	19 0.7480	13 0.5118	0.6 0.024	0.4 0.016	6.5 0.256	22.1 0.870	4.8 0.189	M6×0.75 1/4"-28UNF
17 11/16	<b>JELS203W3</b> <b>JELS203-011W3</b>	17 0.6875	40 1.5748	28.6 1.126	19 0.7480	13 0.5118	0.6 0.024	0.4 0.016	6.5 0.256	22.1 0.870	4.8 0.189	M6×0.75 1/4"-28UNF
20 3/4	<b>JELS204W3</b> <b>JELS204-012W3</b>	20 0.7500	47 1.8504	31 1.220	21.5 0.8465	15 0.5906	1 0.039	0.6 0.024	7.5 0.295	23.5 0.925	4.8 0.189	M6×0.75 1/4"-28UNF
25 13/16 7/8 15/16 1	<b>JELS205W3</b> <b>JELS205-013W3</b> <b>JELS205-014W3</b> <b>JELS205-015W3</b> <b>JELS205-100W3</b>	25 0.8125 0.8750 0.9375 1.0000	52 2.0472	31 1.220	21.5 0.8465	15 0.5906	1 0.039	0.6 0.024	7.5 0.295	23.5 0.925	4.8 0.189	M6×0.75 1/4"-28UNF
30 1 1/16 1 1/8 1 3/16 1 1/4	<b>JELS206W3</b> <b>JELS206-101W3</b> <b>JELS206-102W3</b> <b>JELS206-103W3</b> <b>JELS206-104W3</b>	30 1.0625 1.1250 1.1875 1.2500	62 2.4409	35.7 1.406	23.8 0.9370	18 0.7087	1 0.039	1 0.039	9 0.354	26.7 1.051	6 0.236	M8×1 5/16"-24UNF
35 1 1/4 1 5/16 1 3/8 1 7/16	<b>JELS207W3</b> <b>JELS207-104W3</b> <b>JELS207-105W3</b> <b>JELS207-106W3</b> <b>JELS207-107W3</b>	35 1.2500 1.3125 1.3750 1.4375	72 2.8346	38.9 1.531	25.4 1.0000	19 0.7480	1.5 0.059	1.5 0.059	9.5 0.374	29.4 1.157	6.8 0.268	M10×1.25 3/8"-24UNF
40 1 1/2 1 9/16	<b>JELS208W3</b> <b>JELS208-108W3</b> <b>JELS208-109W3</b>	40 1.5000 1.5625	80 3.1496	43.7 1.720	30.2 1.1890	22 0.8661	1.5 0.059	1.5 0.059	11 0.433	32.7 1.287	6.8 0.268	M10×1.25 3/8"-24UNF

Nominal dimensions mm inch		Basic load ratings		Mass
<i>d</i> <sub>3</sub>	<i>B</i> <sub>5</sub>	N lbf		kg lb
		dynamic <i>C</i> <sub>r</sub>	static <i>C</i> <sub>or</sub>	
29 1.142	13.6 0.535	9 600 2 160	4 600 1 030	0.13 0.26
29 1.142	13.6 0.535	9 600 2 160	4 600 1 030	0.13 0.26 0.24
29 1.142	13.6 0.535	9 600 2 160	4 600 1 030	0.10 0.22
33 1.299	13.5 0.531	12 800 2 890	6 650 1 500	0.18 0.42
38 1.496	13.5 0.531	14 000 3 150	7 850 1 770	0.20 0.54 0.51 0.48 0.44
44.5 1.752	15.9 0.626	19 500 4 400	11 300 2 540	0.34 0.84 0.79 0.75 0.70
55.5 2.185	17.5 0.689	25 700 5 750	15 300 3 450	0.53 1.29 1.24 1.18 1.12
60 2.362	18.3 0.720	29 100 6 550	17 800 4 000	0.71 1.64 1.57



## Ball bearings



Shaft dia. mm	Bearing number	Nominal dimensions				Basic load ratings		Mass kg lb
		$d$	$D$ mm inch	$B_4$	$r$ min.	dynamic $C_r$ N lbf	static $C_{or}$ N lbf	
10	CS200LLU	10 0.3937	30 1.1811	9 0.3543	0.6 0.024	5 100 1 150	2 390 540	0.03 0.07
12	CS201LLU	12 0.4724	32 1.2598	10 0.3937	0.6 0.024	6 100 1 370	2 750 615	0.04 0.09
15	CS202LLU	15 0.5906	35 1.3780	11 0.4331	0.6 0.024	7 750 1 740	3 600 805	0.04 0.09
17	CS203LLU	17 0.6693	40 1.5748	12 0.4724	0.6 0.024	9 600 2 160	4 600 1 030	0.06 0.13
20	CS204LLU	20 0.7874	47 1.8504	14 0.5512	1 0.039	12 800 2 890	6 650 1 500	0.10 0.22
25	CS205LLU	25 0.9843	52 2.0472	15 0.5906	1 0.039	14 000 3 150	7 850 1 770	0.13 0.29
30	CS206LLU	30 1.1811	62 2.4409	16 0.6299	1 0.039	19 500 4 400	11 300 2 540	0.20 0.44
35	CS207LLU	35 1.3780	72 2.8346	17 0.6693	1.5 0.059	25 700 5 750	15 300 3 450	0.29 0.64
40	CS208LLU	40 1.5748	80 3.1496	18 0.7087	1.5 0.059	29 100 6 550	17 800 4 000	0.37 0.82

## Worldwide Sales Offices and Manufacturing Plants

### NSK LTD.-HEADQUARTERS, TOKYO, JAPAN

www.nsk.com

Nisei Bldg., 1-6-3 Ohsaki, Shinagawa-ku, Tokyo 141-8560, Japan	
INDUSTRIAL MACHINERY BUSINESS DIVISION-HEADQUARTERS	
P: 03-3779-7227 F: 03-3779-7644	C: 81
GLOBAL AFTERMARKET DEPARTMENT	
P: 03-3779-7253 F: 03-3779-7644	C: 81
PRECISION MACHINERY DEPARTMENT	
P: 03-3779-7163 F: 03-3779-7644	C: 81
MECHATRONICS BUSINESS DEPARTMENT	
P: 0466-21-3027 F: 0466-21-3206	C: 81
AUTOMOTIVE BUSINESS DIVISION-HEADQUARTERS	
P: 03-3779-7189 F: 03-3779-7917	C: 81

### ●Africa

<b>South Africa:</b>	
<b>NSK SOUTH AFRICA (PTY) LTD.</b>	
23 Galaxy Avenue, Libro Business Park, Sandton, Gauteng, P.O. Box 1157, Johannesburg, South Africa	
P: 011-458-3600 F: 011-458-3608	C: 27

### ●Asia and Oceania

<b>Australia:</b>	
<b>NSK AUSTRALIA PTY. LTD.</b> www.au.nsk.com	
MELBOURNE 11 Dalmore Drive, Scoresby, Victoria 3179, Australia	
P: 03-9764-8302 F: 03-9764-8304	C: 61
SYDNEY 24-28 River Road West, Parramatta, New South Wales 2150, Australia	
P: 02-8843-8100 F: 02-8993-8406	C: 61
BRISBANE 1760 Saltnurst Street, Coopers Plains, Queensland 4108, Australia	
P: 07-3347-2600 F: 07-3345-3176	C: 61
PERTH Unit 1, 71 Tacoma Circuit, Canning Vale, Western Australia 6155, Australia	
P: 08-9256-5000 F: 08-9256-1044	C: 61

<b>China:</b>	
<b>NSK HONG KONG LTD.</b>	
HONG KONG Suite 814, World Commerce Centre, Harbour City, T.S.T. KLN, Hong Kong	
P: 02739-9933 F: 02739-9323	C: 852
<b>SHENZHEN</b> Room B809-09, Jueshi Tower, Jiabing Road, Luohu, Shenzhen, China (518001)	
P: 0755-25904886 F: 0755-25904883	C: 86

<b>KUNSHAN NSK CO., LTD.</b>	
OFFICE/PLANT 258 South Huang Pu Jiang Rd., Kunshan Economic & Technical Development Zone, Jiang Su, China (215335)	
P: 0512-5771-5554 F: 0512-5771-5689	C: 86

<b>CHANGSHU NSK NEEDLE BEARING CO., LTD.</b>	
OFFICE/PLANT No. 66 Dongnan Road, Changshu Southeast Economic Development Zone, Changshu City, Jiangsu, China (215500)	
P: 0512-5230-1111 F: 0512-5230-6011	C: 86

<b>NSK STEERING SYSTEMS DONGGUAN CO., LTD.</b>	
OFFICE/PLANT High-tech Park, Shilong Road, Dongguan, Guangdong, China (523119)	
P: 0769-2262-0960 F: 0769-2318-2867	C: 86

<b>ZHANGJIAGANG NSK PRECISION MACHINERY CO., LTD.</b>	
OFFICE/PLANT No. 34 Zhenxing Road, Zhangjiagang Economic Development Zone, Zhangjiagang City, Jiangsu Province, China (215600)	
P: 0512-5867-6498 F: 0512-5818-0970	C: 86

<b>SUZHOU NSK BEARINGS CO., LTD.</b>	
OFFICE/PLANT No. 22 Taishan Road, Suzhou New District, Jiangsu, China (215129)	
P: 0512-6665-5666 F: 0512-6665-9138	C: 86

<b>NSK (CHINA) RESEARCH &amp; DEVELOPMENT CO., LTD.</b>	
JIANGSU No.8 NSK Rd., Huajiao Economic Development Zone, Kunshan, Jiangsu, China (215332)	
P: 0512-5796-3000 F: 0512-5796-3300	C: 86

<b>NSK (SHANGHAI) TRADING CO., LTD.</b>	
JIANGSU 10th Fl, Building No.A, Shanghai Far East International Plaza, 319 Xian Xia Road, Shanghai, China (200051)	
P: 021-6235-0198 F: 021-6235-1858	C: 86

<b>NSK (CHINA) INVESTMENT CO., LTD.</b> www.nsk.com.cn	
HEAD OFFICE No.2 NSK Rd., Huajiao Economic Development Zone, Kunshan, Jiangsu, China (215332)	
P: 0512-5796-3000 F: 0512-5796-3300	C: 86

<b>BELING</b> Room 2116, Beijing Fortune Bldg., 5 Dong San Huan Bei Lu, Chao Yang District, Beijing, China (100004)	
P: 010-6590-8161 F: 010-6590-8166	C: 86

<b>GUANGZHOU</b> Room 3101/3102/3106A, Guangdong Telecom Plaza, 18 Zhongshan Er Road, Guangzhou, Guangdong, China (510080)	
P: 020-3786-4833 F: 020-3786-4501	C: 86

<b>CHENGDU</b> Room1117, Lippo Tower, No.82 North Kehua Road, Chengdu, Sichuan, China (610041)	
P: 028-8528-9680 F: 028-8528-3690	C: 86

<b>SHENYANG</b> Room 3805~3806 Tower A Royal Wanxin International Mansion No.390 Qingnian Street, Heping District, Shenyang, Liaoning, China (110003)	
P: 024-2334-2868 F: 024-2334-2058	C: 86

<b>NSK CHINA SALES CO., LTD.</b>	
HEAD OFFICE No.2 NSK Rd., Huajiao Economic Development Zone, Kunshan, Jiangsu, China (215332)	
P: 0512-5796-3000 F: 0512-5796-3300	C: 86

<b>CHANGCHUN</b> Room 1001, Building A, Zhongyin Building, 727 Xi'an Road, Changchun, Jilin Province, China (130061)	
P: 0431-8998-8682 F: 0431-8998-8670	C: 86

<b>TIAN JIN</b> Room 06, 09F The Exchange Tower 2, No. 189 Nanjing Road, Heping District, Tianjin, China (300050)	
P: 022-8319-5030 F: 022-8319-5033	C: 86

<b>NANJING</b> A1 22F, Golden Eagle International Plaza, No.89 Hanzhong Road, Nanjing, Jiangsu Province, China (210029)	
P: 025-8472-6671 F: 025-8472-6687	C: 86

<b>CHONGQING</b> Room 2306, Unit B, No.137, Ke Yuan 2nd Road, Julongpo District, Chongqing, China (400039)	
P: 023-8806-5310 F: 023-8606-5292	C: 86

<b>NSK-WARNER (SHANGHAI) CO., LTD.</b>	
PLANT No. 2518 Huancheng Road (West) Fengxian District, Shanghai, China (201401)	
P: 021-3365-5707 F: 021-3365-5262	C: 86

P: Phone F: Fax C: Country Code Printed in Japan

<b>AKS PRECISION BALL (HANGZHOU) CO., LTD.</b>	
PLANT No. 189 Hongda Road, Xiaoshan Area of Economic & Technological Development Zone, Hangzhou, Zhejiang, China (311231)	
P: 0571-2280-1288 F: 0571-2280-1268	C: 86

<b>NSK-YAGI PRECISION FORGING (ZHANGJIAGANG) CO., LTD.</b>	
PLANT No. 34 Zhenxing Road, Zhangjiagang Economic Development Zone, Zhangjiagang City, Jiangsu Province, China (215600)	
P: 0512-5867-6496 F: 0512-5818-0970	C: 86

<b>NSK-WANDA ELECTRIC POWER ASSISTED STEERING SYSTEMS CO., LTD.</b>	
OFFICE/PLANT 1833 Yatao Road, Wenyuan Town, Xiaoshan, Hangzhou, Zhejiang, China (311258)	
P: 0571-8231-4818 F: 0571-8248-6656	C: 86

<b>India:</b>	
<b>RANE NSK STEERING SYSTEMS LTD.</b>	
CHENNAI 14, Rajagopalan Salai, Vallancherry, Guduvanchery, Tamil Nadu-603 202, India	
P: 044-474-06017 F: 044-274-66001	C: 91

<b>BAWAL</b> Plot No.28A, Sector 6, HSIDC Growth Centre Bawal, District Rewari, Haryana	
-123 501, India	
P: 01284-356281 F: 01284-264280	C: 91

<b>NSK INDIA SALES CO. PVT. LTD.</b>	
CHENNAI New No.7, Old No.5, Boat Club Road, Chennai-600 028, India	
P: 044-2433-1161 F: 044-2433-1160	C: 91

<b>GURGAON</b> 107, Park Centra, Sector-30, Opposite 32nd Milestone, NH-8, Gurgaon, Haryana-122 001, India	
P: 0124-4104-530 F: 0124-4104-532	C: 91

<b>KOLKATA</b> 502, Trinity Towers, 83, Toppa Road, Kolkata-700 046, India	
P: 033-4001-2062 F: 033-4001-2064	C: 91

<b>MUMBAI</b> 321, A Wing, Anura Centre, 82, Mahakali Caves Road, Andheri East, Mumbai -400 093, India	
P: 022-2838-7787 F: 022-2838-5191	C: 91

<b>NSK-ABC BEARINGS LTD.</b>	
OFFICE/PLANT Plot No.A2, SIPCOT Growth Centre, Oragadam, Mathur Village, Sripurambudur Taluk, Kanchheepuram District, Tamil Nadu-602 105, India	
P: 044-2714-3000 F: 044-2714-3099	C: 91

<b>Indonesia:</b>	
<b>PT. NSK BEARINGS MANUFACTURING INDONESIA</b>	
JAKARTA PLANT Blok M4, Kawasari Berkat MM2100 Industrial Town Cikarang Barat, Bekasi 17520, Indonesia	
P: 021-898-0155 F: 021-898-0156	C: 62

<b>PT. NSK INDONESIA</b> www.id.nsk.com	
JAKARTA Summitas II, 6th Floor, Jl. Jend Sudirman Kav. 61-62, Jakarta 12190, Indonesia	
P: 021-252-3458 F: 021-252-3223	C: 62

<b>PT. NSK-WARNER INDONESIA</b>	
BEKASI MM2100 Industrial Town, Cikarang Barat, Bekasi 17520, Indonesia	
P: 021-8998-3216 F: 021-8998-3218	C: 62

<b>Korea:</b>	
<b>NSK KOREA CO., LTD.</b> www.kr.nsk.com	
SEOUL Posco Center (West Wing) 9F, 892, Daechi-dong, Kangnam-ku, Seoul, 135-777, Korea	
P: 02-3287-0300 F: 02-3287-0345	C: 82

<b>CHANGWON PLANT</b> 60, Seongsan-dong, Changwon, Kyungsangnam-do, 641-315, Korea	
P: 055-287-6001 F: 055-285-9982	C: 82

<b>Malaysia:</b>	
<b>NSK BEARINGS (MALAYSIA) SDN. BHD.</b> www.my.nsk.com	
HEAD OFFICE No. 2, Jalan Pemaju 1, U1/15, Seksyen 11, Uicom Gemangan Industrial Park, 40150 Shah Alam, Selangor, Malaysia	
P: 03-7803-8859 F: 03-7806-9982	C: 60

<b>PRAI</b> No.36, Jalan kikiik, Taman Inderawasih, 13600 Prai, Penang, Malaysia	
P: 04-3902275 F: 04-3991830	C: 60

<b>JOHOR BAHRU</b> 88 Jalan Ros Merah 2/17, Taman Johor Jaya, 81100 Johor Bahru, Johor, Malaysia	
P: 07-3546290 F: 07-3546291	C: 60

<b>KOTA KINABALU</b> Lot 10, Lig Kurma 4, Likas Ind, Centre, 5/12 Miles Jln Tuaran, 88450 Inanam, Sabah, Malaysia	
P: 088-421260 F: 088-421261	C: 60

<b>IPOH</b> Gr. Floor, 19 Jan Bendahara, 31650 Ipoh, Perak, Malaysia	
P: 05-2555000 F: 05-2553373	C: 60

<b>NSK MICRO PRECISION (M) SDN. BHD.</b> www.my.nsk.com	
MALAYSIA PLANT No.43 Jalan Taming Dua, Taman Taming Jaya 43300 Balakong, Selangor Danli Ehsan, Malaysia	
P: 03-8961-3960 F: 03-8961-3968	C: 60

<b>New Zealand:</b>	
<b>NSK NEW ZEALAND LTD.</b> www.nsk-rhp.co.nz	
AUCKLAND 3 To Apunga Place, Mt. Wellington, Auckland, New Zealand	
P: 09-276-4992 F: 09-276-4082	C: 64

<b>Philippines:</b>	
<b>NSK REPRESENTATIVE OFFICE</b>	
MANILA 8th Floor The Salcedo Towers 169 H.V. dela Costa St., Salcedo Village Makati City, Philippines 1227	
P: 02-893-9543 F: 02-893-9173	C: 63

<b>Singapore:</b>	
<b>NSK INTERNATIONAL (SINGAPORE) PTE LTD.</b>	
SINGAPORE 238A, Thomson Road, #24-01/05, Novena Square Tower A, Singapore 307684	
P: 6496-8000 F: 6250-5845	C: 65

<b>NSK SINGAPORE (PRIVATE) LTD.</b> www.nsk-singapore.com.sg	
SINGAPORE 238A, Thomson Road, #24-01/05, Novena Square Tower A, Singapore 307684	
P: 6496-8000 F: 6250-5845	C: 65

<b>Taiwan:</b>	
<b>TAIWAN NSK PRECISION CO., LTD.</b>	
TAIPEI 11F., No.87, Song Jiang Rd., Jhongshan District, Taipei City 104, Taiwan R.O.C.	
P: 02-2509-3305 F: 02-2509-1393	C: 866

<b>TAICHUNG</b> 107-7, Sec. 3, Wen Xing Rd., Taichung City 407, Taiwan R.O.C.	
P: 04-2311-7978 F: 04-2311-2627	C: 866

<b>TAINAN</b> No.8 Daye 1st Rd., Southern Taiwan Science Park, Tainan County 741, Taiwan R.O.C.	
P: 06-505-5861 F: 06-505-5081	C: 866

## Worldwide Sales Offices and Manufacturing Plants

P: Phone F: Fax C: Country Code Printed in Japan

<b>TAIWAN NSK TECHNOLOGY CO., LTD.</b>	
TAIPEI 11F., No.87, Song Jiang Rd., Jhongshan District, Taipei City 104, Taiwan R.O.C.	
P: 02-2509-3305 F: 02-2509-1393	C: 866

<b>Thailand:</b>	
<b>NSK BEARINGS (THAILAND) PVT. LTD.</b>	
BANGKOK 26 Sol On-Nuch 55/1, Prater District, Bangkok 10250, Thailand	
P: 02320-2555 F: 02320-2826	C: 66

<b>NSK BEARINGS MANUFACTURING (THAILAND) CO., LTD.</b>	
OFFICE/PLANT 700/430 Moo 7, Amata Nakorn Industrial Estate, T.Donhuaior, A.Muangchonburi, Chonburi 20000, Thailand	
P: 038-454-010 F: 038-454-017	C: 66

<b>SIAM NSK STEERING SYSTEMS CO., LTD.</b>	
OFFICE/PLANT 90 Moo 9, Walligrow Industrial Estate, Km.26 Bangna-Trad Rd., Bangwaoo, Bangkokook, Chachoengsao 24180, Thailand	
P: 038-522-343 F: 038-522-351	C: 66

<b>NSK ASIA PACIFIC TECHNOLOGY CENTRE (THAILAND) CO., LTD.</b>	
CHONBURI 700/430 Moo 7, Amata Nakorn Industrial Estate, T.Donhuaior, A.Muangchonburi, Chonburi 20000, Thailand	
P: 038-454-631 F: 038-454-634	C: 66

<b>Vietnam:</b>	
<b>NSK VIETNAM CO., LTD.</b>	
HEAD OFFICE Techno Center, Room 204-205, Thang Long Industrial Park, Dong Anh District, Hanoi, Vietnam	
P: 04-3955-0159 F: 04-3955-0158	C: 84

<b>NSK REPRESENTATIVE OFFICE</b>	
HO CHI MINH CITY Suite 307, Metropolitan Building, 235 Dong Khoi Street, District 1, HCMC, Vietnam	
P: 08-3822-7907 F: 08-3822-7910	C: 84

### ●Europe

<b>NSK EUROPE LTD. (EUROPEAN HEADQUARTERS)</b> www.eu.nsk.com	
MAIDENHEAD Belmont Place, Belmont Road, Maidenhead, Berkshire SL6 6TB, U.K.	
P: 01628-509-800 F: 01628-509-808	C: 44

<b>France:</b>	
<b>NSK FRANCE S.A.S.</b>	
PARIS Quartier de l'Europe, 2 Rue Georges Guynemer, 78283 Guyanecourt, France	
P: 01-30-57-39-39 F: 01-30-57-00-01	C: 33

<b>Germany:</b>	
<b>NSK DEUTSCHLAND GMBH</b>	
HEAD OFFICE Harkortsrasse 15, D-40880 Ratingen, Germany	
P: 02102-4810 F: 02102-4812-290	C: 49

<b>STUTT GART</b> Liebknechtstrasse 33, DE-70565 Stuttgart-Vaihingen, Germany	
P: 0711-73082-0 F: 0711-73082-269	C: 49

<b>WOLFSBURG</b> Heinrich-Nordhoff-Strasse 102, D-38440 Wolfsburg, Germany	
P: 05361-27647-10 F: 05361-27647-70	C: 49

<b>INGOLDSTADT</b> Ingolstadt, D-85055 Ingolstadt, Germany	
P: 0841-901-4640 F: 0841-901-4642	C: 49

<b>NSK PRECISION EUROPE GMBH</b>	
DUSSELDORF Harkortsrasse 15, D-40880 Ratingen, Germany	
P: 02102-4810 F: 02102-4812-290</	

**European NSK Sales Offices****UK**

NSK UK Ltd.  
Northern Road, Newark  
Nottinghamshire NG24 2JF  
Tel. +44 (0) 1636 605123  
Fax +44 (0) 1636 602775  
info-uk@nsk.com

**France**

NSK France S.A.S.  
Quartier de l'Europe  
2, Rue Georges Guynemer  
78283 Guyancourt Cedex  
Tel. +33 (0) 1 30573939  
Fax +33 (0) 1 30570001  
info-fr@nsk.com

**Germany**

NSK Deutschland GmbH  
Harkortstraße 15  
40880 Ratingen  
Tel. +49 (0) 2102 4810  
Fax +49 (0) 2102 4812290  
info-de@nsk.com

**Italy**

NSK Italia S.p.A.  
Via Garibaldi 215 - C.P. 103  
20024 Garbagnate  
Milanese (MI)  
Tel. +39 02 995191  
Fax +39 02 99025778  
info-it@nsk.com

**Norway**

**Nordic Sales Office**  
NSK Europe Norwegian Branch NUF  
Østre Kullerød 5  
N-3241 Sandefjord  
Tel. +47 33 293160  
Fax +47 33 429002  
info-de@nsk.com

**Poland & CEE**

NSK Polska Sp. z o.o.  
Warsaw Branch  
Ul. Migdałowa 4/73  
02-796 Warszawa  
Tel. +48 22 6451525  
Fax +48 22 6451529  
info-pl@nsk.com

**Spain**

NSK Spain, S.A.  
C/ Tarragona, 161 Cuerdo Bajo  
2ª Planta, 08014 Barcelona  
Tel. +34 93 2892763  
Fax +34 93 4335776  
info-es@nsk.com

**Sweden**

NSK Sweden Office  
Karolinen Företagscenter  
Våxnäsgratan 10  
SE-65340 Karlstad  
Tel. +46 5410 3545  
Fax +46 5410 3544  
info-de@nsk.com

**Turkey**

NSK Rulmanlari Orta Doğu Tic. Ltd. Şti  
19 Mayıs Mah. Atatürk Cad.  
Ulya Engin İş Merkezi No: 68 Kat. 6  
P.K.: 34734 – Kozyatağı – İstanbul  
Tel. +90 216 3550398  
Fax +90 216 3550399  
turkey@nsk.com

**Please also visit our website: [www.nskeurope.com](http://www.nskeurope.com)**

**Global NSK: [www.nsk.com](http://www.nsk.com)**

